

Package ‘CDatanet’

March 12, 2023

Type Package

Title Modeling Count Data with Peer Effects

Version 2.1.0

Date 2023-03-10

Description

Likelihood-based estimation and data generation from a class of models used to estimate peer effects on count data by controlling for the network endogeneity. This class includes count data models with social interactions (Houndetoungan 2022; <[doi:10.2139/ssrn.3721250](https://doi.org/10.2139/ssrn.3721250)>), spatial tobit models (Xu and Lee 2015; <[doi:10.1016/j.jeconom.2015.05.004](https://doi.org/10.1016/j.jeconom.2015.05.004)>), and spatial linear-in-means models (Lee 2004; <[doi:10.1111/j.1468-0262.2004.00558.x](https://doi.org/10.1111/j.1468-0262.2004.00558.x)>).

License GPL-3

Language en-US

Encoding UTF-8

BugReports <https://github.com/ahoundetoungan/CDatanet/issues>

URL <https://github.com/ahoundetoungan/CDatanet>

Depends R (>= 3.5.0)

Imports Rcpp (>= 1.0.0), Formula, formula.tools, ddpcr, Matrix

LinkingTo Rcpp, RcppArmadillo, RcppProgress, RcppDist, RcppNumerical, RcppEigen

RoxygenNote 7.2.3

Suggests ggplot2, MASS, knitr, rmarkdown

NeedsCompilation yes

Author Elysee Aristide Houndetoungan [cre, aut]

Maintainer Elysee Aristide Houndetoungan <ariel92and@gmail.com>

Repository CRAN

Date/Publication 2023-03-12 16:00:02 UTC

R topics documented:

CDatanet-package	2
cdnet	3
homophily	6
homophily.FE	9
sar	12
sart	14
simcdnet	17
simsar	20
sim sart	22
summary.cdnet	25
summary.sar	26
summary.sart	27
Index	28

CDatanet-package	<i>The CDatanet package</i>
------------------	-----------------------------

Description

The **CDatanet** package implements the count data model with social interactions and the dyadic linking model developed in Houndetoungan (2022). It also simulates data from the count data model and implements the Spatial Autoregressive Tobit model (LeSage, 2000; Xu and Lee, 2015) for left censored data and the Spatial Autoregressive Model (Lee, 2004). Network formation models, such as that studied by Yan et al. (2019), are also implemented. To make the computations faster **CDatanet** uses C++ through the **Rcpp** package (Eddelbuettel et al., 2011).

Author(s)

Maintainer: Elysee Aristide Houndetoungan <arie192and@gmail.com>

References

- Eddelbuettel, D., & Francois, R. (2011). **Rcpp**: Seamless R and C++ integration. *Journal of Statistical Software*, 40(8), 1-18, doi:10.18637/jss.v040.i08.
- Houndetoungan, E. A. (2022). Count Data Models with Social Interactions under Rational Expectations. Available at SSRN 3721250, doi:10.2139/ssrn.3721250.
- Lee, L. F. (2004). Asymptotic distributions of quasi-maximum likelihood estimators for spatial autoregressive models. *Econometrica*, 72(6), 1899-1925, doi:10.1111/j.14680262.2004.00558.x.
- Xu, X., & Lee, L. F. (2015). Maximum likelihood estimation of a spatial autoregressive Tobit model. *Journal of Econometrics*, 188(1), 264-280, doi:10.1016/j.jeconom.2015.05.004.
- Yan, T., Jiang, B., Fienberg, S. E., & Leng, C. (2019). Statistical inference in a directed network model with covariates. *Journal of the American Statistical Association*, 114(526), 857-868, doi:10.1080/01621459.2018.1448829.

See Also

Useful links:

- <https://github.com/ahoundetoungan/CDatanet>
- Report bugs at <https://github.com/ahoundetoungan/CDatanet/issues>

cdnet

Estimate Count Data Model with Social Interactions using NPL Method

Description

cdnet is used to estimate peer effects on counting data with rational expectations (see details). The model is presented in Houndetoungan (2022).

Usage

```
cdnet(
  formula,
  contextual,
  Glist,
  Rbar = NULL,
  estim.rho = FALSE,
  starting = list(theta = NULL, deltabar = NULL, delta = NULL, rho = NULL),
  yb0 = NULL,
  optimizer = "fastlbfgs",
  npl.ctr = list(),
  opt.ctr = list(),
  cov = TRUE,
  data
)
```

Arguments

- | | |
|------------|---|
| formula | an object of class <code>formula</code> : a symbolic description of the model. The formula should be as for example $y \sim x_1 + x_2 \mid x_1 + x_2$ where y is the endogenous vector, the listed variables before the pipe, x_1 , x_2 are the individual exogenous variables and the listed variables after the pipe, x_1 , x_2 are the contextual observable variables. Other formulas may be $y \sim x_1 + x_2$ for the model without contextual effects, $y \sim -1 + x_1 + x_2 \mid x_1 + x_2$ for the model without intercept or $y \sim x_1 + x_2 \mid x_2 + x_3$ to allow the contextual variable to be different from the individual variables. |
| contextual | (optional) logical; if true, this means that all individual variables will be set as contextual variables. Set the the formula as $y \sim x_1 + x_2$ and contextual as TRUE is equivalent to set the formula as $y \sim x_1 + x_2 \mid x_1 + x_2$. |
| Glist | the adjacency matrix or list sub-adjacency matrix. |

Rbar	the value of Rbar. If not provided, it is automatically set at $\text{quantile}(y, 0.9)$.
estim.rho	indicates if the parameter ρ should be estimated or set to zero.
starting	(optional) starting value of $\theta = (\lambda, \beta', \gamma)'$, $\bar{\delta}$, $\delta = (\delta_2, \dots, \delta_{\bar{R}})$, and ρ . The parameter γ should be removed if the model does not contain contextual effects (see details).
yb0	(optional) expectation of y .
optimizer	is either <code>fastlbfgs</code> (L-BFGS optimization method of the package RcppNumerical), <code>nlm</code> (referring to the function <code>nlm</code>), or <code>optim</code> (referring to the function <code>optim</code>). Other arguments of these functions such as <code>control</code> and <code>method</code> can be defined through the argument <code>opt.ctr</code> .
npl.ctr	list of controls for the NPL method (see details).
opt.ctr	list of arguments to be passed in <code>optim_lbfgs</code> of the package RcppNumerical , <code>nlm</code> or <code>optim</code> (the solver set in <code>optimizer</code>), such as <code>maxit</code> , <code>eps_f</code> , <code>eps_g</code> , <code>control</code> , <code>method</code> , ...
cov	a Boolean indicating if the covariance should be computed.
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in <code>data</code> , the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>cdnet</code> is called.

Details

Model:

Following Houndetoungan (2022), the count data \mathbf{y} is generated from a latent variable \mathbf{y}^* . The latent variable is given for all i as

$$y_i^* = \lambda \mathbf{g}_i \mathbf{E}(\bar{\mathbf{y}} | \mathbf{X}, \mathbf{G}) + \mathbf{x}_i' \beta + \mathbf{g}_i \mathbf{X} \gamma + \epsilon_i,$$

where $\epsilon_i \sim N(0, 1)$.

Then, $y_i = r$ iff $a_r \leq y_i^* \leq a_{r+1}$, where $a_0 = -\text{inf}$, $a_1 = 0$, $a_r = \sum_{k=1}^r \delta_k$. The parameter are subject to the constraints $\delta_r \geq \lambda$ if $1 \leq r \leq \bar{R}$, and $\delta_r = (r - \bar{R})^\rho \bar{\delta} + \lambda$ if $r \geq \bar{R} + 1$. The unknown parameters to be estimated are λ , β , γ , $\delta_2, \dots, \delta_{\bar{R}}$, $\bar{\delta}$, and ρ .

npl.ctr:

The model parameters is estimated using the Nested Partial Likelihood (NPL) method. This approach starts with a guess of θ and \bar{y} and constructs iteratively a sequence of θ and \bar{y} . The solution converges when the L_1 distance between two consecutive θ and \bar{y} is less than a tolerance. The argument `npl.ctr` is an optional list which contain

- `tol` the tolerance of the NPL algorithm (default 1e-4),
- `maxit` the maximal number of iterations allowed (default 500),
- `print` a boolean indicating if the estimate should be printed at each step.
- `S` the number of simulation performed use to compute integral in the covariance by important sampling.

Value

A list consisting of:

info	list of general information about the model.
estimate	NPL estimator.
yb	ybar (see details), expectation of y.
Gyb	average of the expectation of y among friends.
cov	list of covariance matrices.
details	step-by-step output as returned by the optimizer.

References

Houndetoungan, E. A. (2022). Count Data Models with Social Interactions under Rational Expectations. Available at SSRN 3721250, [doi:10.2139/ssrn.3721250](https://doi.org/10.2139/ssrn.3721250).

See Also

[sart](#), [sar](#), [simcdnet](#).

Examples

```
set.seed(123)
# Groups' size
nvec <- sample(100:500, 2)
M     <- length(nvec)
n     <- sum(nvec)

# Parameters
lambda <- 0.4
beta  <- c(1.5, 2.2, -0.9)
gamma <- c(1.5, -1.2)
delta <- c(1, 0.87, 0.75, 0.6)
delbar <- 0.05
rho   <- 0.5
theta <- c(lambda, beta, gamma)

# X
X     <- cbind(rnorm(n, 1, 1), rexp(n, 0.4))

# Network
Glist <- list()

for (m in 1:M) {
  nm      <- nvec[m]
  Gm      <- matrix(0, nm, nm)
  max_d   <- 30
  for (i in 1:nm) {
    tmp    <- sample((1:nm)[-i], sample(0:max_d, 1))
    Gm[i, tmp] <- 1
  }
}
```

```

rs          <- rowSums(Gm); rs[rs == 0] <- 1
Gm          <- Gm/rs
Glist[[m]] <- Gm
}

# data
data <- data.frame(x1 = X[,1], x2 = X[,2])

ytmp <- simcdnet(formula = ~ x1 + x2 | x1 + x2, Glist = Glist, theta = theta,
                 deltabar = delbar, delta = delta, rho = rho, data = data)

y <- ytmp$y

# plot histogram
hist(y, breaks = max(y))

data <- data.frame(yt = y, x1 = data$x1, x2 = data$x2)
rm(list = ls()[!(ls() %in% c("Glist", "data"))])

out <- cdnet(formula = yt ~ x1 + x2, contextual = TRUE, Glist = Glist,
             data = data, Rbar = 10, estim.rho = TRUE, optimizer = "nlm")
summary(out)

```

homophily

Estimate Network Formation Model with Degree Heterogeneity as Random Effects

Description

homophily implements a Bayesian estimator for network formation model with homophily. The model includes degree heterogeneity as random effects (see details).

Usage

```

homophily(
  network,
  formula,
  data,
  fixed.effects = FALSE,
  init = list(),
  iteration = 1000,
  print = TRUE
)

```

Arguments

network matrix or list of sub-matrix of social interactions containing 0 and 1, where links are represented by 1

formula	an object of class formula : a symbolic description of the model. The formula should be as for example $\sim x1 + x2$ where $x1, x2$ are explanatory variable of links formation
data	an optional data frame, list or environment (or object coercible by as.data.frame to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>homophily</code> is called.
fixed.effects	boolean indicating if sub-network heterogeneity as fixed effects should be included.
init	(optional) list of starting values containing beta, an K-dimensional vector of the explanatory variables parameter, mu an n-dimensional vector, and nu an n-dimensional vector, smu2 the variance of mu, and snu2 the variance of nu, where K is the number of explanatory variables and n is the number of individuals.
iteration	the number of iterations to be performed.
print	boolean indicating if the estimation progression should be printed.

Details

Let p_{ij} be a probability for a link to go from the individual i to the individual j . This probability is specified as

$$p_{ij} = F(\mathbf{x}'_{ij}\beta + \mu_j + \nu_j)$$

where F is the cumulative of the standard normal distribution. Unobserved degree heterogeneity is captured by μ_i and ν_j . The latter are treated as random effects.

Value

A list consisting of:

n	number of individuals in each network.
n.obs	number of observations.
n.links	number of links.
K	number of explanatory variables.
posterior	list of simulations from the posterior distribution.
iteration	number of performed iterations.
init	returned list of starting values.

See Also

[homophily.FE](#).

Examples

```
set.seed(1234)
library(MASS)
M <- 4 # Number of sub-groups
```

```

nvec      <- round(runif(M, 100, 500))
beta      <- c(.1, -.1)
Glist     <- list()
dX        <- matrix(0, 0, 2)
mu        <- list()
nu        <- list()
cst       <- runif(M, -1.5, 0)
smu2     <- 0.2
snu2     <- 0.2
rho       <- 0.8
Smunu    <- matrix(c(smu2, rho*sqrt(smu2*snu2), rho*sqrt(smu2*snu2), snu2), 2)
for (m in 1:M) {
  n      <- nvec[m]
  tmp    <- mvrnorm(n, c(0, 0), Smunu)
  mum    <- tmp[,1] - mean(tmp[,1])
  num    <- tmp[,2] - mean(tmp[,2])
  X1     <- rnorm(n, 0, 1)
  X2     <- rbinom(n, 1, 0.2)
  Z1     <- matrix(0, n, n)
  Z2     <- matrix(0, n, n)

  for (i in 1:n) {
    for (j in 1:n) {
      Z1[i, j] <- abs(X1[i] - X1[j])
      Z2[i, j] <- 1*(X2[i] == X2[j])
    }
  }

  Gm      <- 1*((cst[m] + Z1*beta[1] + Z2*beta[2] +
               kronecker(mum, t(num), "+") + rnorm(n^2)) > 0)

  diag(Gm) <- 0
  diag(Z1) <- NA
  diag(Z2) <- NA
  Z1      <- Z1[!is.na(Z1)]
  Z2      <- Z2[!is.na(Z2)]

  dX      <- rbind(dX, cbind(Z1, Z2))
  Glist[[m]] <- Gm
  mu[[m]] <- mum
  nu[[m]] <- num
}

mu <- unlist(mu)
nu <- unlist(nu)

out <- homophily(network = Glist, formula = ~ dX, fixed.effects = TRUE,
                 iteration = 1e3)

# plot simulations
plot(out$posterior$beta[,1], type = "l")
abline(h = cst[1], col = "red")
plot(out$posterior$beta[,2], type = "l")
abline(h = cst[2], col = "red")

```



```

plot(out$posterior$beta[,3], type = "l")
abline(h = cst[3], col = "red")
plot(out$posterior$beta[,4], type = "l")
abline(h = cst[4], col = "red")

plot(out$posterior$beta[,5], type = "l")
abline(h = beta[1], col = "red")
plot(out$posterior$beta[,6], type = "l")
abline(h = beta[2], col = "red")

plot(out$posterior$sigma2_mu, type = "l")
abline(h = smu2, col = "red")
plot(out$posterior$sigma2_nu, type = "l")
abline(h = snu2, col = "red")
plot(out$posterior$rho, type = "l")
abline(h = rho, col = "red")

i <- 10
plot(out$posterior$mu[,i], type = "l")
abline(h = mu[i], col = "red")
plot(out$posterior$nu[,i], type = "l")
abline(h = nu[i], col = "red")

```

homophily.FE

Estimate Network Formation Model with Degree Heterogeneity as Fixed Effects

Description

homophily.FE is used to estimate a network formation model with homophily. The model includes degree heterogeneity as fixed effects (see details).

Usage

```

homophily.FE(
  network,
  formula,
  data,
  init = NULL,
  opt.ctr = list(maxit = 300, eps_f = 1e-06, eps_g = 1e-05),
  print = TRUE
)

```

Arguments

network matrix or list of sub-matrix of social interactions containing 0 and 1, where links are represented by 1

formula	an object of class <code>formula</code> : a symbolic description of the model. The formula should be as for example <code>~ x1 + x2</code> where <code>x1</code> , <code>x2</code> are explanatory variable of links formation
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>homophily</code> is called.
init	(optional) either a list of starting values containing <code>beta</code> , an <code>K</code> -dimensional vector of the explanatory variables parameter, <code>mu</code> an <code>n</code> -dimensional vector, and <code>nu</code> an <code>n</code> -dimensional vector, where <code>K</code> is the number of explanatory variables and <code>n</code> is the number of individuals; or a vector of starting value for <code>c(beta, mu, nu)</code> .
opt.ctr	(optional) is a list of <code>maxit</code> , <code>eps_f</code> , and <code>eps_g</code> , which are control parameters used by the solver <code>optim_lbfgs</code> , of the package RcppNumerical .
print	Boolean indicating if the estimation progression should be printed.

Details

Let p_{ij} be a probability for a link to go from the individual i to the individual j . This probability is specified as

$$p_{ij} = F(\mathbf{x}'_{ij}\beta + \mu_j + \nu_j)$$

where F is the cumulative of the standard normal distribution. Unobserved degree heterogeneity is captured by μ_i and ν_j . The latter are treated as fixed effects. As shown by Yan et al. (2019), the estimator of the parameter β is biased. A bias correction is then necessary and is not implemented in this version. However the estimator of μ_i and ν_j are consistent.

Value

A list consisting of:

<code>n</code>	number of individuals in each network.
<code>n.obs</code>	number of observations.
<code>n.links</code>	number of links.
<code>K</code>	number of explanatory variables.
<code>estimate</code>	maximizer of the log-likelihood.
<code>loglike</code>	maximized log-likelihood.
<code>optim</code>	returned value of the optimization solver, which contains details of the optimization. The solver used is <code>optim_lbfgs</code> of the package RcppNumerical .
<code>init</code>	returned list of starting value.
<code>loglike(init)</code>	log-likelihood at the starting value.

References

Yan, T., Jiang, B., Fienberg, S. E., & Leng, C. (2019). Statistical inference in a directed network model with covariates. *Journal of the American Statistical Association*, 114(526), 857-868, doi:10.1080/01621459.2018.1448829.

See Also[homophily.](#)**Examples**

```

set.seed(1234)
M      <- 2 # Number of sub-groups
nvec   <- round(runif(M, 20, 50))
beta   <- c(.1, -.1)
Glist  <- list()
dX     <- matrix(0, 0, 2)
mu     <- list()
nu     <- list()
Emunu  <- runif(M, -1.5, 0) #expectation of mu + nu
smu2   <- 0.2
snu2   <- 0.2
for (m in 1:M) {
  n     <- nvec[m]
  mum   <- rnorm(n, 0.7*Emunu[m], smu2)
  num   <- rnorm(n, 0.3*Emunu[m], snu2)
  X1    <- rnorm(n, 0, 1)
  X2    <- rbinom(n, 1, 0.2)
  Z1    <- matrix(0, n, n)
  Z2    <- matrix(0, n, n)

  for (i in 1:n) {
    for (j in 1:n) {
      Z1[i, j] <- abs(X1[i] - X1[j])
      Z2[i, j] <- 1*(X2[i] == X2[j])
    }
  }

  Gm    <- 1*((Z1*beta[1] + Z2*beta[2] +
              kronecker(mum, t(num), "+") + rlogis(n^2)) > 0)
  diag(Gm) <- 0
  diag(Z1) <- NA
  diag(Z2) <- NA
  Z1     <- Z1[!is.na(Z1)]
  Z2     <- Z2[!is.na(Z2)]

  dX     <- rbind(dX, cbind(Z1, Z2))
  Glist[[m]] <- Gm
  mu[[m]] <- mum
  nu[[m]] <- num
}

mu <- unlist(mu)
nu <- unlist(nu)

out <- homophily.FE(network = Glist, formula = ~ -1 + dX)
muhat <- out$estimate$mu

```

```
nuhat <- out$estimate$nu
```

 sar

Estimate SAR model

Description

sar is used to estimate peer effects continuous variables (see details). The model is presented in Lee(2004).

Usage

```
sar(
  formula,
  contextual,
  Glist,
  lambda0 = NULL,
  optimizer = "optim",
  opt.ctr = list(),
  print = TRUE,
  cov = TRUE,
  data
)
```

Arguments

formula	an object of class formula : a symbolic description of the model. The formula should be as for example $y \sim x1 + x2 \mid x1 + x2$ where y is the endogenous vector, the listed variables before the pipe, $x1$, $x2$ are the individual exogenous variables and the listed variables after the pipe, $x1$, $x2$ are the contextual observable variables. Other formulas may be $y \sim x1 + x2$ for the model without contextual effects, $y \sim -1 + x1 + x2 \mid x1 + x2$ for the model without intercept or $y \sim x1 + x2 \mid x2 + x3$ to allow the contextual variable to be different from the individual variables.
contextual	(optional) logical; if true, this means that all individual variables will be set as contextual variables. Set the formula as $y \sim x1 + x2$ and contextual as TRUE is equivalent to set the formula as $y \sim x1 + x2 \mid x1 + x2$.
Glist	the adjacency matrix or list sub-adjacency matrix.
lambda0	(optional) starting value of λ . The parameter γ should be removed if the model does not contain contextual effects (see details).
optimizer	is either <code>nlm</code> (referring to the function nlm) or <code>optim</code> (referring to the function optim). Other arguments of these functions such as, the control values and the method can be defined through the argument <code>opt.ctr</code> .
opt.ctr	list of arguments of <code>nlm</code> or <code>optim</code> (the one set in <code>optimizer</code>) such as control, method, ...

print	a Boolean indicating if the estimate should be printed at each step.
cov	a Boolean indicating if the covariance should be computed.
data	an optional data frame, list or environment (or object coercible by as.data.frame to a data frame) containing the variables in the model. If not found in data, the variables are taken from environment(formula), typically the environment from which mcmcARD is called.

Details

Model:

The variable y is given for all i as

$$y_i = \lambda \mathbf{g}_i y + \mathbf{x}_i' \beta + \mathbf{g}_i \mathbf{X} \gamma + \epsilon_i,$$

where $\epsilon_i \sim N(0, \sigma^2)$.

Value

A list consisting of:

info	list of general information on the model.
estimate	Maximum Likelihood (ML) estimator.
cov	covariance matrix of the estimate.
details	outputs as returned by the optimizer.

References

Lee, L. F. (2004). Asymptotic distributions of quasi-maximum likelihood estimators for spatial autoregressive models. *Econometrica*, 72(6), 1899-1925, doi:[10.1111/j.14680262.2004.00558.x](https://doi.org/10.1111/j.14680262.2004.00558.x).

See Also

[sart](#), [cdnet](#), [simsar](#).

Examples

```
# Groups' size
M <- 5 # Number of sub-groups
nvec <- round(runif(M, 100, 1000))
n <- sum(nvec)

# Parameters
lambda <- 0.4
beta <- c(2, -1.9, 0.8)
gamma <- c(1.5, -1.2)
sigma <- 1.5
theta <- c(lambda, beta, gamma, sigma)

# X
```

```

X      <- cbind(rnorm(n, 1, 1), rexp(n, 0.4))

# Network
Glist <- list()

for (m in 1:M) {
  nm      <- nvec[m]
  Gm      <- matrix(0, nm, nm)
  max_d   <- 30
  for (i in 1:nm) {
    tmp    <- sample((1:nm)[-i], sample(0:max_d, 1))
    Gm[i, tmp] <- 1
  }
  rs      <- rowSums(Gm); rs[rs == 0] <- 1
  Gm      <- Gm/rs
  Glist[[m]] <- Gm
}

# data
data    <- data.frame(x1 = X[,1], x2 = X[,2])

rm(list = ls()[!(ls() %in% c("Glist", "data", "theta"))])

ytmp    <- simsar(formula = ~ x1 + x2 | x1 + x2, Glist = Glist,
                  theta = theta, data = data)

y       <- ytmp$y

# plot histogram
hist(y, breaks = max(y))

data    <- data.frame(yt = y, x1 = data$x1, x2 = data$x2)
rm(list = ls()[!(ls() %in% c("Glist", "data"))])

out     <- sar(formula = yt ~ x1 + x2, contextual = TRUE,
               Glist = Glist, optimizer = "optim", data = data)
summary(out)

```

sart

Estimate sart model

Description

sart is used to estimate peer effects on censored data (see details). The model is presented in Xu and Lee(2015).

Usage

```
sart(
  formula,
  contextual,
  Glist,
  theta0 = NULL,
  yb0 = NULL,
  optimizer = "fastlbfgs",
  npl.ctr = list(),
  opt.ctr = list(),
  print = TRUE,
  cov = TRUE,
  RE = FALSE,
  data
)
```

Arguments

formula	an object of class formula : a symbolic description of the model. The formula should be as for example $y \sim x_1 + x_2 \mid x_1 + x_2$ where y is the endogenous vector, the listed variables before the pipe, x_1, x_2 are the individual exogenous variables and the listed variables after the pipe, x_1, x_2 are the contextual observable variables. Other formulas may be $y \sim x_1 + x_2$ for the model without contextual effects, $y \sim -1 + x_1 + x_2 \mid x_1 + x_2$ for the model without intercept or $y \sim x_1 + x_2 \mid x_2 + x_3$ to allow the contextual variable to be different from the individual variables.
contextual	(optional) logical; if true, this means that all individual variables will be set as contextual variables. Set the formula as $y \sim x_1 + x_2$ and contextual as TRUE is equivalent to set the formula as $y \sim x_1 + x_2 \mid x_1 + x_2$.
Glist	the adjacency matrix or list sub-adjacency matrix.
theta0	(optional) starting value of $\theta = (\lambda, \beta, \gamma, \sigma)$. The parameter γ should be removed if the model does not contain contextual effects (see details).
yb0	(optional) expectation of y .
optimizer	is either <code>fastlbfgs</code> (L-BFGS optimization method of the package RcppNumerical), <code>nlm</code> (referring to the function nlm), or <code>optim</code> (referring to the function optim). Other arguments of these functions such as, <code>control</code> and <code>method</code> can be defined through the argument <code>opt.ctr</code> .
npl.ctr	list of controls for the NPL method (see cdnet).
opt.ctr	list of arguments to be passed in <code>optim_lbfgs</code> of the package RcppNumerical , <code>nlm</code> or <code>optim</code> (the solver set in <code>optimizer</code>), such as <code>maxit</code> , <code>eps_f</code> , <code>eps_g</code> , <code>control</code> , <code>method</code> , ...
print	a Boolean indicating if the estimate should be printed at each step.
cov	a Boolean indicating if the covariance should be computed.
RE	a Boolean which indicates if the model is under rational expectation of not.

`data` an optional data frame, list or environment (or object coercible by [as.data.frame](#) to a data frame) containing the variables in the model. If not found in `data`, the variables are taken from `environment(formula)`, typically the environment from which `sart` is called.

Details

Model:

The left-censored variable y is generated from a latent variable y^* . The latent variable is given for all i as

$$y_i^* = \lambda \mathbf{g}_i y + \mathbf{x}_i' \beta + \mathbf{g}_i \mathbf{X} \gamma + \epsilon_i,$$

where $\epsilon_i \sim N(0, \sigma^2)$.

The count variable y_i is then define that is $y_i = 0$ if $y_i^* \leq 0$ and $y_i = y_i^*$ otherwise.

Value

A list consisting of:

<code>info</code>	list of general information on the model.
<code>estimate</code>	Maximum Likelihood (ML) estimator.
<code>yb</code>	ybar (see details), expectation of y .
<code>Gyb</code>	average of the expectation of y among friends.
<code>cov</code>	List of covariances.
<code>details</code>	outputs as returned by the optimizer.

References

Xu, X., & Lee, L. F. (2015). Maximum likelihood estimation of a spatial autoregressive Tobit model. *Journal of Econometrics*, 188(1), 264-280, [doi:10.1016/j.jeconom.2015.05.004](https://doi.org/10.1016/j.jeconom.2015.05.004).

See Also

[sar](#), [cdnet](#), [simsart](#).

Examples

```
# Groups' size
M <- 5 # Number of sub-groups
nvec <- round(runif(M, 100, 1000))
n <- sum(nvec)

# Parameters
lambda <- 0.4
beta <- c(2, -1.9, 0.8)
gamma <- c(1.5, -1.2)
sigma <- 1.5
theta <- c(lambda, beta, gamma, sigma)
```



```

# X
X      <- cbind(rnorm(n, 1, 1), rexp(n, 0.4))

# Network
Glist <- list()

for (m in 1:M) {
  nm      <- nvec[m]
  Gm      <- matrix(0, nm, nm)
  max_d   <- 30
  for (i in 1:nm) {
    tmp    <- sample((1:nm)[-i], sample(0:max_d, 1))
    Gm[i, tmp] <- 1
  }
  rs      <- rowSums(Gm); rs[rs == 0] <- 1
  Gm      <- Gm/rs
  Glist[[m]] <- Gm
}

# data
data    <- data.frame(x1 = X[,1], x2 = X[,2])

rm(list = ls()[!(ls() %in% c("Glist", "data", "theta"))])

ytmp    <- simsart(formula = ~ x1 + x2 | x1 + x2, Glist = Glist,
                  theta = theta, data = data)

y       <- ytmp$y

# plot histogram
hist(y)

opt.ctr <- list(method = "Nelder-Mead",
                control = list(abstol = 1e-16, abstol = 1e-11, maxit = 5e3))
data    <- data.frame(yt = y, x1 = data$x1, x2 = data$x2)
rm(list = ls()[!(ls() %in% c("Glist", "data"))])

out     <- sart(formula = yt ~ x1 + x2, optimizer = "nlm",
               contextual = TRUE, Glist = Glist, data = data)
summary(out)

```

Description

simcdnet is used simulate counting data with rational expectations (see details). The model is presented in Houndetoungan (2022).

Usage

```
simcdnet(
  formula,
  contextual,
  Glist,
  theta,
  deltabar,
  delta = NULL,
  rho = 0,
  tol = 1e-10,
  maxit = 500,
  data
)
```

Arguments

formula	an object of class formula : a symbolic description of the model. The formula should be as for example $y \sim x_1 + x_2 \mid x_1 + x_2$ where y is the endogenous vector, the listed variables before the pipe, x_1, x_2 are the individual exogenous variables and the listed variables after the pipe, x_1, x_2 are the contextual observable variables. Other formulas may be $y \sim x_1 + x_2$ for the model without contextual effects, $y \sim -1 + x_1 + x_2 \mid x_1 + x_2$ for the model without intercept or $y \sim x_1 + x_2 \mid x_2 + x_3$ to allow the contextual variable to be different from the individual variables.
contextual	(optional) logical; if true, this means that all individual variables will be set as contextual variables. Set the formula as $y \sim x_1 + x_2$ and contextual as TRUE is equivalent to set the formula as $y \sim x_1 + x_2 \mid x_1 + x_2$.
Glist	the adjacency matrix or list sub-adjacency matrix.
theta	the true value of the vector $\theta = (\lambda, \beta', \gamma)'$. The parameter γ should be removed if the model does not contain contextual effects (see details).
deltabar	the true value of $\bar{\delta}$.
delta	the true value of the vector $\delta = (\delta_2, \dots, \delta_{\bar{R}})$. If NULL, then \bar{R} is set to one and delta is empty.
rho	the true value of ρ .
tol	the tolerance value used in the Fixed Point Iteration Method to compute the expectancy of y . The process stops if the L_1 distance between two consecutive values of the expectancy of y is less than tol.
maxit	the maximal number of iterations in the Fixed Point Iteration Method.
data	an optional data frame, list or environment (or object coercible by as.data.frame to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>mcmcARD</code> is called.

Details

Following Houndetoungan (2022), the count data \mathbf{y} is generated from a latent variable \mathbf{y}^* . The latent variable is given for all i as

$$y_i^* = \lambda \mathbf{g}_i \mathbf{E}(\bar{\mathbf{y}} | \mathbf{X}, \mathbf{G}) + \mathbf{x}_i' \beta + \mathbf{g}_i \mathbf{X} \gamma + \epsilon_i,$$

where $\epsilon_i \sim N(0, 1)$.

Then, $y_i = r$ iff $a_r \leq y_i^* \leq a_{r+1}$, where $a_0 = -\inf$, $a_1 = 0$, $a_r = \sum_{k=1}^r \delta_k$. The parameter are subject to the constraints $\delta_r \geq \lambda$ if $1 \leq r \leq \bar{R}$, and $\delta_r = (r - \bar{R})^\rho \bar{\delta} + \lambda$ if $r \geq \bar{R} + 1$.

Value

A list consisting of:

yst	ys (see details), the latent variable.
y	the observed count data.
yb	ybar (see details), the expectation of y.
Gyb	the average of the expectation of y among friends.
marg.effects	the marginal effects.
rho	the return value of rho.
Rmax	infinite sums in the marginal effects are approximated by sums up to Rmax.
iteration	number of iterations performed by sub-network in the Fixed Point Iteration Method.

References

Houndetoungan, E. A. (2022). Count Data Models with Social Interactions under Rational Expectations. Available at SSRN 3721250, [doi:10.2139/ssrn.3721250](https://doi.org/10.2139/ssrn.3721250).

See Also

[cdnet](#), [simsart](#), [simsar](#).

Examples

```
# Groups' size
M <- 5 # Number of sub-groups
nvec <- round(runif(M, 100, 1000))
n <- sum(nvec)

# Parameters
lambda <- 0.4
beta <- c(1.5, 2.2, -0.9)
gamma <- c(1.5, -1.2)
delta <- c(1, 0.87, 0.75, 0.6)
delbar <- 0.05
theta <- c(lambda, beta, gamma)
```

```

# X
X    <- cbind(rnorm(n, 1, 1), rexp(n, 0.4))

# Network
Glist <- list()

for (m in 1:M) {
  nm      <- nvec[m]
  Gm      <- matrix(0, nm, nm)
  max_d   <- 30
  for (i in 1:nm) {
    tmp    <- sample((1:nm)[-i], sample(0:max_d, 1))
    Gm[i, tmp] <- 1
  }
  rs      <- rowSums(Gm); rs[rs == 0] <- 1
  Gm      <- Gm/rs
  Glist[[m]] <- Gm
}

# data
data    <- data.frame(x1 = X[,1], x2 = X[,2])

rm(list = ls()[!(ls() %in% c("Glist", "data", "theta", "delta", "delbar"))])

ytmp    <- simcdnet(formula = ~ x1 + x2 | x1 + x2, Glist = Glist, theta = theta,
                    deltabar = delbar, delta = delta, rho = 0, data = data)

y       <- ytmp$y

# plot histogram
hist(y, breaks = max(y))

```

simsar

Simulate data from the linear-in-mean Model with Social Interactions

Description

simsar is used to simulate continuous variables with social interactions (see details). The model is presented in Lee(2004).

Usage

```
simsar(formula, contextual, Glist, theta, data)
```

Arguments

formula an object of class [formula](#): a symbolic description of the model. The formula should be as for example $y \sim x1 + x2 \mid x1 + x2$ where y is the endogenous vector, the listed variables before the pipe, $x1$, $x2$ are the individual exogenous

variables and the listed variables after the pipe, x_1 , x_2 are the contextual observable variables. Other formulas may be $y \sim x_1 + x_2$ for the model without contextual effects, $y \sim -1 + x_1 + x_2 \mid x_1 + x_2$ for the model without intercept or $y \sim x_1 + x_2 \mid x_2 + x_3$ to allow the contextual variable to be different from the individual variables.

contextual	(optional) logical; if true, this means that all individual variables will be set as contextual variables. Set the formula as $y \sim x_1 + x_2$ and contextual as TRUE is equivalent to set the formula as $y \sim x_1 + x_2 \mid x_1 + x_2$.
Glist	the adjacency matrix or list sub-adjacency matrix.
theta	the parameter value as $\theta = (\lambda, \beta, \gamma, \sigma)$. The parameter γ should be removed if the model does not contain contextual effects (see details).
data	an optional data frame, list or environment (or object coercible by as.data.frame to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>mcmcARD</code> is called.

Details

The variable y is given for all i as

$$y_i = \lambda \mathbf{g}_i y + \mathbf{x}'_i \beta + \mathbf{g}_i \mathbf{X} \gamma + \epsilon_i,$$

where $\epsilon_i \sim N(0, \sigma^2)$.

Value

A list consisting of:

y	the observed count data.
Gy	the average of y among friends.

References

Lee, L. F. (2004). Asymptotic distributions of quasi-maximum likelihood estimators for spatial autoregressive models. *Econometrica*, 72(6), 1899-1925, doi:10.1111/j.14680262.2004.00558.x.

See Also

[sar](#), [simsart](#), [simcdnet](#).

Examples

```
# Groups' size
M <- 5 # Number of sub-groups
nvec <- round(runif(M, 100, 1000))
n <- sum(nvec)

# Parameters
lambda <- 0.4
```

```

beta <- c(2, -1.9, 0.8)
gamma <- c(1.5, -1.2)
sigma <- 1.5
theta <- c(lambda, beta, gamma, sigma)

# X
X <- cbind(rnorm(n, 1, 1), rexp(n, 0.4))

# Network
Glist <- list()

for (m in 1:M) {
  nm <- nvec[m]
  Gm <- matrix(0, nm, nm)
  max_d <- 30
  for (i in 1:nm) {
    tmp <- sample((1:nm)[-i], sample(0:max_d, 1))
    Gm[i, tmp] <- 1
  }
  rs <- rowSums(Gm); rs[rs == 0] <- 1
  Gm <- Gm/rs
  Glist[[m]] <- Gm
}

# data
data <- data.frame(x1 = X[,1], x2 = X[,2])

rm(list = ls()[!(ls() %in% c("Glist", "data", "theta"))])

ytmp <- simsart(formula = ~ x1 + x2 | x1 + x2, Glist = Glist,
                theta = theta, data = data)
y <- ytmp$y

# plot histogram
hist(y)

```

simsart

Simulate data from the Tobit Model with Social Interactions

Description

simsart is used to simulate censored data with social interactions (see details). The model is presented in Xu and Lee(2015).

Usage

```

simsart(
  formula,

```

```

contextual,
Glist,
theta,
tol = 1e-15,
maxit = 500,
RE = FALSE,
data
)

```

Arguments

formula	an object of class formula : a symbolic description of the model. The formula should be as for example $y \sim x1 + x2 \mid x1 + x2$ where y is the endogenous vector, the listed variables before the pipe, $x1, x2$ are the individual exogenous variables and the listed variables after the pipe, $x1, x2$ are the contextual observable variables. Other formulas may be $y \sim x1 + x2$ for the model without contextual effects, $y \sim -1 + x1 + x2 \mid x1 + x2$ for the model without intercept or $y \sim x1 + x2 \mid x2 + x3$ to allow the contextual variable to be different from the individual variables.
contextual	(optional) logical; if true, this means that all individual variables will be set as contextual variables. Set the formula as $y \sim x1 + x2$ and contextual as TRUE is equivalent to set the formula as $y \sim x1 + x2 \mid x1 + x2$.
Glist	the adjacency matrix or list sub-adjacency matrix.
theta	the parameter value as $\theta = (\lambda, \beta, \gamma, \sigma)$. The parameter γ should be removed if the model does not contain contextual effects (see details).
tol	the tolerance value used in the Fixed Point Iteration Method to compute y . The process stops if the L_1 distance between two consecutive values of y is less than tol .
maxit	the maximal number of iterations in the Fixed Point Iteration Method.
RE	a Boolean which indicates if the model is under rational expectation or not.
data	an optional data frame, list or environment (or object coercible by as.data.frame to a data frame) containing the variables in the model. If not found in data, the variables are taken from environment (formula), typically the environment from which <code>mcmcARD</code> is called.

Details

The left-censored variable y is generated from a latent variable y^* . The latent variable is given for all i as

$$y_i^* = \lambda \mathbf{g}_i y + \mathbf{x}_i' \beta + \mathbf{g}_i \mathbf{X} \gamma + \epsilon_i,$$

where $\epsilon_i \sim N(0, \sigma^2)$.

The censored variable y_i is then defined that is $y_i = 0$ if $y_i^* \leq 0$ and $y_i = y_i^*$ otherwise.

Value

A list consisting of:

yst	ys (see details), the latent variable.
y	the censored variable.
yb	expectation of y under rational expectation.
Gy	the average of y among friends.
Gyb	Average of expectation of y among friends under rational expectation.
marg.effects	the marginal effects.
iteration	number of iterations performed by sub-network in the Fixed Point Iteration Method.

References

Xu, X., & Lee, L. F. (2015). Maximum likelihood estimation of a spatial autoregressive Tobit model. *Journal of Econometrics*, 188(1), 264-280, doi:10.1016/j.jeconom.2015.05.004.

See Also

[sart](#), [simsar](#), [simcdnet](#).

Examples

```
# Groups' size
M <- 5 # Number of sub-groups
nvec <- round(runif(M, 100, 1000))
n <- sum(nvec)

# Parameters
lambda <- 0.4
beta <- c(2, -1.9, 0.8)
gamma <- c(1.5, -1.2)
sigma <- 1.5
theta <- c(lambda, beta, gamma, sigma)

# X
X <- cbind(rnorm(n, 1, 1), rexp(n, 0.4))

# Network
Glist <- list()

for (m in 1:M) {
  nm <- nvec[m]
  Gm <- matrix(0, nm, nm)
  max_d <- 30
  for (i in 1:nm) {
    tmp <- sample((1:nm)[-i], sample(0:max_d, 1))
    Gm[i, tmp] <- 1
  }
  rs <- rowSums(Gm); rs[rs == 0] <- 1
  Gm <- Gm/rs
  Glist[[m]] <- Gm
}
```



```

# data
data  <- data.frame(x1 = X[,1], x2 = X[,2])

rm(list = ls()[!(ls() %in% c("Glist", "data", "theta"))])

ytmp  <- simsart(formula = ~ x1 + x2 | x1 + x2, Glist = Glist,
                 theta = theta, data = data)

y     <- ytmp$y

# plot histogram
hist(y)

```

summary.cdnet

Summarize Count Data Model with Social Interactions

Description

Summary and print methods for the class `cdnet` as returned by the function `cdnet`.

Usage

```

## S3 method for class 'cdnet'
summary(object, Glist, data, S = 1000L, ...)

## S3 method for class 'summary.cdnet'
print(x, ...)

## S3 method for class 'cdnet'
print(x, ...)

## S3 method for class 'cdnets'
summary(object, ...)

## S3 method for class 'summary.cdnets'
print(x, ...)

## S3 method for class 'cdnets'
print(x, ...)

```

Arguments

`object` an object of class `cdnet`, output of the function `cdnet`.

`Glist` adjacency matrix or list sub-adjacency matrix. This is not necessary if the covariance method was computed in `cdnet`.

data	a dataframe containing the explanatory variables. This is not necessary if the covariance method was computed in <code>cdnet</code> .
S	number of simulation to be used to compute integral in the covariance by important sampling.
...	further arguments passed to or from other methods.
x	an object of class <code>summary.cdnet</code> , output of the function <code>summary.cdnet</code> , class <code>summary.cdnets</code> , list of outputs of the function <code>summary.cdnet</code> (when the model is estimated many times to control for the endogeneity) or class <code>cdnet</code> of the function <code>cdnet</code> .

Value

A list of the same objects in object.

summary.sar	<i>Summarize SAR Model</i>
-------------	----------------------------

Description

Summary and print methods for the class `sar` as returned by the function `sar`.

Usage

```
## S3 method for class 'sar'
summary(object, ...)

## S3 method for class 'summary.sar'
print(x, ...)

## S3 method for class 'sar'
print(x, ...)

## S3 method for class 'sars'
summary(object, ...)

## S3 method for class 'summary.sars'
print(x, ...)

## S3 method for class 'sars'
print(x, ...)
```

Arguments

object	an object of class <code>sar</code> , output of the function <code>sar</code> .
...	further arguments passed to or from other methods.
x	an object of class <code>summary.sar</code> , output of the function <code>summary.sar</code> or class <code>sar</code> , output of the function <code>sar</code> .

Value

A list of the same objects in object.

summary.sart	<i>Summarize sart Model</i>
--------------	-----------------------------

Description

Summary and print methods for the class sart as returned by the function [sart](#).

Usage

```
## S3 method for class 'sart'
summary(object, Glist, data, ...)

## S3 method for class 'summary.sart'
print(x, ...)

## S3 method for class 'sart'
print(x, ...)

## S3 method for class 'sarts'
summary(object, ...)

## S3 method for class 'summary.sarts'
print(x, ...)

## S3 method for class 'sarts'
print(x, ...)
```

Arguments

object	an object of class sart, output of the function sart .
Glist	adjacency matrix or list sub-adjacency matrix. This is not necessary if the covariance method was computed in cdnet .
data	dataframe containing the explanatory variables. This is not necessary if the covariance method was computed in cdnet .
...	further arguments passed to or from other methods.
x	an object of class summary.sart, output of the function summary.sart or class sart, output of the function sart .

Value

A list of the same objects in object.

Index

`as.data.frame`, [4](#), [7](#), [10](#), [13](#), [16](#), [18](#), [21](#), [23](#)

`CDatanet` (`CDatanet`-package), [2](#)

`CDatanet`-package, [2](#)

`cdnet`, [3](#), [13](#), [15](#), [16](#), [19](#), [25–27](#)

`formula`, [3](#), [7](#), [10](#), [12](#), [15](#), [18](#), [20](#), [23](#)

`homophily`, [6](#), [11](#)

`homophily.FE`, [7](#), [9](#)

`nlm`, [4](#), [12](#), [15](#)

`optim`, [4](#), [12](#), [15](#)

`print.cdnets` (`summary.cdnets`), [25](#)

`print.cdnets` (`summary.cdnets`), [25](#)

`print.sars` (`summary.sars`), [26](#)

`print.sars` (`summary.sars`), [26](#)

`print.sart` (`summary.sart`), [27](#)

`print.sarts` (`summary.sart`), [27](#)

`print.summary.cdnets` (`summary.cdnets`), [25](#)

`print.summary.cdnets` (`summary.cdnets`), [25](#)

`print.summary.sars` (`summary.sars`), [26](#)

`print.summary.sars` (`summary.sars`), [26](#)

`print.summary.sart` (`summary.sart`), [27](#)

`print.summary.sarts` (`summary.sart`), [27](#)

`sar`, [5](#), [12](#), [16](#), [21](#), [26](#)

`sart`, [5](#), [13](#), [14](#), [24](#), [27](#)

`simcdnets`, [5](#), [17](#), [21](#), [24](#)

`simars`, [13](#), [19](#), [20](#), [24](#)

`simarsart`, [16](#), [19](#), [21](#), [22](#)

`summary.cdnets`, [25](#), [26](#)

`summary.cdnets` (`summary.cdnets`), [25](#)

`summary.sars`, [26](#), [26](#)

`summary.sars` (`summary.sars`), [26](#)

`summary.sart`, [27](#), [27](#)

`summary.sarts` (`summary.sart`), [27](#)