

Package ‘EdSurvey’

July 19, 2021

Version 2.7.0

Date 2021-07-16

Title Analysis of NCES Education Survey and Assessment Data

Author Paul Bailey [aut, cre],
Ahmad Emad [aut],
Huade Huo [aut],
Michael Lee [aut],
Yuqi Liao [aut],
Alex Lishinski [aut],
Trang Nguyen [aut],
Qingshu Xie [aut],
Jiao Yu [aut],
Ting Zhang [aut],
Eric Buehler [aut],
person(`Sun-joo`, ``Lee", role=`aut`),
person(`Emmanuel`, ``Sikali", role=`pdr`, email = `Emmanuel.Sikali@ed.gov`)),
Jeppe Bundsgaard [ctb],
Ren C'deBaca [ctb],
Anders Astrup Christensen [ctb]

Maintainer Paul Bailey <pbailey@air.org>

Depends R (>= 3.5.0), car, lfactors (>= 1.0.3)

Imports data.table (>= 1.11.4), Formula, glm2, haven (>= 2.2.0), LaF (>= 0.7), lme4, MASS, Matrix, methods, NAEPprimer, quantreg, readxl, tibble, wCorr, NAEPirtparams, WeMix (>= 3.1.8), xtable, Dire

URL <https://www.air.org/project/nces-data-r-project-edsurvey>

Description Read in and analyze functions for education survey and assessment data from the National Center for Education Statistics (NCES) <<https://nces.ed.gov/>>, including National Assessment of Educational Progress (NAEP) data <<https://nces.ed.gov/nationsreportcard/>> and data from the International Assessment Database: Organisation for Economic Co-operation and Development (OECD) <<https://www.oecd.org/>>, including Programme for International Student Assessment (PISA), Teaching and Learning International Survey (TALIS), Programme for the Inter-

national Assessment of Adult Competencies (PIAAC), and International Association for the Evaluation of Educational Achievement (IEA) <<https://www.iea.nl/>>, including Trends in International Mathematics and Science Study (TIMSS), TIMSS Advanced, Progress in International Reading Literacy Study (PIRLS), International Civic and Citizenship Study (ICCS), International Computer and Information Literacy Study (ICILS), and Civic Education Study (CivEd).

License GPL-2

VignetteBuilder knitr

Suggests dplyr, knitr, testthat, withr, rmarkdown, RColorBrewer, doParallel, parallel

RoxygenNote 7.1.1

Note This publication was prepared for NCES under Contract No. ED-IES-12-D-0002 with the American Institutes for Research. Mention of trade names, commercial products, or organizations does not imply endorsement by the U.S. Government.

Encoding UTF-8

NeedsCompilation no

Repository CRAN

Date/Publication 2021-07-19 20:20:03 UTC

R topics documented:

EdSurvey-package	4
achievementLevels	5
as.data.frame	9
cbind	9
contourPlot	10
cor.sdf	11
dim.edsurvey.data.frame	15
DoFCorrection	16
downloadCivEDICCS	18
downloadECLS_K	19
downloadELS	20
downloadHSLS	21
downloadICILS	22
downloadPIAAC	22
downloadPIRLS	23
downloadPISA	24
downloadPISA_YAFS	26
downloadTALIS	27
downloadTIMSS	28
downloadTIMSSAdv	29
download_ePIRLS	30
edsurvey.data.frame	31
edsurvey.data.frame.list	36
edsurveyTable	38

edsurveyTable2pdf	42
gap	44
getData	51
getPlausibleValue	54
getWeightJkReplicates	55
glm.sdf	56
hasPlausibleValue	60
isWeight	61
levelsSDF	62
lm.sdf	63
merge	67
mixed.sdf	68
mml.sdf	71
mvrlm.sdf	74
oddsRatio	78
parseNAEPdct	79
percentile	79
print.achievementLevels	82
print.edsurvey.data.frame	83
print.gap	84
readBB_2001	84
readBB_2003	86
readBB_2012	87
readBPS_1994	89
readBPS_2001	90
readBPS_2009	91
readBPS_2014	93
readBTLS	94
readCivEDICCS	95
readECLS_B	97
readECLS_K1998	98
readECLS_K2011	99
readELS	101
readHSB_Senior	103
readHSB_Sophomore	104
readHSLS	106
readICILS	107
readNAEP	109
readNLS72	111
readPIAAC	112
readPIRLS	113
readPISA	115
readPISA_YAFS	117
readTALIS	118
readTIMSS	120
readTIMSSAdv	123
read_ePIRLS	124
rebindAttributes	126

recode.sdf	127
rename.sdf	128
rq.sdf	129
scoreTIMSS	132
SD	133
searchSDF	135
showCodebook	136
showCutPoints	138
showPlausibleValues	138
showWeights	139
subset	140
summary2	142
updatePlausibleValue	144
varEstToCov	145
waldTest	147

Index	150
--------------	------------

EdSurvey-package	<i>Analysis of NCES Education Survey and Assessment Data</i>
------------------	--

Description

The EdSurvey package uses appropriate methods for analyzing NCES datasets with a small memory footprint. Existing system control files, included with the data, are used to read in and format the data for further processing.

Details

To get started using EdSurvey, see the vignettes for tutorials and the statistical methodologies. Use `vignette("introduction", package="EdSurvey")` to see the vignettes.

The package provides functions called `readNAEP`, `readCivEDICCS`, `readICILS`, `readPIAAC`, `readPIRLS`, `read_ePIRLS`, `readPISA`, `readTALIS`, `readTIMSS`, `readTIMSSAdv`, and `readECLS_K2011` to read in NCES datasets. The functions `achievementLevels`, `cor.sdf`, `edsurveyTable`, `summary2`, `lm.sdf`, `logit.sdf`, `mixed.sdf`, `rq.sdf`, `percentile`, and `gap` can then be used to analyze data. For advanced users, `getData` extracts the data of interest as a data frame for further processing.

achievementLevels *Achievement Levels*

Description

Returns achievement levels using weights and variance estimates appropriate for the `edsurvey.data.frame`.

Usage

```
achievementLevels(
  achievementVars = NULL,
  aggregateBy = NULL,
  data,
  cutpoints = NULL,
  returnDiscrete = TRUE,
  returnCumulative = FALSE,
  weightVar = NULL,
  jrrIMax = 1,
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  recode = NULL,
  returnNumberOfPSU = FALSE,
  returnVarEstInputs = FALSE
)
```

Arguments

achievementVars	character vector indicating variables to be included in the achievement levels table, potentially with a subject scale or subscale. When the subject scale or subscale is omitted, the default subject scale or subscale is used. You can find the default composite scale and all subscales using the function showPlausibleValues .
aggregateBy	character vector specifying variables by which to aggregate achievement levels. The percentage column sums up to 100 for all levels of all variables specified here. When set to the default of NULL, the percentage column sums up to 100 for all levels of all variables specified in <code>achievementVars</code> .
data	an <code>edsurvey.data.frame</code>
cutpoints	numeric vector indicating cutpoints. Set to standard NAEP cutpoints for Basic, Proficient, and Advanced by default.
returnDiscrete	logical indicating if discrete achievement levels should be returned. Defaults to TRUE.
returnCumulative	logical indicating if cumulative achievement levels should be returned. Defaults to FALSE. The first and last categories are the same as defined for discrete levels.

weightVar	character string indicating the weight variable to use. Only the name of the weight variable needs to be included here, and any replicate weights will be automatically included. When this argument is NULL, the function uses the default. Use <code>showWeights</code> to find the default.
jrrIMax	a numeric value. When using the jackknife variance estimation method, the default estimation option, <code>jrrIMax=1</code> , uses the sampling variance from the first plausible value as the component for sampling variance estimation. The V_{jrr} term (see <i>Statistical Methods Used in EdSurvey</i> for the definition of V_{jrr}) can be estimated with any number of plausible values, and values larger than the number of plausible values on the survey (including Inf) will result in all plausible values being used. Higher values of <code>jrrIMax</code> lead to longer computing times and more accurate variance estimates.
omittedLevels	a logical value. When set to the default value (TRUE), it drops those levels in all factor variables that are specified in <code>achievementVars</code> and <code>aggregateBy</code> . Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the omitted levels.
defaultConditions	a logical value. When set to the default value of TRUE, uses the default conditions stored in an <code>edsurvey.data.frame</code> to subset the data. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the default conditions.
recode	a list of lists to recode variables. Defaults to NULL. Can be set as <code>recode = list(var1= list(from=c("a", "b", "c"), to="d"))</code> . See Examples.
returnNumberOfPSU	a logical value set to TRUE to return the number of primary sampling units (PSUs)
returnVarEstInputs	a logical value set to TRUE to return the inputs to the jackknife and imputation variance estimates, which allows for the computation of covariances between estimates.

Details

The `achievementLevels` function applies appropriate weights and the variance estimation method for each `edsurvey.data.frame`, with several arguments for customizing the aggregation and output of the analysis results. Namely, by using these optional arguments, users can choose to generate the percentage of students performing at each achievement level (discrete), generate the percentage of students performing at or above each achievement level (cumulative), calculate the percentage distribution of students by achievement level (discrete or cumulative) and selected characteristics (specified in `aggregateBy`), and compute the percentage distribution of students by selected characteristics within a specific achievement level.

Calculation of percentages: The details of the methods are shown in the vignette titled *Statistical Methods Used in EdSurvey* in “Estimation of Weighted Percentages When Plausible Values Are Present” and are used to calculate all cumulative and discrete probabilities.

When the requested achievement levels are discrete (`returnDiscrete = TRUE`), the percentage \mathcal{A} is the percentage of students (within the categories specified in `aggregateBy`) whose scores lie in the range $[cutPoints_i, cutPoints_{i+1})$, $i = 0, 1, \dots, n$. `cutPoints` is the score thresholds provided by the user with `cutPoints_0` taken to be 0. `cutPoints` are set to NAEP standard cut-points for achievement levels by default. To aggregate by a specific variable, for example, `dsex`,

specify `dsex` in `aggregateBy` and all other variables in `achievementVars`. To aggregate by subscale, specify the name of the subscale (e.g., `num_oper`) in `aggregateBy` and all other variables in `achievementVars`.

When the requested achievement levels are cumulative (`returnCumulative = TRUE`), the percentage \mathcal{A} is the percentage of students (within the categories specified in `aggregateBy`) whose scores lie in the range $[\text{cutPoints}_i, \infty)$, $i = 1, 2, \dots, n - 1$. The first and last categories are the same as defined for discrete levels.

Calculation of standard error of percentages: The method used to calculate the standard error of the percentages is described in the vignette titled [Statistical Methods Used in EdSurvey](#) in the sections “Estimation of the Standard Error of Weighted Percentages When Plausible Values Are Present, Using the Jackknife Method” and “Estimation of the Standard Error of Weighted Percentages When Plausible Values Are Not Present, Using the Taylor Series Method.” For “Estimation of the Standard Error of Weighted Percentages When Plausible Values Are Present, Using the Jackknife Method,” the value of `jrrIMax` sets the value of m^* .

Value

A list containing up to two data frames, one discrete achievement levels (when `returnDiscrete` is `TRUE`) and one for cumulative achievement levels (when `returnCumulative` is `TRUE`). The `data.frame` contains the following columns:

Level	one row for each level of the specified achievement cutpoints
Variables in <code>achievementVars</code>	one column for each variable in <code>achievementVars</code> and one row for each level of each variable in <code>achievementVars</code>
Percent	the percentage of students at or above each achievement level aggregated as specified by <code>aggregateBy</code>
StandardError	the standard error of the percentage, accounting for the survey sampling methodology. See the vignette titled Statistical Methods Used in EdSurvey .
N	the number of observations in the incoming data (the number of rows when <code>omittedLevels</code> and <code>defaultConditions</code> are set to <code>FALSE</code>)
wtDN	the weighted number of observations in the data
nPSU	the number of PSUs at or above each achievement level aggregated as specified by <code>aggregateBy</code> . Only returned with <code>returnNumberOfPSU=TRUE</code> .

Author(s)

Huade Huo, Ahmad Emad, and Trang Nguyen

References

Rubin, D. B. (1987). *Multiple imputation for nonresponse in surveys*. New York, NY: Wiley.

as.data.frame	<i>Coerce to a Data Frame</i>
---------------	-------------------------------

Description

Function to coerce a `light.edsurvey.data.frame` to a `data.frame`.

Usage

```
## S3 method for class 'light.edsurvey.data.frame'  
as.data.frame(x, ...)
```

Arguments

x	a <code>light.edsurvey.data.frame</code>
...	other arguments to be passed to as.data.frame

Value

a `data.frame`

Author(s)

Trang Nguyen

cbind	<i>Combine R Objects by Rows or Columns</i>
-------	---

Description

Implements [cbind](#) and [rbind](#) for `light.edsurvey.data.frame` class. It takes a sequence of `vector`, `matrix`, `data.frame`, or `light.edsurvey.data.frame` arguments and combines by columns or rows, respectively.

Usage

```
cbind(..., deparse.level = 1)
```

```
rbind(..., deparse.level = 1)
```

Arguments

...	one or more objects of class <code>vector</code> , <code>data.frame</code> , <code>matrix</code> , or <code>light.edsurvey.data.frame</code>
deparse.level	integer determining under which circumstances column and row names are built from the actual arguments. See cbind .

Details

Because `cbind` and `rbind` are standard generic functions that do not use method dispatch, we set this function as generic, which means it overwrites `base::cbind` and `base::rbind` on loading. If none of the specified elements are of class `light.edsurvey.data.frame`, the function will revert to the standard base method. However, to be safe, you might want to explicitly use `base::cbind` when needed after loading the package.

The returned object will contain attributes only from the first `light.edsurvey.data.frame` object in the call to `cbind.light.edsurvey.data.frame`.

Value

a matrix-like object like `matrix` or `data.frame`. Returns a `light.edsurvey.data.frame` if there is at least one `light.edsurvey.data.frame` in the list of arguments.

Author(s)

Trang Nguyen, Michael Lee, and Paul Bailey

See Also

`cbind`

contourPlot

Overlaid Scatter and Contour Plots

Description

Diagnostic plots for regressions can become too dense to interpret. This function helps by adding a contour plot over the points to allow the density of points to be seen, even when an area is entirely covered in points.

Usage

```
contourPlot(  
  x,  
  y,  
  m = 30L,  
  xrange,  
  yrange,  
  xkernel,  
  ykernel,  
  nlevels = 9L,  
  densityColors = heat.colors(nlevels),  
  pointColors = "gray",  
  ...  
)
```

Arguments

x	numeric vector of the x data to be plotted
y	numeric vector of the y data to be plotted
m	integer value of the number of x and y grid points
xrange	numeric vector of length two indicating x-range of plot; defaults to range(x)
yrange	numeric vector of length two indicating y-range of plot; defaults to range(y)
xkernel	numeric indicating the standard deviation of Normal x kernel to use in generating contour plot
ykernel	numeric indicating the standard deviation of Normal y kernel to use in generating contour plot
nlevels	integer with the number of levels of the contour plot
densityColors	colors to use, specified as in par. Defaults to the heat.colors with nlevels. When specified, colors overrides nlevels.
pointColors	color for the plot points
...	additional arguments to be passed to a plot call that generates the scatter plot and the contour plot

Author(s)

Yuqi Liao and Paul Bailey

Examples

```
## Not run:
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))
lm1 <- lm.sdf(composite ~ pared * dsex + sdracem, sdf)
# plot the results
contourPlot(x=lm1$fitted.values,
            y=lm1$residuals[,1], # use only the first plausible value
            m=30,
            xlab="fitted values",
            ylab="residuals",
            main="Figure 1")
# add a line indicating where the residual is zero
abline(0,0)

## End(Not run)
```

cor.sdf

Bivariate Correlation

Description

Computes the correlation of two variables on an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`. The correlation accounts for plausible values and the survey design.

Usage

```

cor.sdf(
  x,
  y,
  data,
  method = c("Pearson", "Spearman", "Polychoric", "Polyserial"),
  weightVar = "default",
  reorder = NULL,
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  recode = NULL,
  condenseLevels = TRUE,
  fisherZ = if (match.arg(method) %in% "Pearson") { TRUE } else { FALSE },
  jrrIMax = Inf,
  verbose = TRUE
)

```

Arguments

<code>x</code>	a character variable name from the data to be correlated with <code>y</code>
<code>y</code>	a character variable name from the data to be correlated with <code>x</code>
<code>data</code>	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>
<code>method</code>	a character string indicating which correlation coefficient (or covariance) is to be computed. One of <code>Pearson</code> (default), <code>Spearman</code> , <code>Polychoric</code> , or <code>Polyserial</code> . For <code>Polyserial</code> , the continuous argument must be <code>x</code> .
<code>weightVar</code>	character indicating the weight variable to use. See Details section in lm.sdf .
<code>reorder</code>	a list of variables to reorder. Defaults to <code>NULL</code> (no variables are reordered). Can be set as <code>reorder = list(var1 = c("a", "b", "c"), var2 = c("4", "3", "2", "1"))</code> . See Examples.
<code>omittedLevels</code>	a logical value. When set to the default value of <code>TRUE</code> , drops those levels of all factor variables that are specified in an <code>edsurvey.data.frame</code> . Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the omitted levels.
<code>defaultConditions</code>	a logical value. When set to the default value of <code>TRUE</code> , uses the default conditions stored in an <code>edsurvey.data.frame</code> to subset the data. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the default conditions.
<code>recode</code>	a list of lists to recode variables. Defaults to <code>NULL</code> . Can be set as <code>recode = list(var1 = list(from = c("a", "b", "c"), to = "d"))</code> . See Examples.
<code>condenseLevels</code>	a logical value. When set to the default value of <code>TRUE</code> and either <code>x</code> or <code>y</code> is a categorical variable, the function will drop all unused levels and rank the levels of the variable before calculating the correlation. When set to <code>FALSE</code> , the numeric levels of the variable remain the same as in the codebook. See Examples.
<code>fisherZ</code>	for standard error and mean calculations, set to <code>TRUE</code> to use the Fisher Z-transformation (see details), or <code>FALSE</code> to use no transformation of the data. The <code>fisherZ</code> argument defaults to Fisher Z-transformation for <code>Pearson</code> and no transformation for other correlation types.

jrrIMax	a numeric value; when using the jackknife variance estimation method, the default estimation option, <code>jrrIMax=Inf</code> , uses the sampling variance from all plausible values as the component for sampling variance estimation. The <code>Vjrr</code> term (see <i>Statistical Methods Used in EdSurvey</i>) can be estimated with any number of plausible values, and values larger than the number of plausible values on the survey (including <code>Inf</code>) will result in all plausible values being used. Higher values of <code>jrrIMax</code> lead to longer computing times and more accurate variance estimates.
verbose	a logical value. Set to <code>FALSE</code> to avoid messages about variable conversion.

Details

The `getData` arguments and `recode.sdf` may be useful. (See Examples.) The correlation methods are calculated as described in the documentation for the `wCorr` package—see `browseVignettes(package="wCorr")`.

When `method` is set to `polyserial`, all `x` arguments are assumed to be continuous and all `y` assumed discrete. Therefore, be mindful of variable selection as this may result in calculations taking a very long time to complete.

The Fisher Z-transformation is both a variance stabilizing and normalizing transformation for the Pearson correlation coefficient (Fisher, 1915). The transformation takes the inverse hyperbolic tangent of the correlation coefficients and then calculates all variances and confidence intervals. These are then transformed back to the correlation space (values between -1 and 1, inclusive) using the hyperbolic tangent function. The Taylor series approximation (or delta method) is applied for the standard errors.

Value

An `edsurvey.cor` that has `print` and `summary` methods.

The class includes the following elements:

<code>correlation</code>	numeric estimated correlation coefficient
<code>Zse</code>	standard error of the correlation ($V_{imp} + V_{jrr}$). In the case of Pearson, this is calculated in the linear <code>atanh</code> space and is not a standard error in the usual sense.
<code>correlates</code>	a vector of length two showing the columns for which the correlation coefficient was calculated
<code>variables</code>	<code>correlates</code> that are discrete
<code>order</code>	a list that shows the order of each variable
<code>method</code>	the type of correlation estimated
<code>Vjrr</code>	the jackknife component of the variance estimate. For Pearson, in the <code>atanh</code> space.
<code>Vimp</code>	the imputation component of the variance estimate. For Pearson, in the <code>atanh</code> space.
<code>weight</code>	the weight variable used
<code>npv</code>	the number of plausible values used
<code>njk</code>	the number of the jackknife replicates used
<code>n0</code>	the original number of observations

nUsed the number of observations used in the analysis—after any conditions and any listwise deletion of missings is applied

se the standard error of the correlation, in the correlation $([-1,1])$ space

ZconfidenceInterval the confidence interval of the correlation in the transformation space

confidenceInterval the confidence interval of the correlation in the correlation $([-1,1])$ space

transformation the name of the transformation used when calculating standard errors

Author(s)

Paul Bailey; relies heavily on the wCorr package, written by Ahmad Emad and Paul Bailey

References

Fisher, R. A. (1915). Frequency distribution of the values of the correlation coefficient in samples from an indefinitely large population. *Biometrika*, 10(4), 507–521.

See Also

cor and weightedCorr

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# for two categorical variables any of the following work
c1_pears <- cor.sdf(x="b017451", y="b003501", data=sdf, method="Pearson",
                  weightVar="origwt")
c1_spear <- cor.sdf(x="b017451", y="b003501", data=sdf, method="Spearman",
                  weightVar="origwt")
c1_polyc <- cor.sdf(x="b017451", y="b003501", data=sdf, method="Polychoric",
                  weightVar="origwt")

c1_pears
c1_spear
c1_polyc

# for categorical variables, users can either keep the original numeric levels of the variables
# or condense the levels (default)
# the following call condenses the levels of the variable 'c046501'
cor.sdf(x="c046501", y="c044006", data=sdf)

# the following call keeps the original levels of the variable 'c046501'
cor.sdf(x="c046501", y="c044006", data=sdf, condenseLevels = FALSE)

# these take awhile to calculate for large datasets, so limit to a subset
sdf_dnf <- subset(sdf, b003601 == 1)
```

```

# for a categorical variable and a scale score any of the following work
c2_pears <- cor.sdf(x="composite", y="b017451", data=sdf_dnf, method="Pearson",
  weightVar="origwt")
c2_spear <- cor.sdf(x="composite", y="b017451", data=sdf_dnf, method="Spearman",
  weightVar="origwt")
c2_polys <- cor.sdf(x="composite", y="b017451", data=sdf_dnf, method="Polyserial",
  weightVar="origwt")

c2_pears
c2_spear
c2_polys

# recode two variables
cor.sdf(x="c046501", y="c044006", data=sdf, method="Spearman", weightVar="origwt",
  recode=list(c046501=list(from="0%",to="None"),
    c046501=list(from=c("1-5%", "6-10%", "11-25%", "26-50%",
      "51-75%", "76-90%", "Over 90%"),
      to="Between 0% and 100%"),
    c044006=list(from=c("1-5%", "6-10%", "11-25%", "26-50%",
      "51-75%", "76-90%", "Over 90%"),
      to="Between 0% and 100%)))

# reorder two variables
cor.sdf(x="b017451", y="sdracem", data=sdf, method="Spearman", weightVar="origwt",
  reorder=list(sdracem=c("White", "Hispanic", "Black", "Asian/Pacific Island",
    "Amer Ind/Alaska Natv", "Other"),
    b017451=c("Every day", "2 or 3 times a week", "About once a week",
    "Once every few weeks", "Never or hardly ever")))

# recode two variables and reorder
cor.sdf(x="pared", y="b013801", data=subset(sdf, !pared %in% "I Don't Know"),
  method="Spearman", weightVar = "origwt",
  recode=list(pared=list(from="Some ed after H.S.", to="Graduated H.S."),
    pared=list(from="Graduated college", to="Graduated H.S."),
    b013801=list(from="0-10", to="Less than 100"),
    b013801=list(from="11-25", to="Less than 100"),
    b013801=list(from="26-100", to="Less than 100")),
  reorder=list(b013801=c("Less than 100", ">100")))

## End(Not run)

```

dim.edsurvey.data.frame

Dimensions of an edsurvey.data.frame or an edsurvey.data.frame.list

Description

Returns the dimensions of an edsurvey.data.frame or an edsurvey.data.frame.list.

Usage

```
## S3 method for class 'edsurvey.data.frame'
dim(x)
```

Arguments

x an `edsurvey.data.frame` or an `edsurvey.data.frame.list`

Value

For an `edsurvey.data.frame`, returns a numeric vector of length two, with the first element being the number of rows and the second element being the number of columns.

For an `edsurvey.data.frame.list`, returns a list of length two, where the first element is named `nrow` and is a numeric vector containing the number of rows for each element of the `edsurvey.data.frame.list`. The second element is named `ncol` and is the number of columns for each element. This is done so that the `nrow` and `ncol` functions return meaningful results, even if nonstandard.

Author(s)

Paul Bailey

DoFCorrection

Degrees of Freedom

Description

Calculates the degrees of freedom for a statistic (or of a contrast between two statistics) based on the jackknife and imputation variance estimates.

Usage

```
DoFCorrection(
  varEstA,
  varEstB = varEstA,
  varA,
  varB = varA,
  method = c("WS", "JR")
)
```

Arguments

varEstA the `varEstInput` object returned from certain functions, such as `lm.sdf` when `returnVarEstInputs=TRUE`). The variable `varA` must be on this dataset. See Examples.

varEstB similar to the `varEstA` argument. If left blank, both are assumed to come from `varEstA`. When set, the degrees of freedom are for a contrast between `varA` and `varB`, and the `varB` values are taken from `varEstB`.

varA	a character that names the statistic in the varEstA argument for which the degrees of freedom calculation is required.
varB	a character that names the statistic in the varEstB argument for which a covariance is required. When varB is specified, returns the degrees of freedom for the contrast between varA and varB.
method	a character that is either WS for the Welch-Satterthwaite formula or JR for the Johnson-Rust correction to the Welch-Satterthwaite formula

Details

This calculation happens under the notion that statistics have little variance within strata, and some strata will contribute fewer than a full degree of freedom.

The functions are not vectorized, so both varA and varB must contain exactly one variable name.

The method used to compute the degrees of freedom is in the vignette titled *Statistical Methods Used in EdSurvey* section “Estimation of Degrees of Freedom.”

Value

numeric; the estimated degrees of freedom

Author(s)

Paul Bailey

References

Johnson, E. G., & Rust, K. F. (1992). Population inferences and variance estimation for NAEP data. *Journal of Educational Statistics, 17*, 175–190.

Examples

```
## Not run:
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))
lm1 <- lm.sdf(composite ~ dsex + b017451, sdf, returnVarEstInputs=TRUE)
summary(lm1)
# this output agrees with summary of lm1 coefficient for dsex
DoFCorrection(lm1$varEstInputs,
              varA="dsexFemale",
              method="JR")

# second example, a covariance term requires more work
# first, estimate the covariance between two regression coefficients
# note that the variable names are parallel to what they are called in lm1 output
covFEveryDay <- varEstToCov(lm1$varEstInputs,
                          varA="dsexFemale",
                          varB="b017451Every day",
                          jkSumMultiplier=EdSurvey::getAttributes(sdf, "jkSumMultiplier"))
# second, find the difference and the SE of the difference
se <- lm1$coefmat["dsexFemale","se"] + lm1$coefmat["b017451Every day","se"] +
      -2*covFEveryDay
# third, calculate the t-statistic
```

```
tv <- (coef(lm1)["dsexFemale"] - coef(lm1)["b017451Every day])/se
# fourth, calculate the p-value, which requires the estimated degrees of freedom
dofFEveryDay <- DoFCorrection(lm1$varEstInputs,
                             varA="dsexFemale",
                             varB="b017451Every day",
                             method="JR")

# finally, the p-value
2*(1-pt(abs(tv), df=dofFEveryDay))

## End(Not run)
```

downloadCivEDICCS *Instructions for Downloading and Unzipping CivED or ICCS Files*

Description

Provides instructions to download CivED or ICCS data to be processed in readCivEDICCS.

Usage

```
downloadCivEDICCS(years = c(1999, 2009, 2016))
```

Arguments

years an integer vector indicating the study year. Valid years are 1999, 2009, and 2016.

Author(s)

Tom Fink

See Also

[readCivEDICCS](#)

Examples

```
## Not run:
# view instructions to manually download study data
downloadCivEDICCS()

## End(Not run)
```

downloadECLS_K *Download and Unzip ECLS_K Files*

Description

Uses an Internet connection to download ECLS_K data. Data come from nces.ed.gov zip files. This function works for 1998 and 2011 data.

Usage

```
downloadECLS_K(root, years = c(1998, 2011), cache = FALSE, verbose = TRUE)
```

Arguments

root	a character string indicating the directory where the ECLS_K data should be stored. Files are placed in a subdirectory named ECLS_K/[year].
years	an integer vector of the assessment years to download. Valid years are 1998 and 2011.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Details

Beginning for the ECLS_K 2011 Study Grade 5 data files, the ChildK5p.zip source data file is a DEFLATE64 compressed zip file. This means that the user must manually extract the contained childK5p.dat file using an external zip program capable of handling DEFLATE64 zip format. As existing R functions are unable to handle this zip format natively.

Author(s)

Tom Fink

See Also

[readECLS_K1998](#) and [readECLS_K2011](#)

Examples

```
## Not run:  
# root argument will vary by operating system conventions  
downloadECLS_K(years=c(1998, 2011), root = "~/")  
  
# cache=TRUE will download then process the datafiles  
downloadECLS_K(years=c(1998, 2011), root = "~/", cache = TRUE)
```

```
# set verbose=FALSE for silent output
# if year not specified, download all years
downloadECLS_K(root="~/", verbose = FALSE)

## End(Not run)
```

downloadELS

Download and Unzip ELS Files

Description

Uses an Internet connection to download ELS data. Data come from nces.ed.gov zip files. This function works for 2002 data.

Usage

```
downloadELS(root, years = c(2002), cache = FALSE, verbose = TRUE)
```

Arguments

root	a character string indicating the directory where the ELS data should be stored. Files are placed in a subdirectory named ELS/[year].
years	an integer vector of the assessment years to download. Valid year is 2002 only.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Author(s)

Tom Fink

See Also

[readELS](#)

Examples

```
## Not run:
# root argument will vary by operating system conventions
downloadELS(years=2002, root = "~/")

# cache=TRUE will download then process the datafiles
downloadELS(years=2002, root = "~/", cache = TRUE)

# set verbose=FALSE for silent output
```

```
# if year not specified, download all years
downloadELS(root=~"/", verbose = FALSE)

## End(Not run)
```

downloadHSLs *Download and Unzip HSLs Files*

Description

Uses an Internet connection to download HSLs data. Data come from nces.ed.gov zip files. This function works for 2009 data.

Usage

```
downloadHSLs(root, years = c(2009), cache = FALSE, verbose = TRUE)
```

Arguments

root	a character string indicating the directory where the HSLs data should be stored. Files are placed in a subdirectory named HSLs/[year].
years	an integer vector of the assessment years to download. Valid year is 2009 only.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Author(s)

Tom Fink

See Also

[readHSLs](#)

Examples

```
## Not run:
# root argument will vary by operating system conventions
downloadHSLs(root = "~/", years=2009)

# set verbose=FALSE for silent output
# if year not specified, download all years
downloadHSLs(root=~"/", verbose = FALSE)

## End(Not run)
```

`downloadICILS`*Instructions for Downloading and Unzipping ICILS Files*

Description

Provides instructions to download ICILS data to be processed in `readICILS`.

Usage

```
downloadICILS(years = c(2013))
```

Arguments

`years` an integer vector indicating the study year. Valid year is 2013 only.

Author(s)

Tom Fink

See Also

[readICILS](#)

Examples

```
## Not run:  
# view instructions to manually download study data  
downloadICILS()  
  
## End(Not run)
```

`downloadPIAAC`*Download and Unzip PIAAC Files*

Description

Uses an Internet connection to download PIAAC data to a computer. Data come from the OECD website.

Usage

```
downloadPIAAC(root, cycle = 1, cache = FALSE, verbose = TRUE)
```

Arguments

root	a character string indicating the directory where the PIAAC data should be stored. Files are placed in a folder named PIAAC/cycle [cycle number].
cycle	a numeric value indicating the assessment cycle to download. Valid cycle is 1 only.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Author(s)

Eric Buehler, Paul Bailey, and Trang Nguyen

Examples

```
## Not run:  
# download all available data for PIAAC round 1 to "~/PIAAC/Round 1" folder  
# root argument will vary by operating system conventions  
downloadPIAAC(root="~/")  
  
## End(Not run)
```

downloadPIRLS

Download and Unzip PIRLS Files

Description

Uses an Internet connection to download PIRLS data. Data come from timssandpirls.bc.edu zip files. This function works for 2001, 2006, 2011, and 2016 data.

Usage

```
downloadPIRLS(  
  root,  
  years = c(2001, 2006, 2011, 2016),  
  cache = FALSE,  
  verbose = TRUE  
)
```

Arguments

root	a character string indicating the directory where the PIRLS data should be stored. Files are placed in a subdirectory named PIRLS/[year].
years	an integer vector of the assessment years to download. Valid years are 2001, 2006, 2011, and 2016.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Author(s)

Tom Fink

See Also

[readPIRLS](#)

Examples

```
## Not run:
# root argument will vary by operating system conventions
downloadPIRLS(year=c(2006, 2011), root = "~/")

# cache=TRUE will download then process the datafiles
downloadPIRLS(year=2011, root = "~/", cache = TRUE)

# set verbose=FALSE for silent output
# if year not specified, download all years
downloadPIRLS(root="~/", verbose = FALSE)

## End(Not run)
```

downloadPISA

Download and Unzip PISA Files

Description

Uses an Internet connection to download PISA data to a computer. Data come from the OECD website.

Usage

```
downloadPISA(
  root,
  years = c(2000, 2003, 2006, 2009, 2012, 2015, 2018),
  database = c("INT", "CBA", "FIN"),
  cache = FALSE,
  verbose = TRUE
)
```

Arguments

root	a character string indicating the directory where the PISA data should be stored. Files are placed in a folder named PISA/[year].
years	an integer vector of the assessment years to download. Valid years are 2000, 2003, 2006, 2009, 2012, 2015, and 2018.
database	a character vector to indicate which database to download from. For 2012, three databases are available (INT = International, CBA = Computer-Based Assessment, and FIN = Financial Literacy). For other years, only INT is available (for example, if PISA 2015 financial literacy is to be downloaded, the database argument should be set to INT). Defaults to INT.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Details

The function uses `download.file` to download files from provided URLs. Some machines might require a different user agent in HTTP(S) requests. If the downloading gives an error or behaves unexpectedly (e.g., a zip file cannot be unzipped or a data file is significantly smaller than expected), users can toggle `HTTPUserAgent` options to find one that works for their machines. One common alternative option is

```
options(HTTPUserAgent="Mozilla/5.0 (Windows NT 6.1; WOW64; rv:53.0) Gecko/20100101 Firefox/53.0")
```

Beginning in the 2018 data files, the `SPSS_STU_COG.zip` source data file is a DEFLATE64 compressed zip file. This means that the user must manually extract the contained `CY07_MSU_STU_COG.sav` file using an external zip program capable of handling DEFLATE64 zip format, as existing R functions are unable to handle this zip format natively.

Author(s)

Yuqi Liao, Paul Bailey, and Trang Nguyen

See Also

[readPISA](#), [download.file](#), [options](#)

Examples

```
## Not run:  
# download PISA 2012 data (for all three databases)  
downloadPISA(years = 2012, database = c("INT", "CBA", "FIN"), root="~/")  
  
# download PISA 2009, 2012, and 2015 data (International Database only)  
# to C:/PISA/2009, C:/PISA/2012, and C:/PISA/2015 folders, respectively  
downloadPISA(years = c(2009, 2012, 2015), root="~/")  
  
## End(Not run)
```

downloadPISA_YAFS

Instructions for Downloading and Unzipping PISA YAFS Files

Description

Provides instructions to download PISA YAFS data to be processed in readPISA_YAFS.

Usage

```
downloadPISA_YAFS(years = c(2016))
```

Arguments

years an integer vector indicating the study year. Valid year is 2016 only.

Author(s)

Tom Fink

See Also

[readPISA_YAFS](#)

Examples

```
## Not run:  
# view instructions to manually download study data  
downloadPISA_YAFS()  
  
## End(Not run)
```

downloadTALIS	<i>Download and Unzip TALIS Files</i>
---------------	---------------------------------------

Description

Uses an Internet connection to download TALIS data. Data come from [OECD TALIS site](#) international zip files. This function works for 2008, 2013, and 2018 data.

Usage

```
downloadTALIS(root, years = c(2008, 2013, 2018), cache = FALSE, verbose = TRUE)
```

Arguments

root	a character string indicating the directory where the TALIS data should be stored. Files are placed in a subdirectory named TALIS/[year].
years	a numeric value indicating the assessment year. Available years are 2008, 2013, and 2018.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Author(s)

Tom Fink and Trang Nguyen

See Also

[readTALIS](#)

Examples

```
## Not run:
# root argument will vary by operating system conventions
downloadTALIS(root = "~/", years = 2018)

# cache=TRUE will download then process the datafiles
downloadTALIS(root = "~/", years = 2015, cache = TRUE)

# set verbose=FALSE for silent output
# if year not specified, download all years
downloadTALIS(root="~/", verbose = FALSE)

## End(Not run)
```

downloadTIMSS *Download and Unzip TIMSS Files*

Description

Uses an Internet connection to download TIMSS data. Data come from timssandpirls.bc.edu zip files. This function works for 2003, 2007, 2011, 2015, and 2019 data.

Usage

```
downloadTIMSS(  
  root,  
  years = c(2003, 2007, 2011, 2015, 2019),  
  cache = FALSE,  
  verbose = TRUE  
)
```

Arguments

root	a character string indicating the directory where the TIMSS data should be stored. Files are placed in a subdirectory named TIMSS/[year].
years	an integer vector of the assessment years to download. Valid years are 2003, 2007, 2011, 2015, and 2019.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Author(s)

Tom Fink

See Also

[readTIMSS](#)

Examples

```
## Not run:  
# root argument will vary by operating system conventions  
downloadTIMSS(year=c(2019, 2015, 2011), root = "~/")  
  
# cache=TRUE will download then process the datafiles  
downloadTIMSS(year=2015, root = "~/", cache = TRUE)  
  
# set verbose=FALSE for silent output
```

```
# if year not specified, download all years
downloadTIMSS(root="~/", verbose = FALSE)

## End(Not run)
```

downloadTIMSSAdv *Download and Unzip TIMSS Advanced Files*

Description

Uses an Internet connection to download TIMSS Advanced data. Data come from timssand-pirls.bc.edu zip files. This function works for 1995, 2008, and 2015 data.

Usage

```
downloadTIMSSAdv(
  root,
  years = c(1995, 2008, 2015),
  cache = FALSE,
  verbose = TRUE
)
```

Arguments

root	a character string indicating the directory where the TIMSS Advanced data should be stored. Files are placed in a subdirectory named TIMSSAdv/[year].
years	an integer vector of the assessment years to download. Valid years are 1995, 2008, and 2015.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Author(s)

Tom Fink

See Also

[readTIMSSAdv](#)

Examples

```
## Not run:
# root argument will vary by operating system conventions
downloadTIMSSAdv(year=c(2008, 2015), root = "~/")

# cache=TRUE will download then process the datafiles
downloadTIMSSAdv(year=2015, root = "~/", cache = TRUE)

# set verbose=FALSE for silent output
# if year not specified, download all years
downloadTIMSSAdv(root="~/", verbose = FALSE)

## End(Not run)
```

download_ePIRLS

Download and Unzip ePIRLS Files

Description

Uses an Internet connection to download ePIRLS data. Data come from timssandpirls.bc.edu zip files. This function works for 2016 data.

Usage

```
download_ePIRLS(root, years = c(2016), cache = FALSE, verbose = TRUE)
```

Arguments

root	a character string indicating the directory where the ePIRLS data should be stored. Files are placed in a subdirectory named ePIRLS/[year].
years	an integer vector of the assessment years to download. Valid year is 2016 only.
cache	a logical value set to process and cache the text (.txt) version of files. This takes a very long time but saves time for future uses of the data. Default value is FALSE.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Author(s)

Tom Fink

See Also

[read_ePIRLS](#)

Examples

```
## Not run:
# root argument will vary by operating system conventions
download_ePIRLS(years=2016, root = "~/")

# cache=TRUE will download then process the datafiles
download_ePIRLS(years=2016, root = "~/", cache = TRUE)

# set verbose=FALSE for silent output
# if year not specified, download all years
download_ePIRLS(root="~/", verbose = FALSE)

## End(Not run)
```

edsurvey.data.frame *EdSurvey Class Constructors and Helpers*

Description

Two new classes in EdSurvey are described in this section: the `edsurvey.data.frame` and `light.edsurvey.data.frame`. The `edsurvey.data.frame` class stores metadata about survey data, and data are stored on the disk (via the LaF package), allowing gigabytes of data to be used easily on a machine otherwise inappropriate for manipulating large datasets. The `light.edsurvey.data.frame` is typically generated by the `getData` function and stores the data in a `data.frame`. Both classes use attributes to manage metadata and allow for correct statistics to be used in calculating results; the `getAttributes` acts as an accessor for these attributes, whereas `setAttributes` acts as a mutator for the attributes. As a convenience, `edsurvey.data.frame` implements the `$` function to extract a variable.

Usage

```
edsurvey.data.frame(
  userConditions,
  defaultConditions,
  dataList = list(),
  weights,
  pvvars,
  subject,
  year,
  assessmentCode,
  dataType,
  gradeLevel,
  achievementLevels,
  omittedLevels,
  survey,
  country,
  psuVar,
  stratumVar,
```

```

    jkSumMultiplier,
    recodes = NULL,
    validateFactorLabels = FALSE,
    forceLower = TRUE,
    reqDecimalConversion = TRUE,
    fr2Path = NULL,
    dim0 = NULL
)

## S3 method for class 'edsurvey.data.frame'
x$i

## S3 replacement method for class 'edsurvey.data.frame'
x$name <- value

## S4 method for signature 'edsurvey.data.frame,ANY'
x %in% table

## S4 method for signature 'edsurvey.data.frame.list,ANY'
x %in% table

getAttributes(data, attribute = NULL)

setAttributes(data, attribute, value)

getPSUVar(
  data,
  weightVar = attributes(getAttributes(data, "weights"))[["default"]]
)

getStratumVar(
  data,
  weightVar = attributes(getAttributes(data, "weights"))[["default"]]
)

```

Arguments

`userConditions` a list of user conditions that includes subsetting or recoding conditions

`defaultConditions`
a list of default conditions that often are set for each survey

`dataList` a list of `dataListItem` objects to model the data structure of the survey

`weights` a list that stores information regarding weight variables. See [Details](#).

`pvvars` a list that stores information regarding plausible values. See [Details](#).

`subject` a character that indicates the subject domain of the given data

`year` a character or numeric that indicates the year of the given data

`assessmentCode` a character that indicates the code of the assessment. Can be National or International.

<code>dataType</code>	a character that indicates the unit level of the main data. Examples include Student, teacher, school, Adult Data.
<code>gradeLevel</code>	a character that indicates the grade level of the given data
<code>achievementLevels</code>	a list of achievement-level categories and cutpoints
<code>omittedLevels</code>	a list of default omitted levels for the given data
<code>survey</code>	a character that indicates the name of the survey
<code>country</code>	a character that indicates the country of the given data
<code>psuVar</code>	a character that indicates the PSU sampling unit variable. Ignored when weights have <code>psuVar</code> defined.
<code>stratumVar</code>	a character that indicates the stratum variable. Ignored when weights have <code>stratumVar</code> defined.
<code>jkSumMultiplier</code>	a numeric value of the jackknife coefficient (used in calculating the jackknife replication estimation)
<code>recodes</code>	a list of variable recodes of the given data
<code>validateFactorLabels</code>	a Boolean that indicates whether the <code>getData</code> function needs to validate factor variables
<code>forceLower</code>	a Boolean; when set to TRUE, will automatically lowercase variable names
<code>reqDecimalConversion</code>	a Boolean; when set to TRUE, a <code>getData</code> call will multiply the raw file value by a decimal multiplier
<code>fr2Path</code>	a character file location for NAEP assessments to identify the location of the codebook file in <code>fr2</code> format
<code>dim0</code>	numeric vector of length two. To speed construction, the dimensions of the data can be provided
<code>x</code>	an <code>edsurvey.data.frame</code>
<code>i</code>	a character, the column name to extract
<code>name</code>	a character vector of the column to edit
<code>value</code>	outside of the assignment context, new value of the given attribute
<code>table</code>	an <code>edsurvey.data.frame</code> or <code>edsurvey.data.frame.list</code> where <code>x</code> is searched for
<code>data</code>	an <code>edsurvey.data.frame</code>
<code>attribute</code>	a character, name of an attribute to get or set
<code>weightVar</code>	a character indicating the full sample weights

Details

The weight list has an element named after each weight variable name that is a list with elements `jkbase` and `jksuffixes`. The `jkbase` variable is a single character indicating the jackknife replicate weight base name, whereas `jksuffixes` is a vector with one element for each jackknife

replicate weight. When the two are pasted together, they should form the complete set of the jack-knife replicate weights. The `weights` argument also can have an attribute that is the default weight. If the primary sampling unit and stratum variables change by weight, they also can be defined on the weight list as `psuVar` and `stratumVar`. When this option is used, it overrides the `psuVar` and `stratumVar` on the `edsurvey.data.frame`, which can be left blank. A weight must define only one of `psuVar` and `stratumVar`.

The `pvvars` list has an element for each subject or subscale score that has plausible values. Each element is a list with a `varnames` element that indicates the column names of the plausible values and an `achievementLevel` argument that is a named vector of the achievement-level cutpoints.

Value

An object of class `edsurvey.data.frame` with the following elements:

Elements that store data connections and data codebooks

`dataList` a list object containing the surveys `dataListItem` objects

Elements that store sample design and default subsetting information of the given survey data

`userConditions` a list containing all user conditions, set using the `subset.edsurvey.data.frame` method

`defaultConditions`
the default subsample conditions

`weights` a list containing the weights. See Details.

`stratumVar` a character that indicates the default strata identification variable name in the data. Often used in Taylor series estimation.

`psuVar` a character that indicates the default PSU (sampling unit) identification variable name in the data. Often used in Taylor series estimation.

`pvvars` a list containing the plausible values. See Details.

`achievementLevels`
default achievement cutoff scores and names. See Details.

`omittedLevels` the levels of the factor variables that will be omitted from the `edsurvey.data.frame`

Elements that store descriptive information of the survey

`survey` the type of survey data

`subject` the subject of the data

`year` the year of assessment

`assessmentCode` the assessment code

`dataType` the type of data (e.g., student or school)

`gradeLevel` the grade of the dataset contained in the `edsurvey.data.frame`

EdSurvey Classes

`edsurvey.data.frame` is an object that stores connection to data on the disk along with important survey sample design information.

`edsurvey.data.frame.list` is a list of `edsurvey.data.frame` objects. It often is used in trend or cross-regional analysis in the `gap` function. See `edsurvey.data.frame.list` for more information on how to create an `edsurvey.data.frame.list`. Users also can refer to the vignette titled *Using EdSurvey for Trend Analysis* for examples.

Besides `edsurvey.data.frame` class, the EdSurvey package also implements the `light.edsurvey.data.frame` class, which can be used by both EdSurvey and non-EdSurvey functions. More particularly, `light.edsurvey.data.frame` is a `data.frame` that has basic survey and sample design information (i.e., plausible values and weights), which will be used for variance estimation in analytical functions. Because it also is a base R `data.frame`, users can apply base R functions for data manipulation. See the vignette titled *Using the getData Function in EdSurvey* for more examples.

Many functions will remove attributes from a data frame, such as a `light.edsurvey.data.frame`, and the `rebindAttributes` function can add them back.

Users can get a `light.edsurvey.data.frame` object by using the `getData` method with `addAttributes=TRUE`.

Basic Methods for EdSurvey Classes

Extracting a column from an edsurvey.data.frame

Users can extract a column from an `edsurvey.data.frame` object using `$` or `[]` like a normal data frame.

Extracting and updating attributes of an object of class edsurvey.data.frame or light.edsurvey.data.frame

Users can use the `getAttributes` method to extract any attribute of an `edsurvey.data.frame` or a `light.edsurvey.data.frame`. A `light.edsurvey.data.frame` will not have attributes related to data connection because data have already been read in memory.

If users want to update an attribute (i.e., `omittedLevels`), they can use the `setAttributes` method.

Author(s)

Tom Fink, Trang Nguyen, and Paul Bailey

See Also

[rebindAttributes](#)

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# run a base R function on a column of edsurvey.data.frame
table(sdf$dsex)
# assignment
table(sdf$b013801)
sdf$books <- ifelse(sdf$b013801 %in% c("0-10", "11-25"), "0-25 books", "26+ books")
```

```

table(sdf$books, sdf$b013801)

# extract default omitted levels of NAEP primer data
getAttributes(sdf, "omittedLevels") #[1] "Multiple" NA          "Omitted"

# update default omitted levels of NAEP primer data
sdf <- setAttributes(sdf, "omittedLevels", c("Multiple", "Omitted", NA, "(Missing)"))
getAttributes(sdf, "omittedLevels") #[1] "Multiple" "Omitted" NA          "(Missing)"

## End(Not run)

```

edsurvey.data.frame.list

EdSurvey Dataset Vectorization

Description

The `edsurvey.data.frame.list` function creates an `edsurvey.data.frame.list` object from a series of `edsurvey.data.frame` objects. `append.edsurvey.data.frame.list` creates an `edsurvey.data.frame.list` from two `edsurvey.data.frame` or `edsurvey.data.frame.list` objects.

An `edsurvey.data.frame.list` is useful for looking at data, for example, across time or graphically, and reduces repetition in function calls. The user may specify a variable that varies across the `edsurvey.data.frame` objects that is then included in further output.

Usage

```
edsurvey.data.frame.list(datalist, cov = NULL, labels = NULL)
```

```
append.edsurvey.data.frame.list(sdfA, sdfB, labelsA = NULL, labelsB = NULL)
```

Arguments

<code>datalist</code>	a list of <code>edsurvey.data.frame</code> s to be combined
<code>cov</code>	a character vector that indicates what varies across the <code>edsurvey.data.frame</code> objects. Guessed if not supplied. For example, if several <code>edsurvey.data.frame</code> s for several different countries are supplied, then <code>cov</code> would be set to the country.
<code>labels</code>	a character vector that specifies labels. Must be the same length as <code>datalist</code> . Not needed if <code>cov</code> exists or can be guessed. See Examples.
<code>sdfA</code>	an <code>edsurvey.data.frame</code> or an <code>edsurvey.data.frame.list</code> to be combined
<code>sdfB</code>	an <code>edsurvey.data.frame</code> or an <code>edsurvey.data.frame.list</code> to be combined
<code>labelsA</code>	a character vector that specifies labels for <code>sdfA</code> when creating the new <code>edsurvey.data.frame.list</code> . <code>labelsA</code> would be ignored if <code>sdfA</code> is an <code>edsurvey.data.frame.list</code> with labels supplied.
<code>labelsB</code>	a character vector that specifies labels for <code>sdfB</code> when creating the new <code>edsurvey.data.frame.list</code> . <code>labelsB</code> would be ignored if <code>sdfB</code> is an <code>edsurvey.data.frame.list</code> with labels supplied.

Details

The `edsurvey.data.frame.list` can be used in place of an `edsurvey.data.frame` in function calls, and results are returned for each of the component `edsurvey.data.frame`s, with the organization of the results varying by the particular method.

An `edsurvey.data.frame.list` can be created from several `edsurvey.data.frame` objects that are related; for example, all are NAEP mathematics assessments but have one or more differences (e.g., they are all from different years). Another example could be data from multiple countries for an international assessment.

When `cov` and `labels` are both missing, `edsurvey.data.frame.list` attempts to guess what variables may be varying and uses those. When there are no varying covariates, generic labels are automatically generated.

Value

`edsurvey.data.frame.list` returns an `edsurvey.data.frame.list` with elements

<code>datalist</code>	a list of <code>edsurvey.data.frame</code> objects
<code>covs</code>	a character vector of key variables that vary within the <code>edsurvey.data.frame.list</code> . When labels are included, they will be included in <code>covs</code> . In the unusual circumstance that <code>sdfA</code> or <code>sdfB</code> is an <code>edsurvey.data.frame.list</code> has <code>covs</code> , and labels are not supplied, the <code>covs</code> are simply pasted together with colons between them.

`append.edsurvey.data.frame.list` returns an `edsurvey.data.frame.list` with elements

<code>datalist</code>	a list of <code>edsurvey.data.frame</code> objects
<code>covs</code>	a character vector of key variables that vary within the <code>edsurvey.data.frame.list</code> . When labels are included, they will be included in <code>covs</code> .

Author(s)

Paul Bailey, Huade Huo

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# NOTE: the following code would not normally have to be run but is used here
# to generate demo data.
# Specifically, make subsets of sdf by the scrpsu variable,
# "Scrambled PSU and school code"
sdfA <- subset(sdf, scrpsu %in% c(5,45,56))
sdfB <- subset(sdf, scrpsu %in% c(75,76,78))
sdfC <- subset(sdf, scrpsu %in% 100:200)
sdfD <- subset(sdf, scrpsu %in% 201:300)

# construct an edsurvey.data.frame.list from these four data sets
sdf1 <- edsurvey.data.frame.list(list(sdfA, sdfB, sdfC, sdfD),
```

```

                                labels=c("A locations",
                                           "B locations",
                                           "C locations",
                                           "D locations"))

# alternative method of building
sdf12 <- sdfA + sdfB + sdfC

# check contents
sdfA %in% sdf1
# note %in% checks by survey (NAEP 2005 Math for sdf,
# sdfA, sdfB, sdfC, and sdfD) not by subset, so this also return TRUE
sdfD %in% sdf12

# this shows how these datasets will be described
sdf1$covs
# get the gaps between Male and Female for each data set
gap1 <- gap("composite", sdf1, dsex=="Male", dsex=="Female")
gap1

# make combine sdfA and sdfB
sdf11a <- edsurvey.data.frame.list(list(sdfA, sdfB),
                                   labels=c("A locations",
                                             "B locations"))

# combine sdfC and sdfD
sdf11b <- edsurvey.data.frame.list(list(sdfC, sdfD),
                                   labels=c("C locations",
                                             "D locations"))

# append to make sdf3 the same as sdf1
sdf13 <- append.edsurvey.data.frame.list(sdf11a, sdf11b)
identical(sdf1, sdf13) #TRUE

# append to make sdf4 the same as sdf1
sdf14 <- append.edsurvey.data.frame.list(
  append.edsurvey.data.frame.list(sdf11a, sdfC, labelsB = "C locations"),
  sdfD,
  labelsB = "D locations")
identical(sdf1, sdf14) #TRUE

## End(Not run)

```

edsurveyTable

EdSurvey Tables With Conditional Means

Description

Returns a summary table (as a data.frame) that shows the number of students, the percentage of students, and the mean value of the outcome (or left-hand side) variable by the predictor (or right-hand side) variable(s).

Usage

```
edsurveyTable(
  formula,
  data,
  weightVar = NULL,
  jrrIMax = 1,
  pctAggregationLevel = NULL,
  returnMeans = TRUE,
  returnSepct = TRUE,
  varMethod = c("jackknife", "Taylor"),
  drop = FALSE,
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  recode = NULL,
  returnVarEstInputs = FALSE
)
```

Arguments

formula	object of class <code>formula</code> , potentially with a subject scale or subscale on the left-hand side and variables to tabulate on the right-hand side. When the left-hand side of the formula is omitted and <code>returnMeans</code> is <code>TRUE</code> , then the default subject scale or subscale is used. You can find the default composite scale and all subscales using the function showPlausibleValues . Note that the order of the right-hand side variables affects the output.
data	object of class <code>edsurvey.data.frame</code> . See readNAEP for how to generate an <code>edsurvey.data.frame</code> .
weightVar	character string indicating the weight variable to use. Note that only the name of the weight variable needs to be included here, and any replicate weights will be automatically included. When this argument is <code>NULL</code> , the function uses the default. Use showWeights to find the default.
jrrIMax	a numeric value; when using the jackknife variance estimation method, the default estimation option, <code>jrrIMax=1</code> , uses the sampling variance from the first plausible value as the component for sampling variance estimation. The V_{jrr} term (see the Details section of lm.sdf to see the definition of V_{jrr}) can be estimated with any number of plausible values, and values larger than the number of plausible values on the survey (including <code>Inf</code>) will result in all of the plausible values being used. Higher values of <code>jrrIMax</code> lead to longer computing times and more accurate variance estimates.
pctAggregationLevel	the percentage variable sums up to 100 for the first <code>pctAggregationLevel</code> columns. So, when set to <code>0</code> , the PCT column adds up to 1 across the entire sample. When set to 1, the PCT column adds up to 1 within each level of the first variable on the right-hand side of the formula; when set to 2, then the percentage adds up to 100 within the interaction of the first and second variable, and so on. Default is <code>NULL</code> , which will result in the lowest feasible aggregation level. See Examples section.

returnMeans	a logical value; set to TRUE (the default) to get the MEAN and SE(MEAN) columns in the returned table described in the Value section.
returnSepct	set to TRUE (the default) to get the SEPCT column in the returned table described in the Value section.
varMethod	a character set to jackknife or Taylor that indicates the variance estimation method to be used.
drop	a logical value. When set to the default value of FALSE, when a single column is returned, it is still represented as a data.frame and is not converted to a vector.
omittedLevels	a logical value. When set to the default value of TRUE, drops those levels of all factor variables that are specified in an edsurvey.data.frame. Use print on an edsurvey.data.frame to see the omitted levels.
defaultConditions	a logical value. When set to the default value of TRUE, uses the default conditions stored in an edsurvey.data.frame to subset the data. Use print on an edsurvey.data.frame to see the default conditions.
recode	a list of lists to recode variables. Defaults to NULL. Can be set as recode = list(var1 = list(from = c("a", "b", "c"), to = "c")).
returnVarEstInputs	a logical value set to TRUE to return the inputs to the jackknife and imputation variance estimates, which allows for the computation of covariances between estimates.

Details

This method can be used to generate a simple one-way, two-way, or n -way table with unweighted and weighted n values and percentages. It also can calculate the average of the subject scale or subscale for students at each level of the cross-tabulation table.

A detailed description of all statistics is given in the vignette titled *Statistical Methods Used in EdSurvey*.

Value

A table with the following columns:

RHS levels	one column for each right-hand side variable. Each row regards students who are at the levels shown in that row.
N	count of the number of students in the survey in the RHS levels
WTD_N	the weighted N count of students in the survey in RHS levels
PCT	the percentage of students at the aggregation level specified by pctAggregationLevel (see Arguments). See the vignette titled <i>Statistical Methods Used in EdSurvey</i> in the section “Estimation of Weighted Percentages” and its first subsection “Estimation of Weighted Percentages When Plausible Values Are Not Present.”
SE(PCT)	the standard error of the percentage, accounting for the survey sampling methodology. When varMethod is the jackknife, the calculation of this column is described in the vignette titled <i>Statistical Methods Used in EdSurvey</i> in the section

	“Estimation of the Standard Error of Weighted Percentages When Plausible Values Are Not Present, Using the Jackknife Method.” When varMethod is set to Taylor, the calculation of this column is described in “Estimation of the Standard Error of Weighted Percentages When Plausible Values Are Not Present, Using the Taylor Series Method.”
MEAN	the mean assessment score for units in the RHS levels, calculated according to the vignette titled <i>Statistical Methods Used in EdSurvey</i> in the section “Estimation of Weighted Means When Plausible Values Are Present.”
SE(MEAN)	the standard error of the MEAN column (the mean assessment score for units in the RHS levels), calculated according to the vignette titled <i>Statistical Methods Used in EdSurvey</i> in the sections “Estimation of Standard Errors of Weighted Means When Plausible Values Are Present, Using the Jackknife Method” or “Estimation of Standard Errors of Weighted Means When Plausible Values Are Present, Using the Taylor Series Method,” depending on the value of varMethod.

When returnVarEstInputs is TRUE, two additional elements are returned. These are meanVarEstInputs and pctVarEstInputs and regard the MEAN and PCT columns, respectively. These two objects can be used for calculating covariances with `varEstToCov`.

Author(s)

Paul Bailey and Ahmad Emad

References

- Binder, D. A. (1983). On the variances of asymptotically normal estimators from complex surveys. *International Statistical Review*, 51(3), 279–292.
- Rubin, D. B. (1987). *Multiple imputation for nonresponse in surveys*. New York, NY: Wiley.

Examples

```
## Not run:
# read in the example data (generated, not real student data)

sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# create a table that shows only the breakdown of dsex
edsurveyTable(composite ~ dsex, data=sdf, returnMeans=FALSE, returnSepct=FALSE)

# create a table with composite scores by dsex
edsurveyTable(composite ~ dsex, data=sdf)

# add a second variable
edsurveyTable(composite ~ dsex + b017451, data=sdf)

# add a second variable, do not omit any levels
edsurveyTable(composite ~ dsex + b017451 + b003501, data=sdf, omittedLevels=FALSE)

# add a second variable, do not omit any levels, change aggregation level
edsurveyTable(composite ~ dsex + b017451 + b003501, data=sdf, omittedLevels=FALSE,
```

```

      pctAggregationLevel=0)

edsurveyTable(composite ~ dsex + b017451 + b003501, data=sdf, omittedLevels=FALSE,
              pctAggregationLevel=1)

edsurveyTable(composite ~ dsex + b017451 + b003501, data=sdf, omittedLevels=FALSE,
              pctAggregationLevel=2)

# variance estimation using the Taylor series
edsurveyTable(composite ~ dsex + b017451 + b003501, data=sdf, varMethod="Taylor")

## End(Not run)

```

edsurveyTable2pdf *PDF File From an edsurveyTable*

Description

Produces the LaTeX code and compiles to a PDF file from the edsurveyTable results.

Usage

```

edsurveyTable2pdf(
  data,
  formula,
  caption = NULL,
  filename = "",
  toCSV = "",
  returnMeans = TRUE,
  estDigits = 2,
  seDigits = 3
)

```

Arguments

data	the result of a call to edsurveyTable
formula	a formula of the form LHS ~ RHS to cast the edsurveyTable results from long format to wide format. This formula takes the form LHS ~ RHS (e.g., var1 + var2 ~ var3). The order of the entries in the formula is essential.
caption	character vector of length one or two containing the table's caption or title. If the length is two, the second item is the "short caption" used when LaTeX generates a List of Tables. Set to NULL to suppress the caption. Default value is NULL.
filename	a character string containing filenames and paths. By default (filename = ""), table will be saved in the working directory (getwd()). Use filename = "CONSOLE" to print LaTeX code in R console without generating a PDF file.
toCSV	a character string containing filenames and paths of .csv table output. "" indicates no .csv output. toCSV is independent to filename, so both a csv file and PDF file would be generated if both filename and toCSV were specified.

returnMeans	a logical value set to TRUE (the default) to generate a PDF with the MEAN and SE(MEAN). It is set to FALSE to generate a PDF with the PCT and SE(PCT). See Value in edsurveyTable .
estDigits	an integer indicating the number of decimal places to be used for estimates. Negative values are allowed. See Details.
seDigits	an integer indicating the number of decimal places to be used for standard errors. Negative values are allowed.

Details

Rounding to a negative number of digits means rounding to a power of 10, so, for example, `estDigits = -2` rounds estimates to the nearest hundred.

Note

For more details, see the vignette titled *Producing LaTeX Tables From edsurveyTable Results With edsurveyTable2pdf*.

Author(s)

Huade Huo

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# create a table with composite scores by dsex and b017451
est1 <- edsurveyTable(composite ~ dsex + b017451, sdf)

# create a table with csv output
edsurveyTable2pdf(data = est1,
  formula = b017451~dsex,
  toCSV = "C:/example table.csv",
  filename = "C:/example table.pdf",
  returnMeans = FALSE)

# create a pdf file using the default subject scale or subscale
# and keep two digits for estimates and three digits for SE after decimal point
edsurveyTable2pdf(est1, b017451~dsex,
  returnMeans = TRUE, estDigits = 2, seDigits = 3)

# create a pdf file using the percentage of students at the
# aggregation level specified by \code{pctAggregationLevel}
# output will be saved as "C:/example table.pdf"
edsurveyTable2pdf(est1,
  b017451~dsex,
  "C:/example table.pdf",
  returnMeans = FALSE)
```

```
## End(Not run)
```

gap

Gap Analysis

Description

Compares the average levels of a variable between two groups that potentially share members.

Usage

```
gap(
  variable,
  data,
  groupA = "default",
  groupB = "default",
  percentiles = NULL,
  achievementLevel = NULL,
  achievementDiscrete = FALSE,
  stDev = FALSE,
  targetLevel = NULL,
  weightVar = NULL,
  jrrIMax = 1,
  varMethod = c("jackknife"),
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  recode = NULL,
  referenceDataIndex = 1,
  returnVarEstInputs = FALSE,
  returnSimpleDoF = FALSE,
  returnSimpleN = FALSE,
  returnNumberOfPSU = FALSE,
  noCov = FALSE,
  pctMethod = c("unbiased", "symmetric", "simple"),
  includeLinkingError = FALSE
)
```

Arguments

variable	a character indicating the variable to be compared, potentially with a subject scale or subscale
data	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>
groupA	an expression or character expression that defines a condition for the subset. This subset will be compared to groupB. If not specified, it will define a whole sample as in data.

groupB	an expression or character expression that defines a condition for the subset. This subset will be compared to groupA. If not specified, it will define a whole sample as in data. If set to NULL, estimates for the second group will be dropped.
percentiles	a numeric vector. The gap function calculates the mean when this argument is omitted or set to NULL. Otherwise, the gap at the percentile given is calculated.
achievementLevel	the achievement level(s) at which percentages should be calculated
achievementDiscrete	a logical indicating if the achievement level specified in the achievementLevel argument should be interpreted as discrete so that just the percentage in that particular achievement level will be included. Defaults to FALSE so that the percentage at or above that achievement level will be included in the percentage.
stDev	a logical, set to TRUE to calculate the gap in standard deviations.
targetLevel	a character string. When specified, calculates the gap in the percentage of students at targetLevel in the variable argument. This is useful for comparing the gap in the percentage of students at a survey response level.
weightVar	a character indicating the weight variable to use. See Details.
jrrIMax	a numeric value; when using the jackknife variance estimation method, the default estimation option, jrrIMax=1, uses the sampling variance from the first plausible value as the component for sampling variance estimation. The Vjrr term, or sampling variance term, can be estimated with any number of plausible values, and values larger than the number of plausible values on the survey (including Inf) will result in all plausible values being used. Higher values of jrrIMax lead to longer computing times and more accurate variance estimates.
varMethod	deprecated parameter, gap always uses the jackknife variance estimation
omittedLevels	a logical value. When set to the default value of TRUE, drops those levels of all factor variables. Use print on an edsurvey.data.frame to see the omitted levels.
defaultConditions	a logical value. When set to the default value of TRUE, uses the default conditions stored in edsurvey.data.frame to subset the data. Use print on an edsurvey.data.frame to see the default conditions.
recode	a list of lists to recode variables. Defaults to NULL. Can be set as recode = list(var1 = list(from = c("a", "b", "c"), to = "d")).
referenceDataIndex	a numeric used only when the data argument is an edsurvey.data.frame.list, indicating which dataset is the reference dataset that other datasets are compared with. Defaults to 1.
returnVarEstInputs	a logical value; set to TRUE to return the inputs to the jackknife and imputation variance estimates which allows for the computation of covariances between estimates.
returnSimpleDoF	a logical value set to TRUE to return the degrees of freedom for some statistics (see Value section) that do not have a <i>t</i> -test; useful primarily for further computation

returnSimpleN	a logical value set to TRUE to add the count (<i>n</i> -size) of observations included in groups A and B in the percentage object
returnNumberOfPSU	a logical value set to TRUE to return the number of PSUs used in the calculation
noCov	set the covariances to zero in result
pctMethod	a character that is one of unbiased or simple. See the help for percentile for more information.
includeLinkingError	a logical value set to TRUE to include the linking error in variance estimation. Standard errors (e.g., <code>diffAAse</code> , <code>diffBBse</code> , and <code>diffABABse</code>) and <i>p</i> -values (e.g., <code>diffAAPvalue</code> , <code>diffBBpvalue</code> , and <code>diffABABpvalue</code>) would be adjusted for comparisons between digitally based assessments (DBA) and paper-based assessments (PBA) data. This option is supported only for NAEP data.

Details

This function calculates the gap between groupA and groupB (which may be omitted to indicate the full sample). The gap is calculated for one of four statistics:

the gap in means The mean score gap (in the score variable) identified in the `variable` argument. This is the default. The means and their standard errors are calculated using the methods described in the [lm.sdf](#) function documentation.

the gap in percentiles The gap between respondents at the percentiles specified in the `percentiles` argument. This is returned when the `percentiles` argument is defined. The mean and standard error are computed as described in the [percentile](#) function documentation.

the gap in achievement levels The gap in the percentage of students at (when `achievementDiscrete` is TRUE) or at or above (when `achievementDiscrete` is FALSE) a particular achievement level. This is used when the `achievementLevel` argument is defined. The mean and standard error are calculated as described in the [achievementLevels](#) function documentation.

the gap in a survey response The gap in the percentage of respondents responding at `targetLevel` to `variable`. This is used when `targetLevel` is defined. The mean and standard deviation are calculated as described in the [edsurveyTable](#) function documentation.

Value

The return type depends on if the class of the data argument is an `edsurvey.data.frame` or an `edsurvey.data.frame.list`. Both include the call (called `call`), a list called `labels`, an object named `percentage` that shows the percentage in `groupA` and `groupB`, and an object that shows the gap called `results`.

The labels include the following elements:

<code>definition</code>	the definitions of the groups
<code>nFullData</code>	the <i>n</i> -size for the full dataset (before applying the definition)
<code>nUsed</code>	the <i>n</i> -size for the data after the group is subsetted and other restrictions (such as omitted values) are applied
<code>nPSU</code>	the number of PSUs used in calculation—only returned when <code>returnNumberOfPSU = TRUE</code>

The percentages are computed according to the vignette titled *Statistical Methods Used in EdSurvey* in the section “Estimation of Weighted Percentages When Plausible Values Are Not Present.” The standard errors are calculated according to “Estimation of the Standard Error of Weighted Percentages When Plausible Values Are Not Present, Using the Jackknife Method.” Standard errors of differences are calculated as the square root of the typical variance formula

$$Var(A - B) = Var(A) + Var(B) - 2Cov(A, B)$$

where the covariance term is calculated as described in the vignette titled *Statistical Methods Used in EdSurvey* in the section “Estimation of Covariances.” These degrees of freedom are available only with the jackknife variance estimation. The degrees of freedom used for hypothesis testing are always set to the number of jackknife replicates in the data.

the data argument is an edsurvey.data.frame When the data argument is an `edsurvey.data.frame`, `gap` returns an S3 object of class `gap`.

The percentage object is a numeric vector with the following elements:

<code>pctA</code>	the percentage of respondents in groupA compared with the whole sample in data
<code>pctAse</code>	the standard error on the percentage of respondents in groupA
<code>dofA</code>	degrees of freedom appropriate for a <i>t</i> -test involving <code>pctA</code> . This value is returned only if <code>returnSimpleDoF=TRUE</code> .
<code>pctB</code>	the percentage of respondents in groupB.
<code>pctBse</code>	the standard error on the percentage of respondents in groupB
<code>dofB</code>	degrees of freedom appropriate for a <i>t</i> -test involving <code>pctA</code> . This value is returned only if <code>returnSimpleDoF=TRUE</code> .
<code>diffAB</code>	the value of <code>pctA</code> minus <code>pctB</code>
<code>covAB</code>	the covariance of <code>pctA</code> and <code>pctB</code> ; used in calculating <code>diffABse</code> .
<code>diffABse</code>	the standard error of <code>pctA</code> minus <code>pctB</code>
<code>diffABpValue</code>	the <i>p</i> -value associated with the <i>t</i> -test used for the hypothesis test that <code>diffAB</code> is zero
<code>dofAB</code>	degrees of freedom used in calculating <code>diffABpValue</code>

The results object is a numeric data frame with the following elements:

<code>estimateA</code>	the mean estimate of groupA (or the percentage estimate if <code>achievementLevel</code> or <code>targetLevel</code> is specified)
<code>estimateAse</code>	the standard error of <code>estimateA</code>
<code>dofA</code>	degrees of freedom appropriate for a <i>t</i> -test involving <code>meanA</code> . This value is returned only if <code>returnSimpleDoF=TRUE</code> .
<code>estimateB</code>	the mean estimate of groupB (or the percentage estimate if <code>achievementLevel</code> or <code>targetLevel</code> is specified)
<code>estimateBse</code>	the standard error of <code>estimateB</code>
<code>dofB</code>	degrees of freedom appropriate for a <i>t</i> -test involving <code>meanB</code> . This value is returned only if <code>returnSimpleDoF=TRUE</code> .

<code>diffAB</code>	the value of <code>estimateA</code> minus <code>estimateB</code>
<code>covAB</code>	the covariance of <code>estimateA</code> and <code>estimateB</code> . Used in calculating <code>diffABse</code> .
<code>diffABse</code>	the standard error of <code>diffAB</code>
<code>diffABpValue</code>	the p -value associated with the t -test used for the hypothesis test that <code>diffAB</code> is zero.
<code>dofAB</code>	degrees of freedom used for the t -test on <code>diffAB</code>

If the `gap` was in achievement levels or percentiles and more than one percentile or achievement level is requested, then an additional column labeled `percentiles` or `achievementLevel` is included in the `results` object.

When `results` has a single row and when `returnVarEstInputs` is `TRUE`, the additional elements `varEstInputs` and `pctVarEstInputs` also are returned. These can be used for calculating covariances with `varEstToCov`.

the data argument is an `edsurvey.data.frame.list` When the data argument is an `edsurvey.data.frame.list`, `gap` returns an S3 object of class `gapList`.

The `results` object in the `edsurveyResultList` is a `data.frame`. Each row regards a particular dataset from the `edsurvey.data.frame`, and a reference dataset is dictated by the `referenceDataIndex` argument.

The percentage object is a `data.frame` with the following elements:

<code>covs</code>	a data frame with a column for each column in the <code>covs</code> . See previous section for more details.
<code>...</code>	all elements in the percentage object in the previous section
<code>diffAA</code>	the difference in <code>pctA</code> between the reference data and this dataset. Set to <code>NA</code> for the reference dataset.
<code>covAA</code>	the covariance of <code>pctA</code> in the reference data and <code>pctA</code> on this row. Used in calculating <code>diffAAse</code> .
<code>diffAAse</code>	the standard error for <code>diffAA</code>
<code>diffAAPValue</code>	the p -value associated with the t -test used for the hypothesis test that <code>diffAA</code> is zero
<code>diffBB</code>	the difference in <code>pctB</code> between the reference data and this dataset. Set to <code>NA</code> for the reference dataset.
<code>covBB</code>	the covariance of <code>pctB</code> in the reference data and <code>pctB</code> on this row. Used in calculating <code>diffAAse</code> .
<code>diffBBse</code>	the standard error for <code>diffBB</code>
<code>diffBBpValue</code>	the p -value associated with the t -test used for the hypothesis test that <code>diffBB</code> is zero
<code>diffABAB</code>	the value of <code>diffAB</code> in the reference dataset minus the value of <code>diffAB</code> in this dataset. Set to <code>NA</code> for the reference dataset.
<code>covABAB</code>	the covariance of <code>diffAB</code> in the reference data and <code>diffAB</code> on this row. Used in calculating <code>diffABABse</code> .
<code>diffABABse</code>	the standard error for <code>diffABAB</code>

`diffABABpValue` the p -value associated with the t -test used for the hypothesis test that `diffABAB` is zero

The `results` object is a `data.frame` with the following elements:

<code>...</code>	all elements in the <code>results</code> object in the previous section
<code>diffAA</code>	the value of <code>groupA</code> in the reference dataset minus the value in this dataset. Set to NA for the reference dataset.
<code>covAA</code>	the covariance of <code>meanA</code> in the reference data and <code>meanA</code> on this row. Used in calculating <code>diffAAse</code> .
<code>diffAAse</code>	the standard error for <code>diffAA</code>
<code>diffAApValue</code>	the p -value associated with the t -test used for the hypothesis test that <code>diffAA</code> is zero
<code>diffBB</code>	the value of <code>groupB</code> in the reference dataset minus the value in this dataset. Set to NA for the reference dataset.
<code>covBB</code>	the covariance of <code>meanB</code> in the reference data and <code>meanB</code> on this row. Used in calculating <code>diffBBse</code> .
<code>diffBBse</code>	the standard error for <code>diffBB</code>
<code>diffBBpValue</code>	the p -value associated with the t -test used for the hypothesis test that <code>diffBB</code> is zero
<code>diffABAB</code>	the value of <code>diffAB</code> in the reference dataset minus the value of <code>diffAB</code> in this dataset. Set to NA for the reference dataset.
<code>covABAB</code>	the covariance of <code>diffAB</code> in the reference data and <code>diffAB</code> on this row. Used in calculating <code>diffABABse</code> .
<code>diffABABse</code>	the standard error for <code>diffABAB</code>
<code>diffABABpValue</code>	the p -value associated with the t -test used for the hypothesis test that <code>diffABAB</code> is zero
<code>sameSurvey</code>	a logical value indicating if this line uses the same survey as the reference line. Set to NA for the reference line.

Author(s)

Paul Bailey, Trang Nguyen, and Huade Huo

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# find the mean score gap in the primer data between males and females
gap("composite", sdf, dsex=="Male", dsex=="Female")

# find the score gap of the quartiles in the primer data between males and females
gap("composite", sdf, dsex=="Male", dsex=="Female", percentile=50)
gap("composite", sdf, dsex=="Male", dsex=="Female", percentile=c(25, 50, 75))
```

```

# find the percent proficient (or higher) gap in the primer data between males and females
gap("composite", sdf, dsex=="Male", dsex=="Female",
    achievementLevel=c("Basic", "Proficient", "Advanced"))

# find the discrete achievement level gap--this is harder to interpret
gap("composite", sdf, dsex=="Male", dsex=="Female",
    achievementLevel="Proficient", achievementDiscrete=TRUE)

# find the percent talk about studies at home (b017451) never or hardly
# ever gap in the primer data between males and females
gap("b017451", sdf, dsex=="Male", dsex=="Female",
    targetLevel="Never or hardly ever")

# example showing how to compare multiple levels
gap("b017451",sdf, dsex=="Male", dsex=="Female", targetLevel="Infrequently",
    recode=list(b017451=list(from=c("Never or hardly ever",
        "Once every few weeks",
        "About once a week"),
        to=c("Infrequently"))))

# make subsets of sdf by scrpsu, "Scrambled PSU and school code"
sdfA <- subset(sdf, scrpsu %in% c(5,45,56))
sdfB <- subset(sdf, scrpsu %in% c(75,76,78))
sdfC <- subset(sdf, scrpsu %in% 100:200)
sdfD <- subset(sdf, scrpsu %in% 201:300)

sdf1 <- edsurvey.data.frame.list(list(sdfA, sdfB, sdfC, sdfD),
    labels=c("A locations", "B locations",
        "C locations", "D locations"))

gap("composite", sdf1, dsex=="Male", dsex=="Female", percentile=c(50))

## End(Not run)

## Not run:
# example showing using linking error with gap
# load Grade 4 math data
# requires NAEP RUD license with these files in the folder the user is currently in
g4math2015 <- readNAEP("M46NT1AT.dat")
g4math2017 <- readNAEP("M48NT1AT.dat")
g4math2019 <- readNAEP("M50NT1AT.dat")

# make an edsurvey.data.frame.list from math grade 4 2015, 2017, and 2019 data
g4math <- edsurvey.data.frame.list(list(g4math2019, g4math2017, g4math2015),
    labels = c("2019", "2017", "2015"))

# gap analysis with linking error in variance estimation across surveys
gap("composite", g4math, dsex == "Male", dsex == "Female", includeLinkingError=TRUE)
gap("composite", g4math, dsex == "Male", dsex == "Female", percentiles = c(10, 25),
    includeLinkingError=TRUE)
gap("composite", g4math, dsex == "Male", dsex == "Female",
    achievementDiscrete = TRUE, achievementLevel=c("Basic", "Proficient", "Advanced"),

```

```

includeLinkingError=TRUE)

## End(Not run)

```

getData *Read Data to a Data Frame*

Description

Reads in selected columns to a `data.frame` or a `light.edsurvey.data.frame`. On an `edsurvey.data.frame`, the data are stored on disk.

Usage

```

getData(
  data,
  varnames = NULL,
  drop = FALSE,
  dropUnusedLevels = TRUE,
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  formula = NULL,
  recode = NULL,
  includeNaLabel = FALSE,
  addAttributes = FALSE,
  returnJKreplicates = TRUE
)

```

Arguments

<code>data</code>	an <code>edsurvey.data.frame</code> or a <code>light.edsurvey.data.frame</code>
<code>varnames</code>	a character vector of variable names that will be returned. When both <code>varnames</code> and a <code>formula</code> are specified, variables associated with both are returned. Set to <code>NULL</code> by default.
<code>drop</code>	a logical value. When set to the default value of <code>FALSE</code> , when a single column is returned, it is still represented as a <code>data.frame</code> and is not converted to a vector.
<code>dropUnusedLevels</code>	a logical value. When set to the default value of <code>TRUE</code> , drops unused levels of all factor variables.
<code>omittedLevels</code>	a logical value. When set to the default value of <code>TRUE</code> , drops those levels of all factor variables that are specified in an <code>edsurvey.data.frame</code> . Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the omitted levels. The omitted levels also can be adjusted with <code>setAttributes</code> ; see Examples.
<code>defaultConditions</code>	a logical value. When set to the default value of <code>TRUE</code> , uses the default conditions stored in an <code>edsurvey.data.frame</code> to subset the data. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the default conditions.

formula	a formula. When included, <code>getData</code> returns data associated with all variables of the formula. When both <code>varnames</code> and a formula are specified, the variables associated with both are returned. Set to <code>NULL</code> by default.
recode	a list of lists to recode variables. Defaults to <code>NULL</code> . Can be set as <code>recode = list(var1 = list(from = c("a", "b", "c"), to = "d"))</code> . See Examples.
includeNaLabel	a logical value to indicate if NA (missing) values are returned as literal NA values or as factor levels coded as NA
addAttributes	a logical value set to <code>TRUE</code> to get a <code>data.frame</code> that can be used in calls to other functions that usually would take an <code>edsurvey.data.frame</code> . This <code>data.frame</code> also is called a <code>light.edsurvey.data.frame</code> . See Description section in edsurvey.data.frame for more information on <code>light.edsurvey.data.frame</code> .
returnJKreplicates	a logical value indicating if JK replicate weights should be returned. Defaults to <code>TRUE</code> .

Details

By default, an `edsurvey.data.frame` does not have data read into memory until `getData` is called and returns a data frame. This structure allows `EdSurvey` to have a minimal memory footprint. To keep the footprint small, you need to limit `varnames` to just the necessary variables.

There are two methods of attaching survey attributes to a `data.frame` to make it usable by the functions in the `EdSurvey` package (e.g., `lm.sdf`): (a) setting the `addAttributes` argument to `TRUE` in the call to `getData` or (b) by appending the attributes to the data frame with `rebindAttributes`.

When `getData` is called, it returns a data frame. Setting the `addAttributes` argument to `TRUE` adds the survey attributes and changes the resultant `data.frame` to a `light.edsurvey.data.frame`.

Alternatively, a `data.frame` can be coerced into a `light.edsurvey.data.frame` using `rebindAttributes`. See Examples in the [rebindAttributes](#) documentation.

If both `formula` and `varnames` are populated, the variables on both will be included.

See the vignette titled *Using the `getData` Function in `EdSurvey`* for long-form documentation on this function.

Value

When `addAttributes` is `FALSE`, `getData` returns a `data.frame` containing data associated with the requested variables. When `addAttributes` is `TRUE`, `getData` returns a `light.edsurvey.data.frame`.

Author(s)

Tom Fink, Paul Bailey, and Ahmad Emad

See Also

[rebindAttributes](#), [subset.edsurvey.data.frame](#)

Examples

```

## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# get two variables, without weights
df <- getData(data=sdf, varnames=c("dsex", "b017451"))
table(df)

# example of using recode
df2 <- getData(data=sdf, varnames=c("dsex", "t088301"),
               recode=list(t088301=list(from=c("Yes, available", "Yes, I have access"),
                                       to=c("Yes")),
                           t088301=list(from=c("No, have no access"),
                                       to=c("No"))))

table(df2)

# when readNAEP is called on a data file, it appends a default
# condition to the edsurvey.data.frame. You can see these conditions
# by printing the sdf
sdf

# As per the default condition specified, getData restricts the data to only
# Reporting Sample. This behavior can be changed as follows:
df2 <- getData(data=sdf, varnames=c("dsex", "b017451"), defaultConditions = FALSE)
table(df2)

# similarly, the default behavior of omitting certain levels specified
# in the edsurvey.data.frame can be changed as follows:
df2 <- getData(data=sdf, varnames=c("dsex", "b017451"), omittedLevels = FALSE)
table(df2)

# omittedLevels can also be edited with setAttributes()
# here, the omitted level "Multiple" is removed from the list
sdfIncludeMultiple <- setAttributes(sdf, "omittedLevels", c(NA, "Omitted"))
# check that it was set
getAttributes(sdfIncludeMultiple, "omittedLevels")
# notice that omittedLevels is TRUE, removing NA and "Omitted" still
dfIncludeMultiple <- getData(data=sdfIncludeMultiple, varnames=c("dsex", "b017451"))
table(dfIncludeMultiple)

# the variable "c052601" is from the school-level data file; merging is handled automatically.
# returns a light.edsurvey.data.frame using addAttributes=TRUE argument
gddat <- getData(data=sdf,
                varnames=c("composite", "dsex", "b017451", "c052601"),
                addAttributes = TRUE)

class(gddat)
# look at the first few lines
head(gddat)

# get a selection of variables, recode using ifelse, and reappend attributes
# with rebindAttributes so that it can be used with EdSurvey analysis functions

```

```
df0 <- getData(sdf, c("composite", "dsex", "b017451", "origwt"))
df0$dsex <- ifelse(df0$dsex=="Male", "boy", "girl")
df0 <- rebindAttributes(df0, sdf)

# getting all the data can use up all the memory and is generally a bad idea
df0 <- getData(sdf, varnames=colnames(sdf),
              omittedLevels=FALSE, defaultConditions=FALSE)

## End(Not run)
```

getPlausibleValue *Get Plausible Value Variables*

Description

Gets the set of variables on an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list` associated with the given subject or subscale.

Usage

```
getPlausibleValue(var, data)
```

Arguments

<code>var</code>	a character vector naming the subject scale or subscale
<code>data</code>	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>

Details

This function will return a set of plausible value names for variables that `hasPlausibleValue` returns as true.

Value

a character vector of the set of variable names for the plausible values

Author(s)

Michael Lee and Paul Bailey

See Also

[showPlausibleValues](#), [updatePlausibleValue](#)

Examples

```
## Not run:  
# read in the example data (generated, not real student data)  
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))  
  
getPlausibleValue(var="composite", data=sdf)  
  
## End(Not run)
```

getWeightJkReplicates *Retrieve the Jackknife Replicate Weights*

Description

Returns the jackknife replicate weights on an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list` associated with a weight variable.

Usage

```
getWeightJkReplicates(var, data)
```

Arguments

var	character indicating the name of the weight variable for which the jackknife replicate weights are desired
data	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>

Value

a character vector of the jackknife replicate weights

Author(s)

Michael Lee and Paul Bailey

Examples

```
## Not run:  
# read in the example data (generated, not real student data)  
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))  
  
getWeightJkReplicates(var="origwt", data=sdf)  
  
## End(Not run)
```

glm.sdf

*EdSurvey Generalized Linear Models***Description**

Fits a logit or probit that uses weights and variance estimates appropriate for the `edsurvey.data.frame`, the `light.edsurvey.data.frame`, or the `edsurvey.data.frame.list`.

Usage

```
glm.sdf(formula, family = binomial(link = "logit"), data,
        weightVar = NULL, relevels = list(),
        varMethod=c("jackknife", "Taylor"), jrrIMax = 1,
        omittedLevels = TRUE, defaultConditions = TRUE, recode = NULL,
        returnNumberOfPSU=FALSE, returnVarEstInputs = FALSE)
```

```
logit.sdf(
  formula,
  data,
  weightVar = NULL,
  relevels = list(),
  varMethod = c("jackknife", "Taylor"),
  jrrIMax = 1,
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  recode = NULL,
  returnNumberOfPSU = FALSE,
  returnVarEstInputs = FALSE
)
```

```
probit.sdf(
  formula,
  data,
  weightVar = NULL,
  relevels = list(),
  varMethod = c("jackknife", "Taylor"),
  jrrIMax = 1,
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  recode = NULL,
  returnVarEstInputs = FALSE
)
```

Arguments

`formula` a formula for the linear model. See `glm`. For logit and probit, we recommend using the `I()` function to define the level used for success. (See Examples.)

family	the glm.sdf function currently fits only the binomial outcome models, such as logit and probit, although other link functions are available for binomial models. See the link argument in the help for family.
data	an edsurvey.data.frame
weightVar	character indicating the weight variable to use (see Details). The weightVar must be one of the weights for the edsurvey.data.frame. If NULL, uses the default for the edsurvey.data.frame.
relevels	a list; used to change the contrasts from the default treatment contrasts to the treatment contrasts with a chosen omitted group. The name of each element should be the variable name, and the value should be the group to be omitted.
varMethod	a character set to “jackknife” or “Taylor” that indicates the variance estimation method to be used. See Details.
jrrIMax	the Vjrr sampling variance term (see <i>Statistical Methods Used in EdSurvey</i>) can be estimated with any positive number of plausible values and is estimated on the lower of the number of available plausible values and jrrIMax. When jrrIMax is set to Inf, all plausible values will be used. Higher values of jrrIMax lead to longer computing times and more accurate variance estimates.
omittedLevels	a logical value. When set to the default value of TRUE, drops those levels of all factor variables that are specified in edsurvey.data.frame. Use print on an edsurvey.data.frame to see the omitted levels.
defaultConditions	a logical value. When set to the default value of TRUE, uses the default conditions stored in an edsurvey.data.frame to subset the data. Use print on an edsurvey.data.frame to see the default conditions.
recode	a list of lists to recode variables. Defaults to NULL. Can be set as recode=list(var1=list(from=c("a", "b", "c"), to="d")).
returnNumberOfPSU	a logical value set to TRUE to return the number of primary sampling units (PSUs)
returnVarEstInputs	a logical value set to TRUE to return the inputs to the jackknife and imputation variance estimates, which allow for the computation of covariances between estimates.

Details

This function implements an estimator that correctly handles left-hand side variables that are logical, allows for survey sampling weights, and estimates variances using the jackknife replication or Taylor series. The vignette titled *Statistical Methods Used in EdSurvey* describes estimation of the reported statistics and how it depends on varMethod.

The coefficients are estimated using the sample weights according to the section “Estimation of Weighted Means When Plausible Values Are Not Present” or the section “Estimation of Weighted Means When Plausible Values Are Present,” depending on if there are assessment variables or variables with plausible values in them.

How the standard errors of the coefficients are estimated depends on the presence of plausible values (assessment variables), But once it is obtained, the t statistic is given by

$$t = \frac{\hat{\beta}}{\sqrt{\text{var}(\hat{\beta})}}$$

where $\hat{\beta}$ is the estimated coefficient and $\text{var}(\hat{\beta})$ is its variance of that estimate.

logit.sdf and probit.sdf are included for convenience only; they give the same results as a call to glm.sdf with the binomial family and the link function named in the function call (logit or probit). By default, glm fits a logistic regression when family is not set, so the two are expected to give the same results in that case. Other types of generalized linear models are not supported.

Variance estimation of coefficients: All variance estimation methods are shown in the vignette titled *Statistical Methods Used in EdSurvey*. When the predicted value does not have plausible values and varMethod is set to jackknife, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Not Present, Using the Jackknife Method.”

When plausible values are present and varMethod is set to jackknife, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Present, Using the Jackknife Method.”

When the predicted value does not have plausible values and varMethod is set to Taylor, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Not Present, Using the Taylor Series Method.”

When plausible values are present and varMethod is set to Taylor, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Present, Using the Taylor Series Method.”

Value

An edsurveyGlm with the following elements:

call	the function call
formula	the formula used to fit the model
coef	the estimates of the coefficients
se	the standard error estimates of the coefficients
Vimp	the estimated variance caused by uncertainty in the scores (plausible value variables)
Vjrr	the estimated variance from sampling
M	the number of plausible values
nPSU	the number of PSUs used in the calculation
varm	the variance estimates under the various plausible values
coefm	the values of the coefficients under the various plausible values
coefmat	the coefficient matrix (typically produced by the summary of a model)
weight	the name of the weight variable

npv	the number of plausible values
njk	the number of the jackknife replicates used
varMethod	always jackknife
varEstInputs	when returnVarEstInputs is TRUE, this element is returned. These are used for calculating covariances with varEstToCov .

Testing

Of the common hypothesis tests for joint parameter testing, only the Wald test is widely used with plausible values and sample weights. As such, it replaces, if imperfectly, the Akaike Information Criteria (AIC), the likelihood ratio test, chi-squared, and analysis of variance (ANOVA, including *F*-tests). See [waldTest](#) or the vignette titled *Methods and Overview of Using EdSurvey for Running Wald Tests*.

Author(s)

Paul Bailey

See Also

[glm](#)

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# by default uses the jackknife variance method using replicate weights
table(sdf$b013801)
logit1 <- logit.sdf(I(b013801 %in% c("26-100", ">100"))) ~ dsex + b017451, data=sdf)
# use summary to get detailed results
summary(logit1)

# Taylor series variance estimation
logit1t <- logit.sdf(I(b013801 %in% c("26-100", ">100"))) ~ dsex + b017451, data=sdf,
                    varMethod="Taylor")
summary(logit1t)

logit2 <- logit.sdf(I(composite >= 300) ~ dsex + b013801, data=sdf)
summary(logit2)

logit3 <- glm.sdf(I(composite >= 300) ~ dsex + b013801, data=sdf,
                 family=quasibinomial(link="logit"))

# Wald test for joint hypothesis that all coefficients in b013801 are zero
waldTest(logit3, "b013801")

summary(logit3)

## End(Not run)
```

hasPlausibleValue	<i>Plausible Value Test</i>
-------------------	-----------------------------

Description

Returns a value indicating if this variable has associated plausible values in an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`.

Usage

```
hasPlausibleValue(var, data)
```

Arguments

<code>var</code>	a character indicating the variable in question
<code>data</code>	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>

Details

This function returns TRUE only when the variable passed to it is the name for a set of plausible values but not if it is an individual plausible value from such a set. Thus, on the NAEP Primer, composite has plausible values (and so TRUE would be returned by this function), but any of the plausible values or variable names defined in the actual data (such as "mrpcm1" or "dsex") are not.

Value

a Boolean (or vector when `var` is a vector) indicating if each element of `var` has plausible values associated with it

Author(s)

Michael Lee and Paul Bailey

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# TRUE
hasPlausibleValue(var="composite", data=sdf)

# FALSE
hasPlausibleValue(var="dsex", data=sdf)

## End(Not run)
```

`isWeight`*Weight Test*

Description

Returns logical values indicating whether a vector of variables is a weight for an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`.

Usage

```
isWeight(var, data)
```

Arguments

<code>var</code>	a character vector of variables
<code>data</code>	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>

Details

Note that this function returns TRUE only when the `var` element is the name of the weight used for making estimates but not if it is one of the individual jackknife replicates.

Value

a logical vector of values indicating if each element of `var` is a weight

Author(s)

Michael Lee and Paul Bailey

Examples

```
## Not run:  
# read in the example data (generated, not real student data)  
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))  
  
# TRUE  
isWeight(var="origwt", data=sdf)  
  
# FALSE  
isWeight(var="dsex", data=sdf)  
  
## End(Not run)
```

 levelsSDF

Print Levels and Labels

Description

Retrieve the levels and labels of a variable from an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`.

Usage

```
levelsSDF(varnames, data, showOmitted = TRUE, showN = TRUE)
```

Arguments

<code>varnames</code>	a vector of character strings to search for in the database connection object (data)
<code>data</code>	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>
<code>showOmitted</code>	a Boolean indicating if omitted levels should be shown
<code>showN</code>	a Boolean indicating if (unweighted) <i>n</i> -sizes should be shown for each response level

Author(s)

Michael Lee and Paul Bailey

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# search variables in the sdf
levelsSDF(varnames="pared", data=sdf)

# search multiple variables
levelsSDF(varnames=c("pared","ell3"), data=sdf)

# search multiple variables in a light.edsurvey.data.frame with recodes
df2 <- getData(data=sdf, varnames=c("dsex", "t088301"),
               recode=list(t088301=list(from=c("Yes, available","Yes, I have access"),
                                       to=c("Yes")),
                           t088301=list(from=c("No, have no access"),
                                       to=c("No"))),
               addAttributes=TRUE)
levelsSDF(varnames=c("dsex","t088301"), data=df2)

## End(Not run)
```

lm.sdf

*EdSurvey Linear Models***Description**

Fits a linear model that uses weights and variance estimates appropriate for the data.

Usage

```
lm.sdf(formula, data, weightVar = NULL, relevels = list(),
        varMethod = c("jackknife", "Taylor"), jrrIMax = 1,
        omittedLevels = TRUE, defaultConditions = TRUE, recode = NULL,
        returnVarEstInputs = FALSE, returnNumberOfPSU = FALSE,
        standardizeWithSamplingVar = FALSE)
```

Arguments

formula	a formula for the linear model. See <code>lm</code> . If <code>y</code> is left blank, the default subject scale or subscale variable will be used. (You can find the default using showPlausibleValues .) If <code>y</code> is a variable for a subject scale or subscale (one of the names shown by showPlausibleValues), then that subject scale or subscale is used.
data	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>
weightVar	a character indicating the weight variable to use (see Details). The <code>weightVar</code> must be one of the weights for the <code>edsurvey.data.frame</code> . If <code>NULL</code> , it uses the default for the <code>edsurvey.data.frame</code> .
relevels	a list. Used to change the contrasts from the default treatment contrasts to the treatment contrasts with a chosen omitted group (the reference group). The name of each element should be the variable name, and the value should be the group to be omitted (the reference group).
varMethod	a character set to “jackknife” or “Taylor” that indicates the variance estimation method to be used. See Details .
jrrIMax	a numeric value; when using the jackknife variance estimation method, the default estimation option, <code>jrrIMax=1</code> , uses the sampling variance from the first plausible value as the component for sampling variance estimation. The <code>Vjrr</code> term (see <i>Statistical Methods Used in EdSurvey</i>) can be estimated with any number of plausible values, and values larger than the number of plausible values on the survey (including <code>Inf</code>) will result in all plausible values being used. Higher values of <code>jrrIMax</code> lead to longer computing times and more accurate variance estimates.
omittedLevels	a logical value. When set to the default value of <code>TRUE</code> , drops those levels of all factor variables that are specified in an <code>edsurvey.data.frame</code> . Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the omitted levels.

defaultConditions	a logical value. When set to the default value of TRUE, uses the default conditions stored in an <code>edsurvey.data.frame</code> to subset the data. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the default conditions.
recode	a list of lists to recode variables. Defaults to NULL. Can be set as <code>recode=list(var1 = list(from= c("a", "b", "c"), to= "d"))</code> . See Examples.
returnVarEstInputs	a logical value set to TRUE to return the inputs to the jackknife and imputation variance estimates, which allow for the computation of covariances between estimates.
returnNumberOfPSU	a logical value set to TRUE to return the number of primary sampling units (PSUs)
standardizeWithSamplingVar	a logical value indicating if the standardized coefficients should have the variance of the regressors and outcome measured with sampling variance. Defaults to FALSE.

Details

This function implements an estimator that correctly handles left-hand side variables that are either numeric or plausible values and allows for survey sampling weights and estimates variances using the jackknife replication method. The vignette titled *Statistical Methods Used in EdSurvey* describes estimation of the reported statistics.

Regardless of the variance estimation, the coefficients are estimated using the sample weights according to the sections “Estimation of Weighted Means When Plausible Values Are Not Present” or “Estimation of Weighted Means When Plausible Values Are Present,” depending on if there are assessment variables or variables with plausible values in them.

How the standard errors of the coefficients are estimated depends on the value of `varMethod` and the presence of plausible values (assessment variables), But once it is obtained, the t statistic is given by

$$t = \frac{\hat{\beta}}{\sqrt{\text{var}(\hat{\beta})}}$$

where $\hat{\beta}$ is the estimated coefficient and $\text{var}(\hat{\beta})$ is the variance of that estimate.

The **coefficient of determination (R-squared value)** is similarly estimated by finding the average R -squared using the average across the plausible values.

Standardized regression coefficients: Standardized regression coefficients can be returned in a call to `summary`, by setting the argument `src` to TRUE. See Examples.

By default, the standardized coefficients are calculated using standard deviations of the variables themselves, including averaging the standard deviation across any plausible values. When `standardizeWithSamplingVar` is set to TRUE, the variance of the standardized coefficient is calculated similar to a regression coefficient and therefore includes the sampling variance in the variance estimate of the outcome variable.

Variance estimation of coefficients: All variance estimation methods are shown in the vignette titled *Statistical Methods Used in EdSurvey*. When `varMethod` is set to the `jackknife` and the predicted value does not have plausible values, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Not Present, Using the Jackknife Method.”

When plausible values are present and `varMethod` is `jackknife`, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Present, Using the Jackknife Method.”

When plausible values are not present and `varMethod` is `Taylor`, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Not Present, Using the Taylor Series Method.”

When plausible values are present and `varMethod` is `Taylor`, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Present, Using the Taylor Series Method.”

Value

An `edsurvey.lm` with the following elements:

<code>call</code>	the function call
<code>formula</code>	the formula used to fit the model
<code>coef</code>	the estimates of the coefficients
<code>se</code>	the standard error estimates of the coefficients
<code>Vimp</code>	the estimated variance from uncertainty in the scores (plausible value variables)
<code>Vjrr</code>	the estimated variance from sampling
<code>M</code>	the number of plausible values
<code>varm</code>	the variance estimates under the various plausible values
<code>coefm</code>	the values of the coefficients under the various plausible values
<code>coefmat</code>	the coefficient matrix (typically produced by the summary of a model)
<code>r.squared</code>	the coefficient of determination
<code>weight</code>	the name of the weight variable
<code>npv</code>	the number of plausible values
<code>jrrIMax</code>	the <code>jrrIMax</code> value used in computation
<code>njk</code>	the number of the jackknife replicates used; set to NA when Taylor series variance estimates are used
<code>varMethod</code>	one of Taylor series or the jackknife
<code>residuals</code>	residuals from the average regression coefficients
<code>PV.residuals</code>	residuals from the by plausible value coefficients
<code>PV.fitted.values</code>	fitted values from the by plausible value coefficients
<code>B</code>	imputation variance covariance matrix, before multiplication by $(M+1)/M$
<code>U</code>	sampling variance covariance matrix

rbar	average relative increase in variance; see van Buuren (2012, eq. 2.29)
nPSU	number of PSUs used in calculation
n0	number of rows on an <code>edsurvey.data.frame</code> before any conditions were applied
nUsed	number of observations with valid data and weights larger than zero
data	data used for the computation
Xstdev	standard deviations of regressors, used for computing standardized regression coefficients when <code>standardizeWithSamplingVar</code> is set to <code>FALSE</code> (the default)
varSummary	the result of running <code>summary2</code> (unweighted) on each variable in the regression
varEstInputs	when <code>returnVarEstInputs</code> is <code>TRUE</code> , this element is returned. These are used for calculating covariances with <code>varEstToCov</code> .
standardizeWithSamplingVar	when <code>standardizeWithSamplingVar</code> is set to <code>TRUE</code> , this element is returned. Calculates the standard deviation of the standardized regression coefficients like any other variable.

Testing

Of the common hypothesis tests for joint parameter testing, only the Wald test is widely used with plausible values and sample weights. As such, it replaces, if imperfectly, the Akaike Information Criteria (AIC), the likelihood ratio test, chi-squared, and analysis of variance (ANOVA, including *F*-tests). See `waldTest` or the vignette titled *Methods and Overview of Using EdSurvey for Running Wald Tests*.

Author(s)

Paul Bailey

References

- Binder, D. A. (1983). On the variances of asymptotically normal estimators from complex surveys. *International Statistical Review*, 51(3), 279–292.
- Rubin, D. B. (1987). *Multiple imputation for nonresponse in surveys*. New York, NY: Wiley.
- van Buuren, S. (2012). *Flexible imputation of missing data*. New York, NY: CRC Press.
- Weisberg, S. (1985). *Applied linear regression* (2nd ed.). New York, NY: Wiley.

See Also

lm

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# by default uses jackknife variance method using replicate weights
```

```

lm1 <- lm.sdf(composite ~ dsex + b017451, data=sdf)
lm1

# the summary function displays detailed results
summary(lm1)

# to show standardized regression coefficients
summary(lm1, src=TRUE)

# to specify a variance method, use varMethod
lm2 <- lm.sdf(composite ~ dsex + b017451, data=sdf, varMethod="Taylor")
lm2
summary(lm2)

# use relevel to set a new omitted category
lm3 <- lm.sdf(composite ~ dsex + b017451, data=sdf, relevels=list(dsex="Female"))
summary(lm3)
# test of a simple joint hypothesis
waldTest(lm3, "b017451")

# use recode to change values for specified variables
lm4 <- lm.sdf(composite ~ dsex + b017451, data=sdf,
              recode=list(b017451=list(from=c("Never or hardly ever",
                                             "Once every few weeks",
                                             "About once a week"),
                                   to=c("Infrequently")),
                          b017451=list(from=c("2 or 3 times a week", "Every day"),
                                       to=c("Frequently"))))
# Note: "Infrequently" is the dropped level for the recoded b017451
summary(lm4)

## End(Not run)

```

merge

EdSurvey Merge

Description

Takes a `data.frame` or a `light.edsurvey.data.frame` and merges with a `light.edsurvey.data.frame`.

Usage

```
## S3 method for class 'light.edsurvey.data.frame'
merge(x, y, ...)
```

Arguments

<code>x</code>	a <code>light.edsurvey.data.frame</code> . The attributes of the resulting <code>light.edsurvey.data.frame</code> are taken from <code>x</code> .
<code>y</code>	either a <code>light.edsurvey.data.frame</code> or a <code>data.frame</code>
<code>...</code>	arguments to be passed to <code>merge</code>

Value

a `light.edsurvey.data.frame` with the same attributes as `x`

Author(s)

Trang Nguyen

See Also

`merge`

Examples

```
## Not run:
# read in NAEP primer data
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))
lsdf <- getData(data=sdf, varnames=c("dsex", "b017451"), addAttributes = TRUE)
df <- data.frame(dsex = c("Male", "Female"), dsex2 = c("Boy", "Girl"))

# merging a light.edsurvey.data.frame with a data.frame
# returns a light.edsurvey.data.frame object
merged_lsdf <- merge(lsdf, df, by = "dsex")
class(merged_lsdf) # "light.edsurvey.data.frame" "data.frame"
head(merged_lsdf) # shows merge results

# merging behaves similarly to base::merge
df2 <- data.frame(dsex = c("Male", "Female"), b017451 = c(1,2))
merged_lsdf2 <- merge(lsdf, df2, by = "dsex")
names(merged_lsdf2) # "dsex" "b017451.x" "b017451.y"
head(merged_lsdf2) # shows merge results

## End(Not run)
```

mixed.sdf

EdSurvey Mixed-Effects Model

Description

Fits a linear weighted mixed-effects model.

Usage

```
mixed.sdf(
  formula,
  data,
  weightVars = NULL,
  weightTransformation = TRUE,
  recode = NULL,
  defaultConditions = TRUE,
```

```

tolerance = 0.01,
nQuad = NULL,
verbose = 0,
family = NULL,
centerGroup = NULL,
centerGrand = NULL,
fast = FALSE,
...
)

```

Arguments

formula	a formula for the multilevel regression or mixed model. See Examples and the vignette titled <i>Methods Used for Estimating Mixed-Effects Models in EdSurvey</i> for more details on how to specify a mixed model. If <i>y</i> is left blank, the default subject scale or subscale variable will be used. (You can find the default using showPlausibleValues .) If <i>y</i> is a variable for a subject scale or subscale (one of the names shown by showPlausibleValues), then that subject scale or subscale is used.
data	an <code>edsurvey.data.frame</code> or a <code>light.edsurvey.data.frame</code>
weightVars	character vector indicating weight variables for corresponding levels to use. The <code>weightVar</code> must be the weights for the <code>edsurvey.data.frame</code> . The weight variables must be in the order of level (from lowest to highest level).
weightTransformation	a logical value to indicate whether the function should standardize weights before using it in the multilevel model. If set to <code>TRUE</code> , the function will look up standard weight transformation methods often used for a specific survey. Weight transformation can be found in the vignette titled <i>Methods Used for Estimating Mixed-Effects Models in EdSurvey</i> . If set to <code>FALSE</code> or if the survey of the specified data does not have a standard weight transformation method, raw weights will be used.
recode	a list of lists to recode variables. Defaults to <code>NULL</code> . Can be set as <code>recode=list(var1 = list(from=c("a", "b", "c"), to="d"))</code> . See Examples in <code>lm.sdf</code> .
defaultConditions	a logical value. When set to the default value of <code>TRUE</code> , uses the default conditions stored in an <code>edsurvey.data.frame</code> to subset the data. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the default conditions.
tolerance	deprecated, no effect
nQuad	deprecated, no effect
verbose	an integer; when set to 1, it will print out the brief progress of the function <code>mix.sdf</code> . Users can use these traced messages for further diagnosis. When set to 2, it will print out the detailed progress, including temporary estimates during the optimization. Defaults to 0, which will run the function without output.
family	this argument is deprecated; please use the <code>WeMix</code> package's <code>mix</code> function directly for binomial models.

centerGroup	a list in which the name of each element is the name of the aggregation level, and the element is a formula of variable names to be group mean centered. For example, to group mean center gender and age within the group student: <code>list("student"= ~gender+age)</code> . Defaults to NULL, which means predictors are not adjusted by group centering. See Examples in the WeMix function <code>mix</code> .
centerGrand	a formula of variable names to be grand mean centered. For example, to center the variable education by overall mean of education: <code>~education</code> . Defaults to NULL, which means predictors are not adjusted by grand centering.
fast	deprecated, no effect
...	other potential arguments to be used in <code>mix</code>

Details

This function uses the `mix` call in the WeMix package to fit mixed models. When the outcome does not have plausible values, the variance estimator directly from the `mix` function is used; these account for covariance at the top level of the model specified by the user.

When the outcome has plausible values, the coefficients are estimated in the same way as in `lm.sdf`, that is, averaged across the plausible values. In addition, the variance of the coefficients is estimated as the sum of the variance estimate from the `mix` function and the imputation variance. The formula for the imputation variance is, again, the same as for `lm.sdf`, with the same estimators as in the vignette titled *Statistical Methods Used in EdSurvey*. In the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Present, Using the Jackknife Method” in the formula for V_{imp} , the variance and estimates of the variance components are estimated with the same formulas as the regression coefficients.

Value

A `mixedSdfResults` object with the following elements:

call	the original call used in <code>mixed.sdf</code>
formula	the formula used to fit the model
coef	a vector of coefficient estimates
se	a vector with the standard error estimates of the coefficients and the standard error of the variance components
vars	estimated variance components of the model
levels	the number of levels in the model
ICC	the intraclass correlation coefficient of the model
npv	the number of plausible values
ngroups	a <code>data.frame</code> that includes the number of observations for each group
n0	the number of observations in the original data
nused	the number of observations used in the analysis

If the formula does not involve plausible values, the function will return the following additional elements:

lnlf	the likelihood function
------	-------------------------

lnl the log-likelihood of the model

If the formula involves plausible values, the function will return the following additional elements:

Vimp the estimated variance from uncertainty in the scores

Vjrr the estimated variance from sampling

Author(s)

Paul Bailey, Trang Nguyen, and Claire Kelley

References

Rabe-Hesketh, S., & Skrondal, A. (2006). Multilevel modelling of complex survey data. *Journal of the Royal Statistical Society: Series A (Statistics in Society)*, 169(4), 805–827.

See Also

WeMix mix function and [lm.sdf](#)

Examples

```
## Not run:
# save TIMSS 2015 data to ~/TIMSS/2015
downloadTIMSS(root="~/", years=2015)
fin <- readTIMSS("~/TIMSS/2015", countries="fin", gradeLvl=4)
# uses all plausible values
mix1 <- mixed.sdf(mmat ~ itsex + (1|idschool), data = fin,
                 weightVar=c("totwgt","schwgt"), weightTransformation=FALSE)
summary(mix1)
# uses only one plausible value
mix2 <- mixed.sdf(asmmat01 ~ itsex + (1|idschool), data = fin,
                 weightVar=c("totwgt","schwgt"), weightTransformation=FALSE)
summary(mix2)

## End(Not run)
```

Description

Prepare IRT parameters and score items and then estimate a linear model with direct estimation.

Usage

```

mml.sdf(
  formula,
  data,
  weightVar = NULL,
  omittedLevels = TRUE,
  composite = TRUE,
  dctPath = NULL,
  verbose = FALSE,
  multiCore = FALSE,
  numberOfCores = NULL,
  minNode = -4,
  maxNode = 4,
  Q = 34,
  scoreDict = defaultNAEPscoreCard(),
  idVar = NULL
)

```

Arguments

formula	a formula for the model.
data	an <code>edsurvey.data.frame</code> for the National Assessment of Educational Progress (NAEP) and the Trends in International Mathematics and Science Study (TIMSS).
weightVar	a character indicating the weight variable to use. The <code>weightVar</code> must be one of the weights for the <code>edsurvey.data.frame</code> . If <code>NULL</code> , it uses the default for the <code>edsurvey.data.frame</code> .
omittedLevels	a logical value. When set to the default value of <code>TRUE</code> , drops the levels of all factor variables that are specified in an <code>edsurvey.data.frame</code> . Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the omitted levels.
composite	logical; for a NAEP composite, setting to <code>FALSE</code> fits the model to all items at once, in a single construct, whereas setting to <code>TRUE</code> fits the model as a NAEP composite (i.e., a weighted average of the subscales). This argument is not applicable for TIMSS.
dctPath	a connection that points to the location of a NAEP <code>dct</code> file. A <code>dct</code> file can be used to input custom item response theory (IRT) parameters and subscale/subtest weights for NAEP assessments compared with those provided in the <code>NAEPirtparams</code> package. Otherwise, the argument defaults to <code>NULL</code> and IRT parameters and subscale weights from <code>NAEPirtparams</code> are used. IRT parameters for TIMSS cannot be supplied through a <code>dctPath</code> and are downloaded by using the downloadTIMSS function.
verbose	logical; indicates whether a detailed printout should display during execution, only for NAEP data.
multiCore	allows the <code>foreach</code> package to be used. You should have already set up the <code>registerDoParallel</code> function in the <code>doParallel</code> package.
numberOfCores	the number of cores to be used when using <code>multiCore</code> . Defaults to 75% of available cores. Users can check available cores with <code>detectCores()</code> .

minNode	numeric; minimum integration point in direct estimation; see mml.
maxNode	numeric; maximum integration point in direct estimation; see mml.
Q	integer; number of integration points per student used when integrating over the levels of the latent outcome construct.
scoreDict	a data.frame that includes guidelines for scoring the provided NAEP data. Here, <i>scoring</i> refers to turning item responses into scores on each item. To see the default scoring guidelines, call the function <code>defaultNAEPScoreCard()</code> , or see the Examples section. See Details for more information on possible scores.
idVar	a variable that is used to explicitly define the name of the student identifier variable to be used from data. Defaults to NULL, and <code>sid</code> is used as the student identifier.

Details

Typically, models are fit with NAEP data using plausible values to integrate out the uncertainty in the measurement of individual student outcomes. When direct estimation is used, the measurement error is integrated out explicitly using Q quadrature points. See documentation for `mml` in the `Dire` package.

The `scoreDict` helps turn response categories that are not simple item responses, such as `Not Reached` and `Multiple`, to something coded as inputs for the `mml` function in `Dire`. How `mml` treats these values depends on the test. For NAEP, for a dichotomous item, 8 is scored as the same proportion correct as the guessing parameter for that item, 0 is an incorrect response, an NA does not change the student's score, and 1 is correct. TIMSS does not require a `scoreDict`.

Value

An `edSurveyMML` object, which is the outcome from `mml.sdf`, with the following elements:

<code>mml</code>	an object containing information from the <code>mml</code> procedure. <code>?mml</code> can be used for further information.
<code>scoreDict</code>	the scoring used in the <code>mml</code> procedure
.	
<code>itemMapping</code>	the item mapping used in the <code>mml</code> procedure
.	

References

Cohen, J., & Jiang, T. (1999). Comparison of partially measured latent traits across nominal subgroups. *Journal of the American Statistical Association*, 94(448), 1035–1044. <https://doi.org/10.2307/2669917>

Examples

```
## Not run:
## Direct Estimation with NAEP
# Load data
sdfNAEP <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))
```

```

# Inspect scoring guidelines
defaultNAEPscoreCard()

# example output:
#       resCat pointMult pointConst
# 1   Multiple         8           0
# 2 Not Reached        NA           NA
# 3   Missing         NA           NA
# 4   Omitted         8           0
# 5  Illegible         0           0
# 6 Non-Rateable       0           0
# 7   Off Task         0           0

# Run NAEP model, warnings are about item codings
mmlNAEP <- mml.sdf(algebra ~ dsex + b013801, sdfNAEP, weightVar='origwt')

# Call with Taylor
summary(mmlNAEP, varType="Taylor", strataVar="repgrp1", PSUVar="jkunit")

## Direct Estimation with TIMSS
# Load data
downloadTIMSS("~/", year=2015)
sdfTIMSS <- readTIMSS("~/TIMSS/2015", countries="usa", grade = "4")

# Run TIMSS model, warnings are about item codings
mmlTIMSS <- mml.sdf(mmat ~ itsex + asbg04, sdfTIMSS, weightVar='totwgt')

# Call with Taylor
summary(mmlTIMSS, varType="Taylor", strataVar="jkzone", PSUVar="jkrep")

## End(Not run)

```

mvrlm.sdf

Multivariate Regression

Description

Fits a multivariate linear model that uses weights and variance estimates appropriate for the `edsurvey.data.frame`.

Usage

```

mvrlm.sdf(
  formula,
  data,
  weightVar = NULL,
  relevels = list(),
  jrrIMax = 1,

```

```

omittedLevels = TRUE,
defaultConditions = TRUE,
recode = NULL,
returnVarEstInputs = FALSE,
estMethod = "OLS"
)

```

Arguments

formula	a Formula package Formula for the linear model. See Formula; left-hand side variables are separated with vertical pipes (<code> </code>). See Examples.
data	an <code>edsurvey.data.frame</code> or an <code>edsurvey.data.frame.list</code>
weightVar	character indicating the weight variable to use (see Details). The <code>weightVar</code> must be one of the weights for the <code>edsurvey.data.frame</code> . If <code>NULL</code> , uses the default for the <code>edsurvey.data.frame</code> .
relevels	a list. Used to change the contrasts from the default treatment contrasts to treatment contrasts with a chosen omitted group (the reference group). To do this, the user puts an element on the list with the same name as a variable to change contrasts on and then make the value for that list element equal to the value that should be the omitted group (the reference group).
jrrIMax	a numeric value; when using the jackknife variance estimation method, the default estimation option, <code>jrrIMax=1</code> , uses the sampling variance from the first plausible value as the component for sampling variance estimation. The V_{jrr} term (see <i>Statistical Methods Used in EdSurvey</i>) can be estimated with any number of plausible values, and values larger than the number of plausible values on the survey (including <code>Inf</code>) will result in all plausible values being used. Higher values of <code>jrrIMax</code> lead to longer computing times and more accurate variance estimates.
omittedLevels	a logical value. When set to the default value of <code>TRUE</code> , drops those levels of all factor variables that are specified in <code>edsurvey.data.frame</code> . Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the omitted levels.
defaultConditions	a logical value. When set to the default value of <code>TRUE</code> , uses the default conditions stored in <code>edsurvey.data.frame</code> to subset the data. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the default conditions.
recode	a list of lists to recode variables. Defaults to <code>NULL</code> . Can be set as <code>recode = list(var1= list(from=c("a", "b", "c"), to="d"))</code> .
returnVarEstInputs	a logical value. Set to <code>TRUE</code> to return the inputs to the jackknife and imputation variance estimates, which allow for computation of covariances between estimates.
estMethod	a character value indicating which estimation method to use. Default is <code>OLS</code> ; other option is <code>GLS</code> .

Details

This function implements an estimator that correctly handles multiple left-hand side variables that are either numeric or plausible values, allows for survey sampling weights, and estimates variances

using the jackknife replication method. The vignette titled *Statistical Methods Used in EdSurvey* describes estimation of the reported statistics.

The **coefficients** are estimated using the sample weights according to the section “Estimation of Weighted Means When Plausible Values Are Not Present” or the section “Estimation of Weighted Means When Plausible Values Are Present,” depending on if there are assessment variables or variables with plausible values in them.

The **coefficient of determination (R-squared value)** is similarly estimated by finding the average R-squared using the sample weights for each set of plausible values.

Variance estimation of coefficients: All variance estimation methods are shown in the vignette titled *Statistical Methods Used in EdSurvey*.

When the predicted value does not have plausible values, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Not Present, Using the Jackknife Method.”

When plausible values are present, the variance of the coefficients is estimated according to the section “Estimation of Standard Errors of Weighted Means When Plausible Values Are Present, Using the Jackknife Method.”

For more information on the specifics of multivariate regression, see the vignette titled *Methods and Overview of Using EdSurvey for Multivariate Regression*.

Value

An `edsurvey.mvrlm` with elements:

<code>call</code>	the function call
<code>formula</code>	the formula used to fit the model
<code>coef</code>	the estimates of the coefficients
<code>se</code>	the standard error estimates of the coefficients
<code>Vimp</code>	the estimated variance caused by uncertainty in the scores (plausible value variables)
<code>Vjrr</code>	the estimated variance caused by sampling
<code>M</code>	the number of plausible values
<code>varm</code>	the variance estimates under the various plausible values
<code>coefm</code>	the values of the coefficients under the various plausible values
<code>coefmat</code>	the coefficient matrix (typically produced by the summary of a model)
<code>r.squared</code>	the coefficient of determination
<code>weight</code>	the name of the weight variable
<code>npv</code>	the number of plausible values
<code>njk</code>	the number of the jackknife replicates used
<code>varEstInputs</code>	When <code>returnVarEstInputs</code> is TRUE, this element is returned. These are used for calculating covariances with <code>varEstToCov</code> .
<code>residuals</code>	residuals for each of the PV models
<code>fitted.values</code>	model fitted values

residCov	residual covariance matrix for dependent variables
residPV	residuals for each dependent variable
inputs	coefficient estimation input matrices
n0	full data n
nUsed	n used for model
B	imputation variance-covariance matrix, before multiplication by $(M+1)/M$
U	sampling variance-covariance matrix

Author(s)

Alex Lishinski and Paul Bailey

See Also

the stats package `lm`, [lm.sdf](#)

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# use | symbol to separate dependent variables in the left-hand side of formula
mvrlm.fit <- mvrlm.sdf(algebra | geometry ~ dsex + m072801, jrrIMax = 5, data = sdf)

# print method returns coefficients, as does coef method
mvrlm.fit
coef(mvrlm.fit)

# for more detailed results, use summary:
summary(mvrlm.fit)

# details of model can also be accessed through components of the returned object; for example:

# coefficients (one column per dependent variable)
mvrlm.fit$coef
# coefficient table with standard errors and p-values (1 table per dependent variable)
mvrlm.fit$coefmat
# R-squared values (one per dependent variable)
mvrlm.fit$r.squared
# residual covariance matrix
mvrlm.fit$residCov

# model residuals and other details are available as well

# show the structure of the residuals objects
str(mvrlm.fit$residuals)
str(mvrlm.fit$residPV)

# dependent variables can have plausible values or not (or a combination)
```

```

mvrlm.fit <- mvrlm.sdf(composite | mrps22 ~ dsex + m072801, data = sdf, jrrIMax = 5)
summary(mvrlm.fit)

mvrlm.fit <- mvrlm.sdf(algebra | geometry | measurement ~ dsex + m072801, data = sdf, jrrIMax = 5)
summary(mvrlm.fit)

mvrlm.fit <- mvrlm.sdf(mrps51 | mrps22 ~ dsex + m072801, data = sdf, jrrIMax = 5)
summary(mvrlm.fit)

# hypotheses about coefficient restrictions can also be tested using the Wald test

mvr <- mvrlm.sdf(algebra | geometry ~ dsex + m072801, data = sdf)

hypothesis <- c("geometry_dsexFemale = 0", "algebra_dsexFemale = 0")

# test statistics based on the F and chi-squared distribution are available
linearHypothesis(mvr, hypothesis = hypothesis, test = "F")
linearHypothesis(mvr, hypothesis = hypothesis, test = "Chisq")

## End(Not run)

```

oddsRatio

Odds Ratios for edsurveyGlm Models

Description

Converts coefficients from edsurveyGlm logit regression model to odds ratios.

Usage

```
oddsRatio(model, alpha = 0.05)
```

Arguments

model	an edsurveyGlm model
alpha	the alpha level for the confidence level

Value

An oddsRatio.edsurveyGlm object with the following elements:

OR	odds ratio coefficient estimates
2.5%	lower bound 95% confidence interval
97.5%	upper bound 95% confidence interval

parseNAEPdct	<i>Format AM dct File for Use with DirectEstimation</i>
--------------	---

Description

Takes an AM dct file and formats it for use with the mml method as paramTab.

Usage

```
parseNAEPdct(dct, mml = TRUE)
```

Arguments

dct	a file location from which to read the dct file
mml	a logical for if the paramTab is being used in mml.sdf

Value

a data.frame in a format suitable for use with mml as a paramTab.

Author(s)

Sun-Joo Lee

percentile	<i>EdSurvey Percentiles</i>
------------	-----------------------------

Description

Calculates the percentiles of a numeric variable in an edsurvey.data.frame, a light.edsurvey.data.frame, or an edsurvey.data.frame.list.

Usage

```
percentile(
  variable,
  percentiles,
  data,
  weightVar = NULL,
  jrrIMax = 1,
  varMethod = c("jackknife", "Taylor"),
  alpha = 0.05,
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  recode = NULL,
```

```

returnVarEstInputs = FALSE,
returnNumberOfPSU = FALSE,
pctMethod = c("symmetric", "unbiased", "simple"),
confInt = TRUE,
dofMethod = c("JR", "WS")
)

```

Arguments

variable	the character name of the variable to percentiles computed, typically a subject scale or subscale
percentiles	a numeric vector of percentiles in the range of 0 to 100 (inclusive)
data	an <code>edsurvey.data.frame</code> or an <code>edsurvey.data.frame.list</code>
weightVar	a character indicating the weight variable to use.
jrrIMax	a numeric value; when using the jackknife variance estimation method, the default estimation option, <code>jrrIMax=1</code> , uses the sampling variance from the first plausible value as the component for sampling variance estimation. The V_{jrr} term (see <i>Statistical Methods Used in EdSurvey</i>) can be estimated with any number of plausible values, and values larger than the number of plausible values on the survey (including <code>Inf</code>) will result in all plausible values being used. Higher values of <code>jrrIMax</code> lead to longer computing times and more accurate variance estimates.
varMethod	a character set to <code>jackknife</code> or <code>Taylor</code> that indicates the variance estimation method used when constructing the confidence intervals. The jackknife variance estimation method is always used to calculate the standard error.
alpha	a numeric value between 0 and 1 indicating the confidence level. An alpha value of 0.05 would indicate a 95% confidence interval and is the default.
omittedLevels	a logical value. When set to the default value of <code>TRUE</code> , drops those levels of all factor variables that are specified in <code>achievementVars</code> and <code>aggregatBy</code> . Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the omitted levels.
defaultConditions	a logical value. When set to the default value of <code>TRUE</code> , uses the default conditions stored in an <code>edsurvey.data.frame</code> to subset the data. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the default conditions.
recode	a list of lists to recode variables. Defaults to <code>NULL</code> . Can be set as <code>recode=list(var1=list(from=c("a", "b", "c"), to="d"))</code> .
returnVarEstInputs	a logical value set to <code>TRUE</code> to return the inputs to the jackknife and imputation variance estimates which allows for the computation of covariances between estimates.
returnNumberOfPSU	a logical value set to <code>TRUE</code> to return the number of primary sampling units (PSUs)
pctMethod	one of "unbiased", "symmetric", "simple"; unbiased produces a weighted median unbiased percentile estimate, whereas <code>simple</code> uses a basic formula that matches previously published results. <code>Symmetric</code> uses a more basic formula but

	requires that the percentile is symmetric to multiplying the quantity by negative one.
confInt	a Boolean indicating if the confidence interval should be returned
dofMethod	passed to DoFCorrection as the method argument

Details

Percentiles, their standard errors, and confidence intervals are calculated according to the vignette titled *Statistical Methods Used in EdSurvey*. The standard errors and confidence intervals are based on separate formulas and assumptions.

The Taylor series variance estimation procedure is not relevant to percentiles because percentiles are not continuously differentiable.

Value

The return type depends on whether the class of the data argument is an `edsurvey.data.frame` or an `edsurvey.data.frame.list`.

The data argument is an `edsurvey.data.frame` When the data argument is an `edsurvey.data.frame`, `percentile` returns an S3 object of class `percentile`. This is a `data.frame` with typical attributes (`names`, `row.names`, and `class`) and additional attributes as follows:

<code>n0</code>	number of rows on <code>edsurvey.data.frame</code> before any conditions were applied
<code>nUsed</code>	number of observations with valid data and weights larger than zero
<code>nPSU</code>	number of PSUs used in the calculation
<code>call</code>	the call used to generate these results

The columns of the `data.frame` are as follows:

<code>percentile</code>	the percentile of this row
<code>estimate</code>	the estimated value of the percentile
<code>se</code>	the jackknife standard error of the estimated percentile
<code>df</code>	degrees of freedom
<code>confInt.ci_lower</code>	the lower bound of the confidence interval
<code>confInt.ci_upper</code>	the upper bound of the confidence interval
<code>nsmall</code>	the number of units with more extreme results, averaged across plausible values

When the `confInt` argument is set to `FALSE`, the confidence intervals are not returned.

The data argument is an `edsurvey.data.frame.list` When the data argument is an `edsurvey.data.frame.list`, `percentile` returns an S3 object of class `percentileList`. This is a `data.frame` with a `call` attribute. The columns in the `data.frame` are identical to those in the previous section, but there also are columns from the `edsurvey.data.frame.list`.

<code>covs</code>	a column for each column in the <code>covs</code> value of the <code>edsurvey.data.frame.list</code> . See Examples.
-------------------	--

When `returnVarEstInputs` is `TRUE`, an attribute `varEstInputs` also is returned that includes the variance estimate inputs used for calculating covariances with [varEstToCov](#).

Author(s)

Paul Bailey

References

Hyndman, R. J., & Fan, Y. (1996). Sample quantiles in statistical packages. *American Statistician*, 50, 361–365.

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# get the median of the composite
percentile("composite", 50, sdf)

# get several percentiles
percentile("composite", c(0,1,25,50,75,99,100), sdf)
# build an edsurvey.data.frame.list
sdfA <- subset(sdf, scrpsu %in% c(5,45,56))
sdfB <- subset(sdf, scrpsu %in% c(75,76,78))
sdfC <- subset(sdf, scrpsu %in% 100:200)
sdfD <- subset(sdf, scrpsu %in% 201:300)

sdf1 <- edsurvey.data.frame.list(list(sdfA, sdfB, sdfC, sdfD),
                                labels=c("A locations",
                                          "B locations",
                                          "C locations",
                                          "D locations"))

# this shows how these datasets will be described:
sdf1$covs

percentile("composite", 50, sdf1)
percentile("composite", c(25, 50, 75), sdf1)

## End(Not run)
```

```
print.achievementLevels
```

```
Print AchievementLevels Results
```

Description

Prints details of discrete and cumulative achievement levels calculated using weights and variance estimates appropriate for the `edsurvey.data.frame`.

Usage

```
## S3 method for class 'achievementLevels'
print(x, printCall = TRUE, printDiscrete = TRUE, printCumulative = TRUE, ...)
```

Arguments

x	an achievementLevels object
printCall	a logical value; by default (TRUE), prints details about plausible values and weights used for calculating achievement levels
printDiscrete	a logical value; by default (TRUE), prints discrete achievement levels if they are present in x
printCumulative	a logical value; by default (TRUE), prints cumulative achievement levels if they are present in x
...	these arguments are not passed anywhere and are included only for compatibility

Author(s)

Huade Huo and Ahmad Emad

print.edsurvey.data.frame

EdSurvey Metadata Summary

Description

Prints metadata regarding an edsurvey.data.frame or an edsurvey.data.frame.list

Usage

```
## S3 method for class 'edsurvey.data.frame'
print(x, printColnames = FALSE, ...)
```

Arguments

x	an edsurvey.data.frame or an edsurvey.data.frame.list
printColnames	a logical value; set to TRUE to see all column names in the edsurvey.data.frame or the edsurvey.data.frame.list
...	these arguments are not passed anywhere and are included only for compatibility

Author(s)

Michael Lee and Paul Bailey

print.gap *Gap Analysis Printing*

Description

Prints labels and a results vector of a gap analysis.

Usage

```
## S3 method for class 'gap'  
print(x, ..., printPercentage = TRUE)
```

```
## S3 method for class 'gapList'  
print(x, ..., printPercentage = TRUE)
```

Arguments

x an R object representing a gap of class gap or gapList
... these arguments are not passed anywhere and are included only for compatibility
printPercentage a logical value set to TRUE to request printing of the percentage in the groups.
 Defaults to TRUE.

Author(s)

Paul Bailey

readBB_2001 *Connect to B&B 2000–2001 Data*

Description

Opens a connection to a Baccalaureate & Beyond 2000–2001 data file and returns an `edsurvey` `data.frame` with information about the file and data.

Usage

```
readBB_2001(  
  b01DER_filepath,  
  b01WT_filepath,  
  masterTxtfilepath,  
  forceReread = FALSE,  
  verbose = TRUE  
)
```

Arguments

b01DER_Filepath	a character value to the main study-derived analytical data file (B01DER.dat). Located within the ECBW/Data Folder.
b01WT_FilePath	a character value to the study weight data file (B01WT.dat). Located within the ECBW/Data Folder.
masterTxtFilepath	a character value of the master format file (master.txt) that contains the meta-data for the b01DER_Filepath and b01WT_FilePath. Located in the ECBW folder.
forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the read function by using existing read-in data already processed.
verbose	a logical value that will determine if you want verbose output while the readBB_2001 function is running to indicate processing progress. The default value is TRUE.

Details

Reads the masterTxtFilepath file to parse the b01DER_Filepath and b01WT_FilePath files to an edsurvey.data.frame. This function creates two cached data files will be saved in the same directory and filename as the b01DER_Filepath file for the B&B 2000–2001 longitudinal survey. The two cached data files will have file extensions of .txt and .meta.

Value

an edsurvey.data.frame for the B&B 2000–2001 longitudinal dataset.

Author(s)

Tom Fink

See Also

[readECLS_K2011](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:
setwd("~/B&B2001/ecbw/B01")

dervFP <- file.path(getwd(), "Data", "B01DER.dat")
wgtFP <- file.path(getwd(), "Data", "B01WT.dat")
mstFP <- file.path(getwd(), "master.txt")

# with verbose output as default
bb2001 <- readBB_2001(dervFP, wgtFP, mstFP)

# silent output
bb2001 <- readBB_2001(dervFP, wgtFP, mstFP, verbose=FALSE)
```

```
# force cache update
bb2001 <- readBB_2001(dervFP, wgtFP, mstFP, forceReread = TRUE)

## End(Not run)
```

readBB_2003

Connect to B&B 1993–2003 Data

Description

Opens a connection to a Baccalaureate & Beyond 1993–2003 data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readBB_2003(
  b03DAS_Filepath,
  b03WEIGHT_FilePath,
  masterTxtFilepath,
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

<code>b03DAS_Filepath</code>	a character value to the main study-derived analytical data file (<code>B03DAS.dat</code>). Located within the ECBW/Data Folder.
<code>b03WEIGHT_FilePath</code>	a character value to the study weight data file (<code>B03WEIGHT.dat</code>). Located within the ECBW/Data Folder.
<code>masterTxtFilepath</code>	a character value of the master format file (<code>master.txt</code>) that contains the meta-data for the <code>b03DAS_Filepath</code> and <code>b03WEIGHT_FilePath</code> . Located in the ECBW folder.
<code>forceReread</code>	a logical value to force rereading of all processed data. The default value of <code>FALSE</code> will speed up the read function by using existing read-in data already processed.
<code>verbose</code>	a logical value that will determine if you want verbose output while the <code>readBB_2003</code> function is running to indicate processing progress. The default value is <code>TRUE</code> .

Details

Reads in the specified `masterTxtFilepath` file to parse the `b03DAS_Filepath` and `b03WEIGHT_FilePath` files for the B&B 1993–2003 longitudinal survey to an `edsurvey.data.frame`. The two created cached data files will be saved in the same directory and filename as the `b03DAS_Filepath` file, having new file extensions of `.txt` and `.meta`.

Value

an `edsurvey.data.frame` for the B&B 1993–2003 longitudinal dataset.

Author(s)

Tom Fink

See Also

[readECLS_K2011](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:
setwd("~/B&B2003/ecbw/B03")

dasFP <- file.path(getwd(), "Data", "B03DAS.dat")
wgtFP <- file.path(getwd(), "Data", "B03WEIGHT.dat")
mstFP <- file.path(getwd(), "master.txt")

# with verbose output as default
bb2003 <- readBB_2003(dasFP, wgtFP, mstFP)

# silent output
bb2003 <- readBB_2003(dasFP, wgtFP, mstFP, verbose=FALSE)

# force data cache update
bb2003 <- readBB_2003(dasFP, wgtFP, mstFP, forceReread = TRUE)

## End(Not run)
```

readBB_2012

Connect to B&B 2008–2012 Data

Description

Opens a connection to a Baccalaureate & Beyond 2008–2012 data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readBB_2012(
  path,
  csvFilename = "b12derived_datafile.csv",
  formatFilename = "b12derived_format.txt",
  metadataFilename = "b12derived_metadata.txt"
)
```

Arguments

path	a character value to the root directory path containing the csvFilename, formatFilename, and metadataFilename data files.
csvFilename	a character value of the derived data file (.csv) containing the raw B&B 2008–2012 data.
formatFilename	a character value of the format file (.txt) that describes the layout of the csvFilename.
metadataFilename	a character value of the metadata file (.txt) that describes additional metadata of the csvFilename.

Details

Reads in the specified csvFilename file for the B&B 2008–2012 longitudinal survey to an edsurvey.data.frame.

Value

an edsurvey.data.frame for the B&B 2008–2012 longitudinal dataset.

Author(s)

Tom Fink

See Also

[readECLS_K2011](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:
# using default filenames
bb <- readBB_2012(path = "~/BB/2012")
dim(bb)

# parameters specified without default filenames
bb <- readBB_2012(path = getwd(),
                  csvFilename = "renamedData.csv",
                  formatFilename = "renamedFormat.txt",
                  metadataFilename = "renamedMeta.txt")
dim(bb)

## End(Not run)
```

`readBPS_1994`*Beginning Postsecondary Students (BPS:90/94) Data*

Description

Opens a connection to a BPS 1990 to 1994 cohort data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readBPS_1994(  
  b94DAT_Filepath,  
  masterTxtFilepath,  
  forceReread = FALSE,  
  verbose = TRUE  
)
```

Arguments

<code>b94DAT_Filepath</code>	a character value of the file path to the student BPS:90/94 (.dat) file
<code>masterTxtFilepath</code>	a character value of the file path to the master.txt file contained within the electronic codebook directory
<code>forceReread</code>	a logical value to force rereading of all processed data. The default value of FALSE will speed up the read function by using existing read-in data already processed.
<code>verbose</code>	a logical value that will determine if you want verbose output while the <code>readHSB_Sophomore</code> function is running to indicate processing progress. The default value is TRUE.

Details

Reads in the student BPS 1990 to 1994 cohort data file to an `edsurvey.data.frame`.

Value

An `edsurvey.data.frame` for the BPS longitudinal dataset.

Author(s)

Sun-joo Lee

See Also

[readBB_2001](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:
setwd("~/BPS1994/")

datFP <- file.path(getwd(), "BPS94", "STUDENT.DAT")
mstFP <- file.path(getwd(), "ECBW", "BP4", "MASTER.TXT")

#with verbose output as default
bps94 <- readBPS_1994(datFP, mstFP)

#silent output
bps94 <- readBPS_1994(datFP, mstFP, verbose=FALSE)

#force data cache update
bps94 <- readBPS_1994(datFP, mstFP, forceReread = TRUE)

## End(Not run)
```

readBPS_2001

Beginning Postsecondary Students (BPS:96/01) Data

Description

Opens a connection to a BPS 1996 to 2001 cohort data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readBPS_2001(
  path = getwd(),
  csvFilename = "bps01derived_datafile.csv",
  formatFilename = "bps01derived_format.txt",
  metadataFilename = "bps01derived_metadata.txt"
)
```

Arguments

<code>path</code>	a character value to the full directory path to the BPS extracted data files
<code>csvFilename</code>	a character value of the derived data file (.csv) containing the raw BPS:96/01 data
<code>formatFilename</code>	a character value of the format file (.txt) that describes the layout of the <code>csvFilename</code>
<code>metadataFilename</code>	a character value of the metadata file (.txt) that describes additional metadata of the <code>csvFilename</code>

Details

Reads in the unzipped derived data files from the BPS longitudinal database of the BPS 1996 to 2001 cohort.

Value

An `edsurvey.data.frame` for the BPS longitudinal dataset.

Author(s)

Tom Fink

See Also

[readBB_2012](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:
# using default filenames
bps01 <- readBPS_2001(path = "~/BPS/2001")
dim(bps01)

# parameters specified without default filenames
bps01 <- readBPS_2001(path = getwd(),
                      csvFilename = "renamedData.csv",
                      formatFilename = "renamedFormat.txt",
                      metadataFilename = "renamedMeta.txt")

dim(bps01)

## End(Not run)
```

readBPS_2009

Beginning Postsecondary Students (BPS:04/09) Data

Description

Opens a connection to a BPS 2004 to 2009 cohort data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readBPS_2009(
  path = getwd(),
  csvFilename = "bps09derived_datafile.csv",
  formatFilename = "bps09derived_format.txt",
  metadataFilename = "bps09derived_metadata.txt"
)
```

Arguments

path	a character value to the full directory path to the BPS extracted data files
csvFilename	a character value of the derived data file (.csv) containing the raw BPS:04/09 data
formatFilename	a character value of the format file (.txt) that describes the layout of the csvFilename
metadataFilename	a character value of the metadata file (.txt) that describes additional metadata of the csvFilename

Details

Reads in the unzipped derived data files from the BPS longitudinal database of the BPS 2004 to 2009 cohort.

Value

An `edsurvey` `data.frame` for the BPS longitudinal dataset.

Author(s)

Tom Fink

See Also

[readBB_2012](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:
# using default filenames
bps09 <- readBPS_2009(path = "~/BPS/2009")
dim(bps09)

# parameters specified without default filenames
bps09 <- readBPS_2009(path = getwd(),
                      csvFilename = "renamedData.csv",
                      formatFilename = "renamedFormat.txt",
                      metadataFilename = "renamedMeta.txt")

dim(bps09)

## End(Not run)
```

`readBPS_2014`*Beginning Postsecondary Students (BPS:12/14) Data*

Description

Opens a connection to a BPS 2012 to 2014 cohort data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readBPS_2014(  
  path = getwd(),  
  csvFilename = "bps14derived_datafile.csv",  
  formatFilename = "bps14derived_format.txt",  
  metadataFilename = "bps14derived_metadata.txt"  
)
```

Arguments

<code>path</code>	a character value to the full directory path to the BPS extracted data files
<code>csvFilename</code>	a character value of the derived data file (.csv) containing the raw BPS:12/14 data
<code>formatFilename</code>	a character value of the format file (.txt) that describes the layout of the <code>csvFilename</code>
<code>metadataFilename</code>	a character value of the metadata file (.txt) that describes additional metadata of the <code>csvFilename</code>

Details

Reads in the unzipped files downloaded from the BPS 2012 to 2014 cohort longitudinal database.

Value

An `edsurvey.data.frame` for the BPS longitudinal dataset.

Author(s)

Sun-joo Lee

See Also

[readBB_2012](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:
# using default filenames
bps14 <- readBPS_2014(path = "~/BPS/2012")
dim(bps14)

# parameters specified without default filenames
bps14 <- readBPS_2014(path = getwd(),
                      csvFilename = "renamedData.csv",
                      formatFilename = "renamedFormat.txt",
                      metadataFilename = "renamedMeta.txt")

dim(bps14)

## End(Not run)
```

readBTLS

Connect to BTLS Data

Description

Opens a connection to the Beginning Teacher Longitudinal Study (BTLS) waves 1 through 5 data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readBTLS(dat_FilePath, spss_FilePath, verbose = TRUE)
```

Arguments

<code>dat_FilePath</code>	a character value to the full path of the BTLS fixed-width (.dat) data file
<code>spss_FilePath</code>	a character value to the full path of the SPSS syntax file to process the <code>dat_FilePath</code>
<code>verbose</code>	a logical value that will determine if you want verbose output while the <code>readBTLS</code> function is running to indicate processing progress (the default value is TRUE)

Details

Reads the `spss_FilePath` file to parse the `dat_FilePath` to an `edsurvey.data.frame`. There is no cached data because the `dat_FilePath` format already is in fixed-width format.

Value

an `edsurvey.data.frame` for the BTLS waves 1 to 5 longitudinal dataset.

Author(s)

Tom Fink

See Also

[readECLS_K2011](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:

fld <- "~/EdSurveyData/BTLS"
datPath <- file.path(fld, "ASCII Data File", "BTLS2011_12.dat")
spsPath <- file.path(fld, "Input Syntax for Stata and SPSS", "BTLS2011_12.sps")

#read in the data to an edsurvey.data.frame
btls <- readBTLS(datPath, spsPath, verbose = TRUE)

dim(btls)

## End(Not run)
```

readCivEDICCS

Connect to ICCS and CivED Data

Description

Opens a connection to an ICCS (2009, 2016) or CivEd (1999) data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readCivEDICCS(
  path,
  countries,
  dataSet = c("student", "teacher"),
  gradeLvl = c("8", "9", "12"),
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

<code>path</code>	a character value of the full directory to the ICCS/CivED extracted SPSS (.sav) set of data
<code>countries</code>	a character vector of the country/countries to include using the three-digit International Organization for Standardization (ISO) country code. A list of country codes can be found on Wikipedia at https://en.wikipedia.org/wiki/ISO_3166-1#Current_codes or other online sources. Consult the <i>ICCS/CivED User Guide</i> to help determine what countries are included within a specific testing year of ICCS/CivED. To select all countries, use a wildcard value of <code>*</code> .

dataSet	a character value of either student or teacher to indicate which set of data is returned. The student-level and teacher-level datasets cannot both be returned at the same time, unlike other IEA datasets. Note: The CivED 1999 study also included student-to-teacher data for Grade 8. Specifying dataSet="student" and gradeLvl=8 will include both the student and teacher data in the resulting edsurvey.data.frame.
gradeLvl	a character value of the grade level to return <ul style="list-style-type: none"> • 8 = eighth grade (the default if not specified) • 9 = ninth grade • 12 = 12th grade (for CivED 1999 only)
forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the readCivEDICCS function by using existing read-in data already processed.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Details

Reads in the unzipped files downloaded from the international database(s) using the [IEA Study Data Repository](#). Data files require the SPSS data file (.sav) format using the default filenames.

When using the getData function with a CivED or ICCS study edsurvey.data.frame, the requested data variables are inspected, and it handles any necessary data merges automatically. The school data always will be returned merged to the student data, even if only school variables are requested. If a 1999 CivED Grade 8 edsurvey.data.frame with teacher data variables is requested by the getData call, it will cause teacher data to be merged. Many students can be linked to many teachers, which varies widely between countries, and not all countries contain teacher data.

Calling the dim function for a CivED 1999 Grade 8 edsurvey.data.frame will result in the row count as if the teacher dataset was merged. This row count will be considered the full data N of the edsurvey.data.frame, even if no teacher data were included in an analysis. The column count returned by dim will be the count of unique column variables across all data levels.

Value

an edsurvey.data.frame for a single specified country or an edsurvey.data.frame.list if multiple countries specified

Author(s)

Tom Fink

See Also

[readNAEP](#), [readTIMSS](#), [getData](#), and [downloadCivEDICCS](#)

Examples

```
## Not run:
eng <- readCivEDICCS("~/ICCS/2009/", countries = c("eng"),
                    gradeLvl = 8, dataSet = "student")
gg <- getData(eng, c("famstruc", "totwgts", "civ"))
head(gg)
edsurveyTable(civ ~ famstruc, eng)

## End(Not run)
```

readECLS_B

Connect to ECLS-B Data

Description

Opens a connection to an ECLS-B data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readECLS_B(
  path = getwd(),
  filename,
  layoutFilename,
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

<code>path</code>	a character value to the full directory path(s) to the ECLS-B extracted fixed-width-format (.dat) set of datafiles.
<code>filename</code>	a character value of the name of the fixed-width-file (.dat) data file in the specified path to be read.
<code>layoutFilename</code>	a character value of the filename of either the ASCII text (.txt) layout file of the filename within the specified path, OR a character value of the filename of the SPSS syntax (.sps) layout file of the filename within the specified path
<code>forceReread</code>	a logical value to force rereading of all processed data. The default value of FALSE will speed up the read function by using existing read-in data already processed.
<code>verbose</code>	a logical value that will determine if you want verbose output while the <code>readECLS-K2011</code> function is running to indicate processing progress. The default value is TRUE.

Details

Reads in the unzipped files downloaded from the ECLS-B longitudinal Database.

Value

An `edsurvey.data.frame` for the ECLS-B longitudinal dataset.

Author(s)

Trang Nguyen

See Also

[readNAEP](#), [getData](#)

readECLS_K1998	<i>Connect to ECLS-K 1998 Data</i>
----------------	------------------------------------

Description

Opens a connection to an ECLS-K 1998 data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readECLS_K1998(
  path = getwd(),
  filename = "eclsk_98_99_k8_child_v1_0.dat",
  layoutFilename = "Layout_k8_child.txt",
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

path	a character value to the full directory path(s) to the ECLS-K-extracted fixed-width-format (.dat) set of data files
filename	a character value of the name of the fixed-width (.dat) data file in the specified path to be read
layoutFilename	a character value of the filename of either the ASCII (.txt) layout file of the filename within the specified path or a character value of the filename of the SPSS syntax (.sps) layout file of the filename within the specified path
forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the read function by using existing read-in data already processed.
verbose	a logical value that will determine if you want verbose output while the readECLS-K1998 function is running to indicate processing progress. The default value is TRUE.

Details

Reads in the unzipped files downloaded from the ECLS–K 1998 longitudinal dataset(s) to an `edsurvey.data.frame`. The ECLS–K 1998–99 study consisted of three distinct separate datasets that cannot be combined: (1) Child Grades K–8 Data, (2) School Base-Year Data, and (3) Teacher Base-Year Data. The `filename` and `layoutFilename` arguments default to the corresponding Child K–8 default filenames.

Value

an `edsurvey.data.frame` for the ECLS–K 1998 longitudinal dataset

Author(s)

Tom Fink

See Also

[readECLS_K2011](#), [readNAEP](#), [getData](#), [downloadECLS_K](#)

Examples

```
## Not run:
# read-in student file with defaults
eclsk_df <- readECLS_K1998(path="~/ECLS_K/1998") #using defaults
d <- getData(eclsk_df, c("childid", "gender", "race"))
summary(d)

## End(Not run)

## Not run:
# read-in with parameters specified
eclsk_df <- readECLS_K1998(path = "~/ECLS_K/1998",
  filename = "eclsk_98_99_k8_child_v1_0.dat",
  layoutFilename = "Layout_k8_child.txt",
  verbose = TRUE,
  forceReread = FALSE)

## End(Not run)
```

readECLS_K2011

Connect to ECLS–K 2011 Data

Description

Opens a connection to an ECLS–K 2011 data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readECLS_K2011(
  path = getwd(),
  filename = "childK5p.dat",
  layoutFilename = "ECLSK2011_K5PUF.sps",
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

path	a character value to the full directory path(s) to the ECLS–K 2010–11 extracted fixed-width-format (.dat) set of data files
filename	a character value of the name of the fixed-width (.dat) data file in the specified path to be read
layoutFilename	a character value of the filename of either the ASCII (.txt) layout file of the filename within the specified path or a character value of the filename of the SPSS syntax (.sps) layout file of the filename within the specified path
forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the read function by using existing read-in data already processed.
verbose	a logical value that will determine if you want verbose output while the readECLS--K2011 function is running to indicate processing progress. The default value is TRUE.

Details

Reads in the unzipped files downloaded from the ECLS–K 2010–11 longitudinal dataset.

Value

an `edsurvey.data.frame` for the ECLS–K 2010–11 longitudinal dataset

Author(s)

Tom Fink

See Also

[readECLS_K1998](#), [readNAEP](#), [getData](#), and [downloadECLS_K](#)

Examples

```
## Not run:
# read-in student file with defaults
eclsk_df <- readECLS_K2011(path="~/ECLS_K/2011") #using defaults
d <- getData(eclsk_df, c("childid", "c1hgt1", "c1wgt1"))
summary(d)

## End(Not run)
```

```
## Not run:
# read-in with parameters specified
eclsk_df <- readECLS_K2011(path = "~/ECLS_K/2011",
                          filename = "childK5p.dat",
                          layoutFilename = "ECLSK2011_K5PUF.sps",
                          forceReread = FALSE,
                          verbose = TRUE)

## End(Not run)
```

readELS

Connect to Education Longitudinal Study (ELS:2002) Data

Description

Opens a connection to an ELS data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readELS(
  path = getwd(),
  filename = "els_02_12_byf3pststu_v1_0.sav",
  wgtFilename = ifelse(filename == "els_02_12_byf3pststu_v1_0.sav",
                       "els_02_12_byf3stubrr_v1_0.sav", NA),
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

<code>path</code>	a character value to the directory path of the extracted set of data files and layout files.
<code>filename</code>	a character value of the name of the SPSS (.sav) data file in the specified path to be read.
<code>wgtFilename</code>	a character value of the name of the associated balanced repeated replication (BRR) weight SPSS (.sav) data file in the specified path to be read. This argument is applicable only for the student-level data, which contains a separate data file containing the weight replicate information. If using default filenames (recommended), then you shouldn't need to specify this parameter because it will inspect the <code>filename</code> argument. For data files with no BRR weight file associated, specify a value of <code>NULL</code> or <code>NA</code> .
<code>forceReread</code>	a logical value to force rereading of all processed data. The default value of <code>FALSE</code> will speed up the read function by using existing read-in data already processed.
<code>verbose</code>	a logical value that will determine if you want verbose output while the <code>readELS</code> function is running to indicate processing progress. The default value is <code>TRUE</code> .

readHSB_Senior	<i>Connect to HS&B Study Senior Data</i>
----------------	--

Description

Opens a connection to a High School & Beyond 1980–1986 Senior cohort data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readHSB_Senior(
  HSR8086_PRI_FilePath,
  HSR8086_SASSyntax_Path,
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

HSR8086_PRI_FilePath	a character value to the main study-derived analytical data file (HSR8086_REV.PRI). Located within the REVISED_ASCII Folder.
HSR8086_SASSyntax_Path	a character value to the SAS syntax file for parsing the HSR8086_REV.PRI data file. Located within the SAS_EXTRACT_LOGIC Folder.
forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the read function by using existing read-in data already processed.
verbose	a logical value that will determine if you want verbose output while the <code>readHSB_Senior</code> function is running to indicate processing progress. The default value is TRUE.

Details

Reads in the specified `HSR8086_SASSyntax_Path` file to parse the `HSR8086_PRI_FilePath` file. A cached data file and metadata file will be saved in the same directory and filename as the `HSR8086_PRI_FilePath` file, having new file extensions of `.txt` and `.meta`, respectively.

Please note the original source `recode` variable has been split into two variables named `recode_str` for the stratum value and `recode_psu` for the primary sampling unit (PSU) value in the resulting cache data.

Value

an `edsurvey.data.frame` for the HS&B Senior 1980–1986 longitudinal dataset

Author(s)

Tom Fink

See Also

[readECLS_K2011](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:
wrkFld <- "~/HSB/SENIOR"

dataPath <- file.path(wrkFld, "REVISED_ASCII", "HSR8086_REV.PRI")
sasPath <- file.path(wrkFld, "SAS_EXTRACT_LOGIC", "HSBsr_READ_HSR8086.SAS")

# with verbose output as default
hsbSR <- readHSB_Senior(dataPath, sasPath)

# silent output
hsbSR <- readHSB_Senior(dataPath, sasPath, verbose = FALSE)

# force cache update
hsbSR <- readHSB_Senior(dataPath, sasPath, forceReread = TRUE)

## End(Not run)
```

readHSB_Sophomore

Connect to HS&B Study Sophomore Data

Description

Opens a connection to a High School & Beyond 1980–1992 Sophomore cohort data file and returns an `edsurvey.data` frame with information about the file and data.

Usage

```
readHSB_Sophomore(
  HS08092_PRI_FilePath,
  HS08092_SASSyntax_Path,
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

`HS08092_PRI_FilePath`

a character value to the main study-derived analytical data file (`HS08092_REV.PRI`). Located within the `REVISED_ASCII` folder.

`HS08092_SASSyntax_Path`

a character value to the SAS syntax file for parsing the `HS08092_REV.PRI` data file. Located within the `SAS_EXTRACT_LOGIC` folder.

forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the read function by using existing read-in data already processed.
verbose	a logical value that will determine if you want verbose output while the readHSB_Sophomore function is running to indicate processing progress. The default value is TRUE.

Details

Reads in the specified HS08092_SASSyntax_Path file to parse the HS08092_PRI_FilePath file. A cached data file and metadata file will be saved in the same directory and filename as the HS08092_PRI_FilePath file, having new file extensions of .txt and .meta, respectively.

Please note the original source reocode variable has been split into two variables named reocode_str for the stratum value and reocode_psu for the primary sampling unit (PSU) value in the resulting cache data.

Value

an edsurvey.data.frame for the HS&B Sophomore 1980–1992 longitudinal dataset

Author(s)

Tom Fink

See Also

[readECLS_K2011](#), [readNAEP](#), and [getData](#)

Examples

```
## Not run:
wrkFld <- "~/HSB/SOPHOMORE"

dataPath <- file.path(wrkFld, "REVISED_ASCII", "HS08092_REV.PRI")
sasPath <- file.path(wrkFld, "SAS_EXTRACT_LOGIC", "HSBso_READ_HS08092.SAS")

# with verbose output as default
hsbSO <- readHSB_Sophomore(dataPath, sasPath)

# silent output
hsbSO <- readHSB_Sophomore(dataPath, sasPath, verbose = FALSE)

# force cache update
hsbSO <- readHSB_Sophomore(dataPath, sasPath, forceReread = TRUE)

## End(Not run)
```

 readHSLs

Connect to High School Longitudinal Study 2009 (HSLs:2009) Data

Description

Opens a connection to an HSLs data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readHSLs(
  path = getwd(),
  filename = "hsls_16_student_v1_0.sav",
  wgtFilename = NA,
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

<code>path</code>	a character value to the full directory path(s) to the HSLs extracted SPSS (.sav) set of data files
<code>filename</code>	a character value of the name of the SPSS (.sav) datafile to be read
<code>wgtFilename</code>	a character value of the name of the associated BRR weight SPSS (.sav) data file in the specified path to be read. This argument is only applicable for the restricted-use student level data, which contains a separate data-file containing the weight replicate information. For data files with no balanced repeated replication (BRR) weight file associated, specify a value of NULL or NA.
<code>forceReread</code>	a logic value to force a rereading of all processed data. The default value of FALSE speeds up the <code>readHSLs</code> function by using existing read-in data already processed.
<code>verbose</code>	a logical value set to TRUE for verbose output that indicates progress

Details

Reads in the unzipped files downloaded from the HSLs longitudinal dataset.

Value

an `edsurvey.data.frame` for the HSLs longitudinal dataset

Note

The SPSS (.sav) format is preferred over the fixed-width-format (.dat) ASCII file format at this time relating to value label issues identified with the ASCII layout specifications.

Author(s)

Tom Fink

See Also[readECLS_K2011](#), [readNAEP](#), and [getData](#)**Examples**

```
## Not run:
# use function default values at working directory
hsls <- readHSLs("~/HSLs/2009")

# specify parameters with verbose output
hsls <- readHSLs(path=~"/HSLs/2009",
                filename = "hsls_16_student_v1_0.sav",
                forceReread = FALSE,
                verbose = TRUE)

# specify parameters silent output
hsls <- readHSLs(path=~"/HSLs/2009",
                filename = "hsls_16_student_v1_0.sav",
                forceReread = FALSE,
                verbose = FALSE)

#for restricted-use student data, replicate weights stored in separate file
hslsRUD <- readHSLs(path=~"/HSLs/2009",
                  filename = "hsls_16_student_v1_0.sav",
                  wgtFilename = "hsls_16_student_BRR_v1_0.sav",
                  forceReread = FALSE,
                  verbose = TRUE)

## End(Not run)
```

readICILS*Connect to ICILS Data*

Description

Opens a connection to an ICILS data file residing on the disk and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readICILS(
  path,
  countries,
  dataSet = c("student", "teacher"),
  forceReread = FALSE,
```

```

    verbose = TRUE
  )

```

Arguments

path	a character value to the full directory path to the ICILS extracted SPSS (.sav) set of data
countries	a character vector of the country/countries to include using the three-digit ISO country code. A list of country codes can be found on Wikipedia at https://en.wikipedia.org/wiki/ISO_3166-1#Current_codes or other online sources. Consult the <i>ICILS User Guide</i> to help determine what countries are included within a specific testing year of ICILS. To select all countries, use a wildcard value of *.
dataSet	a character value of either student (the default if not specified) or teacher to indicate which set of data is returned. The student-level and teacher-level datasets cannot both be returned at the same time, unlike other IEA datasets.
forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the readICILS function by using existing read-in data already processed.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Details

Reads in the unzipped files downloaded from the ICILS international dataset(s) using the [IEA Study Data Repository](#). Data files require the SPSS data file (.sav) format using the default filenames.

Value

an `edsurvey.data.frame` for a single specified country or an `edsurvey.data.frame.list` if multiple countries specified

Author(s)

Tom Fink and Jeppe Bundsgaard (updated for 2018)

See Also

[readNAEP](#), [readTIMSS](#), and [getData](#)

Examples

```

## Not run:
pol <- readICILS("~/ICILS/2013", countries = "pol", dataSet = "student")
gg <- getData(pol, c("idstud", "cil", "is1g18b"))
head(gg)
edsurveyTable(cil ~ is1g18b, pol)

## End(Not run)

```

readNAEP

*Connect to NAEP Data***Description**

Opens a connection to an NAEP data file residing on the disk and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readNAEP(
  path,
  defaultWeight = "origwt",
  defaultPvs = "composite",
  omittedLevels = c("Multiple", NA, "Omitted"),
  frPath = NULL
)
```

Arguments

<code>path</code>	a character value indicating the full filepath location and name of the (.dat) data file
<code>defaultWeight</code>	a character value that indicates the default weight specified in the resulting <code>edsurvey.data.frame</code> . Default value is <code>origwt</code> if not specified.
<code>defaultPvs</code>	a character value that indicates the default plausible value specified in the resulting <code>edsurvey.data.frame</code> . Default value is <code>composite</code> if not specified.
<code>omittedLevels</code>	a character vector indicating which factor levels/labels should be excluded. When set to the default value of <code>c('Multiple', NA, 'Omitted')</code> , adds the vector to the <code>edsurvey.data.frame</code> .
<code>frPath</code>	a character value indicating the location of the <code>fr2</code> parameter layout file included with the data companion to parse the specified filepath data file

Details

The function uses the `frPath` file layout (.fr2) data to read in the fixed-width data file (.dat) and builds the `edsurvey.data.frame`.

NAEP includes both scaled scores and theta scores, with the latter having names ending in `_theta`.

When a NAEP administration includes a linking error variable those variables are included and end in `_linking`. When present, simply use the `_linking` version of a variable to get a standard error estimate that includes linking error.

Value

An `edsurvey.data.frame` containing the following elements:

userConditions a list containing all user conditions set using the `subset.edsurvey.data.frame` method
 defaultConditions the default conditions to be applied to the `edsurvey.data.frame`
 data an LaF object containing a connection to the student dataset on disk
 dataSch an LaF object containing a connection to the school dataset on disk
 dataTch not applicable for NAEP data; returns NULL
 weights a list containing the weights found on the `edsurvey.data.frame`
 pvvar a list containing the plausible values found on the `edsurvey.data.frame`
 subject the subject of the dataset contained in the `edsurvey.data.frame`
 year the year of assessment of the dataset contained in the `edsurvey.data.frame`
 assessmentCode the code of the dataset contained in the `edsurvey.data.frame`
 dataType the type of data (whether student or school) contained in the `edsurvey.data.frame`
 gradeLevel the grade of the dataset contained in the `edsurvey.data.frame`
 achievementLevels default NAEP achievement cutoff scores
 omittedLevels the levels of the factor variables that will be omitted from the `edsurvey.data.frame`
 fileFormat a `data.frame` containing the parsed information from the student `.fr2` file associated with the data
 fileFormatSchool a `data.frame` containing the parsed information from the school `.fr2` file associated with the data
 fileFormatTeacher not applicable for NAEP data; returns NULL
 survey the type of survey data contained in the `edsurvey.data.frame`

Author(s)

Tom Fink and Ahmad Emad

Examples

```

# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))
sdf

## Not run:
# To read in an NCES file first set the directory to the ~/Data subfolder,
# then read in the appropriate .dat file:
setwd("location/of/Data")
sdf <- readNAEP(path="M36NT2PM.dat")

# Or read in the .dat file directly through the folder pathway:
sdf <- readNAEP(path="location/of/Data/M36NT2PM.dat")

## End(Not run)

```

`readNLS72`*Connect to NLS-72 Study Data*

Description

Opens a connection to a National Longitudinal Study of the High School Class of 1972 (NLS-72) cohort data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readNLS72(  
  NLS7286_PRI_FilePath,  
  NLS7286_SASSyntax_Path,  
  forceReread = FALSE,  
  verbose = TRUE  
)
```

Arguments

<code>NLS7286_PRI_FilePath</code>	a character value to the main study derived analytical data file (NLS7286_REV.PRI). Located within the REVISED_ASCII folder.
<code>NLS7286_SASSyntax_Path</code>	a character value to the SAS syntax file for parsing the NLS7286_REV.PRI data file. Located within the SAS_EXTRACT_LOGIC folder.
<code>forceReread</code>	a logical value to force rereading of all processed data. The default value of FALSE will speed up the read function by using existing read-in data already processed.
<code>verbose</code>	a logical value that will determine if you want verbose output while the <code>readNLS72</code> function is running to indicate processing progress. The default value is TRUE.

Details

Reads in the specified `NLS7286_SASSyntax_Path` file to parse the `NLS7286_PRI_FilePath` file. A cached data file and metadata file will be saved in the same directory and filename as the `NLS7286_PRI_FilePath` file, having new file extensions of `.csv` and `.meta`, respectively.

Value

an `edsurvey.data.frame` for the National Longitudinal Study of the High School Class of 1972 longitudinal dataset

Author(s)

Tom Fink

See Also

[readHSB_Sophomore](#), [readHSB_Senior](#), and [getData](#)

readPIAAC

Connect to PIAAC Data

Description

Opens a connection to a PIAAC data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readPIAAC(
  path,
  countries,
  forceReread = FALSE,
  verbose = TRUE,
  usaOption = "12_14"
)
```

Arguments

<code>path</code>	a character value to the full directory path to the PIAAC .csv files and Microsoft Excel codebook
<code>countries</code>	a character vector of the country/countries to include using the three-digit ISO country code. A list of country codes can be found in the PIAAC codebook or https://en.wikipedia.org/wiki/ISO_3166-1#Current_codes . If files are downloaded using downloadPIAAC , a country dictionary text file can be found in the filepath. You can use * to indicate all countries available. For the usa, the year must be specified using: <code>usa12_14</code> or <code>usa17</code> .
<code>forceReread</code>	a logical value to force rereading of all processed data. Defaults to FALSE. Setting <code>forceReread</code> to be TRUE will cause PIAAC data to be reread and increase the processing time.
<code>verbose</code>	a logical value that will determine if you want verbose output while the function is running to indicate the progress. Defaults to TRUE.
<code>usaOption</code>	a character value of 12_14 or 17 that specifies what year of the USA survey should be used when loading all countries by using * in the <code>countries</code> argument. This will only make a difference when loading all countries. Defaults to 12_14.

Details

Reads in the unzipped .csv files downloaded from the PIAAC dataset using the OECD repository (<https://www.oecd.org/skills/piaac/>). Users can use [downloadPIAAC](#) to download all required files automatically.

Value

an `edsurvey.data.frame` for a single specified country or an `edsurvey.data.frame.list` if multiple countries specified

Author(s)

Trang Nguyen

References

Organisation for Economic Co-operation and Development. (2016). *Technical report of the survey of adult skills (PIAAC)* (2nd ed.). Paris, France: Author. Retrieved from https://www.oecd.org/skills/piaac/PIAAC_Technical_Report_2nd_Edition_Full_Report.pdf

See Also

[getData](#) and [downloadPIAAC](#)

Examples

```
## Not run:
# the following call returns an edsurvey.data.frame to PIAAC for Canada
can <- readPIAAC("~/PIAAC/Cycle 1/", countries = "can")

# extract a data.frame with a few variables
gg <- getData(can, c("c_d05", "ageg10lfs"))
head(gg)

# conduct an analysis on the edsurvey.data.frame
edsurveyTable(~ c_d05 + ageg10lfs, data = can)

## End(Not run)
```

readPIRLS

Connect to PIRLS Data

Description

Opens a connection to a PIRLS data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readPIRLS(path, countries, forceReread = FALSE, verbose = TRUE)
```

Arguments

path	a character value to the full directory path to the PIRLS extracted SPSS (.sav) set of data
countries	a character vector of the country/countries to include using the three-digit ISO country code. A list of country codes can be found on Wikipedia at https://en.wikipedia.org/wiki/ISO_3166-1#Current_codes or other online sources. Consult the <i>PIRLS User Guide</i> to help determine what countries are included within a specific testing year of PIRLS. To select all countries, use a wildcard value of *.
forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the readPIRLS function by using existing read-in data already processed.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Details

Reads in the unzipped files downloaded from the PIRLS international database(s) using the [IEA Study Data Repository](#). Data files require the SPSS data file (.sav) format using the default file-names.

A PIRLS `edsurvey.data.frame` includes three distinct data levels:

- student
- school
- teacher

When the `getData` function is called using a PIRLS `edsurvey.data.frame`, the requested data variables are inspected, and it handles any necessary data merges automatically. The school data always will be returned merged to the student data, even if only school variables are requested. If teacher variables are requested by the `getData` call, it will cause teacher data to be merged. Many students can be linked to many teachers, which varies widely between countries.

Please note that calling the `dim` function for a PIRLS `edsurvey.data.frame` will result in the row count as if the teacher dataset was merged. This row count will be considered the full data `N` of the `edsurvey.data.frame`, even if no teacher data were included in an analysis. The column count returned by `dim` will be the count of unique column variables across all three data levels.

Value

an `edsurvey.data.frame` for a single specified country or an `edsurvey.data.frame.list` if multiple countries specified

Author(s)

Tom Fink

See Also

[readNAEP](#), [readTIMSS](#), [getData](#), and [downloadPIRLS](#)

Examples

```
## Not run:
nor <- readPIRLS("~/PIRLS/2011", countries = c("nor"))
gg <- getData(nor, c("itsex", "totwgt", "rrea"))
head(gg)
edsurveyTable(rrea ~ itsex, nor)

## End(Not run)
```

readPISA

Connect to PISA Data

Description

Opens a connection to a PISA data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readPISA(
  path,
  database = c("INT", "CBA", "FIN"),
  countries,
  cognitive = c("score", "response", "none"),
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

<code>path</code>	a character vector to the full directory path(s) to the PISA-extracted fixed-width files and SPSS control files (.txt).
<code>database</code>	a character to indicate a selected database. Must be one of INT (general database that most people use), CBA (computer-based database in PISA 2012 only), or FIN (financial literacy database in PISA 2012 and 2018). Defaults to INT.
<code>countries</code>	a character vector of the country/countries to include using the three-digit ISO country code. A list of country codes can be found in the PISA codebook or https://en.wikipedia.org/wiki/ISO_3166-1#Current_codes . If files are downloaded using <code>downloadPISA</code> , a country dictionary text file can be found in the filepath.
<code>cognitive</code>	one of none, score, or response. Default is score. The PISA database often has three student files: student questionnaire, cognitive item response, and scored cognitive item response. The first file is used as the main student file with student background information. Users can choose whether to merge score or response data into the main file or not (if none).

forceReread	a logical value to force rereading of all processed data. Defaults to FALSE. Setting forceReread to be TRUE will cause PISA data to be reread and increase processing time.
verbose	a logical value that will determine if you want verbose output while the function is running to indicate progress. Defaults to TRUE.

Details

Reads in the unzipped files downloaded from the PISA database using the OECD Repository (<https://www.oecd.org/pisa/>). Users can use `downloadPISA` to download all required files. Student questionnaire files (with weights and plausible values) are used as main files, which are then merged with cognitive, school, and parent files (if available).

The average first-time processing time for 1 year and one database for all countries is 10–15 minutes. If `forceReread` is set to be FALSE, the next time this function is called will take only 5–10 seconds.

For the PISA 2000 study, please note that the study weights are subject specific. Each weight has different adjustment factors for reading, mathematics, and science based on its original subject source file. For example, the `w_fstuwt_read` weight is associated with the reading subject data file. Special care must be used to select the correct weight based on your specific analysis. See the OECD documentation for further details. Use the `showWeights` function to see all three student level subject weights:

- `w_fstuwt_read` = Reading (default)
- `w_fstuwt_scie` = Science
- `w_fstuwt_math` = Mathematics

Value

an `edsurvey.data.frame` for a single specified country or an `edsurvey.data.frame.list` if multiple countries are specified

Author(s)

Tom Fink, Trang Nguyen, and Paul Bailey

References

Organisation for Economic Co-operation and Development. (2017). *PISA 2015 technical report*. Paris, France: OECD Publishing. Retrieved from <https://www.oecd.org/pisa/data/2015-technical-report/>

See Also

`getData` and `downloadPISA`

Examples

```
## Not run:
# the following call returns an edsurvey.data.frame to
# PISA 2012 International Database for Singapore
sgp2012 <- readPISA(path = "~/PISA/2012", database = "INT", countries = "sgp")

# extract a data.frame with a few variables
gg <- getData(sgp2012, c("cnt","read","w_fstuw"))
head(gg)

# conduct an analysis on the edsurvey.data.frame
edsurveyTable(read ~ st04q01 + st20q01, data = sgp2012)

## End(Not run)
```

readPISA_YAFS

PISA YAFS (Young Adult Follow-up Study)

Description

Opens a connection to the Programme for International Student Assessment (PISA) YAFS 2016 data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readPISA_YAFS(
  datPath = file.path(getwd(), "PISA_YAFS2016_Data.dat"),
  spsPath = file.path(getwd(), "PISA_YAFS2016_SPSS.sps"),
  esdf_PISA2012_USA = NULL
)
```

Arguments

`datPath` a character value of the file location where the data file (.dat) file is saved.

`spsPath` a character value of the file location where the SPSS (.sps) script file is saved to parse the `datPath` data file.

`esdf_PISA2012_USA` (optional) an `edsurvey.data.frame` of the USA PISA 2012 data if planning to analyze the PISA YAFS data alongside the USA PISA 2012 dataset.

Details

Reads in the unzipped files for the PISA YAFS. The PISA YAFS dataset is a follow-up study of a subset of the students who participated in the PISA 2012 USA study. It can be analyzed on its own as a singular dataset or optionally merged with the PISA 2012 USA data, in which case there will be two sets of weights in the merged dataset (the default PISA YAFS weights and the PISA 2012 USA weights).

Value

An `edsurvey.data.frame` for the PISA YAFS dataset if the `esdf_PISA2012_USA` parameter is `NULL`. If the PISA 2012 USA `edsurvey.data.frame` is specified for the `esdf_PISA2012_USA` parameter, then the resulting dataset will return an `edsurvey.data.frame` allowing analysis for a combined dataset.

Author(s)

Tom Fink

See Also

[readPISA](#)

Examples

```
## Not run:
#Return an edsurvey.data.frame for only the PISA YAFS dataset.
#Either omit, or set the esdf_PISA2012_USA to a NULL value.
yafs <- readPISA_YAFS(datPath = "~/PISA YAFS/2016/PISA_YAFS2016_Data.dat",
                    spsPath = "~/PISA YAFS/2016/PISA_YAFS2016_SPSS.sps",
                    esdf_PISA2012_USA = NULL)

#If wanting to analyze the PISA YAFS dataset in conjunction with the PISA 2012
#United States of America (USA) dataset, it should be read in first to an edsurvey.data.frame.
#Then pass the resulting edsurvey.data.frame as a parameter for the
#esdf_PISA2012_USA argument. No other edsurvey.data.frames are supported.
usa2012 <- readPISA("~/PISA/2012", database = "INT", countries = "usa")

yafs <- readPISA_YAFS(datPath = "~/PISA YAFS/2016/PISA_YAFS2016_Data.dat",
                    spsPath = "~/PISA YAFS/2016/PISA_YAFS2016_SPSS.sps",
                    esdf_PISA2012_USA = usa2012)

head(yafs)

## End(Not run)
```

readTALIS

Connect to TALIS Data

Description

Opens a connection to a TALIS data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readTALIS(
  path,
  countries,
  isced = c("b", "a", "c"),
  dataLevel = c("teacher", "school"),
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

path	a character vector to the full directory path(s) to the TALIS SPSS files (.sav)
countries	a character vector of the country/countries to include using the three-digit ISO country code. A list of country codes can be found in the TALIS codebook, or you can use https://en.wikipedia.org/wiki/ISO_3166-1#Current_codes . You can use * to indicate all countries available.
isced	a character value that is one of a, b, or c. a stands for <i>Primary Level</i> , b is for <i>Lower Secondary Level</i> , and c is for <i>Upper Secondary Level</i> . Default to b.
dataLevel	a character value that indicates which data level to be used. It can be teacher (the default) or school (see details).
forceReread	a logical value to force rereading of all processed data. Defaults to FALSE. Setting forceReread to be TRUE will cause readTALIS data to be reread and increase processing time.
verbose	a logical value that will determine if you want verbose output while the function is running to indicate the progress. Defaults to TRUE.

Details

Reads in the unzipped files downloaded from the TALIS database using the OECD Repository (<https://www.oecd.org/education/talis/>). If dataLevel is set to be teacher, it treats the teacher data file as the main dataset, and merges school data into teacher data for each country automatically. Use this option if wanting to analyze just teacher variables, or both teacher and school level variables together. If dataLevel is set school, it uses only the school data file (no teacher data will be available).

Value

an `edsurvey.data.frame` for a single specified country or an `edsurvey.data.frame.list` if multiple countries specified

Author(s)

Paul Bailey, Tom Fink, and Trang Nguyen

References

Organisation for Economic Co-operation and Development. (2018). *TALIS 2018 technical report*. Retrieved from https://www.oecd.org/education/talis/TALIS_2018_Technical_Report.pdf

See Also

[getData](#) and [downloadTALIS](#)

Examples

```
## Not run:
#TALIS 2018 - school level data for all countries
talis18 <- readTALIS(path = "~/TALIS/2018",
                    isced = "b",
                    dataLevel = "school",
                    countries = "*")

#unweighted summary
result <- summary2(talis18, "tc3g01", weightVar = "")

#print usa results to console
result$usa

# the following call returns an edsurvey.data.frame to TALIS 2013
# for US teacher-level data at secondary level
usa2013 <- readTALIS(path = "~/TALIS/2013", isced = "b",
                    dataLevel = "teacher", countries = "usa")

# extract a data.frame with a few variables
gg <- getData(usa2013, c("tt2g05b", "tt2g01"))
head(gg)

# conduct an analysis on the edsurvey.data.frame
edsurveyTable(tt2g05b ~ tt2g01, data = usa2013)

## End(Not run)
```

readTIMSS

Connect to TIMSS Data

Description

Opens a connection to a TIMSS data file and returns an edsurvey.data.frame with information about the file and data.

Usage

```
readTIMSS(
  path,
  countries,
  gradeLvl = c("4", "8", "4b", "8b"),
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

path	a character vector to the full directory path(s) to the TIMSS extracted SPSS (.sav) set of data
countries	a character vector of the country/countries to include using the three-digit ISO country code. A list of country codes can be found on Wikipedia at https://en.wikipedia.org/wiki/ISO_3166-1#Current_codes or other online sources. Consult the <i>TIMSS User Guide</i> documentation to help determine what countries are included within a specific testing year of TIMSS and for country code definitions. To select all countries available, use a wildcard value of *.
gradeLvl	a character value to indicate the specific grade level you wish to return <ul style="list-style-type: none"> • 4 = fourth grade (the default if not specified) • 8 = eighth grade • 4B = fourth grade bridge study (TIMSS 2019 only) • 8B = eight grade bridge study (TIMSS 2019 only)
forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the readTIMSS function by using existing read-in data already processed.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Details

Reads in the unzipped files downloaded from the TIMSS international database(s) using the [IEA Study Data Repository](#). Data files require the SPSS data file (.sav) format using the default file-names.

A TIMSS edsurvey.data.frame includes three distinct data levels:

- student
- school
- teacher

When the getData function is called using a TIMSS edsurvey.data.frame, the requested data variables are inspected, and it handles any necessary data merges automatically. The school data always will be returned merged to the student data, even if only school variables are requested. If teacher variables are requested by the getData call, it will cause teacher data to be merged. Many students can be linked to many teachers, which varies widely between countries.

Please note that calling the `dim` function for a `TIMSS edsurvey.data.frame` will result in the row count as if the teacher dataset was merged. This row count will be considered the full data `N` of the `edsurvey.data.frame`, even if no teacher data were included in an analysis. The column count returned by `dim` will be the count of unique column variables across all three data levels.

Beginning with TIMSS 2015, a numeracy dataset was designed to assess mathematics at the end of the primary school cycle for countries where most children are still developing fundamental mathematics skills. The numeracy dataset is handled automatically for the user and is included within the fourth-grade dataset `gradeLvl=4`. Most numeracy countries have a 4th grade dataset in addition to their numeracy dataset, but some do not. For countries that have both a numeracy and a 4th grade dataset, the two datasets are combined into one `edsurvey.data.frame` for that country. Data variables missing from either dataset are kept, with NA values inserted for the dataset records where that variable did not exist. Data variables common to both datasets are kept as a single data variable, with records retaining their original values from the source dataset. Consult the *TIMSS User Guide* for further information.

For the TIMSS 2019 study, a bridge study was conducted to help compute adjustment factors between the electronic test format and the paper/pencil format. The bridge study is considered separate from the normal TIMSS 2019 study. The `gradeLvl` parameter now includes a "4B" option for the Grade 4 bridge study, and the "8B" option for the Grade 8 bridge study files.

Value

an `edsurvey.data.frame` for a single specified country or an `edsurvey.data.frame.list` if multiple countries specified

Author(s)

Tom Fink

See Also

[readNAEP](#), [getData](#), and [downloadTIMSS](#)

Examples

```
## Not run:
# single country specified
fin <- readTIMSS("~/TIMSS/2015", countries = c("fin"), gradeLvl = 4)
gg <- getData(fin, c("asbg01", "totwgt", "srea"))
head(gg)
edsurveyTable(srea ~ asbg01, fin)

# multiple countries returned as edsurvey.data.frame.list, specify all countries with '*' argument
timss2011 <- readTIMSS("~/TIMSS/2011", countries="*", gradeLvl = 8, verbose = TRUE)
# print out edsurvey.data.frame.list covariates
timss2011$covs

## End(Not run)
```

readTIMSSAdv *Connect to TIMSS Advanced Data*

Description

Opens a connection to a TIMSS Advanced data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
readTIMSSAdv(
  path,
  countries,
  subject = c("math", "physics"),
  forceReread = FALSE,
  verbose = TRUE
)
```

Arguments

<code>path</code>	a character vector to the full directory path to the TIMSS Advanced extracted SPSS (.sav) set of data
<code>countries</code>	a character vector of the country/countries to include using the three-digit ISO country code. A list of country codes can be found on Wikipedia at https://en.wikipedia.org/wiki/ISO_3166-1#Current_codes or other online sources. Consult the <i>TIMSS Advanced User Guide</i> to help determine what countries are included within a specific testing year of TIMSS Advanced. To select all countries, use a wildcard value of <code>*</code> .
<code>subject</code>	a character value to indicate if you wish to import the math or physics dataset. Only one subject can be read in at a time.
<code>forceReread</code>	a logical value to force rereading of all processed data. The default value of <code>FALSE</code> will speed up the <code>readTIMSSAdv</code> function by using existing read-in data already processed.
<code>verbose</code>	a logical value to either print or suppress status message output. The default value is <code>TRUE</code> .

Details

Reads in the unzipped files downloaded from the TIMSS Advanced international database(s) using the [IEA Study Data Repository](#). Data files require the SPSS data file (.sav) format using the default filenames.

A TIMSS Advanced `edsurvey.data.frame` includes three distinct data levels:

- student
- school
- teacher

When the `getData` function is called using a TIMSS Advanced `edsurvey.data.frame`, the requested data variables are inspected, and it handles any necessary data merges automatically. The school data always will be returned merged to the student data, even if only school variables are requested. If teacher variables are requested by the `getData` call it will cause the teacher data to be merged. Many students can be linked to many teachers, which varies widely between countries.

Please note that calling the `dim` function for a TIMSS Advanced `edsurvey.data.frame` will result in the row count as if the teacher dataset was merged. This row count will be considered the full data N of the `edsurvey.data.frame`, even if no teacher data were included in an analysis. The column count returned by `dim` will be the count of unique column variables across all three data levels.

Value

an `edsurvey.data.frame` for a single specified country or an `edsurvey.data.frame.list` if multiple countries specified

Author(s)

Tom Fink

See Also

[readNAEP](#), [readTIMSS](#), [getData](#), and [downloadTIMSSAdv](#)

Examples

```
## Not run:
swe <- readTIMSSAdv("~/TIMSSAdv/2015",
                   countries = c("swe"), subject = "math")
gg <- getData(swe, c("itsex", "totwgt", "malg"))
head(gg)
edsurveyTable(malg ~ itsex, swe)

## End(Not run)
```

read_ePIRLS

Connect to ePIRLS Data

Description

Opens a connection to an ePIRLS data file and returns an `edsurvey.data.frame` with information about the file and data.

Usage

```
read_ePIRLS(path, countries, forceReread = FALSE, verbose = TRUE)
```

Arguments

path	a character value to the full directory path to the ePIRLS extracted SPSS (.sav) set of data
countries	a character vector of the country/countries to include using the three-digit ISO country code. A list of country codes can be found on Wikipedia at https://en.wikipedia.org/wiki/ISO_3166-1#Current_codes or other online sources. Consult the <i>ePIRLS User Guide</i> to help determine what countries are included within a specific testing year of ePIRLS. To select all countries, use a wildcard value of *.
forceReread	a logical value to force rereading of all processed data. The default value of FALSE will speed up the read_ePIRLS function by using existing read-in data already processed.
verbose	a logical value to either print or suppress status message output. The default value is TRUE.

Details

Reads in the unzipped files downloaded from the ePIRLS international database(s) using the [IEA Study Data Repository](#). Data files require the SPSS data file (.sav) format using the default file-names.

An ePIRLS `edsurvey.data.frame` includes three distinct data levels:

- student
- school
- teacher

When the `getData` function is called using an ePIRLS `edsurvey.data.frame`, the requested data variables are inspected, and it handles any necessary data merges automatically. The school data always will be returned merged to the student data, even if only school variables are requested. If teacher variables are requested by the `getData` call, it will cause teacher data to be merged. A student can be linked to many teachers, which varies widely between countries.

Please note that calling the `dim` function for an ePIRLS `edsurvey.data.frame` will result in the row count as if the teacher dataset was merged. This row count will be considered the full data N of the `edsurvey.data.frame`, even if no teacher data were included in an analysis. The column count returned by `dim` will be the count of unique column variables across all three data levels.

Value

an `edsurvey.data.frame` for a single specified country or an `edsurvey.data.frame.list` if multiple countries are specified

Author(s)

Tom Fink

See Also

[readNAEP](#), [readTIMSS](#), [getData](#), and [download_ePIRLS](#)

Examples

```
## Not run:
usa <- read_ePIRLS("~/ePIRLS/2016", countries = c("usa"))
gg <- getData(usa, c("itsex", "totwgt", "erea"))
head(gg)
edsurveyTable(erea ~ itsex, usa)

## End(Not run)
```

rebindAttributes *Copy Data Frame Attributes*

Description

Many R functions strip attributes from data frame objects. This function assigns the attributes from the `attributeData` argument to the data frame in the `data` argument.

Usage

```
rebindAttributes(data, attributeData)
```

Arguments

<code>data</code>	a <code>data.frame</code>
<code>attributeData</code>	an <code>edsurvey.data.frame</code> or <code>light.edsurvey.data.frame</code> that contains the desired attributes

Value

a `data.frame` with a class of a `light.edsurvey.data.frame` containing all elements of data and the attributes (except names and row.names) from `attributeData`

Author(s)

Paul Bailey and Trang Nguyen

Examples

```
## Not run:
require(dplyr)
PISA2012 <- readPISA(path = paste0(edsurveyHome, "PISA/2012"),
                   database = "INT",
                   countries = "ALB", verbose=TRUE)
ledf <- getData(data = PISA2012, varnames = c("cnt", "oecd", "wfstuwt",
                                             "st62q04", "st62q11",
                                             "st62q13", "math"),
               omittedLevels = FALSE, addAttributes = TRUE)
```

```

omittedLevels <- c('Invalid', 'N/A', 'Missing', 'Miss', 'NA', '(Missing)')
for (i in c("st62q04", "st62q11", "st62q13")) {
  ledf[,i] <- factor(ledf[,i], exclude=omittedLevels)
}

# after applying some dplyr functions, the "light.edsurvey.data.frame" becomes just "data.frame"
PISA2012_ledf <- ledf %>%
  rowwise() %>%
  mutate(avg_3 = mean(c(st62q04, st62q11, st62q13), na.rm = TRUE)) %>%
  ungroup() %>%
  rebindAttributes(PISA2012) # could also be called with ledf
class(PISA2012_ledf)
# again, a light.edsurvey.data.frame
lma <- lm.sdf(math ~ avg_3,data=PISA2012_ledf)
summary(lma)

PISA2012_ledf <- ledf %>%
  rowwise() %>%
  mutate(avg_3 = mean(c(st62q04, st62q11, st62q13), na.rm = TRUE)) %>%
  ungroup() %>%
  rebindAttributes(ledf) # return attributes and make a light.edsurvey.data.frame
# again a light.edsurvey.data.frame
lma <- lm.sdf(math ~ avg_3,data=PISA2012_ledf)
summary(lma)

## End(Not run)

```

recode.sdf

Recode Levels Within Variables

Description

Recodes variables in an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`.

Usage

```
recode.sdf(x, recode)
```

Arguments

`x` an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`
`recode` a list of recoding rules. See Examples for the format of recoding rules.

Value

an object of the same class as `x` with the `recode` added to it

Author(s)

Trang Nguyen and Paul Bailey

Examples

```
## Not run:
# filepath argument will vary by operating system conventions
usaG4.15 <- readTIMSS("~/TIMSS/2015", "usa", 4)
d <- getData(usaG4.15, "itsex")
summary(d) #show details: MALE/FEMALE
usaG4.15 <- recode.sdf(usaG4.15,
                      recode = list(itsex=list(from=c("MALE"),
                                                to=c("BOY")),
                                     itsex=list(from=c("FEMALE"),
                                                to=c("GIRL"))))

d <- getData(usaG4.15, "itsex") #apply recode
summary(d) #show details: BOY/GIRL

## End(Not run)
```

 rename.sdf

Modify Variable Names

Description

Renames variables in an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`. This function often is used when users want to conduct a gap analysis across years but variable names differ across two years of data.

Usage

```
rename.sdf(x, oldnames, newnames, avoid_duplicated = TRUE)
```

Arguments

<code>x</code>	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>
<code>oldnames</code>	a character vector of old variable names
<code>newnames</code>	a character vector of new variable names to replace the corresponding old names
<code>avoid_duplicated</code>	a logical value to indicate whether to avoid renaming the variable if the corresponding new name already exists in the data. Defaults to TRUE.

Details

All variable names are coerced to lowercase to comply with the EdSurvey standard.

Value

an object of the same class as `x` with new variable names

Author(s)

Trang Nguyen

See Also[gap](#)**Examples**

```
## Not run:
usaG4.15 <- readTIMSS("~/TIMSS/2015", "usa", 4)
usaG4.15.renamed <- rename.sdf(usaG4.15,
                              c("itsex", "mmat"),
                              c("gender", "math_overall"))
lm1 <- lm.sdf(math_overall ~ gender, data = usaG4.15.renamed)
summary(lm1)

## End(Not run)
```

rq.sdf

*EdSurvey Quantile Regression Models***Description**

Fits a quantile regression model that uses weights and variance estimates appropriate for the data.

Usage

```
rq.sdf(
  formula,
  data,
  tau = 0.5,
  weightVar = NULL,
  releveles = list(),
  jrrIMax = 1,
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  recode = NULL,
  returnNumberOfPSU = FALSE,
  ...
)
```

Arguments

formula a formula for the quantile regression model. See `rq` in the `quantreg` package. If `y` is left blank, the default subject scale or subscale variable will be used. (You can find the default using [showPlausibleValues](#).) If `y` is a variable for a subject scale or subscale (one of the names shown by [showPlausibleValues](#)), then that subject scale or subscale is used.

<code>data</code>	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>
<code>tau</code>	the quantile to be estimated. The value could be set between 0 and 1 with a default of 0.5.
<code>weightVar</code>	a character indicating the weight variable to use. The <code>weightVar</code> must be one of the weights for the <code>edsurvey.data.frame</code> . If <code>NULL</code> , it uses the default for the <code>edsurvey.data.frame</code> .
<code>relevels</code>	a list. Used to change the contrasts from the default treatment contrasts to the treatment contrasts with a chosen omitted group (the reference group). The name of each element should be the variable name, and the value should be the group to be omitted (the reference group).
<code>jrrIMax</code>	when using the jackknife variance estimation method, the default estimation option, <code>jrrIMax=1</code> , uses the sampling variance from the first plausible value as the component for sampling variance estimation. The V_{jrr} term can be estimated with any number of plausible values, and values larger than the number of plausible values on the survey (including <code>Inf</code>) will result in all plausible values being used. Higher values of <code>jrrIMax</code> lead to longer computing times and more accurate variance estimates.
<code>omittedLevels</code>	a logical value. When set to the default value of <code>TRUE</code> , drops those levels of all factor variables that are specified in an <code>edsurvey.data.frame</code> . Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the omitted levels.
<code>defaultConditions</code>	a logical value. When set to the default value of <code>TRUE</code> , uses the default conditions stored in an <code>edsurvey.data.frame</code> to subset the data. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the default conditions.
<code>recode</code>	a list of lists to recode variables. Defaults to <code>NULL</code> . Can be set as <code>recode=list(var1 = list(from=c("a", "b", "c"), to="d"))</code> .
<code>returnNumberOfPSU</code>	a logical value set to <code>TRUE</code> to return the number of primary sampling units (PSUs)
<code>...</code>	additional parameters passed from <code>rq</code>

Details

The function computes an estimate on the τ -th conditional quantile function of the response, given the covariates, as specified by the `formula` argument. Like `lm.sdf()`, the function presumes a linear specification for the quantile regression model (i.e., that the `formula` defines a model that is linear in parameters). Unlike `lm.sdf()`, the jackknife is the only applicable variance estimation method used by the function.

For further details on quantile regression models and how they are implemented in R, see Koenker and Bassett (1978), Koenker (2005), and the vignette from the `quantreg` package— accessible by `vignette("rq", package="quantreg")`—on which this function is built.

For further details on how left-hand side variables, survey sampling weights, and estimated variances are correctly handled, see `lm.sdf` or the vignette titled *Statistical Methods Used in EdSurvey*.

Value

An `edsurvey.rq` with the following elements:

<code>call</code>	the function call
<code>formula</code>	the formula used to fit the model
<code>tau</code>	the quantile to be estimated
<code>coef</code>	the estimates of the coefficients
<code>se</code>	the standard error estimates of the coefficients
<code>Vimp</code>	the estimated variance from uncertainty in the scores (plausible value variables)
<code>Vjrr</code>	the estimated variance from sampling
<code>M</code>	the number of plausible values
<code>varm</code>	the variance estimates under the various plausible values
<code>coefm</code>	the values of the coefficients under the various plausible values
<code>coefmat</code>	the coefficient matrix (typically produced by the summary of a model)
<code>weight</code>	the name of the weight variable
<code>npv</code>	the number of plausible values
<code>njk</code>	the number of the jackknife replicates used; set to NA when Taylor series variance estimates are used
<code>rho</code>	the mean value of the objective function across the plausible values

Author(s)

Trang Nguyen, Paul Bailey, and Yuqi Liao

References

- Binder, D. A. (1983). On the variances of asymptotically normal estimators from complex surveys. *International Statistical Review*, 51(3), 279–292.
- Johnson, E. G., & Rust, K. F. (1992). Population inferences and variance estimation for NAEP data. *Journal of Education Statistics*, 17(2), 175–190.
- Koenker, R. W., & Bassett, G. W. (1978). Regression quantiles, *Econometrica*, 46, 33–50.
- Koenker, R. W. (2005). *Quantile regression*. Cambridge, UK: Cambridge University Press.
- Rubin, D. B. (1987). *Multiple imputation for nonresponse in surveys*. New York, NY: Wiley.

See Also

rq

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# conduct quantile regression at a given tau value (by default, tau is set to be 0.5)
rq1 <- rq.sdf(composite ~ dsex + b017451, data=sdf, tau = 0.8)
summary(rq1)

## End(Not run)
```

scoreTIMSS

EdSurvey Direct Estimation - TIMSS scoring

Description

Scoring TIMSS data

Usage

```
scoreTIMSS(edf, polyParamTab, dichotParamTab)
```

Arguments

edf a TIMSS `light.edsurvey.data.frame` or `edsurvey.data.frame`
polyParamTab a dataframe containing IRT parameters for all polytomous items in edf
dichotParamTab a dataframe containing IRT parameters for all dichotomous items in edf

Details

This function scores TIMSS data. For multiple choice items, correct answers are assigned 1 point, and incorrect answers are assigned 0 points. For constructed response items, correct answers are assigned 2 points, partially correct answers are assigned 1 point, and incorrect answers are assigned 0 points. For both types of items, "NOT REACHED" and "OMITTED OR INVALID" are assigned 0 points.

Value

scored edf

SD *EdSurvey Standard Deviation*

Description

Calculate the standard deviation of a numeric variable in an `edsurvey.data.frame`.

Usage

```
SD(
  data,
  variable,
  weightVar = NULL,
  jrrIMax = 1,
  varMethod = "jackknife",
  omittedLevels = TRUE,
  defaultConditions = TRUE,
  recode = NULL,
  targetLevel = NULL,
  jkSumMultiplier = 1,
  returnVarEstInputs = FALSE
)
```

Arguments

<code>data</code>	an <code>edsurvey.data.frame</code> , an <code>edsurvey.data.frame.list</code> , or a <code>light.edsurvey.data.frame</code>
<code>variable</code>	character vector of variable names
<code>weightVar</code>	character weight variable name. Default is the default weight of <code>data</code> if it exists. If the given survey data do not have a default weight, the function will produce unweighted statistics instead. Can be set to <code>NULL</code> to return unweighted statistics.
<code>jrrIMax</code>	a numeric value; when using the jackknife variance estimation method, the default estimation option, <code>jrrIMax=1</code> , uses the sampling variance from the first plausible value as the component for sampling variance estimation. The <code>Vjrr</code> term (see <i>Statistical Methods Used in EdSurvey</i>) can be estimated with any number of plausible values, and values larger than the number of plausible values on the survey (including <code>Inf</code>) will result in all plausible values being used. Higher values of <code>jrrIMax</code> lead to longer computing times and more accurate variance estimates.
<code>varMethod</code>	deprecated parameter; <code>gap</code> always uses the jackknife variance estimation
<code>omittedLevels</code>	a logical value. When set to <code>TRUE</code> , drops those levels of the specified variable. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the omitted levels. Defaults to <code>FALSE</code> .
<code>defaultConditions</code>	a logical value. When set to the default value of <code>TRUE</code> , uses the default conditions stored in an <code>edsurvey.data.frame</code> to subset the data. Use <code>print</code> on an <code>edsurvey.data.frame</code> to see the default conditions.

recode	a list of lists to recode variables. Defaults to NULL. Can be set as <code>recode = list(var1 = list(from = c("a", "b", "c"), to = "d"))</code> .
targetLevel	a character string. When specified, calculates the gap in the percentage of students at <code>targetLevel</code> in the <code>variable</code> argument, which is useful for comparing the gap in the percentage of students at a survey response level.
jkSumMultiplier	when the jackknife variance estimation method—or balanced repeated replication (BRR) method—multiplies the final jackknife variance estimate by a value, set <code>jkSumMultiplier</code> to that value. For an <code>edsurvey.data.frame</code> , or a <code>light.edsurvey.data.frame</code> , the recommended value can be recovered with <code>EdSurvey::getAttributes(myData, "jkSumMultiplier")</code> .
returnVarEstInputs	a logical value set to TRUE to return the inputs to the jackknife and imputation variance estimates, which allows for the computation of covariances between estimates.

Value

SD returns:

mean the mean assessment score for `variable`, calculated according to the vignette titled [Statistical Methods Used in EdSurvey](#)

std the standard deviation of the mean

stdSE the standard error of the `std`

sd the degrees of freedom of the `std`

When `returnVarEstInputs` is TRUE, an attribute `varEstInputs` also is returned that includes the variance estimate inputs used for calculating covariances with [varEstToCov](#).

Author(s)

Paul Bailey and Huade Huo

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# get standard deviation for Male's composite score
SD(data = subset(sdf, dsex == "Male"), variable = "composite")

# get several standard deviations

# build an edsurvey.data.frame.list
sdfA <- subset(sdf, scrpsu %in% c(5,45,56))
sdfB <- subset(sdf, scrpsu %in% c(75,76,78))
sdfC <- subset(sdf, scrpsu %in% 100:200)
sdfD <- subset(sdf, scrpsu %in% 201:300)
```

```

sdf1 <- edsurvey.data.frame.list(list(sdfA, sdfB, sdfC, sdfD),
                                labels=c("A locations",
                                          "B locations",
                                          "C locations",
                                          "D locations"))

# this shows how these datasets will be described:
sdf1$covs

SD(data = sdf1, variable = "composite")

## End(Not run)

```

searchSDF

EdSurvey Codebook Search

Description

Retrieves variable names and labels for an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list` using character string matching.

Usage

```
searchSDF(string, data, fileFormat = NULL, levels = FALSE)
```

Arguments

<code>string</code>	a vector of character strings to search for in the database connection object (<code>data</code>). The function will search the codebook for a matching character string using regular expressions. When a string has several elements, all must be present for a variable to be returned.
<code>data</code>	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>
<code>fileFormat</code>	a character string indicating the data source to search for variables. The default <code>NULL</code> argument searches all codebooks.
<code>levels</code>	a logical value; set to <code>TRUE</code> to return a snapshot of the levels in an <code>edsurvey.data.frame</code>

Value

a `data.frame` that shows the variable names, labels, and levels (if applicable) from an `edsurvey.data.frame` or a `light.edsurvey.data.frame` based on a matching character string

Author(s)

Michael Lee and Paul Bailey

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# search both the student and school files by a character string
searchSDF(string="book", data=sdf)

# use the `|` (OR) operator to search several strings simultaneously
searchSDF(string="book|home|value", data=sdf)

# use a vector of strings to search for variables that contain multiple strings,
# such as both "book" and "home"
searchSDF(string=c("book","home"), data=sdf)

# search only the student files by a character string
searchSDF(string="algebra", data=sdf, fileFormat="student")

# search both the student and school files and return a glimpse of levels
searchSDF(string="value", data=sdf, levels=TRUE)

# save the search as an object to return a full data.frame of search
ddf <- searchSDF(string="value", data=sdf, levels=TRUE)
ddf

## End(Not run)
```

showCodebook

Summary Codebook

Description

Retrieves variable names, variable labels, and value labels for an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`.

Usage

```
showCodebook(
  data,
  fileFormat = NULL,
  labelLevels = FALSE,
  includeRecodes = FALSE
)
```

Arguments

`data` an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`

<code>fileFormat</code>	a character string indicating the data source to search for variables. The default NULL argument searches all available codebooks in the database connection object.
<code>labelLevels</code>	a logical value; set to TRUE to return a snapshot of the label levels in an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code> . When set to FALSE (the default), label levels are removed.
<code>includeRecodes</code>	a logical value; set to TRUE to return value labels that have been recoded in an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code> . When set to FALSE (the default), only the original value labels are included in the returned <code>data.frame</code> .

Value

a `data.frame` that shows the variable names, variable labels, value labels, value levels (if applicable), and the file format data source from an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`

Author(s)

Michael Lee and Paul Bailey

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# search both the student and school files, returning levels for variable values
showCodebook(sdf, c("student","school"), labelLevels = TRUE, includeRecodes = FALSE)

# return codebook information for the student file, excluding variable value levels,
# including recoded variables
sdf <- recode.sdf(sdf, recode = list(dsex = list(from = c("Male"), to = c("MALE"))))
showCodebook(sdf, c("student"), labelLevels = FALSE, includeRecodes = TRUE)

# return codebook information for the student file, including variable value levels
# and recoded variables
showCodebook(sdf, c("student","school"), labelLevels = FALSE, includeRecodes = TRUE)

# return codebook information for all codebooks in an edsurvey.data.frame; commonly use View()
View(showCodebook(sdf))

## End(Not run)
```

showCutPoints	<i>Retrieve Achievement Level Cutpoints</i>
---------------	---

Description

Retrieves a summary of the achievement level cutpoints for a selected study represented in an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`.

Usage

```
showCutPoints(data)
```

Arguments

`data` an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`

Author(s)

Michael Lee and Paul Bailey

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# show the cut points
showCutPoints(data=sdf)

## End(Not run)
```

showPlausibleValues	<i>Plausible Value Variable Names</i>
---------------------	---------------------------------------

Description

Prints a summary of the subject scale or subscale and the associated variables for their plausible values for an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`.

Usage

```
showPlausibleValues(data, verbose = FALSE)
```

Arguments

`data` an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`

`verbose` a logical value; set to `TRUE` to get the variable names for plausible values. Otherwise, prints only the subject scale or subscale names for variables that use plausible values.

Author(s)

Michael Lee and Paul Bailey

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# show the plausible values
showPlausibleValues(data=sdf, verbose=TRUE)

## End(Not run)
```

showWeights *Retrieve Weight Variables*

Description

Prints a summary of the weights in an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`.

Usage

```
showWeights(data, verbose = FALSE)
```

Arguments

`data` an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`

`verbose` a logical value; set to `TRUE` to print the complete list of jackknife replicate weights associated with each full sample weight; otherwise, prints only the full sample weights

Author(s)

Michael Lee and Paul Bailey

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# show the weights
showWeights(sdf, TRUE)

## End(Not run)
```

subset	<i>EdSurvey Subset</i>
--------	------------------------

Description

Subsets an `edsurvey.data.frame`, an `edsurvey.data.frame.list`, or a `light.edsurvey.data.frame`.

Usage

```
## S3 method for class 'edsurvey.data.frame'
subset(x, subset, ..., inside = FALSE)
```

Arguments

<code>x</code>	an <code>edsurvey.data.frame</code> , an <code>edsurvey.data.frame.list</code> , or a <code>light.edsurvey.data.frame</code>
<code>subset</code>	a logical expression indicating elements or rows to keep
<code>...</code>	not used; included only for compatibility
<code>inside</code>	set to <code>TRUE</code> to prevent the substitute condition from being called on it (see Details)

Details

Any variables defined on condition that are not references to column names on the `edsurvey.data.frame` and are part of the environment where `subset.edsurvey.data.frame` was called will be evaluated in the environment from which `subset.edsurvey.data.frame` was called. Similar to the difficulty of using `subset` within a function call because of the call to `substitute` on condition, this function is difficult to use (with `inside` set to the default value of `FALSE`) inside another function call. See Examples for how to call this function from within another function.

Value

an object of the same class as `x`

Author(s)

Paul Bailey and Trang Nguyen

References

Wickham, H. (2014). *Advanced R*. Boca Raton, FL: Chapman & Hall/CRC.

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# table to compare to subsequent tables with subsets
edsurveyTable(composite ~ dsex, data=sdf, returnMeans=FALSE, returnSepct=FALSE)

# subset to just males
newsdf <- subset(x=sdf, subset= dsex == "Male")
# table of dsex after subset
edsurveyTable(composite ~ dsex, data=newsdf, returnMeans=FALSE, returnSepct=FALSE)

# Variable names that are not in the sdf get resolved in the parent frame.
# practically, that means that the following two subset
# calls sdfM1 and sdfM2 do the same thing
male_var <- "Male"
sdfM1 <- subset(x=sdf, subset= dsex == male_var)
sdfM2 <- subset(x=sdf, subset= dsex == "Male")
table(getData(data=sdfM1, varnames="dsex"))
table(getData(data=sdfM2, varnames="dsex"))

# variable can also be resolved as members of lists
genders <- c("Male", "Female", "not a sex level")
sdfn <- subset(x=sdf, subset= dsex == genders[2])
table(getData(data=sdfn, varnames="dsex"))

# variables can also be subset using %in%
sdfM3 <- subset(x=sdf, subset= dsex %in% c("Male", "not a sex level"))
table(getData(data=sdfM3, varnames="dsex"))

# if you need to call a name on the sdf dynamically, you can use as.name
dsex_stdin <- as.name("dsex")
sdfM4 <- subset(x=sdf, subset= dsex_stdin == "Male")
table(getData(data=sdfM4, varnames="dsex"))

# Here is an example of how one might want to call
# subset from within a function or loop.
# First, define a few variables to use dynamically
rhs_vars <- c("dsex", "b017451")
lvls <- c("Male", "Female")

# create a parsed condition
cond <- parse(text=paste0(rhs_vars[1], " == \"",lvls[1],"\"))[[1]]

# when inside=TRUE a parsed condition can be passed to subset
dsdf <- subset(x=sdf, subset=cond, inside=TRUE)
```

```

# check the result
table(getData(data=dsdf, varnames="dsex"))

# both of these return data, but uses substantial memory
head(sdf[ , c("origwt","m145101")])
head(sdf[[c("origwt","m145101")]])

# subset an edsurvey.data.frame.list
sdfA <- subset(sdf, scrpsu %in% c(5,45,56))
sdfB <- subset(sdf, scrpsu %in% c(75,76,78))
sdfC <- subset(sdf, scrpsu %in% 100:200)
sdfD <- subset(sdf, scrpsu %in% 201:300)

# construct an edsurvey.data.frame.list from these four datasets
sdf1 <- edsurvey.data.frame.list(list(sdfA, sdfB, sdfC, sdfD),
                                labels=c("A locations",
                                          "B locations",
                                          "C locations",
                                          "D locations"))

sdf12 <- subset(sdf1, dsex=="Male")
# the number of rows in each element of the sdf1
nrow(sdf1)
# the number of rows after subsetting each element to just the Males
nrow(sdf12)

## End(Not run)

```

summary2

Summarize edsurvey.data.frame Variables

Description

Summarizes edsurvey.data.frame variables.

Usage

```

summary2(
  data,
  variable,
  weightVar = attr(getAttributes(data, "weights"), "default"),
  omittedLevels = FALSE
)

```

Arguments

data an edsurvey.data.frame, an edsurvey.data.frame.list, or light.edsurvey.data.frame
variable character vector of variable names

weightVar	character weight variable name. Default is the default weight of data if it exists. If the given survey data do not have a default weight, the function will produce unweighted statistics instead. Can be set to NULL to return unweighted statistics.
omittedLevels	a logical value. When set to TRUE, drops those levels of the specified variable. Use print on an edsurvey.data.frame to see the omitted levels. Defaults to FALSE.

Value

summary of weighted or unweighted statistics of a given variable in an edsurvey.data.frame

For categorical variables, the summary results are a crosstab of all variables and include the following:

[variable name]	level of the variable in the column name that the row regards. There is one column per element of variable.
N	number of cases for each category. Weighted N also is produced if users choose to produce weighted statistics.
Percent	percentage of each category. Weighted percent also is produced if users choose to produce weighted statistics.
SE	standard error of the percentage statistics

For continuous variables, the summary results are by variable and include the following:

Variable	name of the variable the row regards
N	total number of cases (both valid and invalid cases)
Min.	smallest value of the variable
1st Qu.	first quantile of the variable
Median	median value of the variable
Mean	mean of the variable
3rd Qu.	third quantile of the variable
Max.	largest value of the variable
SD	standard deviation or weighted standard deviation
NA's	number of NA in variable and in weight variables
Zero-weights	number of zero-weight cases if users choose to produce weighted statistics

If the weight option is chosen, the function produces weighted percentile and standard deviation. Refer to the vignette titled *Statistical Methods Used in EdSurvey* and the vignette titled *Methods Used for Estimating Percentiles in EdSurvey* for how the function calculates these statistics (with and without plausible values).

Author(s)

Paul Bailey and Trang Nguyen

See Also[percentile](#)**Examples**

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# print out summary of weighted statistics of a continuous variable
summary2(sdf, "composite")
# print out summary of weighted statistics of a variable, including omitted levels
summary2(sdf, "b017451", omittedLevels = FALSE)
# make a crosstab
summary2(sdf, c("b017451", "dsex"), omittedLevels = FALSE)

# print out summary of unweighted statistics of a variable
summary2(sdf, "composite", weightVar = NULL)

## End(Not run)
```

updatePlausibleValue *Update Plausible Value Variable Names*

Description

Changes the name used to refer to a set of plausible values from `oldVar` to `newVar` in an `edsurvey.data.frame`, a `light.edsurvey.data.frame`, or an `edsurvey.data.frame.list`.

Usage

```
updatePlausibleValue(oldVar, newVar, data)
```

Arguments

<code>oldVar</code>	a character value indicating the existing name of the variable
<code>newVar</code>	a character value indicating the new name of the variable
<code>data</code>	an <code>edsurvey.data.frame</code> , a <code>light.edsurvey.data.frame</code> , or an <code>edsurvey.data.frame.list</code>

Value

an object of the same class as the `data` argument, with the name of the plausible value updated from `oldVar` to `newVar`

Author(s)

Michael Lee and Paul Bailey

See Also

[getPlausibleValue](#) and [showPlausibleValues](#)

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package="NAEPprimer"))

# get the PVs before
showPlausibleValues(sdf)
sdf2 <- updatePlausibleValue("composite", "overall", sdf)
showPlausibleValues(sdf2)
lm1 <- lm.sdf(overall ~ b017451, data=sdf2)
summary(lm1)

## End(Not run)
```

varEstToCov

Covariance Estimation

Description

When the variance of a derived statistic (e.g., a difference) is required, the covariance between the two statistics must be calculated. This function uses results generated by various functions (e.g., a [lm.sdf](#)) to find the covariance between two statistics.

Usage

```
varEstToCov(
  varEstA,
  varEstB = varEstA,
  varA,
  varB = varA,
  jkSumMultiplier,
  returnComponents = FALSE
)
```

Arguments

varEstA a list of two data.frames returned by a function after the returnVarEstInputs argument was turned on. The statistic named in the varA argument must be present in each data.frame.

varEstB a list of two data.frames returned by a function after the returnVarEstInputs argument was turned on. The statistic named in the varA argument must be present in each data.frame. When the same as varEstA, the covariance is within one result.

varA	a character that names the statistic in the varEstA argument for which a covariance is required
varB	a character that names the statistic in the varEstB argument for which a covariance is required
jkSumMultiplier	when the jackknife variance estimation method—or balanced repeated replication (BRR) method—multiplies the final jackknife variance estimate by a value, set jkSumMultiplier to that value. For an <code>edsurvey.data.frame</code> or a <code>light.edsurvey.data.frame</code> , the recommended value can be recovered with <code>EdSurvey::getAttributes(myData, "jkSumMultiplier")</code> .
returnComponents	set to TRUE to return the imputation variance separate from the sampling variance

Details

These functions are not vectorized, so `varA` and `varB` must contain exactly one variable name.

The method used to compute the covariance is in the vignette titled *Statistical Methods Used in EdSurvey*

The method used to compute the degrees of freedom is in the vignette titled *Statistical Methods Used in EdSurvey* in the section “Estimation of Degrees of Freedom.”

Value

a numeric value; the jackknife covariance estimate. If `returnComponents` is TRUE, returns a vector of length three, `V` is the variance estimate, `Vsamp` is the sampling component of the variance, and `Vimp` is the imputation component of the variance

Author(s)

Paul Bailey

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# estimate a regression
lm1 <- lm.sdf(composite ~ dsex + b017451, sdf, returnVarEstInputs=TRUE)
summary(lm1)
# estimate the covariance between two regression coefficients
# note that the variable names are parallel to what they are called in lm1 output
covFEveryDay <- varEstToCov(lm1$varEstInputs,
                           varA="dsexFemale",
                           varB="b017451Every day",
                           jkSumMultiplier=EdSurvey::getAttributes(sdf, "jkSumMultiplier"))
# the estimated difference between the two coefficients
# note: unname prevents output from being named after the first coefficient
unname(coef(lm1)["dsexFemale"] - coef(lm1)["b017451Every day"])
```

```
# the standard error of the difference
# uses the formula SE(A-B) = sqrt(var(A) + var(B) - 2*cov(A,B))
sqrt(lm1$coefmat["dsexFemale", "se"]^2
      + lm1$coefmat["b017451Every day", "se"]^2
      - 2 * covEveryDay)

## End(Not run)
```

 waldTest

Wald Tests

Description

Tests on coefficient(s) of `edsurveyGlm` and `edsurveyLm` models.

Usage

```
waldTest(model, coefficients, H0 = NULL)
```

Arguments

<code>model</code>	an <code>edsurveyGlm</code> and <code>edsurveyLm</code>
<code>coefficients</code>	coefficients to be tested, by name or position in <code>coef</code> vector. See Details.
<code>H0</code>	reference values to test coefficients against, default = 0

Details

When plausible values are present, likelihood ratio tests cannot be used. However, the Wald test can be used to test estimated parameters in a model, with the null hypothesis being that a parameter(s) is equal to some value(s). In the default case where the null hypothesis value of the parameters is 0, if the test fails to reject the null hypothesis, removing the variables from the model will not substantially harm the fit of that model. Alternative null hypothesis values also can be specified with the `H0` argument. See Examples.

Coefficients to test can be specified by an integer (or integer vector) corresponding to the order of coefficients in the summary output. Coefficients also can be specified using a character vector, to specify coefficient names to test. The name of a factor variable can be used to test all levels of that variable.

This test produces both chi-square and *F*-tests; their calculation is described in the vignette titled *Methods and Overview of Using EdSurvey for Running Wald Tests*.

Value

An `edsurveyWaldTest` object with the following elements:

<code>Sigma</code>	coefficient covariance matrix
<code>coefficients</code>	indices of the coefficients tested
<code>H0</code>	null hypothesis values of coefficients tested
<code>result</code>	result object containing the values of the chi-square and <i>F</i> -tests
<code>hypoMatrix</code>	hypothesis matrix used for the Wald Test

Author(s)

Alex Lishinski and Paul Bailey

References

Diggle, P. J., Liang, K.-Y., & Zeger, S. L. (1994). *Analysis of longitudinal data*. Oxford, UK: Clarendon Press.

Draper, N. R., & Smith, H. (1998). *Applied regression analysis*. New York, NY: Wiley.

Fox, J. (1997). *Applied regression analysis, linear models, and related methods*. Thousand Oaks, CA: SAGE.

[Institute for Digital Research and Education. (n.d.). FAQ: How are the likelihood ratio, Wald, and LaGrange multiplier (score) tests different and/or similar?](<https://stats.idre.ucla.edu/other/mult-pkg/faq/general/faqhow-are-the-likelihood-ratio-wald-and-lagrange-multiplier-score-tests-different-andor-similar/>). Los Angeles: University of California at Los Angeles. Retrieved from <https://stats.idre.ucla.edu/other/mult-pkg/faq/general/faqhow-are-the-likelihood-ratio-wald-and-lagrange-multiplier-score-tests-different-andor-similar/>

Korn, E., & Graubard, B. (1990). Simultaneous testing of regression coefficients with complex survey data: Use of Bonferroni t statistics. *The American Statistician*, 44(4), 270–276.

Examples

```
## Not run:
# read in the example data (generated, not real student data)
sdf <- readNAEP(system.file("extdata/data", "M36NT2PM.dat", package = "NAEPprimer"))

# example with glm model
myLogit <- logit.sdf(dsex ~ b017451 + b003501, data = sdf, returnVarEstInputs = T)

# single coefficient integer
waldTest(model = myLogit, coefficients = 2)

# set of coefficients integer vector
waldTest(model = myLogit, coefficients = 2:5)

# specify levels of factor variable to test
waldTest(myLogit, c("b017451Every day", "b017451About once a week"))

# specify all levels of factor variable to test
waldTest(myLogit, "b017451")

# example with lm model
fit <- lm.sdf(composite ~ dsex + b017451, data = sdf, returnVarEstInputs = T)

waldTest(model = fit, coefficients = "b017451")

# examples with alternative (nonzero) null hypothesis values
waldTest(model = myLogit, coefficients = 2, H0 = 0.5)
```

```
waldTest(model = myLogit, coefficients = 2:5, H0 = c(0.5, 0.6, 0.7, 0.8))  
waldTest(model = myLogit, coefficients = "b017451", H0 = c(0.5, 0.6, 0.7, 0.8))  
waldTest(model = myLogit, coefficients = c("b017451Every day", "b017451About once a week"),  
          H0 = c(0.1, 0.2))  
  
## End(Not run)
```

Index

- `$.edsurvey.data.frame`
(`edsurvey.data.frame`), 31
- `$<- .edsurvey.data.frame`
(`edsurvey.data.frame`), 31
- `%in%,edsurvey.data.frame,ANY-method`
(`edsurvey.data.frame`), 31
- `%in%,edsurvey.data.frame.list,ANY-method`
(`edsurvey.data.frame`), 31
- `achievementLevels`, 4, 5, 46
- `append.edsurvey.data.frame.list`
(`edsurvey.data.frame.list`), 36
- `as.data.frame`, 9, 9
- `cbind`, 9, 9
- `contourPlot`, 10
- `cor.sdf`, 4, 11
- `dim.edsurvey.data.frame`, 15
- `DoFCorrection`, 16, 81
- `download_ePIRLS`, 30, 125
- `downloadCivEDICCS`, 18, 96
- `downloadECLS_K`, 19, 99, 100, 102
- `downloadELS`, 20
- `downloadHSLS`, 21
- `downloadICILS`, 22
- `downloadPIAAC`, 22, 112, 113
- `downloadPIRLS`, 23, 114
- `downloadPISA`, 24, 115, 116
- `downloadPISA_YAFS`, 26
- `downloadTALIS`, 27, 120
- `downloadTIMSS`, 28, 72, 122
- `downloadTIMSSAdv`, 29, 124
- `EdSurvey-package`, 4
- `edsurvey.data.frame`, 31, 52
- `edsurvey.data.frame.list`, 35, 36
- `edsurveyTable`, 4, 38, 42, 43, 46
- `edsurveyTable2pdf`, 42
- `gap`, 4, 35, 44, 129
- `getAttributes(edsurvey.data.frame)`, 31
- `getData`, 4, 13, 35, 51, 85, 87–89, 91–93, 95, 96, 98–100, 102, 104, 105, 107, 108, 112–114, 116, 120, 122, 124, 125
- `getPlausibleValue`, 54, 145
- `getPSUVar(edsurvey.data.frame)`, 31
- `getStratumVar(edsurvey.data.frame)`, 31
- `getWeightJkReplicates`, 55
- `glm(glm.sdf)`, 56
- `glm.sdf`, 56
- `hasPlausibleValue`, 54, 60
- `isWeight`, 61
- `levelsSDF`, 62
- `lm(lm.sdf)`, 63
- `lm.sdf`, 4, 12, 16, 39, 46, 63, 71, 77, 130, 145
- `logit.sdf`, 4
- `logit.sdf(glm.sdf)`, 56
- `merge`, 67
- `mixed.sdf`, 4, 68
- `mml.sdf`, 71
- `mvr1m.sdf`, 74
- `oddsRatio`, 78
- `parseNAEPdct`, 79
- `percentile`, 4, 46, 79, 144
- `print.achievementLevels`, 82
- `print.edsurvey.data.frame`, 83
- `print.gap`, 84
- `print.gapList(print.gap)`, 84
- `probit.sdf(glm.sdf)`, 56
- `rbind`, 9
- `rbind(cbind)`, 9
- `read_ePIRLS`, 4, 30, 124
- `readBB_2001`, 84, 89
- `readBB_2003`, 86

readBB_2012, [87](#), [91–93](#)
readBPS_1994, [89](#)
readBPS_2001, [90](#)
readBPS_2009, [91](#)
readBPS_2014, [93](#)
readBTLS, [94](#)
readCivEDICCS, [4](#), [18](#), [95](#)
readECLS_B, [97](#)
readECLS_K1998, [19](#), [98](#), [100](#)
readECLS_K2011, [4](#), [19](#), [85](#), [87](#), [88](#), [95](#), [99](#), [99](#),
[102](#), [104](#), [105](#), [107](#)
readELS, [20](#), [101](#)
readHSB_Senior, [103](#), [112](#)
readHSB_Sophomore, [104](#), [112](#)
readHSLs, [21](#), [106](#)
readICILS, [4](#), [22](#), [107](#)
readNAEP, [4](#), [39](#), [85](#), [87–89](#), [91–93](#), [95](#), [96](#),
[98–100](#), [102](#), [104](#), [105](#), [107](#), [108](#),
[109](#), [114](#), [122](#), [124](#), [125](#)
readNLS72, [111](#)
readPIAAC, [4](#), [112](#)
readPIRLS, [4](#), [24](#), [113](#)
readPISA, [4](#), [25](#), [115](#), [118](#)
readPISA_YAFS, [26](#), [117](#)
readTALIS, [4](#), [27](#), [118](#)
readTIMSS, [4](#), [28](#), [96](#), [108](#), [114](#), [120](#), [124](#), [125](#)
readTIMSSAdv, [4](#), [29](#), [123](#)
rebindAttributes, [35](#), [52](#), [126](#)
recode.sdf, [13](#), [127](#)
rename.sdf, [128](#)
rq (rq.sdf), [129](#)
rq.sdf, [4](#), [129](#)

scoreTIMSS, [132](#)
SD, [133](#)
searchSDF, [135](#)
setAttributes (edsurvey.data.frame), [31](#)
showCodebook, [136](#)
showCutPoints, [138](#)
showPlausibleValues, [5](#), [39](#), [54](#), [63](#), [69](#), [129](#),
[138](#), [145](#)
showWeights, [6](#), [39](#), [139](#)
subset, [140](#)
subset.edsurvey.data.frame, [52](#)
summary2, [4](#), [142](#)

updatePlausibleValue, [54](#), [144](#)

varEstToCov, [41](#), [48](#), [59](#), [66](#), [76](#), [81](#), [134](#), [145](#)

waldTest, [59](#), [66](#), [147](#)