

Package ‘PLNmodels’

February 12, 2023

Title Poisson Lognormal Models

Version 1.0.1

Description The Poisson-lognormal model and variants (Chiquet, Mariadassou and Robin, 2021 <[doi:10.3389/fevo.2021.588292](https://doi.org/10.3389/fevo.2021.588292)>) can be used for a variety of multivariate problems when count data are at play, including principal component analysis for count data, discriminant analysis, model-based clustering and network inference. Implements variational algorithms to fit such models accompanied with a set of functions for visualization and diagnostic.

URL <https://pln-team.github.io/PLNmodels/>

BugReports <https://github.com/pln-team/PLNmodels/issues>

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.2.3

Depends R (>= 3.4)

LazyData true

biocViews

Imports methods, stats, MASS, future, future.apply, R6, glassoFast, Matrix, Rcpp, nloptr, igraph, grid, gridExtra, dplyr, tidyr, purrr, ggplot2, corrplot, magrittr, torch, rlang

Suggests knitr, rmarkdown, testthat, pkgdown, spelling, factoextra

LinkingTo Rcpp, RcppArmadillo, nloptr

VignetteBuilder knitr

Collate 'PLNfit-class.R' 'PLN.R' 'PLNLDA.R' 'PLNLDAfit-S3methods.R'
'PLNLDAfit-class.R' 'PLNPCA.R' 'PLNPCAfamily-S3methods.R'
'PLNfamily-class.R' 'PLNPCAfamily-class.R'
'PLNPCAfit-S3methods.R' 'PLNPCAfit-class.R'
'PLNfamily-S3methods.R' 'PLNfit-S3methods.R' 'PLNmixture.R'
'PLNmixturefamily-S3methods.R' 'PLNmixturefamily-class.R'
'PLNmixturefit-S3methods.R' 'PLNmixturefit-class.R'
'PLNmodels-package.R' 'PLNnetwork.R'

'PLNnetworkfamily-S3methods.R' 'PLNnetworkfamily-class.R'
 'PLNnetworkfit-S3methods.R' 'PLNnetworkfit-class.R'
 'RcppExports.R' 'barents.R' 'import_utils.R' 'mollusk.R'
 'oaks.R' 'plot_utils.R' 'trichoptera.R' 'utils-pipe.R'
 'utils.R' 'zzz.R'

Language en-US

NeedsCompilation yes

Author Julien Chiquet [aut, cre] (<<https://orcid.org/0000-0002-3629-3429>>),
 Mahendra Mariadassou [aut] (<<https://orcid.org/0000-0003-2986-354X>>),
 Stéphane Robin [ctb],
 Giovanni Poggiato [ctb],
 François Gindraud [aut]

Maintainer Julien Chiquet <julien.chiquet@inrae.fr>

Repository CRAN

Date/Publication 2023-02-12 14:42:07 UTC

R topics documented:

barents	3
coef.PLNfit	4
coef.PLNLDAfit	5
coef.PLNmixturefit	6
coefficient_path	7
compute_offset	7
extract_probs	9
fitted.PLNfit	10
fitted.PLNmixturefit	11
getBestModel.PLNPCAfamily	11
getModel.PLNPCAfamily	12
mollusk	13
oaks	14
PLN	16
PLNfamily	17
PLNfit	19
PLNfit_diagonal	24
PLNfit_fixedcov	26
PLNfit_spherical	29
PLNLDA	30
PLNLDAfit	32
PLNLDAfit_diagonal	36
PLNLDA_param	37
PLNmixture	39
PLNmixturefamily	40
PLNmixturefit	43
PLNmixture_param	47
PLNmodels	49

PLNnetwork	50
PLNnetworkfamily	51
PLNnetworkfit	54
PLNnetwork_param	58
PLNPCA	60
PLNPCAfamily	61
PLNPCAfit	63
PLNPCA_param	69
PLN_param	70
plot.PLNfamily	72
plot.PLNLDAfit	73
plot.PLNmixturefamily	74
plot.PLNmixturefit	75
plot.PLNnetworkfamily	76
plot.PLNnetworkfit	77
plot.PLNPCAfamily	79
plot.PLNPCAfit	80
predict.PLNfit	81
predict.PLNLDAfit	82
predict.PLNmixturefit	83
predict_cond	84
prepare_data	85
rPLN	87
sigma.PLNfit	88
sigma.PLNmixturefit	89
stability_selection	90
standard_error.PLNPCAfit	91
trichoptera	93
vcov.PLNfit	94
Index	95

barents

Barents fish data set

Description

This data set gives the abundance of 30 fish species observed in 89 sites in the Barents sea. For each site, 4 additional covariates are known. Subsample of the original datasets studied by Fossheim et al, 2006.

Usage

barents

Format

A data frame with 6 variables:

- Abundance: A 30 fish species by 89 sites count matrix
- Offset: A 30 fish species by 116 samples offset matrix, measuring the sampling effort in each site
- 4 covariates for latitude, longitude, depth (in meters), temperature (in Celsius degrees).

Source

Data from M. Fossheim and coauthors.

References

Fossheim, Maria, Einar M. Nilssen, and Michaela Aschan. "Fish assemblages in the Barents Sea." *Marine Biology Research* 2.4 (2006). doi:[10.1080/17451000600815698](https://doi.org/10.1080/17451000600815698)

Examples

```
data(barents)
```

```
coef.PLNfit
```

Extract model coefficients

Description

Extracts model coefficients from objects returned by `PLN()` and its variants

Usage

```
## S3 method for class 'PLNfit'
coef(object, type = c("main", "covariance"), ...)
```

Arguments

`object` an R6 object with class `PLNfit`
`type` type of parameter that should be extracted. Either "main" (default) for

B

or "covariance" for

Σ

`...` additional parameters for S3 compatibility. Not used

Value

A matrix of coefficients extracted from the PLNfit model.

See Also

[sigma.PLNfit\(\)](#), [vcov.PLNfit\(\)](#), [standard_error.PLNfit\(\)](#)

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ 1 + offset(log(Offset)), data = trichoptera)
coef(myPLN) ## B
coef(myPLN, type = "covariance") ## Sigma
```

code: coef.PLNLDAfit

Extracts model coefficients from objects returned by [PLNLDA\(\)](#)

Description

The method for objects returned by [PLNLDA\(\)](#) only returns coefficients associated to the

$$\Theta$$

part of the model (see the PLNLDA vignette for mathematical details).

Usage

```
## S3 method for class 'PLNLDAfit'
coef(object, ...)
```

Arguments

object	an R6 object with class PLNLDAfit
...	additional parameters for S3 compatibility. Not used

Value

Either NULL or a matrix of coefficients extracted from the PLNLDAfit model.

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLNLDA <- PLNLDA(Abundance ~ Wind, grouping = Group, data = trichoptera)
coef(myPLNLDA)
```

coef.PLNmixturefit *Extract model coefficients*

Description

Extracts model coefficients from objects returned by [PLN\(\)](#) and its variants

Usage

```
## S3 method for class 'PLNmixturefit'
coef(object, type = c("main", "means", "covariance", "mixture"), ...)
```

Arguments

object	an R6 object with class PLNmixturefit
type	type of parameter that should be extracted. Either "main" (default) for Θ , "means" for μ , "mixture" for π or "covariance" for Σ
...	additional parameters for S3 compatibility. Not used

Value

A matrix of coefficients extracted from the PLNfit model.

See Also

[sigma.PLNmixturefit\(\)](#)

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLNmixture(Abundance ~ 1 + offset(log(Offset)),
  data = trichoptera, control = PLNmixture_param(smoothing = "none")) %>% getBestModel()
coef(myPLN) ## Theta - empty here
coef(myPLN, type = "mixture") ## pi
coef(myPLN, type = "means") ## mu
coef(myPLN, type = "covariance") ## Sigma
```

coefficient_path	<i>Extract the regularization path of a PLNnetwork fit</i>
------------------	--

Description

Extract the regularization path of a PLNnetwork fit

Usage

```
coefficient_path(Robject, precision = TRUE, corr = TRUE)
```

Arguments

Robject	an object with class <code>PLNnetworkfamily</code> , i.e. an output from <code>PLNnetwork()</code>
precision	a logical, should the coefficients of the precision matrix Omega or the covariance matrix Sigma be sent back. Default is TRUE.
corr	a logical, should the correlation (partial in case <code>precision = TRUE</code>) be sent back. Default is TRUE.

Value

Sends back a tibble/data.frame.

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
fits <- PLNnetwork(Abundance ~ 1, data = trichoptera)
head(coefficient_path(fits))
```

compute_offset	<i>Compute offsets from a count data using one of several normalization schemes</i>
----------------	---

Description

Computes offsets from the count table using one of several normalization schemes (TSS, CSS, RLE, GMPR, etc) described in the literature.

Usage

```
compute_offset(
  counts,
  offset = c("TSS", "GMPR", "RLE", "CSS", "Wrench", "none"),
  ...
)
```

Arguments

counts	Required. An abundance count table, preferably with dimensions names and species as columns.
offset	Optional. Normalization scheme used to compute scaling factors used as offset during PLN inference. Available schemes are "TSS" (Total Sum Scaling, default), "CSS" (Cumulative Sum Scaling, used in metagenomeSeq), "RLE" (Relative Log Expression, used in DESeq2), "GMPR" (Geometric Mean of Pairwise Ratio, introduced in Chen et al., 2018), Wrench (introduced in Kumar et al., 2018) or "none". Alternatively the user can supply its own vector or matrix of offsets (see note for specification of the user-supplied offsets).
...	Additional parameters passed on to specific methods (for now CSS and RLE)

Details

RLE has additional pseudocounts and type arguments to add pseudocounts to the observed counts (defaults to 0L) and to compute offsets using only positive counts (if type == "poscounts"). This mimics the behavior of DESeq2::DESeq() when using sfType == "poscounts". CSS has an additional reference argument to choose the location function used to compute the reference quantiles (defaults to median as in the Nature publication but can be set to mean to reproduce behavior of functions cumNormStat* from metagenomeSeq). Wrench has two additional parameters: groups to specify sample groups and type to either reproduce exactly the default Wrench::wrench() behavior (type = "wrench", default) or to use simpler heuristics (type = "simple"). Note that (i) CSS normalization fails when the median absolute deviation around quantiles does not become instable for high quantiles (limited count variations both within and across samples) and/or one sample has less than two positive counts, (ii) RLE fails when there are no common species across all samples (unless type == "poscounts" has been specified) and (iii) GMPR fails if a sample does not share any species with all other samples.

Value

If offset = "none", NULL else a vector of length nrow(counts) with one offset per sample.

References

- Chen, L., Reeve, J., Zhang, L., Huang, S., Wang, X. and Chen, J. (2018) GMPR: A robust normalization method for zero-inflated count data with application to microbiome sequencing data. PeerJ, 6, e4600 doi:[10.7717/peerj.4600](https://doi.org/10.7717/peerj.4600)
- Paulson, J. N., Colin Stine, O., Bravo, H. C. and Pop, M. (2013) Differential abundance analysis for microbial marker-gene surveys. Nature Methods, 10, 1200-1202 doi:[10.1038/nmeth.2658](https://doi.org/10.1038/nmeth.2658)
- Anders, S. and Huber, W. (2010) Differential expression analysis for sequence count data. Genome Biology, 11, R106 doi:[10.1186/gb20101110r106](https://doi.org/10.1186/gb20101110r106)
- Kumar, M., Slud, E., Okrah, K. et al. (2018) Analysis and correction of compositional bias in sparse sequencing count data. BMC Genomics 19, 799 doi:[10.1186/s1286401851605](https://doi.org/10.1186/s1286401851605)

Examples

```
data(trichoptera)
```



```

counts <- trichoptera$Abundance
compute_offset(counts)
## Other normalization schemes
compute_offset(counts, offset = "RLE", pseudocounts = 1)
compute_offset(counts, offset = "Wrench", groups = trichoptera$Covariate$Group)
compute_offset(counts, offset = "GMPR")
## User supplied offsets
my_offset <- setNames(rep(1, nrow(counts)), rownames(counts))
compute_offset(counts, offset = my_offset)

```

extract_probs

Extract edge selection frequency in bootstrap subsamples

Description

Extracts edge selection frequency in networks reconstructed from bootstrap subsamples during the stars stability selection procedure, as either a matrix or a named vector. In the latter case, edge names follow igraph naming convention.

Usage

```

extract_probs(
  Robject,
  penalty = NULL,
  index = NULL,
  crit = c("StARS", "BIC", "EBIC"),
  format = c("matrix", "vector"),
  tol = 1e-05
)

```

Arguments

Robject	an object with class PLNnetworkfamily , i.e. an output from PLNnetwork()
penalty	penalty used for the bootstrap subsamples
index	Integer index of the model to be returned. Only the first value is taken into account.
crit	a character for the criterion used to performed the selection. Either "BIC", "ICL", "EBIC", "StARS", "R_squared". Default is ICL for PLNPCA, and BIC for PLNnetwork. If StARS (Stability Approach to Regularization Selection) is chosen and stability selection was not yet performed, the function will call the method stability_selection() with default argument.
format	output format. Either a matrix (default) or a named vector.
tol	tolerance for rounding error when comparing penalties.

Value

Either a matrix or named vector of edge-wise probabilities. In the latter case, edge names follow igraph convention.

Examples

```

data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
nets <- PLNnetwork(Abundance ~ 1 + offset(log(Offset)), data = trichoptera)
## Not run:
stability_selection(nets)
probs <- extract_probs(nets, crit = "StARS", format = "vector")
probs

## End(Not run)

## Not run:
## Add edge attributes to graph using igraph
net_stars <- getBestModel(nets, "StARS")
g <- plot(net_stars, type = "partial_cor", plot=F)
library(igraph)
E(g)$prob <- probs[as_ids(E(g))]
g

## End(Not run)

```

fitted.PLNfit	<i>Extracts model fitted values from objects returned by PLN() and its variants</i>
---------------	---

Description

Extracts model fitted values from objects returned by [PLN\(\)](#) and its variants

Usage

```

## S3 method for class 'PLNfit'
fitted(object, ...)

```

Arguments

object	an R6 object with class PLNfit
...	additional parameters for S3 compatibility. Not used

Value

A matrix of Fitted values extracted from the object object.

fitted.PLNmixturefit *Extracts model fitted values from objects returned by `PLNmixture()` and its variants*

Description

Extracts model fitted values from objects returned by `PLNmixture()` and its variants

Usage

```
## S3 method for class 'PLNmixturefit'
fitted(object, ...)
```

Arguments

object an R6 object with class `PLNmixturefit`
 ... additional parameters for S3 compatibility. Not used

Value

A matrix of Fitted values extracted from the object object.

getBestModel.PLNPCAfamily
Best model extraction from a collection of models

Description

Best model extraction from a collection of models

Usage

```
## S3 method for class 'PLNPCAfamily'
getBestModel(Robject, crit = c("ICL", "BIC"), ...)

getBestModel(Robject, crit, ...)

## S3 method for class 'PLNmixturefamily'
getBestModel(Robject, crit = c("ICL", "BIC"), ...)

## S3 method for class 'PLNnetworkfamily'
getBestModel(Robject, crit = c("BIC", "EBIC", "StARS"), ...)
```

Arguments

Robjct	an object with class PLNPCAfamily or PLNnetworkfamily
crit	a character for the criterion used to performed the selection. Either "BIC", "ICL", "EBIC", "StARS", "R_squared". Default is ICL for PLNPCA, and BIC for PLNnetwork. If StARS (Stability Approach to Regularization Selection) is chosen and stability selection was not yet performed, the function will call the method <code>stability_selection()</code> with default argument.
...	additional parameters for StARS criterion (only for PLNnetwork). <code>stability</code> , a scalar indicating the target stability ($= 1 - 2 \beta$) at which the network is selected. Default is 0.9.

Value

Send back an object with class `PLNPCAfit` or `PLNnetworkfit`

Methods (by class)

- `getBestModel(PLNPCAfamily)`: Model extraction for `PLNPCAfamily`
- `getBestModel(PLNmixturefamily)`: Model extraction for `PLNmixturefamily`
- `getBestModel(PLNnetworkfamily)`: Model extraction for `PLNnetworkfamily`

Examples

```
## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPCA <- PLNPCA(Abundance ~ 1 + offset(log(Offset)), data = trichoptera, ranks = 1:4)
myModel <- getBestModel(myPCA)

## End(Not run)
```

`getModel.PLNPCAfamily` *Model extraction from a collection of models*

Description

Model extraction from a collection of models

Usage

```
## S3 method for class 'PLNPCAfamily'
getModel(Robjct, var, index = NULL)

getModel(Robjct, var, index)

## S3 method for class 'PLNmixturefamily'
```

```

getModel(Robject, var, index = NULL)

## S3 method for class 'PLNnetworkfamily'
getModel(Robject, var, index = NULL)

```

Arguments

Robject	an R6 object with class PLNPCAfamily or PLNnetworkfamily
var	value of the parameter (rank for PLNPCA , sparsity for PLNnetwork) that identifies the model to be extracted from the collection. If no exact match is found, the model with closest parameter value is returned with a warning.
index	Integer index of the model to be returned. Only the first value is taken into account.

Value

Sends back an object with class [PLNPCAfit](#) or [PLNnetworkfit](#).

Methods (by class)

- `getModel(PLNPCAfamily)`: Model extraction for [PLNPCAfamily](#)
- `getModel(PLNmixturefamily)`: Model extraction for [PLNmixturefamily](#)
- `getModel(PLNnetworkfamily)`: Model extraction for [PLNnetworkfamily](#)

Examples

```

## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPCA <- PLNPCA(Abundance ~ 1 + offset(log(Offset)), data = trichoptera, ranks = 1:5)
myModel <- getModel(myPCA, 2)

## End(Not run)

```

mollusk

Mollusk data set

Description

This data set gives the abundance of 32 mollusk species in 163 samples. For each sample, 4 additional covariates are known.

Usage

```
mollusk
```

Format

A list with 2 two data frames:

Abundance a 163 x 32 data frame of abundancies/counts (163 samples and 32 mollusk species)

Covariate a 163 x 4 data frame of covariates:

site a factor with 8 levels indicating the sampling site

season a factor with 4 levels indicating the season

method a factor with 2 levels for the method of sampling - wood or string

duration a numeric with 3 levels for the time of exposure in week

In order to prepare the data for using formula in multivariate analysis (multiple outputs and inputs), use `prepare_data()`. Original data set has been extracted from ade4.

Source

Data from Richardot-Coulet, Chessel and Bournaud.

References

Richardot-Coulet, M., Chessel D. and Bournaud M. (1986) Typological value of the benthos of old beds of a large river. Methodological approach. Archiv für Hydrobiologie, 107, 363–383.

See Also

`prepare_data()`

Examples

```
data(mollusk)
mollusc <- prepare_data(mollusk$Abundance, mollusk$Covariate)
```

oaks

Oaks amplicon data set

Description

This data set gives the abundance of 114 taxa (66 bacterial OTU, 48 fungal OTUs) in 116 samples. For each sample, 11 additional covariates are known.

Usage

oaks

Format

A data frame with 13 variables:

- Abundance: A 114 taxa by 116 samples count matrix
- Offset: A 114 taxa by 116 samples offset matrix
- Sample: Unique sample id
- tree: Tree status with respect to the pathogen (susceptible, intermediate or resistant)
- branch: Unique branch id in each tree (4 branches were sampled in each tree, with 10 leaves per branch)
- leafNO: Unique leaf id in each tree (40 leaves were sampled in each tree)
- distTObase: Distance of the sampled leaf to the base of the branch
- distTOTrunk: Distance of the sampled leaf to the base of the tree trunk
- distTOground: Distance of the sampled leaf to the base of the ground
- pmInfection: Powdery mildew infection, proportion of the upper leaf area displaying mildew symptoms
- orientation: Orientation of the branch (South-West SW or North-East NE)
- readsTOTfun: Total number of ITS1 reads for that leaf
- readsTOTbac: Total number of 16S reads for that leaf

Source

Data from B. Jakuschkin and coauthors.

References

Jakuschkin, B., Fievet, V., Schwaller, L. et al. Deciphering the Pathobiome: Intra- and Interkingdom Interactions Involving the Pathogen *Erysiphe alphitoides*. *Microb Ecol* 72, 870–880 (2016).
[doi:10.1007/s002480160777x](https://doi.org/10.1007/s002480160777x)

See Also

[prepare_data\(\)](#)

Examples

```
data(oaks)
## Not run:
oaks_networks <- PLNnetwork(formula = Abundance ~ 1 + offset(log(Offset)), data = oaks)

## End(Not run)
```

PLN

Poisson lognormal model

Description

Fit the multivariate Poisson lognormal model with a variational algorithm. Use the (g)lm syntax for model specification (covariates, offsets, weights).

Usage

```
PLN(formula, data, subset, weights, control = PLN_param())
```

Arguments

formula	an object of class "formula": a symbolic description of the model to be fitted.
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which PLN is called.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
weights	an optional vector of observation weights to be used in the fitting process.
control	a list-like structure for controlling the optimization, with default generated by <code>PLN_param()</code> . See the associated documentation for details.

Value

an R6 object with class `PLNfit`

See Also

The class `PLNfit` and the configuration function `PLN_param()`

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ 1, data = trichoptera)
```

 PLNfamily

 An R6 Class to represent a collection of PLNfit

Description

super class for [PLNPCAfamily](#) and [PLNnetworkfamily](#).

Public fields

`responses` the matrix of responses common to every models

`covariates` the matrix of covariates common to every models

`offsets` the matrix of offsets common to every models

`weights` the vector of observation weights

`inception` a [PLNfit](#) object, obtained when no sparsifying penalty is applied.

`models` a list of [PLNfit](#) object, one per penalty.

Active bindings

`criteria` a data frame with the values of some criteria (approximated log-likelihood, BIC, ICL, etc.) for the collection of models / fits BIC and ICL are defined so that they are on the same scale as the model log-likelihood, i.e. with the form, $\text{loglik} - 0.5 \text{ penalty}$

`convergence` sends back a data frame with some convergence diagnostics associated with the optimization process (method, optimal value, etc)

Methods

Public methods:

- [PLNfamily\\$new\(\)](#)
- [PLNfamily\\$postTreatment\(\)](#)
- [PLNfamily\\$getModel\(\)](#)
- [PLNfamily\\$plot\(\)](#)
- [PLNfamily\\$show\(\)](#)
- [PLNfamily\\$print\(\)](#)
- [PLNfamily\\$clone\(\)](#)

Method `new()`: Create a new [PLNfamily](#) object.

Usage:

```
PLNfamily$new(responses, covariates, offsets, weights, control)
```

Arguments:

`responses` the matrix of responses common to every models

`covariates` the matrix of covariates common to every models

`offsets` the matrix of offsets common to every models

`weights` the vector of observation weights

control list controlling the optimization and the model

Returns: A new [PLNfamily](#) object

Method `postTreatment()`: Update fields after optimization

Usage:

`PLNfamily$postTreatment(config)`

Arguments:

`config` a list for controlling the post-treatment.

Method `getModel()`: Extract a model from a collection of models

Usage:

`PLNfamily$getModel(var, index = NULL)`

Arguments:

`var` value of the parameter (rank for PLNPCA, sparsity for PLNnetwork) that identifies the model to be extracted from the collection. If no exact match is found, the model with closest parameter value is returned with a warning.

`index` Integer index of the model to be returned. Only the first value is taken into account.

Returns: A [PLNfit](#) object

Method `plot()`: Lineplot of selected criteria for all models in the collection

Usage:

`PLNfamily$plot(criteria, reverse)`

Arguments:

`criteria` A valid model selection criteria for the collection of models. Includes `loglik`, `BIC` (all), `ICL` (PLNPCA) and `pen_loglik`, `EBIC` (PLNnetwork)

`reverse` A logical indicating whether to plot the value of the criteria in the "natural" direction (`loglik - penalty`) or in the "reverse" direction (`-2 loglik + penalty`). Default to `FALSE`, i.e. use the natural direction, on the same scale as the log-likelihood.

Returns: A [ggplot2](#) object

Method `show()`: User friendly print method

Usage:

`PLNfamily$show()`

Method `print()`: User friendly print method

Usage:

`PLNfamily$print()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`PLNfamily$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

See Also

[getModel\(\)](#)

 PLNfit

An R6 Class to represent a PLNfit in a standard, general framework

Description

The function `PLN()` fit a model which is an instance of a object with class `PLNfit`. Objects produced by the functions `PLNnetwork()`, `PLNPCA()`, `PLNmixture()` and `PLNLDA()` also enjoy the methods of `PLNfit()` by inheritance.

This class comes with a set of R6 methods, some of them being useful for the user and exported as S3 methods. See the documentation for `coef()`, `sigma()`, `predict()`, `vcov()` and `standard_error()`.

Fields are accessed via active binding and cannot be changed by the user.

Active bindings

`n` number of samples

`q` number of dimensions of the latent space

`p` number of species

`d` number of covariates

`nb_param` number of parameters in the current PLN model

`model_par` a list with the matrices of the model parameters: `B` (covariates), `Sigma` (covariance), `Omega` (precision matrix), plus some others depending on the variant)

`var_par` a list with the matrices of the variational parameters: `M` (means) and `S2` (variances)

`optim_par` a list with parameters useful for monitoring the optimization

`latent` a matrix: values of the latent vector (`Z` in the model)

`latent_pos` a matrix: values of the latent position vector (`Z`) without covariates effects or offset

`fitted` a matrix: fitted values of the observations (`A` in the model)

`vcov_coef` matrix of sandwich estimator of the variance-covariance of `B` (need fixed -ie known-covariance at the moment)

`vcov_model` character: the model used for the residual covariance

`weights` observational weights

`loglik` (weighted) variational lower bound of the loglikelihood

`loglik_vec` element-wise variational lower bound of the loglikelihood

`BIC` variational lower bound of the BIC

`entropy` Entropy of the variational distribution

`ICL` variational lower bound of the ICL

`R_squared` approximated goodness-of-fit criterion

`criteria` a vector with `loglik`, `BIC`, `ICL` and number of parameters

Methods

Public methods:

- `PLNfit$new()`
- `PLNfit$update()`
- `PLNfit$optimize()`
- `PLNfit$optimize_vestep()`
- `PLNfit$postTreatment()`
- `PLNfit$predict()`
- `PLNfit$predict_cond()`
- `PLNfit$show()`
- `PLNfit$print()`
- `PLNfit$clone()`

Method `new()`: Initialize a `PLNfit` model

Usage:

```
PLNfit$new(responses, covariates, offsets, weights, formula, control)
```

Arguments:

`responses` the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`covariates` design matrix (called X in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`offsets` offset matrix (called O in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`weights` an optional vector of observation weights to be used in the fitting process.

`formula` model formula used for fitting, extracted from the formula in the upper-level call

`control` a list-like structure for controlling the fit, see `PLN_param()`.

Method `update()`: Update a `PLNfit` object

Usage:

```
PLNfit$update(
  B = NA,
  Sigma = NA,
  Omega = NA,
  M = NA,
  S = NA,
  Ji = NA,
  R2 = NA,
  Z = NA,
  A = NA,
  monitoring = NA
)
```

Arguments:

`B` matrix of regression matrix

`Sigma` variance-covariance matrix of the latent variables

Omega precision matrix of the latent variables. Inverse of Sigma.
 M matrix of variational parameters for the mean
 S matrix of variational parameters for the variance
 Ji vector of variational lower bounds of the log-likelihoods (one value per sample)
 R2 approximate R^2 goodness-of-fit criterion
 Z matrix of latent vectors (includes covariates and offset effects)
 A matrix of fitted values
 monitoring a list with optimization monitoring quantities
Returns: Update the current `PLNfit` object

Method `optimize()`: Call to the NLOpt or TORCH optimizer and update of the relevant fields

Usage:

```
PLNfit$optimize(responses, covariates, offsets, weights, config)
```

Arguments:

responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in `PLNfamily-class`
 covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in `PLNfamily-class`
 offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in `PLNfamily-class`
 weights an optional vector of observation weights to be used in the fitting process.
 config part of the control argument which configures the optimizer

Method `optimize_vestep()`: Result of one call to the VE step of the optimization procedure: optimal variational parameters (M, S) and corresponding log likelihood values for fixed model parameters (Sigma, B). Intended to position new data in the latent space.

Usage:

```

PLNfit$optimize_vestep(
  covariates,
  offsets,
  responses,
  weights,
  B = self$model_par$B,
  Omega = self$model_par$Omega,
  control = PLN_param(backend = "nlopt")
)

```

Arguments:

covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in `PLNfamily-class`
 offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in `PLNfamily-class`
 responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in `PLNfamily-class`
 weights an optional vector of observation weights to be used in the fitting process.

B Optional fixed value of the regression parameters

Omega precision matrix of the latent variables. Inverse of Sigma.

control a list-like structure for controlling the fit, see `PLN_param()`.

Sigma variance-covariance matrix of the latent variables

Returns: A list with three components:

- the matrix M of variational means,
- the matrix S2 of variational variances
- the vector `log.lik` of (variational) log-likelihood of each new observation

Method `postTreatment()`: Update R2, fisher and `std_err` fields after optimization

Usage:

```
PLNfit$postTreatment(
  responses,
  covariates,
  offsets,
  weights = rep(1, nrow(responses)),
  config,
  nullModel = NULL
)
```

Arguments:

`responses` the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`covariates` design matrix (called X in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`offsets` offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`weights` an optional vector of observation weights to be used in the fitting process.

`config` a list for controlling the post-treatments (optional bootstrap, jackknife, R2, etc.). See details

`nullModel` null model used for approximate R2 computations. Defaults to a GLM model with same design matrix but not latent variable.

Details: The list of parameters `config` controls the post-treatment processing, with the following entries:

- `jackknife` boolean indicating whether jackknife should be performed to evaluate bias and variance of the model parameters. Default is FALSE.
- `bootstrap` integer indicating the number of bootstrap resamples generated to evaluate the variance of the model parameters. Default is 0 (inactivated).
- `variational_var` boolean indicating whether variational Fisher information matrix should be computed to estimate the variance of the model parameters (highly underestimated). Default is FALSE.
- `rsquared` boolean indicating whether approximation of R2 based on deviance should be computed. Default is TRUE
- `trace` integer for verbosity. should be > 1 to see output in post-treatments

Method `predict()`: Predict position, scores or observations of new data.

Usage:

```
PLNfit$predict(newdata, type = c("link", "response"), envir = parent.frame())
```

Arguments:

newdata A data frame in which to look for variables with which to predict. If omitted, the fitted values are used.

type Scale used for the prediction. Either `link` (default, predicted positions in the latent space) or `response` (predicted counts).

envir Environment in which the prediction is evaluated

Returns: A matrix with predictions scores or counts.

Method `predict_cond()`: Predict position, scores or observations of new data, conditionally on the observation of a (set of) variables

Usage:

```
PLNfit$predict_cond(
  newdata,
  cond_responses,
  type = c("link", "response"),
  var_par = FALSE,
  envir = parent.frame()
)
```

Arguments:

newdata a data frame containing the covariates of the sites where to predict

cond_responses a data frame containing the count of the observed variables (matching the names of the provided as data in the PLN function)

type Scale used for the prediction. Either `link` (default, predicted positions in the latent space) or `response` (predicted counts).

var_par Boolean. Should new estimations of the variational parameters of mean and variance be sent back, as attributes of the matrix of predictions. Default to `FALSE`.

envir Environment in which the prediction is evaluated

Returns: A matrix with predictions scores or counts.

Method `show()`: User friendly print method

Usage:

```
PLNfit$show(
  model = paste("A multivariate Poisson Lognormal fit with", self$vcov_model,
    "covariance model.\n")
)
```

Arguments:

model First line of the print output

Method `print()`: User friendly print method

Usage:

```
PLNfit$print()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNfit$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ 1, data = trichoptera)
class(myPLN)
print(myPLN)

## End(Not run)
```

PLNfit_diagonal	<i>An R6 Class to represent a PLNfit in a standard, general framework, with diagonal residual covariance</i>
-----------------	--

Description

The function `PLNLDA()` produces an instance of an object with class `PLNLDAfit`.

This class comes with a set of methods, some of them being useful for the user: See the documentation for the methods inherited by `PLNfit()`, the `plot()` method for LDA visualization and `predict()` method for prediction

Super class

```
PLNmodels::PLNfit -> PLNfit_diagonal
```

Active bindings

nb_param number of parameters in the current PLN model

vcov_model character: the model used for the residual covariance

Methods**Public methods:**

- `PLNfit_diagonal$new()`
- `PLNfit_diagonal$clone()`

Method `new()`: Initialize a `PLNfit` model

Usage:

```
PLNfit_diagonal$new(responses, covariates, offsets, weights, formula, control)
```

Arguments:

responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class
covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in PLNfamily-class
offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class
weights an optional vector of observation weights to be used in the fitting process.
formula model formula used for fitting, extracted from the formula in the upper-level call
control a list for controlling the optimization. See details.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNfit_diagonal$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Super classes

`PLNmodels::PLNfit -> PLNmodels::PLNLDAfit -> PLNLDAfit_spherical`

Active bindings

`vcov_model` character: the model used for the residual covariance

Methods

Public methods:

- `PLNLDAfit_spherical$new()`
- `PLNLDAfit_spherical$clone()`

Method `new()`: Initialize a `PLNfit` model

Usage:

```
PLNLDAfit_spherical$new(
  grouping,
  responses,
  covariates,
  offsets,
  weights,
  formula,
  control
)
```

Arguments:

`grouping` a factor specifying the class of each observation used for discriminant analysis.

responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`covariates` design matrix (called `X` in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`offsets` offset matrix (called `O` in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`weights` an optional vector of observation weights to be used in the fitting process.

`formula` model formula used for fitting, extracted from the formula in the upper-level call

`control` a list for controlling the optimization. See details.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNLDAfit_spherical$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ 1, data = trichoptera)
class(myPLN)
print(myPLN)

## End(Not run)
## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLNLDA <- PLNLDA(Abundance ~ 1, data = trichoptera, control = PLN_param(covariance = "spherical"))
class(myPLNLDA)
print(myPLNLDA)

## End(Not run)
```

PLNfit_fixedcov	<i>An R6 Class to represent a PLNfit in a standard, general framework, with fixed (inverse) residual covariance</i>
-----------------	---

Description

An R6 Class to represent a PLNfit in a standard, general framework, with fixed (inverse) residual covariance

An R6 Class to represent a PLNfit in a standard, general framework, with fixed (inverse) residual covariance

Super class

```
PLNmodels::PLNfit -> PLNfit_fixedcov
```

Active bindings

nb_param number of parameters in the current PLN model
vcov_model character: the model used for the residual covariance
vcov_coef matrix of sandwich estimator of the variance-covariance of B (needs known covariance at the moment)

Methods**Public methods:**

- [PLNfit_fixedcov\\$new\(\)](#)
- [PLNfit_fixedcov\\$optimize\(\)](#)
- [PLNfit_fixedcov\\$postTreatment\(\)](#)
- [PLNfit_fixedcov\\$clone\(\)](#)

Method `new()`: Initialize a `PLNfit` model

Usage:

`PLNfit_fixedcov$new(responses, covariates, offsets, weights, formula, control)`

Arguments:

`responses` the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`covariates` design matrix (called X in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`offsets` offset matrix (called O in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`weights` an optional vector of observation weights to be used in the fitting process.

`formula` model formula used for fitting, extracted from the formula in the upper-level call

`control` a list for controlling the optimization. See details.

Method `optimize()`: Call to the NLOpt or TORCH optimizer and update of the relevant fields

Usage:

`PLNfit_fixedcov$optimize(responses, covariates, offsets, weights, config)`

Arguments:

`responses` the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`covariates` design matrix (called X in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`offsets` offset matrix (called O in the model). Will usually be extracted from the corresponding field in `PLNfamily`-class

`weights` an optional vector of observation weights to be used in the fitting process.

`config` part of the `control` argument which configures the optimizer

Method `postTreatment()`: Update R2, fisher and `std_err` fields after optimization

Usage:

```

PLNfit_fixedcov$postTreatment(
  responses,
  covariates,
  offsets,
  weights = rep(1, nrow(responses)),
  config,
  nullModel = NULL
)

```

Arguments:

`responses` the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`covariates` design matrix (called X in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`offsets` offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`weights` an optional vector of observation weights to be used in the fitting process.

`config` a list for controlling the post-treatments (optional bootstrap, jackknife, R2, etc.). See details

`nullModel` null model used for approximate R2 computations. Defaults to a GLM model with same design matrix but not latent variable.

Details: The list of parameters `config` controls the post-treatment processing, with the following entries:

- `trace` integer for verbosity. should be > 1 to see output in post-treatments
- `jackknife` boolean indicating whether jackknife should be performed to evaluate bias and variance of the model parameters. Default is FALSE.
- `bootstrap` integer indicating the number of bootstrap resamples generated to evaluate the variance of the model parameters. Default is 0 (inactivated).
- `variational_var` boolean indicating whether variational Fisher information matrix should be computed to estimate the variance of the model parameters (highly underestimated). Default is FALSE.
- `rsquared` boolean indicating whether approximation of R2 based on deviance should be computed. Default is TRUE

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNfit_fixedcov$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```

## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ 1, data = trichoptera)
class(myPLN)

```

```
print(myPLN)

## End(Not run)
```

PLNfit_spherical	<i>An R6 Class to represent a PLNfit in a standard, general framework, with spherical residual covariance</i>
------------------	---

Description

An R6 Class to represent a PLNfit in a standard, general framework, with spherical residual covariance

An R6 Class to represent a PLNfit in a standard, general framework, with spherical residual covariance

Super class

`PLNmodels::PLNfit` -> PLNfit_spherical

Active bindings

`nb_param` number of parameters in the current PLN model

`vcov_model` character: the model used for the residual covariance

Methods

Public methods:

- `PLNfit_spherical$new()`
- `PLNfit_spherical$clone()`

Method `new()`: Initialize a `PLNfit` model

Usage:

```
PLNfit_spherical$new(responses, covariates, offsets, weights, formula, control)
```

Arguments:

`responses` the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`covariates` design matrix (called X in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`offsets` offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`weights` an optional vector of observation weights to be used in the fitting process.

`formula` model formula used for fitting, extracted from the formula in the upper-level call

`control` a list for controlling the optimization. See details.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNfit_spherical$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ 1, data = trichoptera)
class(myPLN)
print(myPLN)

## End(Not run)
```

 PLNLDA

Poisson lognormal model towards Linear Discriminant Analysis

Description

Fit the Poisson lognormal for LDA with a variational algorithm. Use the (g)lm syntax for model specification (covariates, offsets).

Usage

```
PLNLDA(formula, data, subset, weights, grouping, control = PLN_param())
```

Arguments

formula	an object of class "formula": a symbolic description of the model to be fitted.
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>lm</code> is called.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
weights	an optional vector of observation weights to be used in the fitting process.
grouping	a factor specifying the class of each observation used for discriminant analysis.
control	a list-like structure for controlling the optimization, with default generated by <code>PLN_param()</code> . See the associated documentation

Details

The parameter control is a list controlling the optimization with the following entries:

- "covariance" character setting the model for the covariance matrix. Either "full" or "spherical". Default is "full".
- "trace" integer for verbosity.
- "inception" Set up the initialization. By default, the model is initialized with a multivariate linear model applied on log-transformed data. However, the user can provide a PLNfit (typically obtained from a previous fit), which often speed up the inference.
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "ftol_abs" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 0
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6
- "xtol_abs" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 0
- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "maxtime" stop when the optimization time (in seconds) exceeds maxtime. Default is -1 (no restriction)
- "algorithm" the optimization method used by NLOPT among LD type, i.e. "CCSAQ", "MMA", "LBFGS", "VAR1", "VAR2". See NLOPT documentation for further details. Default is "CCSAQ".

Value

an R6 object with class `PLNLDAfit()`

See Also

The class `PLNLDAfit`

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLNLDA <- PLNLDA(Abundance ~ 1, grouping = Group, data = trichoptera)
```

 PLNLDAfit

 An R6 Class to represent a PLNfit in a LDA framework

Description

The function `PLNLDA()` produces an instance of an object with class `PLNLDAfit`.

This class comes with a set of methods, some of them being useful for the user: See the documentation for the methods inherited by `PLNfit()`, the `plot()` method for LDA visualization and `predict()` method for prediction

Super class

`PLNmodels::PLNfit -> PLNLDAfit`

Active bindings

`rank` the dimension of the current model

`nb_param` number of parameters in the current PLN model

`model_par` a list with the matrices associated with the estimated parameters of the PLN model: B (covariates), Sigma (latent covariance), C (latent loadings), P (latent position) and Mu (group means)

`percent_var` the percent of variance explained by each axis

`corr_map` a matrix of correlations to plot the correlation circles

`scores` a matrix of scores to plot the individual factor maps

`group_means` a matrix of group mean vectors in the latent space.

Methods

Public methods:

- `PLNLDAfit$new()`
- `PLNLDAfit$optimize()`
- `PLNLDAfit$postTreatment()`
- `PLNLDAfit$setVisualization()`
- `PLNLDAfit$plot_individual_map()`
- `PLNLDAfit$plot_correlation_map()`
- `PLNLDAfit$plot_LDA()`
- `PLNLDAfit$predict()`
- `PLNLDAfit$show()`
- `PLNLDAfit$clone()`

Method `new()`: Initialize a `PLNLDAfit` object

Usage:


```

PLNLDAfit$new(
  grouping,
  responses,
  covariates,
  offsets,
  weights,
  formula,
  control
)

```

Arguments:

grouping a factor specifying the class of each observation used for discriminant analysis.
 responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class
 covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in PLNfamily-class
 offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class
 weights an optional vector of observation weights to be used in the fitting process.
 formula model formula used for fitting, extracted from the formula in the upper-level call
 control list controlling the optimization and the model

Method optimize(): Compute group means and axis of the LDA (noted B in the model) in the latent space, update corresponding fields

Usage:

```
PLNLDAfit$optimize(grouping, responses, covariates, offsets, weights, config)
```

Arguments:

grouping a factor specifying the class of each observation used for discriminant analysis.
 responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class
 covariates design matrix. Automatically built from the covariates and the formula from the call
 offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class
 weights an optional vector of observation weights to be used in the fitting process.
 config list controlling the optimization
 X Abundance matrix.

Method postTreatment(): Update R2, fisher and std_err fields and visualization

Usage:

```
PLNLDAfit$postTreatment(grouping, responses, covariates, offsets, config)
```

Arguments:

grouping a factor specifying the class of each observation used for discriminant analysis.
 responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class

covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in PLNfamily-class

offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class

config list controlling the post-treatment

Method `setVisualization()`: Compute LDA scores in the latent space and update corresponding fields.

Usage:

```
PLNLDAfit$setVisualization(scale.unit = FALSE)
```

Arguments:

`scale.unit` Logical. Should LDA scores be rescaled to have unit variance

Method `plot_individual_map()`: Plot the factorial map of the LDA

Usage:

```
PLNLDAfit$plot_individual_map(
  axes = 1:min(2, self$rank),
  main = "Individual Factor Map",
  plot = TRUE
)
```

Arguments:

`axes` numeric, the axes to use for the plot when `map = "individual" or "variable"`. Default is `c(1,min(rank))`

`main` character. A title for the single plot (individual or variable factor map). If NULL (the default), an hopefully appropriate title will be used.

`plot` logical. Should the plot be displayed or sent back as ggplot object

Returns: a [ggplot](#) graphic

Method `plot_correlation_map()`: Plot the correlation circle of a specified axis for a [PLNLDAfit](#) object

Usage:

```
PLNLDAfit$plot_correlation_map(
  axes = 1:min(2, self$rank),
  main = "Variable Factor Map",
  cols = "default",
  plot = TRUE
)
```

Arguments:

`axes` numeric, the axes to use for the plot when `map = "individual" or "variable"`. Default is `c(1,min(rank))`

`main` character. A title for the single plot (individual or variable factor map). If NULL (the default), an hopefully appropriate title will be used.

`cols` a character, factor or numeric to define the color associated with the variables. By default, all variables receive the default color of the current palette.

plot logical. Should the plot be displayed or sent back as ggplot object

Returns: a [ggplot](#) graphic

Method plot_LDA(): Plot a summary of the [PLNLDAfit](#) object

Usage:

```
PLNLDAfit$plot_LDA(
  nb_axes = min(3, self$rank),
  var_cols = "default",
  plot = TRUE
)
```

Arguments:

nb_axes scalar: the number of axes to be considered when map = "both". The default is min(3,rank).

var_cols a character, factor or numeric to define the color associated with the variables. By default, all variables receive the default color of the current palette.

plot logical. Should the plot be displayed or sent back as ggplot object

Returns: a [grob](#) object

Method predict(): Predict group of new samples

Usage:

```
PLNLDAfit$predict(
  newdata,
  type = c("posterior", "response", "scores"),
  scale = c("log", "prob"),
  prior = NULL,
  control = PLN_param(backend = "nlopt"),
  envir = parent.frame()
)
```

Arguments:

newdata A data frame in which to look for variables, offsets and counts with which to predict.

type The type of prediction required. The default are posterior probabilities for each group (in either unnormalized log-scale or natural probabilities, see "scale" for details), "response" is the group with maximal posterior probability and "scores" is the average score along each separation axis in the latent space, with weights equal to the posterior probabilities.

scale The scale used for the posterior probability. Either log-scale ("log", default) or natural probabilities summing up to 1 ("prob").

prior User-specified prior group probabilities in the new data. If NULL (default), prior probabilities are computed from the learning set.

control a list for controlling the optimization. See [PLN\(\)](#) for details.

envir Environment in which the prediction is evaluated

Method show(): User friendly print method

Usage:

```
PLNLDAfit$show()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNLDAfit$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

The function [PLNLDA](#).

Examples

```
## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLNLDA <- PLNLDA(Abundance ~ 1, grouping = Group, data = trichoptera)
class(myPLNLDA)
print(myPLNLDA)

## End(Not run)
```

PLNLDAfit_diagonal	<i>An R6 Class to represent a PLNfit in a LDA framework with diagonal covariance</i>
--------------------	--

Description

The function [PLNLDA\(\)](#) produces an instance of an object with class [PLNLDAfit](#).

This class comes with a set of methods, some of them being useful for the user: See the documentation for the methods inherited by [PLNfit\(\)](#), the [plot\(\)](#) method for LDA visualization and [predict\(\)](#) method for prediction

Super classes

```
PLNmodels::PLNfit -> PLNmodels::PLNLDAfit -> PLNLDAfit_diagonal
```

Active bindings

`vcov_model` character: the model used for the residual covariance

Methods

Public methods:

- [PLNLDAfit_diagonal\\$new\(\)](#)
- [PLNLDAfit_diagonal\\$clone\(\)](#)

Method `new()`: Initialize a [PLNfit](#) model

Usage:

```
PLNLDAfit_diagonal$new(
  grouping,
  responses,
  covariates,
  offsets,
  weights,
  formula,
  control
)
```

Arguments:

grouping a factor specifying the class of each observation used for discriminant analysis.

responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class

covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in PLNfamily-class

offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class

weights an optional vector of observation weights to be used in the fitting process.

formula model formula used for fitting, extracted from the formula in the upper-level call

control a list for controlling the optimization. See details.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNLDAfit_diagonal$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLNLDA <- PLNLDA(Abundance ~ 1, data = trichoptera, control = PLN_param(covariance = "diagonal"))
class(myPLNLDA)
print(myPLNLDA)

## End(Not run)
```

Description

Helper to define list of parameters to control the PLNLDA fit. All arguments have defaults.

Usage

```

PLNLDA_param(
  backend = c("nlopt", "torch"),
  trace = 1,
  covariance = c("full", "diagonal", "spherical"),
  config_post = list(),
  config_optim = list(),
  inception = NULL
)

```

Arguments

backend	optimization back used, either "nlopt" or "torch". Default is "nlopt"
trace	a integer for verbosity.
covariance	character setting the model for the covariance matrix. Either "full", "diagonal" or "spherical". Default is "full".
config_post	a list for controlling the post-treatments (optional bootstrap, jackknife, R2, etc.). See details
config_optim	a list for controlling the optimizer (either "nlopt" or "torch" backend). See details
inception	Set up the parameters initialization: by default, the model is initialized with a multivariate linear model applied on log-transformed data, and with the same formula as the one provided by the user. However, the user can provide a PLNfit (typically obtained from a previous fit), which sometimes speeds up the inference.

Details

The list of parameters `config_optim` controls the optimizers. When "nlopt" is chosen the following entries are relevant

- "algorithm" the optimization method used by NLOPT among LD type, e.g. "CCSAQ", "MMA", "LBFGS". See NLOPT documentation for further details. Default is "CCSAQ".
- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6
- "ftol_abs" stop when an optimization step changes the objective function by less than ftol_abs. Default is 0.0 (disabled)
- "xtol_abs" stop when an optimization step changes every parameters by less than xtol_abs. Default is 0.0 (disabled)
- "maxtime" stop when the optimization time (in seconds) exceeds maxtime. Default is -1 (disabled)

When "torch" backend is used, with the following entries are relevant:

- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6

The list of parameters `config_post` controls the post-treatment processing, with the following entries:

- `jackknife` boolean indicating whether jackknife should be performed to evaluate bias and variance of the model parameters. Default is FALSE.
- `bootstrap` integer indicating the number of bootstrap resamples generated to evaluate the variance of the model parameters. Default is 0 (inactivated).
- `variational_var` boolean indicating whether variational Fisher information matrix should be computed to estimate the variance of the model parameters (highly underestimated). Default is TRUE.
- `rsquared` boolean indicating whether approximation of R2 based on deviance should be computed. Default is TRUE

Value

list of parameters configuring the fit.

PLNmixture	<i>Poisson lognormal mixture model</i>
------------	--

Description

Fit the mixture variants of the Poisson lognormal with a variational algorithm. Use the (g)lm syntax for model specification (covariates, offsets).

Usage

```
PLNmixture(formula, data, subset, clusters = 1:5, control = PLNmixture_param())
```

Arguments

<code>formula</code>	an object of class "formula": a symbolic description of the model to be fitted.
<code>data</code>	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>lm</code> is called.
<code>subset</code>	an optional vector specifying a subset of observations to be used in the fitting process.
<code>clusters</code>	a vector of integer containing the successive number of clusters (or components) to be considered
<code>control</code>	a list-like structure for controlling the optimization, with default generated by <code>PLNmixture_param()</code> . See the associated documentation for details.

Value

an R6 object with class [PLNmixturefamily](#), which contains a collection of models with class [PLNmixturefit](#)

See Also

The classes [PLNmixturefamily](#), [PLNmixturefit](#) and [PLNmixture_param\(\)](#)

Examples

```
## Use future to dispatch the computations on 2 workers
## Not run:
future::plan("multisession", workers = 2)

## End(Not run)

data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myMixtures <- PLNmixture(Abundance ~ 1 + offset(log(Offset)), clusters = 1:4, data = trichoptera,
                        control = PLNmixture_param(smoothing = 'none'))

# Shut down parallel workers
## Not run:
future::plan("sequential")

## End(Not run)
```

PLNmixturefamily

An R6 Class to represent a collection of PLNmixturefit

Description

The function [PLNmixture\(\)](#) produces an instance of this class.

This class comes with a set of methods, some of them being useful for the user: See the documentation for [getBestModel\(\)](#), [getModel\(\)](#) and [plot\(\)](#).

Super class

[PLNmodels::PLNfamily](#) -> [PLNmixturefamily](#)

Active bindings

`clusters` vector indicating the number of clusters considered is the successively fitted models

Methods**Public methods:**

- `PLNmixturefamily$new()`
- `PLNmixturefamily$optimize()`
- `PLNmixturefamily$smooth()`
- `PLNmixturefamily$plot()`
- `PLNmixturefamily$plot_objective()`
- `PLNmixturefamily$getBestModel()`
- `PLNmixturefamily$show()`
- `PLNmixturefamily$print()`
- `PLNmixturefamily$clone()`

Method `new()`: helper function for forward smoothing: split a group
Initialize all models in the collection.

Usage:

```
PLNmixturefamily$new(
  clusters,
  responses,
  covariates,
  offsets,
  formula,
  control
)
```

Arguments:

`clusters` the dimensions of the successively fitted models
`responses` the matrix of responses common to every models
`covariates` the matrix of covariates common to every models
`offsets` the matrix of offsets common to every models
`formula` model formula used for fitting, extracted from the formula in the upper-level call
`control` a list for controlling the optimization. See details.
`control` a list for controlling the optimization. See details.

Method `optimize()`: Call to the optimizer on all models of the collection

Usage:

```
PLNmixturefamily$optimize(config)
```

Arguments:

`config` a list for controlling the optimization

Method `smooth()`: function to restart clustering to avoid local minima by smoothing the log-likelihood values as a function of the number of clusters

Usage:

```
PLNmixturefamily$smooth(control)
```

Arguments:

control a list to control the smoothing process

Method `plot()`: Lineplot of selected criteria for all models in the collection

Usage:

```
PLNmixturefamily$plot(criteria = c("loglik", "BIC", "ICL"), reverse = FALSE)
```

Arguments:

criteria A valid model selection criteria for the collection of models. Any of "loglik", "BIC" or "ICL" (all).

reverse A logical indicating whether to plot the value of the criteria in the "natural" direction (loglik - 0.5 penalty) or in the "reverse" direction (-2 loglik + penalty). Default to FALSE, i.e use the natural direction, on the same scale as the log-likelihood..

Returns: A [ggplot2](#) object

Method `plot_objective()`: Plot objective value of the optimization problem along the penalty path

Usage:

```
PLNmixturefamily$plot_objective()
```

Returns: a [ggplot](#) graph

Method `getBestModel()`: Extract best model in the collection

Usage:

```
PLNmixturefamily$getBestModel(crit = c("BIC", "ICL", "loglik"))
```

Arguments:

crit a character for the criterion used to performed the selection. Either "BIC", "ICL" or "loglik". Default is ICL

Returns: a [PLNmixturefit](#) object

Method `show()`: User friendly print method

Usage:

```
PLNmixturefamily$show()
```

Method `print()`: User friendly print method

Usage:

```
PLNmixturefamily$print()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNmixturefamily$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

The function [PLNmixture](#), the class [PLNmixturefit](#)

 PLNmixturefit

An R6 Class to represent a PLNfit in a mixture framework

Description

The function `PLNmixture` produces a collection of models which are instances of object with class `PLNmixturefit`. A `PLNmixturefit` (say, with k components) is itself a collection of k `PLNfit`.

This class comes with a set of methods, some of them being useful for the user: See the documentation for ...

Active bindings

`n` number of samples

`p` number of dimensions of the latent space

`k` number of components

`d` number of covariates

`components` components of the mixture (PLNfits)

`latent` a matrix: values of the latent vector (Z in the model)

`latent_pos` a matrix: values of the latent position vector (Z) without covariates effects or offset

`posteriorProb` matrix of posterior probability for cluster belonging

`memberships` vector for cluster index

`mixtureParam` vector of cluster proportions

`optim_par` a list with parameters useful for monitoring the optimization

`nb_param` number of parameters in the current PLN model

`entropy_clustering` Entropy of the variational distribution of the cluster (multinomial)

`entropy_latent` Entropy of the variational distribution of the latent vector (Gaussian)

`entropy` Full entropy of the variational distribution (latent vector + clustering)

`loglik` variational lower bound of the loglikelihood

`loglik_vec` element-wise variational lower bound of the loglikelihood

`BIC` variational lower bound of the BIC

`ICL` variational lower bound of the ICL (include entropy of both the clustering and latent distributions)

`R_squared` approximated goodness-of-fit criterion

`criteria` a vector with `loglik`, `BIC`, `ICL`, and number of parameters

`model_par` a list with the matrices of parameters found in the model (Θ , Σ , μ and Π)

`vcov_model` character: the model used for the covariance (either "spherical", "diagonal" or "full")

`fitted` a matrix: fitted values of the observations (A in the model)

`group_means` a matrix of group mean vectors in the latent space.

Methods

Public methods:

- `PLNmixturefit$new()`
- `PLNmixturefit$optimize()`
- `PLNmixturefit$predict()`
- `PLNmixturefit$plot_clustering_data()`
- `PLNmixturefit$plot_clustering_pca()`
- `PLNmixturefit$postTreatment()`
- `PLNmixturefit$show()`
- `PLNmixturefit$print()`
- `PLNmixturefit$clone()`

Method `new()`: Optimize a the
Initialize a `PLNmixturefit` model

Usage:

```
PLNmixturefit$new(
  responses,
  covariates,
  offsets,
  posteriorProb,
  formula,
  control
)
```

Arguments:

`responses` the matrix of responses common to every models
`covariates` the matrix of covariates common to every models
`offsets` the matrix of offsets common to every models
`posteriorProb` matrix of posterior probability for cluster belonging
`formula` model formula used for fitting, extracted from the formula in the upper-level call
`control` a list for controlling the optimization.

Method `optimize()`: Optimize a `PLNmixturefit` model

Usage:

```
PLNmixturefit$optimize(responses, covariates, offsets, config)
```

Arguments:

`responses` the matrix of responses common to every models
`covariates` the matrix of covariates common to every models
`offsets` the matrix of offsets common to every models
`config` a list for controlling the optimization

Method `predict()`: Predict group of new samples

Usage:

```

PLNmixturefit$predict(
  newdata,
  type = c("posterior", "response", "position"),
  prior = matrix(rep(1/self$k, self$k), nrow(newdata), self$k, byrow = TRUE),
  control = PLNmixture_param(),
  envir = parent.frame()
)

```

Arguments:

newdata A data frame in which to look for variables, offsets and counts with which to predict.

type The type of prediction required. The default posterior are posterior probabilities for each group, *response* is the group with maximal posterior probability and *latent* is the averaged latent coordinate (without offset and nor covariate effects), with weights equal to the posterior probabilities.

prior User-specified prior group probabilities in the new data. The default uses a uniform prior.

control a list-like structure for controlling the fit. See [PLNmixture_param\(\)](#) for details.

envir Environment in which the prediction is evaluated

Method `plot_clustering_data()`: Plot the matrix of expected mean counts (without offsets, without covariate effects) reordered according the inferred clustering

Usage:

```

PLNmixturefit$plot_clustering_data(
  main = "Expected counts reorder by clustering",
  plot = TRUE,
  log_scale = TRUE
)

```

Arguments:

main character. A title for the plot. An hopefully appropriate title will be used by default.

plot logical. Should the plot be displayed or sent back as [ggplot](#) object

log_scale logical. Should the color scale values be log-transform before plotting? Default is TRUE.

Returns: a [ggplot](#) graphic

Method `plot_clustering_pca()`: Plot the individual map of a PCA performed on the latent coordinates, where individuals are colored according to the memberships

Usage:

```

PLNmixturefit$plot_clustering_pca(
  main = "Clustering labels in Individual Factor Map",
  plot = TRUE
)

```

Arguments:

main character. A title for the plot. An hopefully appropriate title will be used by default.

plot logical. Should the plot be displayed or sent back as [ggplot](#) object

Returns: a [ggplot](#) graphic

Method `postTreatment()`: Update fields after optimization

Usage:

```
PLNmixturefit$postTreatment(  
  responses,  
  covariates,  
  offsets,  
  weights,  
  config,  
  nullModel  
)
```

Arguments:

`responses` the matrix of responses common to every models

`covariates` the matrix of covariates common to every models

`offsets` the matrix of offsets common to every models

`weights` an optional vector of observation weights to be used in the fitting process.

`config` a list for controlling the post-treatment

`nullModel` null model used for approximate R2 computations. Defaults to a GLM model with same design matrix but not latent variable.

Method `show()`: User friendly print method

Usage:

```
PLNmixturefit$show()
```

Method `print()`: User friendly print method

Usage:

```
PLNmixturefit$print()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNmixturefit$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

The function [PLNmixture](#), the class [PLNmixturefamily](#)

PLNmixture_param *Control of a PLNmixture fit*

Description

Helper to define list of parameters to control the PLNmixture fit. All arguments have defaults.

Usage

```
PLNmixture_param(
  backend = "nlopt",
  trace = 1,
  covariance = "spherical",
  init_cl = "kmeans",
  smoothing = "both",
  config_optim = list(),
  inception = NULL
)
```

Arguments

backend	optimization back used, either "nlopt" or "torch". Default is "nlopt"
trace	a integer for verbosity.
covariance	character setting the model for the covariance matrices of the mixture components. Either "full", "diagonal" or "spherical". Default is "spherical".
init_cl	The initial clustering to apply. Either, 'kmeans', 'CAH' or a user defined clustering given as a list of clusterings, the size of which is equal to the number of clusters considered. Default is 'kmeans'.
smoothing	The smoothing to apply. Either, 'none', 'forward', 'backward' or 'both'. Default is 'both'.
config_optim	a list for controlling the optimizer (either "nlopt" or "torch" backend). See details
inception	Set up the parameters initialization: by default, the model is initialized with a multivariate linear model applied on log-transformed data, and with the same formula as the one provided by the user. However, the user can provide a PLNfit (typically obtained from a previous fit), which sometimes speeds up the inference.

Details

The list of parameters `config_optim` controls the optimizers. When "nlopt" is chosen the following entries are relevant

- "it_smooth" number of forward/backward iteration of smoothing. Default is 2.
- "algorithm" the optimization method used by NLOPT among LD type, e.g. "CCSAQ", "MMA", "LBFGS". See NLOPT documentation for further details. Default is "CCSAQ".

- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6
- "ftol_out" outer solver stops when an optimization step changes the objective function by less than xtol multiply by the absolute value of the parameter. Default is 1e-6
- "maxit_out" outer solver stops when the number of iteration exceeds out.maxit. Default is 50
- "ftol_abs" stop when an optimization step changes the objective function by less than ftol_abs. Default is 0.0 (disabled)
- "xtol_abs" stop when an optimization step changes every parameters by less than xtol_abs. Default is 0.0 (disabled)
- "maxtime" stop when the optimization time (in seconds) exceeds maxtime. Default is -1 (disabled)

When "torch" backend is used, with the following entries are relevant:

- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6
- "ftol_out" outer solver stops when an optimization step changes the objective function by less than xtol multiply by the absolute value of the parameter. Default is 1e-6
- "maxit_out" outer solver stops when the number of iteration exceeds out.maxit. Default is 50

The list of parameters `config_post` controls the post-treatment processing, with the following entries:

- jackknife boolean indicating whether jackknife should be performed to evaluate bias and variance of the model parameters. Default is FALSE.
- bootstrap integer indicating the number of bootstrap resamples generated to evaluate the variance of the model parameters. Default is 0 (inactivated).
- variational_var boolean indicating whether variational Fisher information matrix should be computed to estimate the variance of the model parameters (highly underestimated). Default is FALSE.
- rsquared boolean indicating whether approximation of R2 based on deviance should be computed. Default is FALSE

Value

list of parameters configuring the fit.

PLNmodels

PLNmodels

Description

The Poisson lognormal model and variants can be used for a variety of multivariate problems when count data are at play (including PCA or LDA for count data, network inference). This package implements efficient variational algorithms to fit such models accompanied with a set of functions for visualization and diagnostic.

Multivariate Poisson lognormal model (aka PLN)

See the main function [PLN\(\)](#) and the associated methods for manipulation.

Also try `vignette("PLN_trichoptera", package="PLNmodels")` for an overview.

Rank Constrained Poisson lognormal for Poisson Principal Component Analysis (aka PLNPCA)

See the main function [PLNPCA\(\)](#) and the associated methods for manipulation.

The Poisson PCA and the associated variational inference is fully explained in Chiquet et al (2018), see reference below.

Also try `vignette("PLNPCA_trichoptera", package="PLNmodels")` for an overview.

Sparse Poisson lognormal model for sparse covariance inference for counts (aka PLNnetwork)

See the main function [PLNnetwork\(\)](#) and the associated methods for manipulation.

Also try `vignette("PLNnetwork_trichoptera", package="PLNmodels")` for an overview.

Poisson lognormal discriminant analysis (aka PLNLDA)

See the main function [PLNLDA\(\)](#) and the associated methods for manipulation.

Also try `vignette("PLNLDA_trichoptera", package="PLNmodels")` for an overview.

Mixtures of Poisson lognormal models for model-based clustering (aka PLNmixture)

See the main function [PLNmixture\(\)](#) and the associated methods for manipulation.

Also try `vignette("PLNmixture_trichoptera", package="PLNmodels")` for an overview.

Author(s)

Julien Chiquet <julien.chiquet@inrae.fr>

Mahendra Mariadassou <mahendra.mariadassou@inrae.fr>

Stéphane Robin <stephane.robin@inrae.fr>

 PLNnetwork

Poisson lognormal model towards sparse network inference

Description

Fit the sparse inverse covariance variant of the Poisson lognormal with a variational algorithm. Use the (g)lm syntax for model specification (covariates, offsets).

Usage

```
PLNnetwork(
  formula,
  data,
  subset,
  weights,
  penalties = NULL,
  control = PLNnetwork_param()
)
```

Arguments

formula	an object of class "formula": a symbolic description of the model to be fitted.
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>lm</code> is called.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
weights	an optional vector of observation weights to be used in the fitting process.
penalties	an optional vector of positive real number controlling the level of sparsity of the underlying network. if <code>NULL</code> (the default), will be set internally. See <code>PLNnetwork_param()</code> for additional tuning of the penalty.
control	a list-like structure for controlling the optimization, with default generated by <code>PLNnetwork_param()</code> . See the corresponding documentation for details;

Value

an R6 object with class `PLNnetworkfamily`, which contains a collection of models with class `PLNnetworkfit`

See Also

The classes `PLNnetworkfamily` and `PLNnetworkfit`, and the and the configuration function `PLNnetwork_param()`.

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
fits <- PLNnetwork(Abundance ~ 1, data = trichoptera)
```

 PLNnetworkfamily

An R6 Class to represent a collection of PLNnetworkfit

Description

The function `PLNnetwork()` produces an instance of this class.

This class comes with a set of methods, some of them being useful for the user: See the documentation for `getBestModel()`, `getModel()` and `plot()`

Super class

```
PLNmodels::PLNfamily -> PLNnetworkfamily
```

Active bindings

`penalties` the sparsity level of the network in the successively fitted models

`stability_path` the stability path of each edge as returned by the stars procedure

`stability` mean edge stability along the penalty path

`criteria` a data frame with the values of some criteria (approximated log-likelihood, (E)BIC, ICL and R2, stability) for the collection of models / fits BIC, ICL and EBIC are defined so that they are on the same scale as the model log-likelihood, i.e. with the form, $\text{loglik} - 0.5 \text{penalty}$

Methods**Public methods:**

- `PLNnetworkfamily$new()`
- `PLNnetworkfamily$optimize()`
- `PLNnetworkfamily$stability_selection()`
- `PLNnetworkfamily$coefficient_path()`
- `PLNnetworkfamily$getBestModel()`
- `PLNnetworkfamily$plot()`
- `PLNnetworkfamily$plot_stars()`
- `PLNnetworkfamily$plot_objective()`
- `PLNnetworkfamily$show()`
- `PLNnetworkfamily$clone()`

Method `new()`: Initialize all models in the collection

Usage:

```

PLNnetworkfamily$new(
  penalties,
  responses,
  covariates,
  offsets,
  weights,
  formula,
  control
)

```

Arguments:

`penalties` a vector of positive real number controlling the level of sparsity of the underlying network.

`responses` the matrix of responses common to every models

`covariates` the matrix of covariates common to every models

`offsets` the matrix of offsets common to every models

`weights` the vector of observation weights

`formula` model formula used for fitting, extracted from the formula in the upper-level call

`control` a list for controlling the optimization.

Returns: Update current `PLNnetworkfit` with smart starting values

Method `optimize()`: Call to the C++ optimizer on all models of the collection

Usage:

```
PLNnetworkfamily$optimize(config)
```

Arguments:

`config` a list for controlling the optimization.

Method `stability_selection()`: Compute the stability path by stability selection

Usage:

```

PLNnetworkfamily$stability_selection(
  subsamples = NULL,
  control = PLNnetwork_param()
)

```

Arguments:

`subsamples` a list of vectors describing the subsamples. The number of vectors (or list length) determines the number of subsamples used in the stability selection. Automatically set to 20 subsamples with size $10 \cdot \sqrt{n}$ if $n \geq 144$ and $0.8 \cdot n$ otherwise following Liu et al. (2010) recommendations.

`control` a list controlling the main optimization process in each call to `PLNnetwork`. See `PLNnetwork()` for details.

Method `coefficient_path()`: Extract the regularization path of a `PLNnetworkfamily`

Usage:

```
PLNnetworkfamily$coefficient_path(precision = TRUE, corr = TRUE)
```

Arguments:

precision Logical. Should the regularization path be extracted from the precision matrix Omega (TRUE, default) or from the variance matrix Sigma (FALSE)
 corr Logical. Should the matrix be transformed to (partial) correlation matrix before extraction? Defaults to TRUE

Method `getBestModel()`: Extract the best network in the family according to some criteria

Usage:

```
PLNnetworkfamily$getBestModel(
  crit = c("BIC", "EBIC", "StARS"),
  stability = 0.9
)
```

Arguments:

`crit` character. Criterion used to perform the selection. Is "StARS" is chosen but `$stability` field is empty, will compute stability path.
`stability` Only used for "StARS" criterion. A scalar indicating the target stability (= 1 - 2 beta) at which the network is selected. Default is 0.9.

Method `plot()`: Display various outputs (goodness-of-fit criteria, robustness, diagnostic) associated with a collection of PLNnetwork fits (a [PLNnetworkfamily](#))

Usage:

```
PLNnetworkfamily$plot(
  criteria = c("loglik", "pen_loglik", "BIC", "EBIC"),
  reverse = FALSE,
  log.x = TRUE
)
```

Arguments:

`criteria` vector of characters. The criteria to plot in `c("loglik", "pen_loglik", "BIC", "EBIC")`. Defaults to all of them.
`reverse` A logical indicating whether to plot the value of the criteria in the "natural" direction (`loglik - 0.5 penalty`) or in the "reverse" direction (`-2 loglik + penalty`). Default to FALSE, i.e use the natural direction, on the same scale as the log-likelihood..
`log.x` logical: should the x-axis be represented in log-scale? Default is TRUE.

Returns: a [ggplot](#) graph

Method `plot_stars()`: Plot stability path

Usage:

```
PLNnetworkfamily$plot_stars(stability = 0.9, log.x = TRUE)
```

Arguments:

`stability` scalar: the targeted level of stability in stability plot. Default is 0.9.
`log.x` logical: should the x-axis be represented in log-scale? Default is TRUE.

Returns: a [ggplot](#) graph

Method `plot_objective()`: Plot objective value of the optimization problem along the penalty path

Usage:

```
PLNnetworkfamily$plot_objective()
```

Returns: a [ggplot](#) graph

Method `show()`: User friendly print method

Usage:

```
PLNnetworkfamily$show()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNnetworkfamily$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

The function [PLNnetwork\(\)](#), the class [PLNnetworkfit](#)

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
fits <- PLNnetwork(Abundance ~ 1, data = trichoptera)
class(fits)
```

PLNnetworkfit

An R6 Class to represent a PLNfit in a sparse inverse covariance framework

Description

The function [PLNnetwork\(\)](#) produces a collection of models which are instances of object with class [PLNnetworkfit](#). This class comes with a set of methods, some of them being useful for the user: See the documentation for [plot\(\)](#) and methods inherited from [PLNfit](#).

Super classes

```
PLNmodels::PLNfit -> PLNmodels::PLNfit_fixedcov -> PLNnetworkfit
```

Active bindings

vcov_model character: the model used for the residual covariance
 penalty the global level of sparsity in the current model
 penalty_weights a matrix of weights controlling the amount of penalty element-wise.
 n_edges number of edges if the network (non null coefficient of the sparse precision matrix)
 nb_param number of parameters in the current PLN model
 pen_loglik variational lower bound of the l1-penalized loglikelihood
 EBIC variational lower bound of the EBIC
 density proportion of non-null edges in the network
 criteria a vector with loglik, penalized loglik, BIC, EBIC, ICL, R_squared, number of parameters, number of edges and graph density

Methods**Public methods:**

- `PLNnetworkfit$new()`
- `PLNnetworkfit$update()`
- `PLNnetworkfit$optimize()`
- `PLNnetworkfit$latent_network()`
- `PLNnetworkfit$plot_network()`
- `PLNnetworkfit$show()`
- `PLNnetworkfit$clone()`

Method `new()`: Initialize a `PLNnetworkfit` object

Usage:

```

PLNnetworkfit$new(
  penalty,
  penalty_weights,
  responses,
  covariates,
  offsets,
  weights,
  formula,
  control
)

```

Arguments:

penalty a positive real number controlling the level of sparsity of the underlying network.
 penalty_weights either a single or a list of $p \times p$ matrix of weights (default filled with 1) to adapt the amount of shrinkage to each pairs of node. Must be symmetric with positive values.
 responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in `PLNfamily-class`
 covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in `PLNfamily-class`

offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class

weights an optional vector of observation weights to be used in the fitting process.

formula model formula used for fitting, extracted from the formula in the upper-level call

control a list for controlling the optimization.

Method `update()`: Update fields of a `PLNnetworkfit` object

Usage:

```
PLNnetworkfit$update(
  penalty = NA,
  B = NA,
  Sigma = NA,
  Omega = NA,
  M = NA,
  S = NA,
  Z = NA,
  A = NA,
  Ji = NA,
  R2 = NA,
  monitoring = NA
)
```

Arguments:

penalty a positive real number controlling the level of sparsity of the underlying network.

B matrix of regression matrix

Sigma variance-covariance matrix of the latent variables

Omega precision matrix of the latent variables. Inverse of Sigma.

M matrix of mean vectors for the variational approximation

S matrix of variance vectors for the variational approximation

Z matrix of latent vectors (includes covariates and offset effects)

A matrix of fitted values

Ji vector of variational lower bounds of the log-likelihoods (one value per sample)

R2 approximate R^2 goodness-of-fit criterion

monitoring a list with optimization monitoring quantities

Method `optimize()`: Call to the C++ optimizer and update of the relevant fields

Usage:

```
PLNnetworkfit$optimize(responses, covariates, offsets, weights, config)
```

Arguments:

responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in PLNfamily-class

covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in PLNfamily-class

offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in PLNfamily-class

`weights` an optional vector of observation weights to be used in the fitting process.
`config` a list for controlling the optimization

Method `latent_network()`: Extract interaction network in the latent space

Usage:

```
PLNnetworkfit$latent_network(type = c("partial_cor", "support", "precision"))
```

Arguments:

`type` edge value in the network. Can be "support" (binary edges), "precision" (coefficient of the precision matrix) or "partial_cor" (partial correlation between species)

Returns: a square matrix of size `PLNnetworkfit$n`

Method `plot_network()`: plot the latent network.

Usage:

```
PLNnetworkfit$plot_network(
  type = c("partial_cor", "support"),
  output = c("igraph", "corrplot"),
  edge.color = c("#F8766D", "#00BFC4"),
  remove.isolated = FALSE,
  node.labels = NULL,
  layout = layout_in_circle,
  plot = TRUE
)
```

Arguments:

`type` edge value in the network. Either "precision" (coefficient of the precision matrix) or "partial_cor" (partial correlation between species).

`output` Output type. Either `igraph` (for the network) or `corrplot` (for the adjacency matrix)

`edge.color` Length 2 color vector. Color for positive/negative edges. Default is `c("#F8766D", "#00BFC4")`. Only relevant for `igraph` output.

`remove.isolated` if TRUE, isolated node are remove before plotting. Only relevant for `igraph` output.

`node.labels` vector of character. The labels of the nodes. The default will use the column names of the response matrix.

`layout` an optional `igraph` layout. Only relevant for `igraph` output.

`plot` logical. Should the final network be displayed or only sent back to the user. Default is TRUE.

Method `show()`: User friendly print method

Usage:

```
PLNnetworkfit$show()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNnetworkfit$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

The function `PLNnetwork()`, the class `PLNnetworkfamily`

Examples

```
## Not run:
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
nets <- PLNnetwork(Abundance ~ 1, data = trichoptera)
myPLNnet <- getBestModel(nets)
class(myPLNnet)
print(myPLNnet)

## End(Not run)
```

 PLNnetwork_param

Control of PLNnetwork fit

Description

Helper to define list of parameters to control the PLN fit. All arguments have defaults.

Usage

```
PLNnetwork_param(
  backend = "nlopt",
  trace = 1,
  n_penalties = 30,
  min_ratio = 0.1,
  penalize_diagonal = TRUE,
  penalty_weights = NULL,
  config_optim = list(),
  inception = NULL
)
```

Arguments

<code>backend</code>	optimization back used, either "nlopt" or "torch". Default is "nlopt"
<code>trace</code>	a integer for verbosity.
<code>n_penalties</code>	an integer that specifies the number of values for the penalty grid when internally generated. Ignored when penalties is non NULL
<code>min_ratio</code>	the penalty grid ranges from the minimal value that produces a sparse to this value multiplied by <code>min_ratio</code> . Default is 0.1.
<code>penalize_diagonal</code>	boolean: should the diagonal terms be penalized in the graphical-Lasso? Default is TRUE

penalty_weights	either a single or a list of $p \times p$ matrix of weights (default filled with 1) to adapt the amount of shrinkage to each pairs of node. Must be symmetric with positive values.
config_optim	a list for controlling the optimizer (either "nlopt" or "torch" backend). See details
inception	Set up the parameters initialization: by default, the model is initialized with a multivariate linear model applied on log-transformed data, and with the same formula as the one provided by the user. However, the user can provide a PLNfit (typically obtained from a previous fit), which sometimes speeds up the inference.

Details

The list of parameters `config_optim` controls the optimizers. When "nlopt" is chosen the following entries are relevant

- "algorithm" the optimization method used by NLOPT among LD type, e.g. "CCSAQ", "MMA", "LBFGS". See NLOPT documentation for further details. Default is "CCSAQ".
- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6
- "ftol_out" outer solver stops when an optimization step changes the objective function by less than xtol multiply by the absolute value of the parameter. Default is 1e-6
- "maxit_out" outer solver stops when the number of iteration exceeds out.maxit. Default is 50
- "ftol_abs" stop when an optimization step changes the objective function by less than ftol_abs. Default is 0.0 (disabled)
- "xtol_abs" stop when an optimization step changes every parameters by less than xtol_abs. Default is 0.0 (disabled)
- "maxtime" stop when the optimization time (in seconds) exceeds maxtime. Default is -1 (disabled)

When "torch" backend is used, with the following entries are relevant:

- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_out" outer solver stops when an optimization step changes the objective function by less than xtol multiply by the absolute value of the parameter. Default is 1e-6
- "maxit_out" outer solver stops when the number of iteration exceeds out.maxit. Default is 50
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6

Value

list of parameters configuring the fit.

Description

Fit the PCA variants of the Poisson lognormal with a variational algorithm. Use the (g)lm syntax for model specification (covariates, offsets).

Usage

```
PLNPCA(formula, data, subset, weights, ranks = 1:5, control = PLNPCA_param())
```

Arguments

formula	an object of class "formula": a symbolic description of the model to be fitted.
data	an optional data frame, list or environment (or object coercible by <code>as.data.frame</code> to a data frame) containing the variables in the model. If not found in data, the variables are taken from <code>environment(formula)</code> , typically the environment from which <code>lm</code> is called.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
weights	an optional vector of observation weights to be used in the fitting process.
ranks	a vector of integer containing the successive ranks (or number of axes to be considered)
control	a list-like structure for controlling the optimization, with default generated by <code>PLNPCA_param()</code> . See the associated documentation. for details.

Value

an R6 object with class `PLNPCAfamily`, which contains a collection of models with class `PLNPCAfit`

See Also

The classes `PLNPCAfamily` and `PLNPCAfit`, and the configuration function `PLNPCA_param()`.

Examples

```
##' ## Use future to dispatch the computations on 2 workers
##' Not run:
##' future::plan("multisession", workers = 2)
##' End(Not run)
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPCA <- PLNPCA(Abundance ~ 1 + offset(log(Offset)), data = trichoptera, ranks = 1:5)
```

```
# Shut down parallel workers
## Not run:
future::plan("sequential")

## End(Not run)
```

 PLNPCAfamily

An R6 Class to represent a collection of PLNPCAfit

Description

The function `PLNPCA()` produces an instance of this class.

This class comes with a set of methods, some of them being useful for the user: See the documentation for `getBestModel()`, `getModel()` and `plot()`.

Super class

```
PLNmodels::PLNfamily -> PLNPCAfamily
```

Active bindings

`ranks` the dimensions of the successively fitted models

Methods

Public methods:

- `PLNPCAfamily$new()`
- `PLNPCAfamily$optimize()`
- `PLNPCAfamily$getModel()`
- `PLNPCAfamily$getBestModel()`
- `PLNPCAfamily$plot()`
- `PLNPCAfamily$show()`
- `PLNPCAfamily$clone()`

Method `new()`: Initialize all models in the collection.

Usage:

```
PLNPCAfamily$new(
  ranks,
  responses,
  covariates,
  offsets,
  weights,
  formula,
  control
)
```

Arguments:

ranks the dimensions of the successively fitted models
responses the matrix of responses common to every models
covariates the matrix of covariates common to every models
offsets the matrix of offsets common to every models
weights the vector of observation weights
formula model formula used for fitting, extracted from the formula in the upper-level call
control list controlling the optimization and the model

Method `optimize()`: Call to the C++ optimizer on all models of the collection

Usage:

```
PLNPCAfamily$optimize(config)
```

Arguments:

config list controlling the optimization.

Method `getModel()`: Extract model from collection and add "PCA" class for compatibility with `factoextra::fviz()`

Usage:

```
PLNPCAfamily$getModel(var, index = NULL)
```

Arguments:

var value of the parameter (rank for PLNPCA, sparsity for PLNnetwork) that identifies the model to be extracted from the collection. If no exact match is found, the model with closest parameter value is returned with a warning.
index Integer index of the model to be returned. Only the first value is taken into account.

Returns: a `PLNPCAfit` object

Method `getBestModel()`: Extract best model in the collection

Usage:

```
PLNPCAfamily$getBestModel(crit = c("ICL", "BIC"))
```

Arguments:

crit a character for the criterion used to performed the selection. Either "ICL", "BIC". Default is ICL

Returns: a `PLNPCAfit` object

Method `plot()`: Lineplot of selected criteria for all models in the collection

Usage:

```
PLNPCAfamily$plot(criteria = c("loglik", "BIC", "ICL"), reverse = FALSE)
```

Arguments:

criteria A valid model selection criteria for the collection of models. Any of "loglik", "BIC" or "ICL" (all).
reverse A logical indicating whether to plot the value of the criteria in the "natural" direction (loglik - penalty) or in the "reverse" direction (-2 loglik + penalty). Default to FALSE, i.e use the natural direction, on the same scale as the log-likelihood.

Returns: A `ggplot2` object

Method `show()`: User friendly print method

Usage:

```
PLNPCAfamily$show()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNPCAfamily$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

The function `PLNPCA()`, the class `PLNPCAfit()`

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPCAs <- PLNPCA(Abundance ~ 1 + offset(log(Offset)), data = trichoptera, ranks = 1:5)
class(myPCAs)
```

PLNPCAfit

An R6 Class to represent a PLNfit in a PCA framework

Description

The function `PLNPCA()` produces a collection of models which are instances of object with class `PLNPCAfit`. This class comes with a set of methods, some of them being useful for the user: See the documentation for the methods inherited by `PLNfit` and the `plot()` methods for PCA visualization

Super class

```
PLNmodels::PLNfit -> PLNPCAfit
```

Active bindings

`rank` the dimension of the current model

`vcov_model` character: the model used for the residual covariance

`nb_param` number of parameters in the current PLN model

`entropy` entropy of the variational distribution

`latent_pos` a matrix: values of the latent position vector (Z) without covariates effects or offset

`model_par` a list with the matrices associated with the estimated parameters of the pPCA model:
 B (covariates), Sigma (covariance), Omega (precision) and C (loadings)

percent_var the percent of variance explained by each axis
 corr_circle a matrix of correlations to plot the correlation circles
 scores a matrix of scores to plot the individual factor maps (a.k.a. principal components)
 rotation a matrix of rotation of the latent space
 eig description of the eigenvalues, similar to percent_var but for use with external methods
 var a list of data frames with PCA results for the variables: coord (coordinates of the variables), cor (correlation between variables and dimensions), cos2 (Cosine of the variables) and contrib (contributions of the variable to the axes)
 ind a list of data frames with PCA results for the individuals: coord (coordinates of the individuals), cos2 (Cosine of the individuals), contrib (contributions of individuals to an axis inertia) and dist (distance of individuals to the origin).
 call Hacky binding for compatibility with factoextra functions

Methods

Public methods:

- [PLNPCAfit\\$new\(\)](#)
- [PLNPCAfit\\$update\(\)](#)
- [PLNPCAfit\\$optimize\(\)](#)
- [PLNPCAfit\\$optimize_vestep\(\)](#)
- [PLNPCAfit\\$project\(\)](#)
- [PLNPCAfit\\$setVisualization\(\)](#)
- [PLNPCAfit\\$postTreatment\(\)](#)
- [PLNPCAfit\\$plot_individual_map\(\)](#)
- [PLNPCAfit\\$plot_correlation_circle\(\)](#)
- [PLNPCAfit\\$plot_PCA\(\)](#)
- [PLNPCAfit\\$show\(\)](#)
- [PLNPCAfit\\$clone\(\)](#)

Method `new()`: Initialize a `PLNPCAfit` object

Usage:

```
PLNPCAfit$new(rank, responses, covariates, offsets, weights, formula, control)
```

Arguments:

rank rank of the PCA (or equivalently, dimension of the latent space)

responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in `PLNfamily`

covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in `PLNfamily`

offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in `PLNfamily`

weights an optional vector of observation weights to be used in the fitting process.

formula model formula used for fitting, extracted from the formula in the upper-level call

control a list for controlling the optimization. See details.

Method `update()`: Update a `PLNPCAfit` object

Usage:

```
PLNPCAfit$update(
  B = NA,
  Sigma = NA,
  Omega = NA,
  C = NA,
  M = NA,
  S = NA,
  Z = NA,
  A = NA,
  Ji = NA,
  R2 = NA,
  monitoring = NA
)
```

Arguments:

`B` matrix of regression matrix

`Sigma` variance-covariance matrix of the latent variables

`Omega` precision matrix of the latent variables. Inverse of `Sigma`.

`C` matrix of PCA loadings (in the latent space)

`M` matrix of mean vectors for the variational approximation

`S` matrix of variance vectors for the variational approximation

`Z` matrix of latent vectors (includes covariates and offset effects)

`A` matrix of fitted values

`Ji` vector of variational lower bounds of the log-likelihoods (one value per sample)

`R2` approximate R^2 goodness-of-fit criterion

`monitoring` a list with optimization monitoring quantities

Returns: Update the current `PLNPCAfit` object

Method `optimize()`: Call to the C++ optimizer and update of the relevant fields

Usage:

```
PLNPCAfit$optimize(responses, covariates, offsets, weights, config)
```

Arguments:

`responses` the matrix of responses (called `Y` in the model). Will usually be extracted from the corresponding field in `PLNfamily`

`covariates` design matrix (called `X` in the model). Will usually be extracted from the corresponding field in `PLNfamily`

`offsets` offset matrix (called `O` in the model). Will usually be extracted from the corresponding field in `PLNfamily`

`weights` an optional vector of observation weights to be used in the fitting process.

`config` part of the control argument which configures the optimizer

Method `optimize_vestep()`: Result of one call to the VE step of the optimization procedure: optimal variational parameters (`M`, `S`) and corresponding log likelihood values for fixed model parameters (`C`, `B`). Intended to position new data in the latent space for further use with PCA.

Usage:

```
PLNPCAfit$optimize_vestep(
  covariates,
  offsets,
  responses,
  weights = rep(1, self$n),
  control = PLNPCA_param(backend = "nlopt")
)
```

Arguments:

covariates design matrix (called X in the model). Will usually be extracted from the corresponding field in [PLNfamily](#)

offsets offset matrix (called O in the model). Will usually be extracted from the corresponding field in [PLNfamily](#)

responses the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in [PLNfamily](#)

weights an optional vector of observation weights to be used in the fitting process.

control a list for controlling the optimization. See details.

Returns: A list with three components:

- the matrix M of variational means,
- the matrix S2 of variational variances
- the vector `log.lik` of (variational) log-likelihood of each new observation

Method `project()`: Project new samples into the PCA space using one VE step

Usage:

```
PLNPCAfit$project(newdata, control = PLNPCA_param(), envir = parent.frame())
```

Arguments:

newdata A data frame in which to look for variables, offsets and counts with which to predict.

control a list for controlling the optimization. See [PLN\(\)](#) for details.

envir Environment in which the projection is evaluated

Returns:

- the named matrix of scores for the newdata, expressed in the same coordinate system as `self$scores`

Method `setVisualization()`: Compute PCA scores in the latent space and update corresponding fields.

Usage:

```
PLNPCAfit$setVisualization(scale.unit = FALSE)
```

Arguments:

scale.unit Logical. Should PCA scores be rescaled to have unit variance

Method `postTreatment()`: Update R2, fisher, std_err fields and set up visualization

Usage:

```

PLNPCAfit$postTreatment(
  responses,
  covariates,
  offsets,
  weights,
  config,
  nullModel
)

```

Arguments:

`responses` the matrix of responses (called Y in the model). Will usually be extracted from the corresponding field in `PLNfamily`

`covariates` design matrix (called X in the model). Will usually be extracted from the corresponding field in `PLNfamily`

`offsets` offset matrix (called O in the model). Will usually be extracted from the corresponding field in `PLNfamily`

`weights` an optional vector of observation weights to be used in the fitting process.

`config` part of the control argument which configures the optimizer

`nullModel` null model used for approximate R2 computations. Defaults to a GLM model with same design matrix but not latent variable.

Details: The list of parameters `config` controls the post-treatment processing, with the following entries:

- `jackknife` boolean indicating whether jackknife should be performed to evaluate bias and variance of the model parameters. Default is FALSE.
- `bootstrap` integer indicating the number of bootstrap resamples generated to evaluate the variance of the model parameters. Default is 0 (inactivated).
- `variational_var` boolean indicating whether variational Fisher information matrix should be computed to estimate the variance of the model parameters (highly underestimated). Default is FALSE.
- `rsquared` boolean indicating whether approximation of R2 based on deviance should be computed. Default is TRUE
- `trace` integer for verbosity. should be > 1 to see output in post-treatments

Method `plot_individual_map()`: Plot the factorial map of the PCA

Usage:

```

PLNPCAfit$plot_individual_map(
  axes = 1:min(2, self$rank),
  main = "Individual Factor Map",
  plot = TRUE,
  cols = "default"
)

```

Arguments:

`axes` numeric, the axes to use for the plot when `map = "individual"` or `"variable"`. Default is `c(1,min(rank))`

`main` character. A title for the single plot (individual or variable factor map). If NULL (the default), an hopefully appropriate title will be used.

plot logical. Should the plot be displayed or sent back as ggplot object
 cols a character, factor or numeric to define the color associated with the individuals. By default, all individuals receive the default color of the current palette.

Returns: a [ggplot](#) graphic

Method `plot_correlation_circle()`: Plot the correlation circle of a specified axis for a [PLNPCAfit](#) object

Usage:

```
PLNPCAfit$plot_correlation_circle(
  axes = 1:min(2, self$rank),
  main = "Variable Factor Map",
  cols = "default",
  plot = TRUE
)
```

Arguments:

axes numeric, the axes to use for the plot when map = "individual" or "variable". Default is `c(1,min(rank))`

main character. A title for the single plot (individual or variable factor map). If NULL (the default), an hopefully appropriate title will be used.

cols a character, factor or numeric to define the color associated with the variables. By default, all variables receive the default color of the current palette.

plot logical. Should the plot be displayed or sent back as ggplot object

Returns: a [ggplot](#) graphic

Method `plot_PCA()`: Plot a summary of the [PLNPCAfit](#) object

Usage:

```
PLNPCAfit$plot_PCA(
  nb_axes = min(3, self$rank),
  ind_cols = "ind_cols",
  var_cols = "var_cols",
  plot = TRUE
)
```

Arguments:

nb_axes scalar: the number of axes to be considered when map = "both". The default is `min(3,rank)`.

ind_cols a character, factor or numeric to define the color associated with the individuals. By default, all variables receive the default color of the current palette.

var_cols a character, factor or numeric to define the color associated with the variables. By default, all variables receive the default color of the current palette.

plot logical. Should the plot be displayed or sent back as ggplot object

Returns: a [grob](#) object

Method `show()`: User friendly print method

Usage:

```
PLNPCAfit$show()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PLNPCAfit$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

The function [PLNPCA](#), the class [PLNPCAfamily](#)

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPCAs <- PLNPCA(Abundance ~ 1 + offset(log(Offset)), data = trichoptera, ranks = 1:5)
myPCA <- getBestModel(myPCAs)
class(myPCA)
print(myPCA)
```

PLNPCA_param

Control of PLNPCA fit

Description

Helper to define list of parameters to control the PLNPCA fit. All arguments have defaults.

Usage

```
PLNPCA_param(
  backend = "nlopt",
  trace = 1,
  config_optim = list(),
  inception = NULL
)
```

Arguments

<code>backend</code>	optimization back used, either "nlopt" or "torch". Default is "nlopt"
<code>trace</code>	a integer for verbosity.
<code>config_optim</code>	a list for controlling the optimizer (either "nlopt" or "torch" backend). See details
<code>inception</code>	Set up the parameters initialization: by default, the model is initialized with a multivariate linear model applied on log-transformed data, and with the same formula as the one provided by the user. However, the user can provide a PLNfit (typically obtained from a previous fit), which sometimes speeds up the inference.

Details

The list of parameters `config_optim` controls the optimizers. When "nlopt" is chosen the following entries are relevant

- "algorithm" the optimization method used by NLOPT among LD type, e.g. "CCSAQ", "MMA", "LBFGS". See NLOPT documentation for further details. Default is "CCSAQ".
- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6
- "ftol_abs" stop when an optimization step changes the objective function by less than ftol_abs. Default is 0.0 (disabled)
- "xtol_abs" stop when an optimization step changes every parameters by less than xtol_abs. Default is 0.0 (disabled)
- "maxtime" stop when the optimization time (in seconds) exceeds maxtime. Default is -1 (disabled)

When "torch" backend is used, with the following entries are relevant:

- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6

Value

list of parameters configuring the fit.

PLN_param

Control of a PLN fit

Description

Helper to define list of parameters to control the PLN fit. All arguments have defaults.

Usage

```
PLN_param(
  backend = c("nlopt", "torch"),
  trace = 1,
  covariance = c("full", "diagonal", "spherical", "fixed"),
  Omega = NULL,
  config_post = list(),
  config_optim = list(),
  inception = NULL
)
```

Arguments

backend	optimization back used, either "nlopt" or "torch". Default is "nlopt"
trace	a integer for verbosity.
covariance	character setting the model for the covariance matrix. Either "full", "diagonal", "spherical" or "fixed". Default is "full".
Omega	precision matrix of the latent variables. Inverse of Sigma. Must be specified if covariance is "fixed"
config_post	a list for controlling the post-treatments (optional bootstrap, jackknife, R2, etc.). See details
config_optim	a list for controlling the optimizer (either "nlopt" or "torch" backend). See details
inception	Set up the parameters initialization: by default, the model is initialized with a multivariate linear model applied on log-transformed data, and with the same formula as the one provided by the user. However, the user can provide a PLNfit (typically obtained from a previous fit), which sometimes speeds up the inference.

Details

The list of parameters `config_optim` controls the optimizers. When "nlopt" is chosen the following entries are relevant

- "algorithm" the optimization method used by NLOPT among LD type, e.g. "CCSAQ", "MMA", "LBFGS". See NLOPT documentation for further details. Default is "CCSAQ".
- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6
- "ftol_abs" stop when an optimization step changes the objective function by less than ftol_abs. Default is 0.0 (disabled)
- "xtol_abs" stop when an optimization step changes every parameters by less than xtol_abs. Default is 0.0 (disabled)
- "maxtime" stop when the optimization time (in seconds) exceeds maxtime. Default is -1 (disabled)

When "torch" backend is used, with the following entries are relevant:

- "maxeval" stop when the number of iteration exceeds maxeval. Default is 10000
- "ftol_rel" stop when an optimization step changes the objective function by less than ftol multiplied by the absolute value of the parameter. Default is 1e-8
- "xtol_rel" stop when an optimization step changes every parameters by less than xtol multiplied by the absolute value of the parameter. Default is 1e-6

The list of parameters `config_post` controls the post-treatment processing, with the following entries:

- jackknife boolean indicating whether jackknife should be performed to evaluate bias and variance of the model parameters. Default is FALSE.
- bootstrap integer indicating the number of bootstrap resamples generated to evaluate the variance of the model parameters. Default is 0 (inactivated).
- variational_var boolean indicating whether variational Fisher information matrix should be computed to estimate the variance of the model parameters (highly underestimated). Default is FALSE.
- rsquared boolean indicating whether approximation of R2 based on deviance should be computed. Default is TRUE

Value

list of parameters configuring the fit.

plot.PLNfamily	<i>Display the criteria associated with a collection of PLN fits (a PLNfamily)</i>
----------------	--

Description

Display the criteria associated with a collection of PLN fits (a PLNfamily)

Usage

```
## S3 method for class 'PLNfamily'
plot(x, criteria = c("loglik", "BIC", "ICL"), reverse = FALSE, ...)
```

Arguments

x	an R6 object with class PLNfamily
criteria	vector of characters. The criteria to plot in c("loglik", "BIC", "ICL"). Default is c("loglik", "BIC", "ICL").
reverse	A logical indicating whether to plot the value of the criteria in the "natural" direction (loglik - 0.5 penalty) or in the "reverse" direction (-2 loglik + penalty). Default to FALSE, i.e use the natural direction, on the same scale as the log-likelihood.
...	additional parameters for S3 compatibility. Not used

Details

The BIC and ICL criteria have the form 'loglik - 1/2 * penalty' so that they are on the same scale as the model log-likelihood. You can change this direction and use the alternate form '-2*loglik + penalty', as some authors do, by setting reverse = TRUE.

Value

Produces a plot representing the evolution of the criteria of the different models considered, highlighting the best model in terms of BIC and ICL (see details).

See Also

[plot.PLNPCAfamily\(\)](#) and [plot.PLNnetworkfamily\(\)](#)

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPCAs <- PLNPCA(Abundance ~ 1 + offset(log(Offset)), data = trichoptera, ranks = 1:5)
## Not run:
plot(myPCAs)

## End(Not run)
```

plot.PLNLDAfit	<i>LDA visualization (individual and/or variable factor map(s)) for a PLNPCAfit object</i>
----------------	--

Description

LDA visualization (individual and/or variable factor map(s)) for a [PLNPCAfit](#) object

Usage

```
## S3 method for class 'PLNLDAfit'
plot(
  x,
  map = c("both", "individual", "variable"),
  nb_axes = min(3, x$rank),
  axes = seq.int(min(2, x$rank)),
  var_cols = "var_colors",
  plot = TRUE,
  main = NULL,
  ...
)
```

Arguments

x	an R6 object with class <code>PLNPCAfit</code>
map	the type of output for the PCA visualization: either "individual", "variable" or "both". Default is "both".
nb_axes	scalar: the number of axes to be considered when map = "both". The default is min(3,rank).

axes	numeric, the axes to use for the plot when map = "individual" or "variable". Default is c(1,min(rank))
var_cols	a character or factor to define the color associated with the variables. By default, all variables receive the default color of the current palette.
plot	logical. Should the plot be displayed or sent back as <code>ggplot2</code> object
main	character. A title for the single plot (individual or variable factor map). If NULL (the default), an hopefully appropriate title will be used.
...	Not used (S3 compatibility).

Value

displays an individual and/or variable factor maps for the corresponding axes, and/or sends back a `ggplot2` or `gtable` object

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLNLDA <- PLNLDA(Abundance ~ 1, grouping = Group, data = trichoptera)
## Not run:
plot(myPLNLDA, map = "individual", nb_axes = 2)

## End(Not run)
```

plot.PLNmixturefamily *Display the criteria associated with a collection of PLNmixture fits (a PLNmixturefamily)*

Description

Display the criteria associated with a collection of PLNmixture fits (a PLNmixturefamily)

Usage

```
## S3 method for class 'PLNmixturefamily'
plot(
  x,
  type = c("criteria", "diagnostic"),
  criteria = c("loglik", "BIC", "ICL"),
  reverse = FALSE,
  ...
)
```

Arguments

x	an R6 object with class <code>PLNmixturefamily</code>
type	a character, either "criteria" or "diagnostic" for the type of plot.
criteria	vector of characters. The criteria to plot in <code>c("loglik", "BIC", "ICL")</code> . Default is <code>c("loglik", "BIC", "ICL")</code> .
reverse	A logical indicating whether to plot the value of the criteria in the "natural" direction (<code>loglik - 0.5 penalty</code>) or in the "reverse" direction (<code>-2 loglik + penalty</code>). Default to FALSE, i.e use the natural direction, on the same scale as the log-likelihood.
...	additional parameters for S3 compatibility. Not used

Details

The BIC and ICL criteria have the form 'loglik - 1/2 * penalty' so that they are on the same scale as the model log-likelihood. You can change this direction and use the alternate form '-2*loglik + penalty', as some authors do, by setting `reverse = TRUE`.

Value

Produces either a diagnostic plot (with `type = 'diagnostic'`) or the evolution of the criteria of the different models considered (with `type = 'criteria'`, the default).

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myMixtures <- PLNmixture(Abundance ~ 1 + offset(log(Offset)),
  data = trichoptera, control = PLNmixture_param(smoothing = "none"))
plot(myMixtures, reverse = TRUE)
```

`plot.PLNmixturefit` *Mixture visualization of a `PLNmixturefit` object*

Description

Represent the result of the clustering either by coloring the individual in a two-dimension PCA factor map, or by representing the expected matrix of count reorder according to the clustering.

Usage

```
## S3 method for class 'PLNmixturefit'
plot(x, type = c("pca", "matrix"), main = NULL, plot = TRUE, ...)
```

Arguments

x	an R6 object with class <code>PLNmixturefit</code>
type	character for the type of plot, either "pca", for or "matrix". Default is "pca".
main	character. A title for the plot. If NULL (the default), an hopefully appropriate title will be used.
plot	logical. Should the plot be displayed or sent back as <code>ggplot</code> object
...	Not used (S3 compatibility).

Value

a `ggplot` graphic

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLNmixture(Abundance ~ 1 + offset(log(Offset)),
  data = trichoptera, control = PLNmixture_param(smoothing = "none")) %>% getBestModel()
## Not run:
plot(myPLN, "pca")
plot(myPLN, "matrix")

## End(Not run)
```

`plot.PLNnetworkfamily` *Display various outputs (goodness-of-fit criteria, robustness, diagnostic) associated with a collection of PLNnetwork fits (a `PLNnetworkfamily`)*

Description

Display various outputs (goodness-of-fit criteria, robustness, diagnostic) associated with a collection of PLNnetwork fits (a `PLNnetworkfamily`)

Usage

```
## S3 method for class 'PLNnetworkfamily'
plot(
  x,
  type = c("criteria", "stability", "diagnostic"),
  criteria = c("loglik", "pen_loglik", "BIC", "EBIC"),
  reverse = FALSE,
  log.x = TRUE,
  stability = 0.9,
  ...
)
```

Arguments

x	an R6 object with class PLNnetworkfamily
type	a character, either "criteria", "stability" or "diagnostic" for the type of plot.
criteria	vector of characters. The criteria to plot in <code>c("loglik", "BIC", "ICL", "R_squared", "EBIC", "pen_loglik")</code> . Default is <code>c("loglik", "pen_loglik", "BIC", "EBIC")</code> . Only relevant when <code>type = "criteria"</code> .
reverse	A logical indicating whether to plot the value of the criteria in the "natural" direction (<code>loglik - 0.5 penalty</code>) or in the "reverse" direction (<code>-2 loglik + penalty</code>). Default to FALSE, i.e use the natural direction, on the same scale as the log-likelihood.
log.x	logical: should the x-axis be represented in log-scale? Default is TRUE.
stability	scalar: the targeted level of stability in stability plot. Default is .9.
...	additional parameters for S3 compatibility. Not used

Details

The BIC and ICL criteria have the form `'loglik - 1/2 * penalty'` so that they are on the same scale as the model log-likelihood. You can change this direction and use the alternate form `'-2*loglik + penalty'`, as some authors do, by setting `reverse = TRUE`.

Value

Produces either a diagnostic plot (with `type = 'diagnostic'`), a stability plot (with `type = 'stability'`) or the evolution of the criteria of the different models considered (with `type = 'criteria'`, the default).

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
fits <- PLNnetwork(Abundance ~ 1, data = trichoptera)
## Not run:
plot(fits)

## End(Not run)
```

`plot.PLNnetworkfit` *Extract and plot the network (partial correlation, support or inverse covariance) from a [PLNnetworkfit](#) object*

Description

Extract and plot the network (partial correlation, support or inverse covariance) from a [PLNnetworkfit](#) object

Usage

```
## S3 method for class 'PLNnetworkfit'
plot(
  x,
  type = c("partial_cor", "support"),
  output = c("igraph", "corrplot"),
  edge.color = c("#F8766D", "#00BFC4"),
  remove.isolated = FALSE,
  node.labels = NULL,
  layout = layout_in_circle,
  plot = TRUE,
  ...
)
```

Arguments

x	an R6 object with class PLNnetworkfit
type	character. Value of the weight of the edges in the network, either "partial_cor" (partial correlation) or "support" (binary). Default is "partial_cor".
output	the type of output used: either 'igraph' or 'corrplot'. Default is 'igraph'.
edge.color	Length 2 color vector. Color for positive/negative edges. Default is c("#F8766D", "#00BFC4"). Only relevant for igraph output.
remove.isolated	if TRUE, isolated node are remove before plotting. Only relevant for igraph output.
node.labels	vector of character. The labels of the nodes. The default will use the column names of the response matrix.
layout	an optional igraph layout. Only relevant for igraph output.
plot	logical. Should the final network be displayed or only sent back to the user. Default is TRUE.
...	Not used (S3 compatibility).

Value

Send back an invisible object (igraph or Matrix, depending on the output chosen) and optionally displays a graph (via igraph or corrplot for large ones)

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
fits <- PLNnetwork(Abundance ~ 1, data = trichoptera)
myNet <- getBestModel(fits)
## Not run:
plot(myNet)

## End(Not run)
```

plot.PLNPCAfamily	<i>Display the criteria associated with a collection of PLNPCA fits (a PLNPCAfamily)</i>
-------------------	--

Description

Display the criteria associated with a collection of PLNPCA fits (a PLNPCAfamily)

Usage

```
## S3 method for class 'PLNPCAfamily'
plot(x, criteria = c("loglik", "BIC", "ICL"), reverse = FALSE, ...)
```

Arguments

x	an R6 object with class PLNPCAfamily
criteria	vector of characters. The criteria to plot in <code>c("loglik", "BIC", "ICL")</code> . Default is <code>c("loglik", "BIC", "ICL")</code> .
reverse	A logical indicating whether to plot the value of the criteria in the "natural" direction (<code>loglik - 0.5 penalty</code>) or in the "reverse" direction (<code>-2 loglik + penalty</code>). Default to <code>FALSE</code> , i.e use the natural direction, on the same scale as the log-likelihood.
...	additional parameters for S3 compatibility. Not used

Details

The BIC and ICL criteria have the form `'loglik - 1/2 * penalty'` so that they are on the same scale as the model log-likelihood. You can change this direction and use the alternate form `'-2*loglik + penalty'`, as some authors do, by setting `reverse = TRUE`.

Value

Produces a plot representing the evolution of the criteria of the different models considered, highlighting the best model in terms of BIC and ICL (see details).

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPCAs <- PLNPCA(Abundance ~ 1 + offset(log(Offset)), data = trichoptera, ranks = 1:5)
## Not run:
plot(myPCAs)

## End(Not run)
```

plot.PLNCAfit	<i>PCA visualization (individual and/or variable factor map(s)) for a PLNCAfit object</i>
---------------	---

Description

PCA visualization (individual and/or variable factor map(s)) for a [PLNCAfit](#) object

Usage

```
## S3 method for class 'PLNCAfit'
plot(
  x,
  map = c("both", "individual", "variable"),
  nb_axes = min(3, x$rank),
  axes = seq.int(min(2, x$rank)),
  ind_cols = "ind_colors",
  var_cols = "var_colors",
  plot = TRUE,
  main = NULL,
  ...
)
```

Arguments

x	an R6 object with class <code>PLNCAfit</code>
map	the type of output for the PCA visualization: either "individual", "variable" or "both". Default is "both".
nb_axes	scalar: the number of axes to be considered when map = "both". The default is <code>min(3, rank)</code> .
axes	numeric, the axes to use for the plot when map = "individual" or map = "variable". Default is <code>c(1, min(rank))</code>
ind_cols	a character, factor or numeric to define the color associated with the individuals. By default, all variables receive the default color of the current palette.
var_cols	a character, factor or numeric to define the color associated with the variables. By default, all variables receive the default color of the current palette.
plot	logical. Should the plot be displayed or sent back as ggplot object
main	character. A title for the single plot (individual or variable factor map). If <code>NULL</code> (the default), an hopefully appropriate title will be used.
...	Not used (S3 compatibility).

Value

displays an individual and/or variable factor maps for the corresponding axes, and/or sends back a [ggplot](#) or `gtable` object

Examples

```

data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPCAs <- PLNPCA(Abundance ~ 1 + offset(log(Offset)), data = trichoptera, ranks = 1:5)
myPCA <- getBestModel(myPCAs)
## Not run:
plot(myPCA, map = "individual", nb_axes=2, ind_cols = trichoptera$Group)
plot(myPCA, map = "variable", nb_axes=2)
plot(myPCA, map = "both", nb_axes=2, ind_cols = trichoptera$Group)

## End(Not run)

```

predict.PLNfit	<i>Predict counts of a new sample</i>
----------------	---------------------------------------

Description

Predict counts of a new sample

Usage

```

## S3 method for class 'PLNfit'
predict(object, newdata, type = c("link", "response"), ...)

```

Arguments

object	an R6 object with class <code>PLNfit</code>
newdata	A data frame in which to look for variables and offsets with which to predict
type	The type of prediction required. The default is on the scale of the linear predictors (i.e. log average count)
...	additional parameters for S3 compatibility. Not used

Value

A matrix of predicted log-counts (if type = "link") or predicted counts (if type = "response").

predict.PLNLDAfit *Predict group of new samples*

Description

Predict group of new samples

Usage

```
## S3 method for class 'PLNLDAfit'
predict(
  object,
  newdata,
  type = c("posterior", "response", "scores"),
  scale = c("log", "prob"),
  prior = NULL,
  control = PLN_param(backend = "nlopt"),
  ...
)
```

Arguments

object	an R6 object with class PLNLDAfit
newdata	A data frame in which to look for variables, offsets and counts with which to predict.
type	The type of prediction required. The default are posterior probabilities for each group (in either unnormalized log-scale or natural probabilities, see "scale" for details), "response" is the group with maximal posterior probability and "scores" is the average score along each separation axis in the latent space, with weights equal to the posterior probabilities.
scale	The scale used for the posterior probability. Either log-scale ("log", default) or natural probabilities summing up to 1 ("prob").
prior	User-specified prior group probabilities in the new data. If NULL (default), prior probabilities are computed from the learning set.
control	a list for controlling the optimization. See PLN() for details.
...	additional parameters for S3 compatibility. Not used

Value

A matrix of posterior probabilities for each group (if type = "posterior"), a matrix of (average) scores in the latent space (if type = "scores") or a vector of predicted groups (if type = "response").

Examples

```

data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myLDA <- PLNLDA(Abundance ~ 0 + offset(log(Offset)),
                grouping = Group,
                data = trichoptera)

## Not run:
post_probs <- predict(myLDA, newdata = trichoptera, type = "posterior", scale = "prob")
head(round(post_probs, digits = 3))
predicted_group <- predict(myLDA, newdata = trichoptera, type = "response")
table(predicted_group, trichoptera$Group, dnn = c("predicted", "true"))

## End(Not run)

```

predict.PLNmixturefit *Prediction for a [PLNmixturefit](#) object*

Description

Predict either posterior probabilities for each group or latent positions based on new samples

Usage

```

## S3 method for class 'PLNmixturefit'
predict(
  object,
  newdata,
  type = c("posterior", "response", "position"),
  prior = matrix(rep(1/object$k, object$k), nrow(newdata), object$k, byrow = TRUE),
  control = PLNmixture_param(),
  ...
)

```

Arguments

object	an R6 object with class PLNmixturefit
newdata	A data frame in which to look for variables, offsets and counts with which to predict.
type	The type of prediction required. The default posterior are posterior probabilities for each group , response is the group with maximal posterior probability and latent is the averaged latent in the latent space, with weights equal to the posterior probabilities.
prior	User-specified prior group probabilities in the new data. The default uses a uniform prior.
control	a list-like structure for controlling the fit. See PLNmixture_param() for details.
...	additional parameters for S3 compatibility. Not used

Value

A matrix of posterior probabilities for each group (if type = "posterior"), a matrix of (average) position in the latent space (if type = "position") or a vector of predicted groups (if type = "response").

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLNmixture(Abundance ~ 1 + offset(log(Offset)),
  data = trichoptera, control = PLNmixture_param(smoothing = "none")) %>% getBestModel()
predict(myPLN, trichoptera, "posterior")
predict(myPLN, trichoptera, "position")
predict(myPLN, trichoptera, "response")
```

predict_cond

Predict counts conditionally

Description

Predict counts of a new sample conditionally on a (set of) observed variables

Usage

```
predict_cond(
  object,
  newdata,
  cond_responses,
  type = c("link", "response"),
  var_par = FALSE
)

## S3 method for class 'PLNfit'
predict_cond(
  object,
  newdata,
  cond_responses,
  type = c("link", "response"),
  var_par = FALSE
)
```

Arguments

object	an R6 object with class <code>PLNfit</code>
newdata	A data frame in which to look for variables and offsets with which to predict
cond_responses	a data frame containing the counts of the observed variables (matching the names provided as data in the PLN function)

type	The type of prediction required. The default is on the scale of the linear predictors (i.e. log average count)
var_par	Boolean. Should new estimations of the variational parameters of mean and variance be sent back, as attributes of the matrix of predictions. Default to FALSE.

Value

A list containing:

pred	A matrix of predicted log-counts (if type = "link") or predicted counts (if type = "response")
M	A matrix containing $E(Z_{\text{uncond}} Y_c)$ for each given site.
S	A matrix containing $\text{Var}(Z_{\text{uncond}} Y_c)$ for each given site (sites are the third dimension of the array)

Methods (by class)

- `predict_cond(PLNfit)`: Predict counts of a new sample conditionally on a (set of) observed variables for a `PLNfit`

Examples

```
data(trichoptera)
trichoptera_prep <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ Temperature + Wind, trichoptera_prep)
#Condition on the set of the first two species in the dataset (Hym, Hys) at the ten first sites
Yc <- trichoptera$Abundance[1:10, c(1, 2), drop=FALSE]
newX <- cbind(1, trichoptera$Covariate[1:10, c("Temperature", "Wind")])
pred <- predict_cond(myPLN, newX, Yc, type = "response")
```

```
prepare_data
```

Prepare data for use in PLN models

Description

Prepare data in proper format for use in PLN model and its variants. The function (i) merges a count table and a covariate data frame in the most comprehensive way and (ii) computes offsets from the count table using one of several normalization schemes (TSS, CSS, RLE, GMPR, Wrench, etc). The function fails with informative messages when the heuristics used for sample matching fail.

Usage

```
prepare_data(counts, covariates, offset = "TSS", ...)
```

Arguments

counts	Required. An abundance count table, preferably with dimensions names and species as columns.
covariates	Required. A covariates data frame, preferably with row names.
offset	Optional. Normalization scheme used to compute scaling factors used as offset during PLN inference. Available schemes are "TSS" (Total Sum Scaling, default), "CSS" (Cumulative Sum Scaling, used in metagenomeSeq), "RLE" (Relative Log Expression, used in DESeq2), "GMPR" (Geometric Mean of Pairwise Ratio, introduced in Chen et al., 2018), Wrench (introduced in Kumar et al., 2018) or "none". Alternatively the user can supply its own vector or matrix of offsets (see note for specification of the user-supplied offsets).
...	Additional parameters passed on to <code>compute_offset()</code>

Value

A data.frame suited for use in `PLN()` and its variants with two special components: an abundance count matrix (in component "Abundance") and an offset vector/matrix (in component "Offset", only if offset is not set to "none")

Note

User supplied offsets should be either vectors/column-matrices or have the same number of column as the original count matrix and either (i) dimension names or (ii) the same dimensions as the count matrix. Samples are trimmed in exactly the same way to remove empty samples.

References

- Chen, L., Reeve, J., Zhang, L., Huang, S., Wang, X. and Chen, J. (2018) GMPR: A robust normalization method for zero-inflated count data with application to microbiome sequencing data. *PeerJ*, 6, e4600 doi:[10.7717/peerj.4600](https://doi.org/10.7717/peerj.4600)
- Paulson, J. N., Colin Stine, O., Bravo, H. C. and Pop, M. (2013) Differential abundance analysis for microbial marker-gene surveys. *Nature Methods*, 10, 1200-1202 doi:[10.1038/nmeth.2658](https://doi.org/10.1038/nmeth.2658)
- Anders, S. and Huber, W. (2010) Differential expression analysis for sequence count data. *Genome Biology*, 11, R106 doi:[10.1186/gb20101110r106](https://doi.org/10.1186/gb20101110r106)
- Kumar, M., Slud, E., Okrah, K. et al. (2018) Analysis and correction of compositional bias in sparse sequencing count data. *BMC Genomics* 19, 799 doi:[10.1186/s12864-018-5160-5](https://doi.org/10.1186/s12864-018-5160-5)

See Also

`compute_offset()` for details on the different normalization schemes

Examples

```
data(trichoptera)
proper_data <- prepare_data(
  counts      = trichoptera$Abundance,
  covariates  = trichoptera$Covariate,
```

```

  offset      = "TSS"
)
proper_data$Abundance
proper_data$Offset

```

rPLN

*PLN RNG***Description**

Random generation for the PLN model with latent mean equal to mu, latent covariance matrix equal to Sigma and average depths (sum of counts in a sample) equal to depths

Usage

```

rPLN(
  n = 10,
  mu = rep(0, ncol(Sigma)),
  Sigma = diag(1, 5, 5),
  depths = rep(10000, n)
)

```

Arguments

n	the sample size
mu	vectors of means of the latent variable
Sigma	covariance matrix of the latent variable
depths	Numeric vector of target depths. The first is recycled if there are not n values

Details

The default value for mu and Sigma assume equal abundances and no correlation between the different species.

Value

a n * p count matrix, with row-sums close to depths, with an attribute "offsets" corresponding to the true generated offsets (in log-scale).

Examples

```

## 10 samples of 5 species with equal abundances, no covariance and target depths of 10,000
rPLN()
## 2 samples of 10 highly correlated species with target depths 1,000 and 100,000
## very different abundances
mu <- rep(c(1, -1), each = 5)
Sigma <- matrix(0.8, 10, 10); diag(Sigma) <- 1
rPLN(n=2, mu = mu, Sigma = Sigma, depths = c(1e3, 1e5))

```

sigma.PLNfit	<i>Extract variance-covariance of residuals 'Sigma'</i>
--------------	---

Description

Extract the variance-covariance matrix of the residuals, usually noted

$$\Sigma$$

in PLN models. This captures the correlation between the species in the latent space.

Usage

```
## S3 method for class 'PLNfit'
sigma(object, ...)
```

Arguments

object	an R6 object with class PLNfit
...	additional parameters for S3 compatibility. Not used

Value

A semi definite positive matrix of size p, assuming there are p species in the model.

See Also

[coef.PLNfit\(\)](#), [standard_error.PLNfit\(\)](#) and [vcov.PLNfit\(\)](#) for other ways to access

$$\Sigma$$

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ 1 + offset(log(Offset)), data = trichoptera)
sigma(myPLN) ## Sigma
```

sigma.PLNmixturefit *Extract variance-covariance of residuals 'Sigma'*

Description

Extract the variance-covariance matrix of the residuals, usually noted

$$\Sigma$$

in PLN models. This captures the correlation between the species in the latent space. or PLNmixture, it is a weighted mean of the variance-covariance matrices of each component.

Usage

```
## S3 method for class 'PLNmixturefit'
sigma(object, ...)
```

Arguments

object an R6 object with class `PLNmixturefit`
 ... additional parameters for S3 compatibility. Not used

Value

A semi definite positive matrix of size p, assuming there are p species in the model.

See Also

`coef.PLNmixturefit()` for other ways to access

$$\Sigma$$

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLNmixture(Abundance ~ 1 + offset(log(Offset)),
  data = trichoptera, control = PLNmixture_param(smoothing = "none")) %>% getBestModel()
sigma(myPLN) ## Sigma
```

stability_selection *Compute the stability path by stability selection*

Description

This function computes the StARS stability criteria over a path of penalties. If a path has already been computed, the function stops with a message unless `force = TRUE` has been specified.

Usage

```
stability_selection(
  Robject,
  subsamples = NULL,
  control = PLNnetwork_param(),
  force = FALSE
)
```

Arguments

Object	an object with class <code>PLNnetworkfamily</code> , i.e. an output from <code>PLNnetwork()</code>
subsamples	a list of vectors describing the subsamples. The number of vectors (or list length) determines the number of subsamples used in the stability selection. Automatically set to 20 subsamples with size $10 \times \sqrt{n}$ if $n \geq 144$ and $0.8 \times n$ otherwise following Liu et al. (2010) recommendations.
control	a list controlling the main optimization process in each call to <code>PLNnetwork</code> . See <code>PLNnetwork()</code> for details.
force	force computation of the stability path, even if a previous one has been detected.

Value

the list of subsamples. The estimated probabilities of selection of the edges are stored in the fields `stability_path` of the initial `Robject` with class `PLNnetworkfamily`

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
fits <- PLNnetwork(Abundance ~ 1, data = trichoptera)
## Not run:
n <- nrow(trichoptera)
subs <- replicate(10, sample.int(n, size = n/2), simplify = FALSE)
stability_selection(fits, subsamples = subs)

## End(Not run)
```

`standard_error.PLNPCAfit`*Component-wise standard errors of B*

Description

Extracts univariate standard errors for the estimated coefficient of B. Standard errors are computed from the (approximate) Fisher information matrix.

Usage

```
## S3 method for class 'PLNPCAfit'
standard_error(
  object,
  type = c("variational", "jackknife", "sandwich"),
  parameter = c("B", "Omega")
)

standard_error(
  object,
  type = c("variational", "jackknife", "sandwich"),
  parameter = c("B", "Omega")
)

## S3 method for class 'PLNfit'
standard_error(
  object,
  type = c("variational", "jackknife", "bootstrap", "sandwich"),
  parameter = c("B", "Omega")
)

## S3 method for class 'PLNfit_fixedcov'
standard_error(
  object,
  type = c("variational", "jackknife", "bootstrap", "sandwich"),
  parameter = c("B", "Omega")
)

## S3 method for class 'PLNmixturefit'
standard_error(
  object,
  type = c("variational", "jackknife", "sandwich"),
  parameter = c("B", "Omega")
)

## S3 method for class 'PLNnetworkfit'
standard_error(
```

```

object,
type = c("variational", "jackknife", "sandwich"),
parameter = c("B", "Omega")
)

```

Arguments

object	an R6 object with class <code>PLNfit</code>
type	string describing the type of variance approximation: "variational", "jackknife", "sandwich" (only for fixed covariance). Default is "variational".
parameter	string describing the target parameter: either B (regression coefficients) or Omega (inverse residual covariance)

Value

A $p * d$ positive matrix (same size as B) with standard errors for the coefficients of B

Methods (by class)

- `standard_error(PLNPCAfit)`: Component-wise standard errors of B in `PLNPCAfit` (not implemented yet)
- `standard_error(PLNfit)`: Component-wise standard errors of B in `PLNfit`
- `standard_error(PLNfit_fixedcov)`: Component-wise standard errors of B in `PLNfit_fixedcov`
- `standard_error(PLNmixturefit)`: Component-wise standard errors of B in `PLNmixturefit` (not implemented yet)
- `standard_error(PLNnetworkfit)`: Component-wise standard errors of B in `PLNnetworkfit` (not implemented yet)

See Also

`vcov.PLNfit()` for the complete variance covariance estimation of the coefficient

Examples

```

data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ 1 + offset(log(Offset)), data = trichoptera,
             control = PLN_param(config_post = list(variational_var = TRUE)))
standard_error(myPLN)

```

trichoptera

Trichoptera data set

Description

Data gathered between 1959 and 1960 during 49 insect trapping nights. For each trapping night, the abundance of 17 Trichoptera species is recorded as well as 6 meteorological variables which may influence the abundance of each species. Finally, the observations (that is to say, the trapping nights), have been classified into 12 groups corresponding to contiguous nights between summer 1959 and summer 1960.

Usage

trichoptera

Format

A list with 2 two data frames:

Abundance a 49 x 17 matrix of abundancies/counts (49 trapping nights and 17 trichoptera species)

Covariate a 49 x 7 data frame of covariates:

Temperature Evening Temperature in Celsius

Wind Wind in m/s

Pressure Pressure in mm Hg

Humidity relative to evening humidity in percent

Cloudiness proportion of sky coverage at 9pm

Precipitation Nighttime precipitation in mm

Group a factor of 12 levels for the definition of the consecutive night groups

In order to prepare the data for using formula in multivariate analysis (multiple outputs and inputs), use `prepare_data()`. We only kept a subset of the original meteorological covariates for illustration purposes.

Source

Data from P. Usseglio-Polatera.

References

Usseglio-Polatera, P. and Auda, Y. (1987) Influence des facteurs météorologiques sur les résultats de piégeage lumineux. *Annales de Limnologie*, 23, 65–79. (code des espèces p. 76) See a data description at <http://pbil.univ-lyon1.fr/R/pdf/ppls034.pdf> (in French)

See Also

`prepare_data()`

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
```

vcov.PLNfit	<i>Calculate Variance-Covariance Matrix for a fitted PLN() model object</i>
-------------	---

Description

Returns the variance-covariance matrix of the main parameters of a fitted [PLN\(\)](#) model object. The main parameters of the model correspond to

$$B$$

, as returned by [coef.PLNfit\(\)](#). The function can also be used to return the variance-covariance matrix of the residuals. The latter matrix can also be accessed via [sigma.PLNfit\(\)](#)

Usage

```
## S3 method for class 'PLNfit'
vcov(object, type = c("main", "covariance"), ...)
```

Arguments

object	an R6 object with class PLNfit	
type	type of parameter that should be extracted. Either "main" (default) for	B
	or "covariance" for	Σ
...	additional parameters for S3 compatibility. Not used	

Value

A matrix of variance/covariance extracted from the [PLNfit](#) model. If type="main" and B is a matrix of size $d * p$, the result is a block-diagonal matrix with p (number of species) blocks of size d (number of covariates). if type="main", it is a symmetric matrix of size p .

See Also

[sigma.PLNfit\(\)](#), [coef.PLNfit\(\)](#), [standard_error.PLNfit\(\)](#)

Examples

```
data(trichoptera)
trichoptera <- prepare_data(trichoptera$Abundance, trichoptera$Covariate)
myPLN <- PLN(Abundance ~ 1 + offset(log(Offset)), data = trichoptera)
vcov(myPLN, type = "covariance") ## Sigma
```

Index

- * **datasets**
 - barents, [3](#)
 - mollusk, [13](#)
 - oaks, [14](#)
 - trichoptera, [93](#)

- barents, [3](#)

- coef(), [19](#)
- coef.PLNfit, [4](#)
- coef.PLNfit(), [88](#), [94](#)
- coef.PLNLDAfit, [5](#)
- coef.PLNmixturefit, [6](#)
- coef.PLNmixturefit(), [89](#)
- coefficient_path, [7](#)
- compute_offset, [7](#)
- compute_offset(), [86](#)

- extract_probs, [9](#)

- factoextra::fviz(), [62](#)
- fitted.PLNfit, [10](#)
- fitted.PLNmixturefit, [11](#)

- getBestModel
 - (getBestModel.PLNPCAfamily), [11](#)
- getBestModel(), [40](#), [51](#), [61](#)
- getBestModel.PLNPCAfamily, [11](#)
- getModel(getModel.PLNPCAfamily), [12](#)
- getModel(), [18](#), [40](#), [51](#), [61](#)
- getModel.PLNPCAfamily, [12](#)
- ggplot, [34](#), [35](#), [42](#), [45](#), [53](#), [54](#), [68](#), [76](#), [80](#)
- ggplot2, [18](#), [42](#), [63](#), [74](#)
- grob, [35](#), [68](#)

- mollusk, [13](#)

- oaks, [14](#)

- PLN, [16](#)
- PLN(), [4](#), [6](#), [10](#), [19](#), [35](#), [49](#), [66](#), [82](#), [86](#), [94](#)

- PLN_param, [70](#)
- PLN_param(), [16](#), [20](#), [22](#), [30](#)
- PLNfamily, [17](#), [17](#), [18](#), [64–67](#), [72](#)
- PLNfit, [4](#), [10](#), [16–19](#), [19](#), [20](#), [21](#), [24](#), [25](#), [27](#), [29](#), [36](#), [54](#), [63](#), [81](#), [84](#), [85](#), [88](#), [92](#), [94](#)
- PLNfit(), [19](#), [24](#), [32](#), [36](#)
- PLNfit_diagonal, [24](#)
- PLNfit_fixedcov, [26](#), [92](#)
- PLNfit_spherical, [29](#)
- PLNLDA, [30](#), [36](#)
- PLNLDA(), [5](#), [19](#), [24](#), [32](#), [36](#), [49](#)
- PLNLDA_param, [37](#)
- PLNLDAfit, [24](#), [31](#), [32](#), [32](#), [34–36](#), [68](#), [82](#)
- PLNLDAfit(), [31](#)
- PLNLDAfit_diagonal, [36](#)
- PLNLDAfit_spherical (PLNfit_diagonal), [24](#)
- PLNmixture, [39](#), [42](#), [43](#), [46](#)
- PLNmixture(), [11](#), [19](#), [40](#), [49](#)
- PLNmixture_param, [47](#)
- PLNmixture_param(), [39](#), [40](#), [45](#), [83](#)
- PLNmixturefamily, [12](#), [13](#), [40](#), [40](#), [46](#), [75](#)
- PLNmixturefit, [6](#), [11](#), [40](#), [42](#), [43](#), [44](#), [75](#), [76](#), [83](#), [89](#), [92](#)
- PLNmodels, [49](#)
- PLNmodels::PLNfamily, [40](#), [51](#), [61](#)
- PLNmodels::PLNfit, [24–26](#), [29](#), [32](#), [36](#), [54](#), [63](#)
- PLNmodels::PLNfit_fixedcov, [54](#)
- PLNmodels::PLNLDAfit, [25](#), [36](#)
- PLNnetwork, [50](#)
- PLNnetwork(), [7](#), [9](#), [19](#), [49](#), [51](#), [52](#), [54](#), [58](#), [90](#)
- PLNnetwork_param, [58](#)
- PLNnetwork_param(), [50](#)
- PLNnetworkfamily, [7](#), [9](#), [12](#), [13](#), [17](#), [50](#), [51](#), [52](#), [53](#), [58](#), [76](#), [77](#), [90](#)
- PLNnetworkfit, [12](#), [13](#), [50](#), [52](#), [54](#), [54](#), [55](#), [56](#), [77](#), [78](#), [92](#)
- PLNPCA, [60](#), [69](#)
- PLNPCA(), [19](#), [49](#), [61](#), [63](#)

PLNPCA_param, 69
PLNPCA_param(), 60
PLNPCAfamily, 12, 13, 17, 60, 61, 69, 79
PLNPCAfit, 12, 13, 60, 62, 63, 63, 64, 65, 68,
73, 80, 92
PLNPCAfit(), 63
plot(), 24, 32, 36, 40, 51, 54, 61, 63
plot.PLNfamily, 72
plot.PLNLDAfit, 73
plot.PLNmixturefamily, 74
plot.PLNmixturefit, 75
plot.PLNnetworkfamily, 76
plot.PLNnetworkfamily(), 73
plot.PLNnetworkfit, 77
plot.PLNPCAfamily, 79
plot.PLNPCAfamily(), 73
plot.PLNPCAfit, 80
predict(), 19, 24, 32, 36
predict.PLNfit, 81
predict.PLNLDAfit, 82
predict.PLNmixturefit, 83
predict_cond, 84
prepare_data, 85
prepare_data(), 14, 15, 93

rPLN, 87

sigma(), 19
sigma.PLNfit, 88
sigma.PLNfit(), 5, 94
sigma.PLNmixturefit, 89
sigma.PLNmixturefit(), 6
stability_selection, 90
stability_selection(), 9, 12
standard_error
 (standard_error.PLNPCAfit), 91
standard_error(), 19
standard_error.PLNfit(), 5, 88, 94
standard_error.PLNPCAfit, 91

trichoptera, 93

vcov(), 19
vcov.PLNfit, 94
vcov.PLNfit(), 5, 88, 92