

Package ‘lsirm12pl’

March 31, 2023

Type Package

Title Latent Space Item Response Model

Version 1.2.0

Date 2023-03-28

Maintainer Jina Park <pja0707@yonsei.ac.kr>

Description Analysis of dichotomous and continuous response data using latent factor by both 1PL LSIRM and 2PL LSIRM as described in Jeon et al. (2021) <[doi:10.1007/s11336-021-09762-5](https://doi.org/10.1007/s11336-021-09762-5)>. It includes original 1PL LSIRM and 2PL LSIRM provided for binary response data and its extension for continuous response data. Bayesian model selection with spike-and-slab prior and method for dealing data with missing value under missing at random, missing completely at random are also supported. Various diagnostic plots are available to inspect the latent space and summary of estimated parameters.

License GPL-3

Imports Rcpp (>= 1.0.5), MCMCpack, ggplot2, GPARotation, dplyr, grDevices, rlang, pROC, coda, spatstat, spatstat.geom, spatstat.random, plotly

LinkingTo Rcpp, RcppArmadillo

Encoding UTF-8

RoxygenNote 7.2.3

Suggests knitr, testthat

Depends R (>= 3.1.0)

LazyData true

NeedsCompilation yes

Author Dongyoung Go [aut],
Gwanghee Kim [aut],
Jina Park [aut, cre],
Ickhoon Jin [ctb],
Minjeong Jeon [ctb]

Repository CRAN

Date/Publication 2023-03-31 13:40:02 UTC

R topics documented:

BFPT	3
diagnostic.lsim	3
lsim	5
lsim.formula	5
lsim12pl	6
lsim1pl	6
lsim1pl_fixed_gamma	7
lsim1pl_fixed_gamma_mar	9
lsim1pl_fixed_gamma_mcar	12
lsim1pl_mar	15
lsim1pl_mar_ss	18
lsim1pl_mcar	21
lsim1pl_mcar_ss	24
lsim1pl_normal	27
lsim1pl_normal_fixed_gamma	28
lsim1pl_normal_fixed_gamma_mar	31
lsim1pl_normal_fixed_gamma_mcar	34
lsim1pl_normal_mar	37
lsim1pl_normal_mar_ss	40
lsim1pl_normal_mcar	43
lsim1pl_normal_mcar_ss	46
lsim1pl_normal_o	50
lsim1pl_normal_ss	53
lsim1pl_o	56
lsim1pl_ss	58
lsim2pl	61
lsim2pl_fixed_gamma	62
lsim2pl_fixed_gamma_mar	65
lsim2pl_fixed_gamma_mcar	68
lsim2pl_mar	71
lsim2pl_mar_ss	74
lsim2pl_mcar	78
lsim2pl_mcar_ss	81
lsim2pl_normal	85
lsim2pl_normal_fixed_gamma	86
lsim2pl_normal_fixed_gamma_mar	88
lsim2pl_normal_fixed_gamma_mcar	92
lsim2pl_normal_mar	95
lsim2pl_normal_mar_ss	98
lsim2pl_normal_mcar	102
lsim2pl_normal_mcar_ss	106
lsim2pl_normal_o	109
lsim2pl_normal_ss	112
lsim2pl_o	116
lsim2pl_ss	119
onepl	122

<i>BFPT</i>	3
plot.lsimr	124
print.summary.lsimr	125
summary.lsimr	126
TDRI	127
twopl	128
Index	130

BFPT	<i>Big Five Personality Test</i>
------	----------------------------------

Description

A dataset containing the result of personality test for 50 questions from 1,000 random sampled people.

Usage

data(BFPT)

Format

A matrix with 1,015,341 rows and 50 columns.

Details

A dataset collected in 2016-2018 through an interactive on-line personality test, containing the result of personality test for 50 questions. 1,000 people are random sampled from the original dataset containing 1,015,341 people. The scale is labeled as 1=Disagree, 3=Neutral and 5=Agree.

Source

<https://www.kaggle.com/tunguz/big-five-personality-test>

diagnostic.lsimr	<i>Diagnostic the result of LSIRM model</i>
------------------	---

Description

diagnostic.lsimr is used to diagnostic the result of LSIRM model.

Usage

```
diagnostic.lsirm(
  object,
  plot = TRUE,
  draw.item = list(beta = "first", theta = "first", alpha = "second"),
  which.draw = c("beta", "gamma"),
  plot.roc = T
)
```

Arguments

<code>object</code>	object of class <code>lsirm</code> .
<code>plot</code>	If TRUE, MCMC diagnostic plots are returned
<code>draw.item</code>	Select items for diagnosis. A default "first" is drawing the first item for selected parameters in <code>which.draw</code> . Parameter "alpha", however, uses "second" as a default value because the first alpha has an estimation issue. Positions and item names are supported. For instance, if the name of item is "i1", "i2", "i3" and its positions is in order, the result of <code>beta = c("i1", "i2", "i3")</code> and <code>beta = c(1, 2, 3)</code> are equivalent.
<code>which.draw</code>	Select parameters for diagnosis. For the 1PL model, "beta", "theta" and "gamma" are available. "alpha" is only available in the 2PL model.
<code>plot.roc</code>	If TRUE, ROC curve and AUC value are returned. This option is only available when input data type is binary.

Value

`diagnostic.lsirm` returns plots for checking MCMC convergence for selected parameters. In binary cases, ROC curve and AUC are supported.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = FALSE))

# 1PL model
diagnostic.lsirm(lsirm_result, plot=TRUE,
  which.draw=c("beta", "theta", "gamma"), plot.roc = TRUE)

# 1PL model, multiple items
diagnostic.lsirm(lsirm_result, plot=TRUE, draw.item=list(beta = c(1,2,3)),
  which.draw=c("beta", "gamma"), plot.roc = TRUE)

lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = FALSE))

# 2PL model
diagnostic.lsirm(lsirm_result, plot=TRUE,
  which.draw=c("beta", "theta", "alpha", "gamma"), plot.roc = TRUE)
```

lsirm	<i>Fit a LSIRM model</i>
-------	--------------------------

Description

[lsirm](#) is used to fit 1PL LSIRM and 2PL LSIRM using Bayesian method as described in Jeon et al. (2021).

Usage

```
lsirm(data, ...)
```

Arguments

data	Matrix; binary or continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
...	Additional arguments for the corresponding function.

Value

lsirm returns an object of list. See corresponding function.

See Also

[lsirm1pl](#) and [lsirm2pl](#)

lsirm.formula	<i>Formula function for LSIRM model</i>
---------------	---

Description

[lsirm.formula](#) is formula object.

Usage

```
## S3 method for class 'formula'
lsirm(formula, ...)
```

Arguments

formula	The form of formula is <code>lsirm(A ~ <term 1>(<term 2> + <term 3> ...))</code> , where A is binary or continuous item response matrix to be analyzed, <term1> is the model you want to fit and has one of the following values: "lsirm1pl" and "lsirm2pl"., and <term 2>, <term 3>, etc., are each options for the model.
...	Additional arguments for the corresponding function.

 lsirm12pl

lsirm12pl-package

Description

Analysis of dichotomous and continuous response data using latent factor by both 1PL LSIRM and 2PL LSIRM as described in Jeon et al. (2021) <doi:10.1007/s11336-021-09762-5>. It includes original 1PL LSIRM and 2PL LSIRM provided for binary response data and its extension for continuous response data. Bayesian model selection with spike-and-slab prior and method for dealing data with missing value under missing at random, missing completely at random are also supported. Various diagnostic plots are available to inspect the latent space and summary of estimated parameters.

 lsirm1pl

Fit a 1pl LSIRM model

Description

[lsirm1pl](#) integrates all functions related to 1pl LSIRM

Usage

```
lsirm1pl(data, spikenslab = FALSE, fixed_gamma = FALSE, missing_data = NA, ...)
```

Arguments

data	Matrix; binary or continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
spikenslab	Whether to use a model selection approach.
fixed_gamma	Whether fix gamma to 1.
missing_data	The assumed missing type. One of NA, "mar" and "mcar". Default uses NA.
...	Additional arguments for the corresponding function.

Value

lsirm1pl returns an object of list. See corresponding function.

Note

If both spikenslab and fixed_gamma are set TRUE, it returns error because both are related to gamma.

See Also

lsirm1pl_o, lsirm1pl_fixed_gamma, lsirm1pl_mar, lsirm1pl_mcar, lsirm1pl_fixed_gamma_mar, lsirm1pl_fixed_gamma_mcar, lsirm1pl_ss, lsirm1pl_mar_ss, lsirm1pl_mcar_ss, lsirm1pl_normal_o, lsirm1pl_normal_fixed_gamma, lsirm1pl_normal_mar, lsirm1pl_normal_mcar, lsirm1pl_normal_fixed_gamma_mar, lsirm1pl_normal_fixed_gamma_mcar, lsirm1pl_normal_ss, lsirm1pl_normal_mar_ss, lsirm1pl_normal_mcar_ss

lsirm1pl_fixed_gamma *1pl LSIRM model fixing gamma to 1.*

Description

`lsirm1pl_fixed_gamma` is used to fit 1pl LSIRM model with gamma fixed to 1. `lsirm1pl_fixed_gamma` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_fixed_gamma(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001
)
```

Arguments

<code>data</code>	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.

<code>nthin</code>	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
<code>nprint</code>	Numeric; MCMC samples is displayed during execution of MCMC chain for each <code>nprint</code> . default value is 500.
<code>jump_beta</code>	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
<code>jump_theta</code>	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
<code>jump_z</code>	Numeric; jumping rule of the proposal density for z. default value is 0.5.
<code>jump_w</code>	Numeric; jumping rule of the proposal density for w. default value is 0.5.
<code>pr_mean_beta</code>	Numeric; mean of normal prior for beta. default value is 0.
<code>pr_sd_beta</code>	Numeric; standard deviation of normal prior for beta. default value is 1.0.
<code>pr_mean_theta</code>	Numeric; mean of normal prior for theta. default value is 0.
<code>pr_a_theta</code>	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
<code>pr_b_theta</code>	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.

Details

`lsirm1pl_fixed_gamma` models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space:

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \beta_i, z_j, w_i)) = \theta_j + \beta_i - \|z_j - w_i\|$$

Value

`lsirm1pl_fixed_gamma` returns an object of list containing the following components:

<code>data</code>	data frame or matrix containing the variables in the model.
<code>bic</code>	Numeric value with the corresponding BIC.
<code>mcmc_inf</code>	number of mcmc iteration, burn-in periods, and thinning intervals.
<code>map_inf</code>	value of log maximum a posterior and iteration number which have log maximum a posterior.
<code>beta_estimate</code>	posterior estimation of beta.
<code>theta_estimate</code>	posterior estimation of theta.
<code>sigma_theta_estimate</code>	posterior estimation of standard deviation of theta.
<code>z_estimate</code>	posterior estimation of z.
<code>w_estimate</code>	posterior estimation of w.
<code>beta</code>	posterior samples of beta.
<code>theta</code>	posterior samples of theta.
<code>theta_sd</code>	posterior samples of standard deviation of theta.
<code>z</code>	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.

w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_z	accept ratio of z.
accept_w	accept ratio of w.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

lsirm_result <- lsirm1pl_fixed_gamma(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = TRUE))
```

```
lsirm1pl_fixed_gamma_mar
```

1pl LSIRM model fixing gamma to 1 for missing at random data.

Description

[lsirm1pl_fixed_gamma_mar](#) is used to fit LSIRM model with gamma fixed to 1 in incomplete data assumed to be missing at random. [lsirm1pl_fixed_gamma_mar](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_fixed_gamma_mar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
```

```

pr_mean_theta = 0,
pr_a_theta = 0.001,
pr_b_theta = 0.001,
missing.val = 99
)

```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_fixed_gamma_mar models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space:

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \beta_i, z_j, w_i)) = \theta_j + \beta_i - \|z_j - w_i\|$$

Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References.

Value

lsirm1pl_fixed_gamma_mar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
imp_estimate	probability of imputating a missing value with 1.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
imp	imputation for missing Values using posterior samples.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)
```

```
# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_fixed_gamma_mar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = TRUE,
missing_data = "mar", missing.val = 99))
```

```
lsirm1pl_fixed_gamma_mcar
```

1pl LSIRM model fixing gamma to 1 for missing completely at random data.

Description

[lsirm1pl_fixed_gamma_mcar](#) is used to fit LSIRM model with gamma fixed to 1 in incomplete data assumed to be missing completely at random. [lsirm1pl_fixed_gamma_mcar](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_fixed_gamma_mcar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  missing.val = 99
)
```

Arguments

<code>data</code>	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
<code>nthin</code>	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
<code>nprint</code>	Numeric; MCMC samples is displayed during execution of MCMC chain for each <code>nprint</code> . default value is 500.
<code>jump_beta</code>	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
<code>jump_theta</code>	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
<code>jump_z</code>	Numeric; jumping rule of the proposal density for z. default value is 0.5.
<code>jump_w</code>	Numeric; jumping rule of the proposal density for w. default value is 0.5.
<code>pr_mean_beta</code>	Numeric; mean of normal prior for beta. default value is 0.
<code>pr_sd_beta</code>	Numeric; standard deviation of normal prior for beta. default value is 1.0
<code>pr_mean_theta</code>	Numeric; mean of normal prior for theta. default value is 0.
<code>pr_a_theta</code>	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
<code>pr_b_theta</code>	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
<code>missing.val</code>	Numeric; a number to replace missing values. default value is 99.

Details

`lsirm1pl_fixed_gamma_mcar` models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space:

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \beta_i, z_j, w_i)) = \theta_j + \beta_i - \|z_j - w_i\|$$

Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing completely at random assumption and data augmentation, see References.

Value

`lsirm1pl_fixed_gamma_mcar` returns an object of list containing the following components:

<code>data</code>	data frame or matrix containing the variables in the model.
<code>missing.val</code>	a number to replace missing values.
<code>bic</code>	Numeric value with the corresponding BIC.
<code>mcmc_inf</code>	number of mcmc iteration, burn-in periods, and thinning intervals.

map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2), ncol=10, nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_fixed_gamma_mcar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = TRUE,
missing_data = "mcar", missing.val = 99))
```

lsirm1pl_mar

*1pl LSIRM model for missing at random data.***Description**

`lsirm1pl_mar` is used to fit 1pl LSIRM model in incomplete data assumed to be missing at random. `lsirm1pl_mar` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_mar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 0.025,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_gamma = 0.5,
  pr_sd_gamma = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  missing.val = 99
)
```

Arguments

<code>data</code>	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
<code>nthin</code>	Numeric; number of thinning, MCMC iterations to discard. default value is 5.

nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_mar models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$\text{logit}(P(Y_{j,i} = 1|\theta_j, \beta_i, \gamma, z_j, w_i)) = \theta_j + \beta_i - \gamma||z_j - w_i||$$

Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References.

Value

lsirm1pl_mar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.

sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
imp_estimate	probability of imputating a missing value with 1.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
imp	imputation for missing Values using posterior samples.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_z	accept ratio of z.
accept_w	accept ratio of w.
accept_gamma	accept ratio of gamma.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_mar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = FALSE,
missing_data = 'mar', missing.val = 99))
```

lsirm1pl_mar_ss	<i>1pl LSIRM model with model selection approach for missing at random data.</i>
-----------------	--

Description

`lsirm1pl_mar_ss` is used to fit 1pl LSIRM model with model selection approach based on spike-and-slab priors in incomplete data assumed to be missing at random. `lsirm1pl_mar_ss` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_mar_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_xi_a = 1,
  pr_xi_b = 1,
  missing.val = 99
)
```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.

niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_mar_ss models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \beta_i, \gamma, z_j, w_i)) = \theta_j + \beta_i - \gamma \|z_j - w_i\|$$

Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References. lsirm1pl_mar_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm1pl_mar_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
imp_estimate	probability of imputating a missing value with 1.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
imp	imputation for missing Values using posterior samples.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.

References

Little, R. J., & Rubin, D. B. (2019). *Statistical analysis with missing data* (Vol. 793). John Wiley & Sons.
 Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2), ncol=10, nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_mar_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = TRUE, fixed_gamma = FALSE,
missing_data = 'mar', missing = 99))
```

lsirm1pl_mcar

1pl LSIRM model for missing completely at random data.

Description

[lsirm1pl_mcar](#) is used to fit 1pl LSIRM model in incomplete data assumed to be missing completely at random. [lsirm1pl_mcar](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_mcar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 0.025,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_gamma = 0.5,
  pr_sd_gamma = 1,
```

```

pr_a_theta = 0.001,
pr_b_theta = 0.001,
missing.val = 99
)

```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_mcar models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \beta_i, \gamma, z_j, w_i)) = \theta_j + \beta_i - \gamma ||z_j - w_i||$$

Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing completely at random assumption and data augmentation, see References.

Value

lsirm1pl_mcar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_z	accept ratio of z.
accept_w	accept ratio of w.
accept_gamma	accept ratio of gamma.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2), ncol=10, nrow=50)
```

```
# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_mcar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = FALSE,
missing_data = 'mcar', missing.val = 99))
```

lsirm1pl_mcar_ss *1pl LSIRM model with model selection approach for missing completely at random data.*

Description

[lsirm1pl_mcar_ss](#) is used to fit LSIRM model with model selection approach based on spike-and-slab priors in incomplete data assumed to be missing completely at random. [lsirm1pl_mcar_ss](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_mcar_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_xi_a = 1,
```



```

    pr_xi_b = 1,
    missing.val = 99
)

```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_mcar_ss models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \beta_i, \gamma, z_j, w_i)) = \theta_j + \beta_i - \gamma \|z_j - w_i\|$$

Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing completely at random assumption and data augmentation, see References. lsirm1pl_mcar_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm1pl_mcar_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
accept_beta	accept ratio of beta.

accept_theta accept ratio of theta.
 accept_w accept ratio of w.
 accept_z accept ratio of z.
 accept_gamma accept ratio of gamma.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.
 Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_mcar_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = TRUE, fixed_gamma = FALSE,
missing_data = 'mcar', missing.val = 99))
```

lsirm1pl_normal	<i>1pl LSIRM model with normal likelihood</i>
-----------------	---

Description

[lsirm1pl_normal](#) integrates all functions related to 1pl LSIRM with normal likelihood using multiplicative effect.

Usage

```
lsirm1pl_normal(  
  data,  
  spikenslab = FALSE,  
  fixed_gamma = FALSE,  
  missing_data = NA,  
  ...  
)
```

Arguments

<code>data</code>	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>spikenslab</code>	Whether to use a model selection approach.
<code>fixed_gamma</code>	Whether fix gamma to 1.
<code>missing_data</code>	The assumed missing type. One of NA, "mar" and "mcar". Default uses NA.
<code>...</code>	Additional arguments for the corresponding function.

Value

`lsirm1pl_normal` returns an object of list. See corresponding function.

Note

If both `spikenslab` and `fixed_gamma` are set TRUE, it returns error because both are related to gamma.

See Also

[lsirm1pl_normal_o](#), [lsirm1pl_normal_fixed_gamma](#), [lsirm1pl_normal_mar](#),
[lsirm1pl_normal_mcar](#), [lsirm1pl_normal_fixed_gamma_mar](#), [lsirm1pl_normal_fixed_gamma_mcar](#),
[lsirm1pl_normal_ss](#), [lsirm1pl_normal_mar_ss](#), [lsirm1pl_normal_mcar_ss](#)

`lsirm1pl_normal_fixed_gamma`

1pl LSIRM model fixing gamma to 1 with normal likelihood

Description

[lsirm1pl_normal_fixed_gamma](#) is used to fit 1pl LSIRM model for continuous variable with gamma fixed to 1. [lsirm1pl_normal_fixed_gamma](#) factorizes continuous item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_normal_fixed_gamma(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
```

```

    jump_beta = 0.4,
    jump_theta = 1,
    jump_z = 0.5,
    jump_w = 0.5,
    pr_mean_beta = 0,
    pr_sd_beta = 1,
    pr_mean_theta = 0,
    pr_a_theta = 0.001,
    pr_b_theta = 0.001,
    pr_a_eps = 0.001,
    pr_b_eps = 0.001
)

```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.

Details

lsirm1pl_normal_fixed_gamma models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space:

$$Y_{j,i} = \theta_j + \beta_i - \|z_j - w_i\| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$.

Value

lsirm1pl_normal_fixed_gamma returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_normal_fixed_gamma(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = TRUE))
```

```
lsirm1pl_normal_fixed_gamma_mar
```

1pl LSIRM model fixing gamma to 1 with normal likelihood for missing at random data.

Description

[lsirm1pl_normal_fixed_gamma_mar](#) is used to fit 1pl LSIRM model for continuous variable with gamma fixed to 1 in incomplete data assumed to be missing at random.

[lsirm1pl_normal_fixed_gamma_mar](#) factorizes continuous item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_normal_fixed_gamma_mar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_a_theta = 0.001,
```

```

pr_b_theta = 0.001,
pr_a_eps = 0.001,
pr_b_eps = 0.001,
missing.val = 99
)

```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_normal_fixed_gamma_mar models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space:

$$Y_{j,i} = \theta_j + \beta_i - ||z_j - w_i|| + e_{ji}$$

where the error $e_{ji} \sim N(0, \sigma^2)$. Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References.

Value

lsirm1pl_normal_fixed_gamma_mar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
imp_estimate	estimation of imputing missing values.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
imp	imputation for missing Values using posterior samples.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99
```

```
lsirm_result <- lsirm1pl_normal_fixed_gamma_mar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = TRUE,
missing_data = "mar", missing.val = 99))
```

```
lsirm1pl_normal_fixed_gamma_mcar
1pl LSIRM model fixing gamma to 1 with normal likelihood for missing
completely at random data.
```

Description

[lsirm1pl_normal_fixed_gamma_mcar](#) is used to fit 1pl LSIRM model for continuous variable with gamma fixed to 1 in incomplete data assumed to be missing completely at random.

[lsirm1pl_normal_fixed_gamma_mcar](#) factorizes continuous item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_normal_fixed_gamma_mcar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,
  missing.val = 99
)
```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
------	--

ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_normal_fixed_gamma_mcar models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space:

$$Y_{j,i} = \theta_j + \beta_i - \|z_j - w_i\| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$ Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing completely at random assumption and data augmentation, see References.

Value

lsirm1pl_normal_fixed_gamma_mcar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.

<code>mcmc_inf</code>	number of mcmc iteration, burn-in periods, and thinning intervals.
<code>map_inf</code>	value of log maximum a posterior and iteration number which have log maximum a posterior.
<code>beta_estimate</code>	posterior estimation of beta.
<code>theta_estimate</code>	posterior estimation of theta.
<code>sigma_theta_estimate</code>	posterior estimation of standard deviation of theta.
<code>sigma_estimate</code>	posterior estimation of standard deviation.
<code>z_estimate</code>	posterior estimation of z.
<code>w_estimate</code>	posterior estimation of w.
<code>beta</code>	posterior samples of beta.
<code>theta</code>	posterior samples of theta.
<code>theta_sd</code>	posterior samples of standard deviation of theta.
<code>sigma</code>	posterior samples of standard deviation.
<code>z</code>	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
<code>w</code>	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
<code>accept_beta</code>	accept ratio of beta.
<code>accept_theta</code>	accept ratio of theta.
<code>accept_w</code>	accept ratio of w.
<code>accept_z</code>	accept ratio of z.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_normal_fixed_gamma_mcar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = TRUE,
missing_data = "mcar", missing.val = 99))
```

lsirm1pl_normal_mar *1pl LSIRM model with normal likelihood for missing at random data.*

Description

`lsirm1pl_normal_mar` is used to fit LSIRM model for continuous variable with 1pl in incomplete data assumed to be missing at random. `lsirm1pl_normal_mar` factorizes continuous item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_normal_mar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_gamma = 0.5,
  pr_sd_gamma = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,
  missing.val = 99
)
```

Arguments

<code>data</code>	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.

nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_normal_mar models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$Y_{j,i} = \theta_j + \beta_i - \gamma \|z_j - w_i\| + e_{ji}$$

where the error $e_{ji} \sim N(0, \sigma^2)$ Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References.

Value

lsirm1pl_normal_mar returns an object of list containing the following components:

data data frame or matrix containing the variables in the model.

missing_val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
imp_estimate	estimation of imputing missing values.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
imp	imputation for missing Values using posterior samples.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)
```

```
# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_normal_mar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = FALSE,
missing_data = 'mar', missing.val = 99))
```

```
lsirm1pl_normal_mar_ss
```

1pl LSIRM model with normal likelihood and model selection approach for missing at random data.

Description

`lsirm1pl_normal_mar_ss` is used to fit LSIRM model with model selection approach based on spike-and-slab priors for continuous variable with 1pl in incomplete data assumed to be missing at random. `lsirm1pl_normal_mar_ss` factorizes continuous item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_normal_mar_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
```



```

    pr_a_eps = 0.001,
    pr_b_eps = 0.001,
    pr_xi_a = 0.001,
    pr_xi_b = 0.001,
    missing.val = 99
)

```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_normal_mar_ss models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$Y_{j,i} = \theta_j + \beta_i - \gamma \|z_j - w_i\| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$. Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References. lsirm1pl_normal_mar_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm1pl_normal_mar_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
imp_estimate	estimation of imputing missing values.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.

w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
imp	imputation for missing Values using posterior samples.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.
 Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_normal_mar_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = TRUE, fixed_gamma = FALSE,
missing_data = 'mar', missing = 99))
```

lsirm1pl_normal_mcar *1pl LSIRM model with normal likelihood for missing completely at random data.*

Description

[lsirm1pl_normal_mcar](#) is used to fit LSIRM model with 1pl in incomplete data assumed to be missing completely at random. [lsirm1pl_normal_mcar](#) factorizes continuous item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_normal_mcar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_gamma = 0.5,
  pr_sd_gamma = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,
  missing.val = 99
)
```

Arguments

<code>data</code>	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
<code>nthin</code>	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
<code>nprint</code>	Numeric; MCMC samples is displayed during execution of MCMC chain for each <code>nprint</code> . default value is 500.
<code>jump_beta</code>	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
<code>jump_theta</code>	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
<code>jump_gamma</code>	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
<code>jump_z</code>	Numeric; jumping rule of the proposal density for z. default value is 0.5.
<code>jump_w</code>	Numeric; jumping rule of the proposal density for w. default value is 0.5.
<code>pr_mean_beta</code>	Numeric; mean of normal prior for beta. default value is 0.
<code>pr_sd_beta</code>	Numeric; standard deviation of normal prior for beta. default value is 1.0.

pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_normal_mcar models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$. Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing at random assumption and data augmentation, see References.

Value

lsirm1pl_normal_mcar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.

beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_normal_mcar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = FALSE,
missing_data = 'mcar', missing.val = 99))
```

lsirm1pl_normal_mcar_ss

1pl LSIRM model with normal likelihood and model selection approach for missing completely at random data.

Description

`lsirm1pl_normal_mcar_ss` is used to fit LSIRM model with model selection approach based on spike-and-slab priors for continuous variable with 1pl in incomplete data assumed to be missing completely at random. `lsirm1pl_normal_mcar_ss` factorizes continuous item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_normal_mcar_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,
  pr_xi_a = 0.001,
  pr_xi_b = 0.001,
  missing.val = 99
)
```

Arguments

<code>data</code>	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.

nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm1pl_normal_mcar_ss models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$. Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing at random assumption and data augmentation, see References. lsirm1pl_normal_mcar_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm1pl_normal_mcar_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.

References

Little, R. J., & Rubin, D. B. (2019). *Statistical analysis with missing data* (Vol. 793). John Wiley & Sons.
 Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm1pl_normal_mcar_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = TRUE, fixed_gamma = FALSE,
missing_data = 'mcar', missing.val = 99))
```

lsirm1pl_normal_o *1pl LSIRM model with normal likelihood.*

Description

[lsirm1pl_normal_o](#) is used to fit LSIRM model for continuous variable with 1pl. [lsirm1pl_normal_o](#) factorizes continuous item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_normal_o(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_gamma = 0.5,
  pr_sd_gamma = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
```

```

    pr_a_eps = 0.001,
    pr_b_eps = 0.001
)

```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.

Details

lsirm1pl_normal_o models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$.

Value

lsirm1pl_normal_o returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1), ncol=10, nrow=50)

lsirm_result <- lsirm1pl_normal_o(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = FALSE))
```

lsirm1pl_normal_ss	<i>1pl LSIRM model with normal likelihood and model selection approach.</i>
--------------------	---

Description

[lsirm1pl_normal_ss](#) is used to fit LSIRM model with model selection approach based on spike-and-slab priors for continuous variable with 1pl. LSIRM factorizes continuous item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_normal_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,
  pr_xi_a = 0.001,
  pr_xi_b = 0.001
)
```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.

niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.

Details

lsirm1pl_normal_ss models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$. lsirm1pl_normal_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm1pl_normal_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.

References

Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: Frequentist and Bayesian strategies (Vol. 33). *The Annals of Statistics*

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1), ncol=10, nrow=50)

lsirm_result <- lsirm1pl_normal_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = TRUE, fixed_gamma = FALSE))
```

lsirm1pl_o	<i>1pl LSIRM model.</i>
------------	-------------------------

Description

`lsirm1pl_o` is used to fit 1pl LSIRM model. `lsirm1pl_o` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_o(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 0.025,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_gamma = 0.5,
  pr_sd_gamma = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001
)
```

Arguments

<code>data</code>	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
-------------------	--

ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.

Details

lsirm1pl_o models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \beta_i, \gamma, z_j, w_i)) = \theta_j + \beta_i - \gamma ||z_j - w_i||$$

Value

lsirm1pl_o returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.

sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_z	accept ratio of z.
accept_w	accept ratio of w.
accept_gamma	accept ratio of gamma.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5),ncol=10,nrow=50)

lsirm_result <- lsirm1pl_o(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = FALSE))
```

lsirm1pl_ss

1pl LSIRM model with model selection approach.

Description

[lsirm1pl_ss](#) is used to fit LSIRM model with model selection approach based on spike-and-slab priors. LSIRM factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm1pl_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_xi_a = 1,
  pr_xi_b = 1
)
```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0

pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.

Details

lsirm1pl_ss models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term:

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \beta_i, \gamma, z_j, w_i)) = \theta_j + \beta_i - \gamma \|z_j - w_i\|$$

lsirm1pl_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm1pl_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.

beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.

References

Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: Frequentist and Bayesian strategies (Vol. 33). The Annals of Statistics

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

lsirm_result <- lsirm1pl_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = TRUE, fixed_gamma = FALSE))
```

lsirm2pl *Fit a 2pl LSIRM model*

Description

[lsirm2pl](#) integrates all functions related to 2pl LSIRM

Usage

```
lsirm2pl(data, spikenslab = FALSE, fixed_gamma = FALSE, missing_data = NA, ...)
```

Arguments

<code>data</code>	Matrix; binary or continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>spikenslab</code>	Whether to use a model selection approach.
<code>fixed_gamma</code>	Whether fix gamma to 1.
<code>missing_data</code>	The assumed missing type. One of NA, "mar" and "mcar". Default uses NA.
<code>...</code>	Additional arguments for the corresponding function.

Value

`lsirm2pl` returns an object of list. See corresponding function.

Note

If both `spikenslab` and `fixed_gamma` are set TRUE, it returns error because both are related to gamma.

See Also

[lsirm2pl_o](#), [lsirm2pl_fixed_gamma](#), [lsirm2pl_mar](#), [lsirm2pl_mcar](#), [lsirm2pl_fixed_gamma_mar](#), [lsirm2pl_fixed_gamma_mcar](#), [lsirm2pl_ss](#), [lsirm2pl_mar_ss](#), [lsirm2pl_mcar_ss](#), [lsirm2pl_normal_o](#), [lsirm2pl_normal_fixed_gamma](#), [lsirm2pl_normal_mar](#), [lsirm2pl_mcar](#), [lsirm2pl_normal_fixed_gamma_mar](#), [lsirm2pl_normal_fixed_gamma_mcar](#), [lsirm2pl_normal_ss](#), [lsirm2pl_normal_mar_ss](#), [lsirm2pl_normal_mcar_ss](#)

`lsirm2pl_fixed_gamma` *2pl LSIRM model fixing gamma to 1.*

Description

`lsirm2pl_fixed_gamma` is used to fit 2pl LSIRM model fixing gamma to 1. `lsirm2pl_fixed_gamma` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_fixed_gamma(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
```

```

    jump_beta = 0.4,
    jump_theta = 1,
    jump_alpha = 1,
    jump_z = 0.5,
    jump_w = 0.5,
    pr_mean_beta = 0,
    pr_sd_beta = 1,
    pr_mean_theta = 0,
    pr_mean_alpha = 0.5,
    pr_sd_alpha = 1,
    pr_a_theta = 0.001,
    pr_b_theta = 0.001
)

```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; standard deviation of normal prior for alpha. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.

Details

lsirm2pl_fixed_gamma models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1|\theta_j, \alpha_i, \beta_i, z_j, w_i)) = \theta_j * \alpha_i + \beta_i - ||z_j - w_i||$$

Value

lsirm2pl_fixed_gamma returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_alpha	accept ratio of alpha.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

lsirm_result <- lsirm2pl_fixed_gamma(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = TRUE))
```

```
lsirm2pl_fixed_gamma_mar
```

2pl LSIRM model fixing gamma to 1 for missing at random data.

Description

`lsirm2pl_fixed_gamma_mar` is used to fit 2pl LSIRM model fixing gamma to 1 in incomplete data assumed to be missing at random. `lsirm2pl_fixed_gamma_mar` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_fixed_gamma_mar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  missing.val = 99
)
```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; standard deviation of normal prior for alpha. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_fixed_gamma_mar models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space. For 2pl model, the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \alpha_i, \beta_i, z_j, w_i)) = \theta_j * \alpha_i + \beta_i - ||z_j - w_i||$$

Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References.

Value

lsirm2pl_fixed_gamma_mar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
imp_estimate	probability of imputating a missing value with 1.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
imp	imputation for missing Values using posterior samples.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_alpha	accept ratio of alpha.

References

Little, R. J., & Rubin, D. B. (2019). *Statistical analysis with missing data* (Vol. 793). John Wiley & Sons.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_fixed_gamma_mar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = TRUE,
  missing_data = "mar"))
```

```
lsirm2pl_fixed_gamma_mcar
```

2pl LSIRM model fixing gamma to 1 for missing completely at random data.

Description

[lsirm2pl_fixed_gamma_mcar](#) is used to fit 2pl LSIRM model fixing gamma to 1 in incomplete data assumed to be missing completely at random. [lsirm2pl_fixed_gamma_mcar](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_fixed_gamma_mcar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
```

```

pr_sd_beta = 1,
pr_mean_theta = 0,
pr_mean_alpha = 0.5,
pr_sd_alpha = 1,
pr_a_theta = 0.001,
pr_b_theta = 0.001,
missing.val = 99
)

```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha. default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_fixed_gamma_mcar models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \alpha_i, \beta_i, z_j, w_i)) = \theta_j * \alpha_i + \beta_i - ||z_j - w_i||$$

Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing completely at random assumption and data augmentation, see References.

Value

`lsirm2pl_fixed_gamma_mar` returns an object of list containing the following components:

<code>data</code>	data frame or matrix containing the variables in the model.
<code>missing.val</code>	a number to replace missing values.
<code>bic</code>	Numeric value with the corresponding BIC.
<code>mcmc_inf</code>	number of mcmc iteration, burn-in periods, and thinning intervals.
<code>map_inf</code>	value of log maximum a posterior and iteration number which have log maximum a posterior.
<code>beta_estimate</code>	posterior estimation of beta.
<code>theta_estimate</code>	posterior estimation of theta.
<code>sigma_theta_estimate</code>	posterior estimation of standard deviation of theta.
<code>alpha_estimate</code>	posterior estimation of alpha.
<code>z_estimate</code>	posterior estimation of z.
<code>w_estimate</code>	posterior estimation of w.
<code>beta</code>	posterior samples of beta.
<code>theta</code>	posterior samples of theta.
<code>theta_sd</code>	posterior samples of standard deviation of theta.
<code>alpha</code>	posterior samples of alpha.
<code>z</code>	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
<code>w</code>	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
<code>accept_beta</code>	accept ratio of beta.
<code>accept_theta</code>	accept ratio of theta.
<code>accept_w</code>	accept ratio of w.
<code>accept_z</code>	accept ratio of z.
<code>accept_alpha</code>	accept ratio of alpha.

References

Little, R. J., & Rubin, D. B. (2019). *Statistical analysis with missing data* (Vol. 793). John Wiley & Sons.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_fixed_gamma_mcar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = TRUE,
  missing_data = "mcar"))
```

lsirm2pl_mar

2pl LSIRM model for missing at random data.

Description

[lsirm2pl_mar](#) is used to fit 2pl LSIRM model in incomplete data assumed to be missing at random. [lsirm2pl_mar](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect in a latent space, while considering the missing element under the assumption of missing at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_mar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_gamma = 0.025,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
```

```

pr_mean_gamma = 0.5,
pr_sd_gamma = 1,
pr_mean_alpha = 0.5,
pr_sd_alpha = 1,
pr_a_theta = 0.001,
pr_b_theta = 0.001,
missing.val = 99
)

```

Arguments

<code>data</code>	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
<code>nthin</code>	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
<code>nprint</code>	Numeric; MCMC samples is displayed during execution of MCMC chain for each <code>nprint</code> . default value is 500.
<code>jump_beta</code>	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
<code>jump_theta</code>	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
<code>jump_alpha</code>	Numeric; jumping rule of the proposal density for alpha. default value is 1.0.
<code>jump_gamma</code>	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
<code>jump_z</code>	Numeric; jumping rule of the proposal density for z. default value is 0.5.
<code>jump_w</code>	Numeric; jumping rule of the proposal density for w. default value is 0.5.
<code>pr_mean_beta</code>	Numeric; mean of normal prior for beta. default value is 0.
<code>pr_sd_beta</code>	Numeric; standard deviation of normal prior for beta. default value is 1.0.
<code>pr_mean_theta</code>	Numeric; mean of normal prior for theta. default value is 0.
<code>pr_mean_gamma</code>	Numeric; mean of log normal prior for gamma. default value is 0.5.
<code>pr_sd_gamma</code>	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
<code>pr_mean_alpha</code>	Numeric; mean of normal prior for alpha. default value is 0.5.
<code>pr_sd_alpha</code>	Numeric; standard deviation of normal prior for alpha. default value is 1.0.
<code>pr_a_theta</code>	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
<code>pr_b_theta</code>	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
<code>missing.val</code>	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_mar models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1|\theta_j, \alpha_i, \beta_i, \gamma, z_j, w_i)) = \theta_j * \alpha_i + \beta_i - \gamma||z_j - w_i||$$

Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References.

Value

lsirm2pl_mar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
imp_estimate	
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
imp	
accept_beta	accept ratio of beta.

accept_theta accept ratio of theta.
 accept_w accept ratio of w.
 accept_z accept ratio of z.
 accept_gamma accept ratio of gamma.
 accept_alpha accept ratio of alpha.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2), ncol=10, nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_mar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = FALSE,
  missing_data = "mar"))
```

lsirm2pl_mar_ss	<i>2pl LSIRM model with model selection approach for missing at random data.</i>
-----------------	--

Description

[lsirm2pl_mar_ss](#) is used to fit 2pl LSIRM model based on spike-and-slab priors in incomplete data assumed to be missing at random. [lsirm2pl_mar_ss](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect in a latent space, while considering the missing element under the assumption of missing at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_mar_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_xi_a = 1,
  pr_xi_b = 1,
  missing.val = 99
)
```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha. default value is 1.0.

jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; standard deviation of normal prior for alpha. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_mar_ss models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \alpha_i, \beta_i, \gamma, z_j, w_i)) = \theta_j * \alpha_i + \beta_i - \gamma ||z_j - w_i||$$

Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References. lsirm2pl_mar_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm2pl_mar_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.

mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
imp_estimate	
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
imp	
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

References

- Little, R. J., & Rubin, D. B. (2019). *Statistical analysis with missing data* (Vol. 793). John Wiley & Sons.
- Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2), ncol=10, nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_mar_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = TRUE, fixed_gamma = FALSE,
  missing_data = "mar"))
```

lsirm2pl_mcar

2pl LSIRM model for missing completely at random data.

Description

`lsirm2pl_mcar` is used to fit 2pl LSIRM model in incomplete data assumed to be missing completely at random. `lsirm2pl_mcar` factorizes item response matrix into column-wise item effect, row-wise respondent effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_mcar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_gamma = 0.025,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
```

```

pr_mean_theta = 0,
pr_mean_gamma = 0.5,
pr_sd_gamma = 1,
pr_mean_alpha = 0.5,
pr_sd_alpha = 1,
pr_a_theta = 0.001,
pr_b_theta = 0.001,
missing.val = 99
)

```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; standard deviation of normal prior for alpha. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_mcar models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1|\theta_j, \alpha_i, \beta_i, \gamma, z_j, w_i)) = \theta_j * \alpha_i + \beta_i - \gamma||z_j - w_i||$$

Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing completely at random assumption and data augmentation, see References.

Value

lsirm2pl_mar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2), ncol=10, nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_mcar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = FALSE,
  missing_data = "mcar"))
```

lsirm2pl_mcar_ss	<i>2pl LSIRM model with model selection approach for missing completely at random data.</i>
------------------	---

Description

[lsirm2pl_mar_ss](#) is used to fit 2pl LSIRM model based on spike-and-slab priors in incomplete data assumed to be missing completely at random. [lsirm2pl_mar_ss](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_mcar_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
```

```

jump_alpha = 1,
jump_gamma = 1,
jump_z = 0.5,
jump_w = 0.5,
pr_mean_beta = 0,
pr_sd_beta = 1,
pr_mean_theta = 0,
pr_spike_mean = -3,
pr_spike_sd = 1,
pr_slab_mean = 0.5,
pr_slab_sd = 1,
pr_mean_alpha = 0.5,
pr_sd_alpha = 1,
pr_a_theta = 0.001,
pr_b_theta = 0.001,
pr_xi_a = 1,
pr_xi_b = 1,
missing.val = 99
)

```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.

pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_mcar_ss models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1|\theta_j, \alpha_i, \beta_i, \gamma, z_j, w_i)) = \theta_j * \alpha_i + \beta_i - \gamma||z_j - w_i||$$

Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References. lsirm2pl_mcar_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm2pl_mar_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.

z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons. Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2), ncol=10, nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_mcar_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = TRUE, fixed_gamma = FALSE,
  missing_data = "mcar"))
```

lsirm2pl_normal	<i>2pl LSIRM model with normal likelihood</i>
-----------------	---

Description

[lsirm2pl_normal](#) integrates all functions related to 2pl LSIRM with normal likelihood.

Usage

```
lsirm2pl_normal(
  data,
  spikenslab = FALSE,
  fixed_gamma = FALSE,
  missing_data = NA,
  ...
)
```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
spikenslab	Whether to use a model selection approach.
fixed_gamma	Whether fix gamma to 1.
missing_data	The assumed missing type. One of NA, "mar" and "mcar". Default uses NA.
...	Additional arguments for the corresponding function.

Value

`lsirm2pl_normal` returns an object of list. See corresponding function.

Note

If both `spikenslab` and `fixed_gamma` are set TRUE, it returns error because both are related to `gamma`.

See Also

[lsirm2pl_normal_o](#), [lsirm2pl_normal_fixed_gamma](#), [lsirm2pl_normal_mar](#),
[lsirm2pl_normal_mcar](#), [lsirm2pl_normal_fixed_gamma_mar](#), [lsirm2pl_normal_fixed_gamma_mcar](#),
[lsirm2pl_normal_ss](#), [lsirm2pl_normal_mar_ss](#), [lsirm2pl_normal_mcar_ss](#)

 lsirm2pl_normal_fixed_gamma

2pl LSIRM model fixing gamma to 1 with normal likelihood

Description

`lsirm2pl_normal_fixed_gamma` is used to fit 2pl LSIRM model with gamma fixed to 1 for continuous variable. `lsirm2pl_normal_fixed_gamma` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_normal_fixed_gamma(  
  data,  
  ndim = 2,  
  niter = 15000,  
  nburn = 2500,  
  nthin = 5,  
  nprint = 500,  
  jump_beta = 0.4,  
  jump_theta = 1,  
  jump_alpha = 1,  
  jump_z = 0.5,  
  jump_w = 0.5,  
  pr_mean_beta = 0,  
  pr_sd_beta = 1,  
  pr_mean_theta = 0,  
  pr_mean_alpha = 0.5,  
  pr_sd_alpha = 1,  
  pr_a_theta = 0.001,  
  pr_b_theta = 0.001,  
  pr_a_eps = 0.001,  
  pr_b_eps = 0.001  
)
```

Arguments

<code>data</code>	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.

nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.

Details

lsirm2pl_normal_fixed_gamma models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$

Value

lsirm2pl_normal_fixed_gamma returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.

beta_estimate posterior estimation of beta.
 theta_estimate posterior estimation of theta.
 sigma_theta_estimate
 posterior estimation of standard deviation of theta.
 sigma_estimate posterior estimation of standard deviation.
 alpha_estimate posterior estimation of alpha.
 z_estimate posterior estimation of z.
 w_estimate posterior estimation of w.
 beta posterior samples of beta.
 theta posterior samples of theta.
 theta_sd posterior samples of standard deviation of theta.
 sigma posterior samples of standard deviation.
 alpha posterior samples of alpha.
 z posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
 w posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
 accept_beta accept ratio of beta.
 accept_theta accept ratio of theta.
 accept_w accept ratio of w.
 accept_z accept ratio of z.
 accept_alpha accept ratio of alpha.

Examples

```

# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1), ncol=10, nrow=50)

lsrm_result <- lsirm2pl_normal_fixed_gamma(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = TRUE))
  
```

lsirm2pl_normal_fixed_gamma_mar

2pl LSIRM model fixing gamma to 1 with normal likelihood for missing at random data.

Description

`lsirm2pl_normal_fixed_gamma_mar` is used to fit 2pl LSIRM model with gamma fixed to 1 for continuous variable in incomplete data assumed to be missing at random.

`lsirm2pl_normal_fixed_gamma_mar` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_normal_fixed_gamma_mar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,
  missing.val = 99
)
```

Arguments

<code>data</code>	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
<code>nthin</code>	Numeric; number of thinning, MCMC iterations to discard. default value is 5.

nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_normal_fixed_gamma_mar models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$ Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References.

Value

lsirm2pl_normal_fixed_gamma_mar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.

map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
imp_estimate	
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
imp	
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_alpha	accept ratio of alpha.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_normal_fixed_gamma_mar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = TRUE,
missing_data = "mar"))
```

```
lsirm2pl_normal_fixed_gamma_mcar
```

2pl LSIRM model fixing gamma to 1 with normal likelihood for missing completely at random data.

Description

[lsirm2pl_normal_fixed_gamma_mcar](#) is used to fit 2pl LSIRM model with gamma fixed to 1 for continuous variable in incomplete data assumed to be missing completely at random.

[lsirm2pl_normal_fixed_gamma_mcar](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_normal_fixed_gamma_mcar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,
  missing.val = 99
)
```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
------	--

ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha default value is 1.0.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_normal_fixed_gamma_mcar models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$ Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing completely at random assumption and data augmentation, see References.

Value

`lsirm2pl_normal_fixed_gamma_mcar` returns an object of list containing the following components:

<code>data</code>	data frame or matrix containing the variables in the model.
<code>missing.val</code>	a number to replace missing values.
<code>bic</code>	Numeric value with the corresponding BIC.
<code>mcmc_inf</code>	number of mcmc iteration, burn-in periods, and thinning intervals.
<code>map_inf</code>	value of log maximum a posterior and iteration number which have log maximum a posterior.
<code>beta_estimate</code>	posterior estimation of beta.
<code>theta_estimate</code>	posterior estimation of theta.
<code>sigma_theta_estimate</code>	posterior estimation of standard deviation of theta.
<code>sigma_estimate</code>	posterior estimation of standard deviation.
<code>alpha_estimate</code>	posterior estimation of alpha.
<code>z_estimate</code>	posterior estimation of z.
<code>w_estimate</code>	posterior estimation of w.
<code>beta</code>	posterior samples of beta.
<code>theta</code>	posterior samples of theta.
<code>theta_sd</code>	posterior samples of standard deviation of theta.
<code>sigma</code>	posterior samples of standard deviation.
<code>alpha</code>	posterior samples of alpha.
<code>z</code>	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
<code>w</code>	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
<code>accept_beta</code>	accept ratio of beta.
<code>accept_theta</code>	accept ratio of theta.
<code>accept_w</code>	accept ratio of w.
<code>accept_z</code>	accept ratio of z.
<code>accept_alpha</code>	accept ratio of alpha.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1), ncol=10, nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2), ncol=10, nrow=50)

# make missing value with missing indicator matrix
```

```

data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_normal_fixed_gamma_mcar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = TRUE,
                                     missing_data = "mcar"))

```

lsirm2pl_normal_mar *2pl LSIRM model with normal likelihood and missing at random data.*

Description

`lsirm2pl_normal_mar` is used to fit 2pl LSIRM model for continuous variable in incomplete data assumed to be missing at random. `lsirm2pl_normal_mar` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```

lsirm2pl_normal_mar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_gamma = 0.5,
  pr_sd_gamma = 1,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,

```

```

    missing.val = 99
)

```

Arguments

<code>data</code>	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>ndim</code>	Numeric; dimension of latent space. default value is 2.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
<code>nthin</code>	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
<code>nprint</code>	Numeric; MCMC samples is displayed during execution of MCMC chain for each <code>nprint</code> . default value is 500.
<code>jump_beta</code>	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
<code>jump_theta</code>	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
<code>jump_alpha</code>	Numeric; jumping rule of the proposal density for alpha default value is 1.0.
<code>jump_gamma</code>	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
<code>jump_z</code>	Numeric; jumping rule of the proposal density for z. default value is 0.5.
<code>jump_w</code>	Numeric; jumping rule of the proposal density for w. default value is 0.5.
<code>pr_mean_beta</code>	Numeric; mean of normal prior for beta. default value is 0.
<code>pr_sd_beta</code>	Numeric; standard deviation of normal prior for beta. default value is 1.0.
<code>pr_mean_theta</code>	Numeric; mean of normal prior for theta. default value is 0.
<code>pr_mean_gamma</code>	Numeric; mean of log normal prior for gamma. default value is 0.5.
<code>pr_sd_gamma</code>	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
<code>pr_mean_alpha</code>	Numeric; mean of normal prior for alpha. default value is 0.5.
<code>pr_sd_alpha</code>	Numeric; mean of normal prior for beta. default value is 1.0.
<code>pr_a_theta</code>	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
<code>pr_b_theta</code>	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
<code>pr_a_eps</code>	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
<code>pr_b_eps</code>	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
<code>missing.val</code>	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_normal_mar models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$Y_{j,i} = \theta_j + \beta_i - \gamma \|z_j - w_i\| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$ Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References.

Value

lsirm2pl_normal_mar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
imp_estimate	estimation of imputing missing values.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
imp	imputation for missing Values using posterior samples.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.

accept_beta accept ratio of beta.
 accept_theta accept ratio of theta.
 accept_w accept ratio of w.
 accept_z accept ratio of z.
 accept_gamma accept ratio of gamma.
 accept_alpha accept ratio of alpha.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```

# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_normal_mar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = FALSE,
  missing_data = "mar"))

```

lsirm2pl_normal_mar_ss

2pl LSIRM model with normal likelihood and model selection approach for missing at random data.

Description

[lsirm2pl_normal_mar_ss](#) is used to fit 2pl LSIRM model with model selection approach based on spike-and-slab priors for continuous variable in incomplete data assumed to be missing at random. [lsirm2pl_normal_mar_ss](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while considering the missing element under the assumption of missing at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_normal_mar_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_xi_a = 0.001,
  pr_xi_b = 0.001,
  missing.val = 99
)
```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.

jump_alpha	Numeric; jumping rule of the proposal density for alpha default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_normal_mar_ss models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$ Under the assumption of missing at random, the model takes the missing element into consideration in the sampling procedure. For the details of missing at random assumption and data augmentation, see References. lsirm2pl_normal_mcar_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm2pl_normal_mar_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
imp_estimate	estimation of imputing missing values.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
imp	imputation for missing Values using posterior samples.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

References

Little, R. J., & Rubin, D. B. (2019). *Statistical analysis with missing data* (Vol. 793). John Wiley & Sons.
 Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example (continuous) item response matrix
data      <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat  <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_normal_mar_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = TRUE, fixed_gamma = FALSE,
                                     missing_data = "mar"))
```

lsirm2pl_normal_mcar *2pl LSIRM model with normal likelihood and missing completely at random data.*

Description

[lsirm2pl_normal_mcar](#) is used to fit 2pl LSIRM model for continuous variable in incomplete data assumed to be missing completely at random. [lsirm2pl_normal_mcar](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_normal_mcar(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
```

```

    jump_gamma = 1,
    jump_z = 0.5,
    jump_w = 0.5,
    pr_mean_beta = 0,
    pr_sd_beta = 1,
    pr_mean_theta = 0,
    pr_mean_gamma = 0.5,
    pr_sd_gamma = 1,
    pr_mean_alpha = 0.5,
    pr_sd_alpha = 1,
    pr_a_theta = 0.001,
    pr_b_theta = 0.001,
    pr_a_eps = 0.001,
    pr_b_eps = 0.001,
    missing.val = 99
)

```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.

pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_normal_mcar models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$ Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing completely at random assumption and data augmentation, see References.

Value

lsirm2pl_normal_mcar returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.

theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_normal_mcar(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = FALSE,
missing_data = "mcar"))
```

```
lsirm2pl_normal_mcar_ss
```

2pl LSIRM model with normal likelihood and model selection approach for missing completely at random data.

Description

`lsirm2pl_normal_mcar_ss` is used to fit 2pl LSIRM model with model selection approach based on spike-and-slab priors for continuous variable in incomplete data assumed to be missing completely at random. `lsirm2pl_normal_mcar_ss` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space, while ignoring the missing element under the assumption of missing completely at random. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_normal_mcar_ss(  
  data,  
  ndim = 2,  
  niter = 15000,  
  nburn = 2500,  
  nthin = 5,  
  nprint = 500,  
  jump_beta = 0.4,  
  jump_theta = 1,  
  jump_alpha = 1,  
  jump_gamma = 1,  
  jump_z = 0.5,  
  jump_w = 0.5,  
  pr_mean_beta = 0,  
  pr_sd_beta = 1,  
  pr_mean_theta = 0,  
  pr_spike_mean = -3,  
  pr_spike_sd = 1,  
  pr_slab_mean = 0.5,  
  pr_slab_sd = 1,  
  pr_mean_alpha = 0.5,  
  pr_sd_alpha = 1,  
  pr_a_eps = 0.001,  
  pr_b_eps = 0.001,  
  pr_a_theta = 0.001,  
  pr_b_theta = 0.001,  
  pr_xi_a = 0.001,  
  pr_xi_b = 0.001,  
  missing.val = 99
```

)

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.
missing.val	Numeric; a number to replace missing values. default value is 99.

Details

lsirm2pl_normal_mcar_ss models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$ Under the assumption of missing completely at random, the model ignores the missing element in doing inference. For the details of missing completely at random assumption and data augmentation, see References. lsirm2pl_normal_mcar_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm2pl_normal_mcar_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
missing.val	a number to replace missing values.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.

z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

References

Little, R. J., & Rubin, D. B. (2019). Statistical analysis with missing data (Vol. 793). John Wiley & Sons.

Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1),ncol=10,nrow=50)

# generate example missing indicator matrix
missing_mat <- matrix(rbinom(500, size = 1, prob = 0.2),ncol=10,nrow=50)

# make missing value with missing indicator matrix
data[missing_mat==1] <- 99

lsirm_result <- lsirm2pl_normal_mcar_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = TRUE, fixed_gamma = FALSE,
missing_data = "mcar"))
```

lsirm2pl_normal_o *2pl LSIRM model with normal likelihood*

Description

[lsirm2pl_normal_o](#) is used to fit 2pl LSIRM model for continuous variable. [lsirm2pl_normal_o](#) factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_normal_o(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_gamma = 0.5,
  pr_sd_gamma = 1,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001
)
```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.

jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; standard deviation of normal prior for alpha. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.

Details

lsirm2pl_normal_o models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$

Value

lsirm2pl_normal_o returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.

alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1), ncol=10, nrow=50)
lsirm_result <- lsirm2pl_normal_o(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = FALSE))
```

lsirm2pl_normal_ss	<i>2pl LSIRM model with normal likelihood and model selection approach.</i>
--------------------	---

Description

`lsirm2pl_normal_ss` is used to fit 2pl LSIRM model for continuous variable with model selection approach. `lsirm2pl_normal_ss` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_normal_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_eps = 0.001,
  pr_b_eps = 0.001,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_xi_a = 0.001,
  pr_xi_b = 0.001
)
```

Arguments

data	Matrix; continuous item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha default value is 1.0.

jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; standard deviation of normal prior for alpha. default value is 1.0.
pr_a_eps	Numeric; shape parameter of inverse gamma prior for variance of data likelihood. default value is 0.001.
pr_b_eps	Numeric; scale parameter of inverse gamma prior for variance of data likelihood default value is 0.001.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.

Details

lsirm2pl_normal_ss models the continuous value of response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$Y_{j,i} = \theta_j + \beta_i - \gamma ||z_j - w_i|| + e_{j,i}$$

where the error $e_{j,i} \sim N(0, \sigma^2)$. lsirm2pl_normal_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm2pl_normal_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.

mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
sigma_estimate	posterior estimation of standard deviation.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
sigma	posterior samples of standard deviation.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

References

Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example (continuous) item response matrix
data <- matrix(rnorm(500, mean = 0, sd = 1), ncol=10, nrow=50)

lsirm_result <- lsirm2pl_normal_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = TRUE, fixed_gamma = FALSE))
```

lsirm2pl_o

2pl LSIRM model

Description

`lsirm2pl_o` is used to fit 2pl LSIRM model. `lsirm2pl_o` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_o(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_gamma = 0.025,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_gamma = 0.5,
  pr_sd_gamma = 1,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001
)
```

Arguments

data	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_gamma	Numeric; mean of log normal prior for gamma. default value is 0.5.
pr_sd_gamma	Numeric; standard deviation of log normal prior for gamma. default value is 1.0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; standard deviation of normal prior for alpha. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.

Details

lsirm2pl_o models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \alpha_i, \beta_i, \gamma, z_j, w_i)) = \theta_j * \alpha_i + \beta_i - \gamma ||z_j - w_i||$$

Value

lsirm2pl_o returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

lsirm_result <- lsirm2pl_o(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = FALSE, fixed_gamma = FALSE))
```

lsirm2pl_ss

*2pl LSIRM model with model selection approach.***Description**

`lsirm2pl_ss` is used to fit 2pl LSIRM model with model selection approach based on spike-and-slab priors. `lsirm2pl_ss` factorizes item response matrix into column-wise item effect, row-wise respondent effect and further embeds interaction effect in a latent space. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect. The resulting latent space provides an interaction map that represents interactions between respondents and items.

Usage

```
lsirm2pl_ss(
  data,
  ndim = 2,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  jump_gamma = 1,
  jump_z = 0.5,
  jump_w = 0.5,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_spike_mean = -3,
  pr_spike_sd = 1,
  pr_slab_mean = 0.5,
  pr_slab_sd = 1,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001,
  pr_xi_a = 1,
  pr_xi_b = 1
)
```

Arguments

<code>data</code>	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
-------------------	--

ndim	Numeric; dimension of latent space. default value is 2.
niter	Numeric; number of iterations to run MCMC sampling. default value is 15000.
nburn	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
nthin	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
nprint	Numeric; MCMC samples is displayed during execution of MCMC chain for each nprint. default value is 500.
jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
jump_alpha	Numeric; jumping rule of the proposal density for alpha. default value is 1.0.
jump_gamma	Numeric; jumping rule of the proposal density for gamma. default value is 0.025.
jump_z	Numeric; jumping rule of the proposal density for z. default value is 0.5.
jump_w	Numeric; jumping rule of the proposal density for w. default value is 0.5.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_spike_mean	Numeric; mean of spike prior for log gamma default value is -3.
pr_spike_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_slab_mean	Numeric; mean of spike prior for log gamma default value is 0.5.
pr_slab_sd	Numeric; standard deviation of spike prior for log gamma default value is 1.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_xi_a	Numeric; first shape parameter of beta prior for latent variable xi. default value is 1.
pr_xi_b	Numeric; second shape parameter of beta prior for latent variable xi. default value is 1.

Details

lsirm2pl_ss models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j and the distance between latent position w_i of item i and latent position z_j of respondent j in the shared metric space, with γ represents the weight of the distance term. For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1|\theta_j, \alpha_i, \beta_i, z_j, w_i)) = \theta_j * \alpha_i + \beta_i - \gamma||z_j - w_i||$$

lsirm2pl_ss model include model selection approach based on spike-and-slab priors for log gamma. For detail of spike-and-slab priors, see References.

Value

lsirm2pl_ss returns an object of list containing the following components:

data	data frame or matrix containing the variables in the model.
bic	Numeric value with the corresponding BIC.
mcmc_inf	number of mcmc iteration, burn-in periods, and thinning intervals.
map_inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
gamma_estimate	posterior estimation of gamma.
alpha_estimate	posterior estimation of alpha.
z_estimate	posterior estimation of z.
w_estimate	posterior estimation of w.
pi_estimate	posterior estimation of phi. inclusion probability of gamma. if estimation of phi is less than 0.5, choose Rasch model with gamma = 0, otherwise latent space model with gamma > 0.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
gamma	posterior samples of gamma.
alpha	posterior samples of alpha.
z	posterior samples of z. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
w	posterior samples of w. The output is 3-dimensional matrix with last axis represent the dimension of latent space.
pi	posterior samples of phi which is indicator of spike and slab prior. If phi is 1, log gamma follows the slab prior, otherwise follows the spike prior.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_w	accept ratio of w.
accept_z	accept ratio of z.
accept_gamma	accept ratio of gamma.
accept_alpha	accept ratio of alpha.

References

Ishwaran, H., & Rao, J. S. (2005). Spike and slab variable selection: frequentist and Bayesian strategies. *The Annals of Statistics*, 33(2), 730-773.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

lsirm_result <- lsirm2pl_ss(data)

# The code following can achieve the same result.
lsirm_result <- lsirm(data ~ lsirm2pl(spikenslab = TRUE, fixed_gamma = FALSE))
```

onepl

1pl Rasch model.

Description

`onepl` is used to fit 1pl Rasch model.

Usage

```
onepl(
  data,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001
)
```

Arguments

<code>data</code>	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
<code>nthin</code>	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
<code>nprint</code>	Numeric; MCMC samples is displayed during execution of MCMC chain for each <code>nprint</code> . default value is 500.

jump_beta	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
jump_theta	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
pr_mean_beta	Numeric; mean of normal prior for beta. default value is 0.
pr_sd_beta	Numeric; standard deviation of normal prior for beta. default value is 1.0.
pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.

Details

onepl models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j :

$$\text{logit}(P(Y_{j,i} = 1 | \theta_j, \beta_i)) = \theta_j + \beta_i$$

Value

onepl returns an object of list containing the following components:

beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

result <- onepl(data)
```

plot.lsimr

Plotting the interaction map of fitted LSIRM model

Description

`plot` is used to plot the latent space of fitted LSIRM model.

Usage

```
## S3 method for class 'lsirm'
plot(
  x,
  option = "interaction",
  rotation = FALSE,
  cluster = FALSE,
  interact = FALSE,
  ...
)
```

Arguments

<code>x</code>	object of class <code>lsirm1pl</code> , <code>lsirm2pl</code> .
<code>option</code>	character; If value is "interaction", draw the interaction map that represents interactions between respondents and items. If value is "beta", draw the boxplot for the posterior samples of beta. If value is "theta", draw the distribution of the theta estimates per total test score for the data. If value is "alpha", draw the boxplot for the posterior samples of alpha. The "alpha" is only available for 2pl LSIRM.
<code>rotation</code>	Logical; If TRUE the latent positions are visualized after oblique (oblimin) rotation.
<code>cluster</code>	Logical; If TRUE the cluster result are visualized by Point Process Cluster Analysis.
<code>interact</code>	Logical; If TRUE, draw the interaction map interactively.
<code>...</code>	Additional arguments for the corresponding function.

Value

`plot` returns the interaction map or boxplot for parameter estimate.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)
lsirm_result <- lsirm(data ~ lsirm1pl(spikenslab = FALSE, fixed_gamma = FALSE))
```

```
plot(lsirm_result)

# use oblique rotation
plot(lsirm_result, rotation = TRUE)
```

```
print.summary.lsirm
```

Summary the result of LSIRM model

Description

[summary](#) is used to summary the result of LSIRM model.

[summary.lsirm](#) is used to summary the result of LSIRM model.

Usage

```
## S3 method for class 'summary.lsirm'
print(x, ...)

## S3 method for class 'summary.lsirm'
print(x, ...)
```

Arguments

x object of class lsirm1pl, lsirm2pl.
 ... Additional arguments.

Value

plot_latent returns the plot of latent space visualize an interaction map that represents interactions between respondents and items.

summary.lsirm contains following elements. A print method is available.

call	R call used to fit the model.
coef	Covariate coefficients posterior means.
mcmc.opt	The number of mcmc iteration, burn-in periods, and thinning intervals.
map.inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
BIC	Numeric value with the corresponding BIC.
method	1pl LSIRM or 2pl LSIRM
missing	The assumed missing type. One of NA, "mar" and "mcar". Default uses NA.
dtype	Binary or Continuous
ss	TRUE if using spike-slab prior

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)
lsirm_result <- lsirm1pl(data = data)
summary(lsirm_result)
```

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)
lsirm_result <- lsirm(data ~ lsirm1pl())
summary(lsirm_result)
```

summary.lsirm

Summary the result of LSIRM model

Description

[summary](#) is used to summary the result of LSIRM model.

Usage

```
## S3 method for class 'lsirm'
summary(object, ...)
```

Arguments

object	object of class lsirm.
...	Additional arguments.

Value

summary.lsirm contains following elements. A print method is available.

call	R call used to fit the model.
coef	Covariate coefficients posterior means.
mcmc.opt	The number of mcmc iteration, burn-in periods, and thinning intervals.
map.inf	value of log maximum a posterior and iteration number which have log maximum a posterior.
BIC	Numeric value with the corresponding BIC.
method	1pl LSIRM or 2pl LSIRM
missing	The assumed missing type. One of NA, "mar" and "mcar". Default uses NA.
dtype	Type of input data(Binary or Continuous).
ss	TRUE if using spike-slab prior

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

# 1PL LSIRM object
lsirm_result <- lsirm(data ~ lsirm1pl())
summary(lsirm_result)
```

TDRI

Inductive Reasoning Developmental Test

Description

TDRI dataset is the answer to Inductive Reasoning Developmental Test of 1,803 Brazilians with age varying from 5 to 85 years.

Usage

```
data(TDRI)
```

Format

A binary matrix with 1,803 rows and 56 columns.

Details

It presents data from 1,803 Brazilians (52.5% female) with age varying from 5 to 85 years ($M = 15.75$; $SD = 12.21$) that answered to the Inductive Reasoning Developmental Test – IRDT, with 56 items designed to assess developmentally sequenced and hierarchically organized inductive reasoning.

Source

https://figshare.com/articles/dataset/TDRI_dataset_csv/3142321

twopl

*2pl Rasch model.***Description**

`twopl` is used to fit 2pl Rasch model. Unlike 1pl model, 2pl model assumes the item effect can vary according to respondent, allowing additional parameter multiplied with respondent effect.

Usage

```
twopl(
  data,
  niter = 15000,
  nburn = 2500,
  nthin = 5,
  nprint = 500,
  jump_beta = 0.4,
  jump_theta = 1,
  jump_alpha = 1,
  pr_mean_beta = 0,
  pr_sd_beta = 1,
  pr_mean_theta = 0,
  pr_mean_alpha = 0.5,
  pr_sd_alpha = 1,
  pr_a_theta = 0.001,
  pr_b_theta = 0.001
)
```

Arguments

<code>data</code>	Matrix; binary item response matrix to be analyzed. Each row is assumed to be respondent and its column values are assumed to be response to the corresponding item.
<code>niter</code>	Numeric; number of iterations to run MCMC sampling. default value is 15000.
<code>nburn</code>	Numeric; number of initial, pre-thinning, MCMC iterations to discard. default value is 2500.
<code>nthin</code>	Numeric; number of thinning, MCMC iterations to discard. default value is 5.
<code>nprint</code>	Numeric; MCMC samples is displayed during execution of MCMC chain for each <code>nprint</code> . default value is 500.
<code>jump_beta</code>	Numeric; jumping rule of the proposal density for beta. default value is 0.4.
<code>jump_theta</code>	Numeric; jumping rule of the proposal density for theta. default value is 1.0.
<code>jump_alpha</code>	Numeric; jumping rule of the proposal density for alpha default value is 1.0.
<code>pr_mean_beta</code>	Numeric; mean of normal prior for beta. default value is 0.
<code>pr_sd_beta</code>	Numeric; standard deviation of normal prior for beta. default value is 1.0.

pr_mean_theta	Numeric; mean of normal prior for theta. default value is 0.
pr_mean_alpha	Numeric; mean of normal prior for alpha. default value is 0.5.
pr_sd_alpha	Numeric; mean of normal prior for beta. default value is 1.0.
pr_a_theta	Numeric; shape parameter of inverse gamma prior for variance of theta. default value is 0.001.
pr_b_theta	Numeric; scale parameter of inverse gamma prior for variance of theta. default value is 0.001.

Details

twopl models the probability of correct response by respondent j to item i with item effect β_i , respondent effect θ_j . For 2pl model, the the item effect is assumed to have additional discrimination parameter α_i multiplied by θ_j :

$$\text{logit}(P(Y_{j,i} = 1|\theta_j, \beta_i, \alpha_i)) = \theta_j * \alpha_i + \beta_i$$

Value

twopl returns an object of list containing the following components:

beta_estimate	posterior estimation of beta.
theta_estimate	posterior estimation of theta.
sigma_theta_estimate	posterior estimation of standard deviation of theta.
alpha_estimate	posterior estimation of alpha.
beta	posterior samples of beta.
theta	posterior samples of theta.
theta_sd	posterior samples of standard deviation of theta.
alpha	posterior samples of alpha.
accept_beta	accept ratio of beta.
accept_theta	accept ratio of theta.
accept_alpha	accept ratio of alpha.

Examples

```
# generate example item response matrix
data <- matrix(rbinom(500, size = 1, prob = 0.5), ncol=10, nrow=50)

result <- twopl(data)
```

Index

BFPT, 3

diagnostic.lsim, 3

lsirm, 5, 5

lsirm.formula, 5, 5

lsirm12pl, 6

lsirm1pl, 5, 6, 6

lsirm1pl_fixed_gamma, 7, 7

lsirm1pl_fixed_gamma_mar, 7, 9, 9

lsirm1pl_fixed_gamma_mcar, 7, 12, 12

lsirm1pl_mar, 7, 15, 15

lsirm1pl_mar_ss, 7, 18, 18

lsirm1pl_mcar, 7, 21, 21

lsirm1pl_mcar_ss, 7, 24, 24

lsirm1pl_normal, 27, 27

lsirm1pl_normal_fixed_gamma, 7, 28, 28

lsirm1pl_normal_fixed_gamma_mar, 7, 28, 31, 31

lsirm1pl_normal_fixed_gamma_mcar, 7, 28, 34, 34

lsirm1pl_normal_mar, 7, 28, 37, 37

lsirm1pl_normal_mar_ss, 7, 28, 40, 40

lsirm1pl_normal_mcar, 7, 28, 43, 43

lsirm1pl_normal_mcar_ss, 7, 28, 46, 47

lsirm1pl_normal_o, 7, 28, 50, 50

lsirm1pl_normal_ss, 7, 28, 53, 53

lsirm1pl_o, 7, 56, 56

lsirm1pl_ss, 7, 58, 58

lsirm2pl, 5, 61, 61

lsirm2pl_fixed_gamma, 62, 62

lsirm2pl_fixed_gamma_mar, 62, 65, 65

lsirm2pl_fixed_gamma_mcar, 62, 68, 68

lsirm2pl_mar, 62, 71, 71

lsirm2pl_mar_ss, 62, 74, 74, 81

lsirm2pl_mcar, 62, 78, 78

lsirm2pl_mcar_ss, 62, 81

lsirm2pl_normal, 85, 85

lsirm2pl_normal_fixed_gamma, 62, 85, 86, 86

lsirm2pl_normal_fixed_gamma_mar, 62, 85, 88, 89

lsirm2pl_normal_fixed_gamma_mcar, 62, 85, 92, 92

lsirm2pl_normal_mar, 62, 85, 95, 95

lsirm2pl_normal_mar_ss, 62, 85, 98, 98

lsirm2pl_normal_mcar, 85, 102, 102

lsirm2pl_normal_mcar_ss, 62, 85, 106, 106

lsirm2pl_normal_o, 62, 85, 109, 109

lsirm2pl_normal_ss, 62, 85, 112, 112

lsirm2pl_o, 62, 116, 116

lsirm2pl_ss, 62, 119, 119

onepl, 122, 122

plot, 124

plot.lsim, 124

print.summary.lsim, 125

summary, 125, 126

summary.lsim, 125, 126

TDRI, 127

twopl, 128, 128